

Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.

Application
For
Certification

FCC ID: ESX4000592

Outbound Rugged Speaker

Model: 4000592
Bluetooth Version: 4.0

2.4GHz Transceiver

Report No.: 140212009SZN-002

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-13]

Prepared and Checked by:

Approved by:

Sign on file

William Chen
Project Engineer

Billy Li
Supervisor
Date: March 28, 2014

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_TX_b

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch

6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etlsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.
MODEL: 4000592
FCC ID: ESX4000592

This report concerns (check one) Original Grant Class II Change

Equipment Type: DXX - Part 15 Low Power Communication Device Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-13 Edition] provision.

Report prepared by:

William Chen
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6F, Block D, Huahan Building, Langshan Road,
Nanshan District, Shenzhen, P. R. China
Phone: (86 755) 8614 0627
Fax: (86 755) 8601 6751

INTERTEK TESTING SERVICES

Table of Contents

<u>1.0 General Description</u>	2
1.1 Product Description	2
1.2 Related Submittal(s) Grants	2
1.3 Test Methodology	2
1.4 Test Facility	2
<u>2.0 System Test Configuration</u>	4
2.1 Justification	4
2.2 EUT Exercising Software	4
2.3 Special Accessories	4
No special accessories used	4
2.4 Equipment Modification	4
2.4 Equipment Modification	4
2.5 Measurement Uncertainty	5
2.6 Support Equipment List and Description	5
<u>3.0 Emission Results</u>	7
3.1 Radiated Test Results	8
3.1.1 Field Strength Calculation	8
3.1.2 Radiated Emission Configuration Photograph	9
3.1.3 Radiated Emissions	9
3.1.4 Transmitter Spurious Emissions	12
3.2 Conducted Emission at Mains Terminals	16
3.2.1 Conducted Emissions Configuration Photograph	16
3.2.2 Conducted Emissions	16
<u>4.0 Equipment Photographs</u>	20
<u>5.0 Product Labelling</u>	22
<u>6.0 Technical Specifications</u>	24
<u>7.0 Instruction Manual</u>	26
<u>8.0 Miscellaneous Information</u>	28
8.1 Bandedge Plot	29
8.2 Emissions Test Procedures	31
<u>9.0 Test Equipment List</u>	34

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	Filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Setup Photo	Conducted Emission	conducted photos.pdf
Test Report	Bandedge Plot	bandedge.pdf
Test Report	20dB BW Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Operation Description	Technical Description	descri.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	agency.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is an Outbound Rugged Speaker. The EUT is powered by a 3.7 VDC rechargeable battery which can be charged by an USB Power Adapter with Output: DC 5V, 1A or PC USB Port. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Bluetooth version: BT 4.0

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is an application for certification of a transceiver for the Outbound Rugged Speaker (BT 4.0 portion). For BT 2.1 mode, please refer to the report with report No.: 140212009SZN-001.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

1.4 Test Facility

The Semi-anechoic chamber and shielding room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch** and located at 6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 242492).

EXHIBIT 2
SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The EUT was powered by a 3.7 VDC fully charged rechargeable battery charged by an USB Power Adapter with AC 120V, 60Hz input or PC (AC 120V/60 Hz for PC power adapter) during the test. Only the worst data was reported.

All packets DH1, DH3 & DH5 mode in modulation type GFSK were tested, and only the worst data was reported in this report.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

The EUT exercise program (provided by client) used during testing was designed to exercise the various system components in a manner similar to a typical use.

2.3 Special Accessories

No special accessories used.

2.4 Equipment Modification

Any modifications installed previous to testing by Guangzhou Panyu Juda Car Audio Equipment Co., Ltd. will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

INTERTEK TESTING SERVICES

2.5 Measurement Uncertainty

When determining the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

Description	Manufacturer	Model No.
iPod	Apple	A1402
USB Charging Cable	N/A	Unshielded, Length 120cm
Adapter	TP-LINK	Model: T050100-2A3 Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5V, 1A
PC	HP	AJ411AV

EXHIBIT 3
EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included worst-case configuration (the configuration which resulted in the highest emission levels).

INTERTEK TESTING SERVICES

3.1 Radiated Test Results

A sample calculation, configuration photographs and data tables of the emissions are included.

3.1.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 62.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
PD = 0 dB
FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 dB μ V/m

Level in μ V/m = Common Antilogarithm [(32 dB μ V/m)/20] = 125.9 μ V/m

INTERTEK TESTING SERVICES

3.1.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

3.1.3 Radiated Emissions

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Worst Case Radiated Emission
at
37.760 MHz

Judgement: Passed by 9.6 dB

TEST PERSONNEL:

Sign on file

William Chen, Project Engineer
Typed/Printed Name


March 25, 2014
Date

INTERTEK TESTING SERVICES


Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.
Model: 4000592
Sample: 1/1
Worst Case Operating Mode: BT Link with Adapter charging

Date of Test: March 25, 2014

Horizontal



Vertical



INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.

Date of Test: March 25, 2014

Model: 4000592

Sample: 1/1

Worst Case Operating Mode: BT Link with Adapter charging

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	30.118	35.8	20.0	5.6	21.4	40.0	-18.6
Horizontal	94.094	37.6	20.0	8.4	26.0	43.5	-17.5
Horizontal	244.370	34.1	20.0	11.7	25.8	46.0	-20.2
Vertical	37.760	32.1	20.0	18.3	30.4	40.0	-9.6
Vertical	91.590	32.1	20.0	15.7	27.8	43.5	-15.7
Vertical	730.340	41.3	20.0	5.4	26.7	46.0	-19.3

- NOTES:
1. Quasi-Peak detector is used except for others stated.
 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. All emissions are below the QP limit.

INTERTEK TESTING SERVICES

3.1.4 Transmitter Spurious Emissions (Radiated)

Worst Case Radiated Emission
at
7440.000 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos. pdf.

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 7.2 dB

TEST PERSONNEL:

Sign on file

William Chen, Project Engineer
Typed/Printed Name

March 25, 2014
Date

INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.
Model: 4000592
Sample: 1/1

Date of Test: March 25, 2014

Worst Case Operating Mode: Transmitting with Adapter charging

Table 2

Radiated Emissions

(2402MHz)

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2402.000	100.8	36.7	28.5	92.6	114.0	-21.4
Vertical	4804.000	55.0	36.7	28.5	46.8	74.0	-27.2
Vertical	7206.000	56.9	36.1	33.1	53.9	74.0	-20.1
Vertical	9608.000	53.7	36.2	37.8	55.3	74.0	-18.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2402.000	86.4	36.7	28.5	78.2	94.0	-15.8
Vertical	4804.000	43.5	36.7	28.5	35.3	54.0	-18.7
Vertical	7206.000	43.5	36.1	33.1	40.5	54.0	-13.5
Vertical	9608.000	39.1	36.2	37.8	40.7	54.0	-13.3

- Notes:
1. Peak Detector Data unless otherwise stated. RBW=1MHz and VBW=3MHz for peak test value, RBW=1MHz and VBW=10Hz for average test value.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: William Chen

TRF No.: FCC 15C_TX_b
FCC ID: ESX4000592

INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.
Model: 4000592
Sample: 1/1

Date of Test: March 25, 2014

Worst Case Operating Mode: Transmitting with Adapter charging

Table 3

Radiated Emissions

(2440MHz)

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2440.000	99.2	36.7	28.5	91.0	114.0	-23.0
Vertical	4880.000	57.0	36.7	28.5	48.8	74.0	-25.2
Vertical	7320.000	59.8	36.1	33.1	56.8	74.0	-17.2
Vertical	9760.000	53.3	36.2	37.8	54.9	74.0	-19.1

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2440.000	85.7	36.7	28.5	77.5	94.0	-16.5
Vertical	4880.000	44.1	36.7	28.5	35.9	54.0	-18.1
Vertical	7320.000	46.8	36.1	33.1	43.8	54.0	-10.2
Vertical	9760.000	39.1	36.2	37.8	40.7	54.0	-13.3

Notes: 1. Peak Detector Data unless otherwise stated. RBW=1MHz and VBW=3MHz for peak test value, RBW=1MHz and VBW=10Hz for average test value.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative value in the margin column shows emission below limit.

4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: William Chen

INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.
 Model: 4000592
 Sample: 1/1

Date of Test: March 25, 2014

Worst Case Operating Mode: Transmitting with Adapter charging

Table 4

Radiated Emissions

(2480MHz)

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2480.000	103.0	36.7	28.6	94.9	114.0	-19.1
Vertical	4960.000	58.0	36.7	28.6	49.9	74.0	-24.1
Vertical	7440.000	62.5	36.1	33.4	59.8	74.0	-14.2
Vertical	9920.000	54.7	36.3	38.2	56.6	74.0	-17.4

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Vertical	2480.000	88.6	36.7	28.5	80.4	94.0	-13.6
Vertical	4960.000	44.7	36.7	28.5	36.5	54.0	-17.5
Vertical	7440.000	49.8	36.1	33.1	46.8	54.0	-7.2
Vertical	9920.000	40.0	36.2	37.8	41.6	54.0	-12.4

- Notes:
1. Peak Detector Data unless otherwise stated. RBW=1MHz and VBW=3MHz for peak test value, RBW=1MHz and VBW=10Hz for average test value.
 2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.

Test Engineer: William Chen

TRF No.: FCC 15C_TX_b
 FCC ID: ESX4000592

INTERTEK TESTING SERVICES

3.2 Conducted Emission at Mains Terminal

3.2.1 Conducted Emissions Configuration Photograph

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

3.2.2 Conducted Emissions

Worst Case Conducted Configuration
At

0.274 MHz

Judgement: Passed by 5.6 dB margin

TEST PERSONNEL:

Sign on file

William Chen, Project Engineer
Typed/Printed Name

March 25, 2014
Date

INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.

Date of Test: March 25, 2014


Model: 4000592

Sample: 1/1

Worst Case Operating Mode: BT Link with Adapter charging

Phase: Live

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.194	41.0	L1	9.7	16.9	63.9
0.274	33.8	L1	9.7	11.1	61.0
0.826	26.2	L1	9.7	21.1	56.0
2.002	26.0	L1	9.9	21.9	56.0
2.774	27.9	L1	9.8	22.0	56.0
10.510	26.1	L1	10.0	22.6	60.0

Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.194	33.7	L1	9.7	20.2	53.9
0.274	45.4	L1	9.7	5.6	51.0
0.826	27.2	L1	9.7	18.8	46.0
2.002	25.1	L1	9.9	20.9	46.0
2.774	24.9	L1	9.8	21.1	46.0
10.510	28.8	L1	10.0	21.2	50.0

TRF No.: FCC 15C_TX_b

FCC ID: ESX4000592

INTERTEK TESTING SERVICES

Applicant: Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.

Date of Test: March 25, 2014


Model: 4000592

Sample: 1/1

Worst Case Operating Mode: BT Link with Adapter charging

Phase: Neutral

Conducted Emission Test - FCC



Result Table QP

Frequency (MHz)	QuasiPeak (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.186	46.9	N	10.2	17.3	64.2
0.274	46.9	N	10.2	14.1	61.0
0.450	35.0	N	10.2	21.9	56.9
0.822	31.8	N	10.3	24.2	56.0
1.610	30.7	N	10.4	25.3	56.0
10.378	32.4	N	10.5	27.6	60.0

Result Table AV

Frequency (MHz)	Average (dB µ V)	Line	Corr. (dB)	Margin (dB)	Limit (dB µ V)
0.186	34.5	N	10.2	19.7	54.2
0.274	41.9	N	10.2	9.1	51.0
0.450	29.5	N	10.2	17.4	46.9
0.822	27.1	N	10.3	18.9	46.0
1.610	24.5	N	10.4	21.5	46.0
10.378	26.4	N	10.5	23.6	50.0

TRF No.: FCC 15C_TX_b

FCC ID: ESX4000592

INTERTEK TESTING SERVICES

EXHIBIT 4
EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs of the tested EUT are saved with filename: external photos.pdf & internal photos.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

INTERTEK TESTING SERVICES

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

EXHIBIT 7
INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandedge, the test procedure and calculation of factor such as pulse desensitization.

INTERTEK TESTING SERVICES

8.1 Bandedge Plot

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bandedge.pdf. From the plot, the field strength of any emissions outside of the specified frequency band are attenuated to the general radiated emission limits in section 15.209. It fulfils the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e (Bandedge Plot).

(i) Lower channel 2402MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

$$\begin{aligned} &= 92.6 \text{ dB}\mu\text{v/m} - 47.1 \text{ dB} \\ &= 45.5 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

$$\begin{aligned} &= 78.2 \text{ dB}\mu\text{v/m} - 47.1 \text{ dB} \\ &= 31.1 \text{ dB}\mu\text{v/m} \end{aligned}$$

(ii) Upper channel 2480MHz:

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the bandedge plot

$$\begin{aligned} &= 94.9 \text{ dB}\mu\text{v/m} - 54.6 \text{ dB} \\ &= 40.3 \text{ dB}\mu\text{v/m} \end{aligned}$$

Average Resultant field strength = Fundamental emissions (Average value) – delta from the bandedge plot

$$\begin{aligned} &= 80.4 \text{ dB}\mu\text{v/m} - 54.6 \text{ dB} \\ &= 25.8 \text{ dB}\mu\text{v/m} \end{aligned}$$

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB μ v/m (Peak Limit) and 54dB μ v/m (Average Limit).

INTERTEK TESTING SERVICES

8.1 Bandedge Plot (cont'd)

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

Figure 8.1 Bandwidth

INTERTEK TESTING SERVICES

8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2009.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Detector function for conducted emissions is in QP & AV mode and IFBW setting is 9 kHz from the frequency band 150 kHz to 30MHz.

INTERTEK TESTING SERVICES

8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2009.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

**EXHIBIT9
TEST EQUIPMENT LIST**

INTERTEK TESTING SERVICES

9.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-03	BiConiLog Antenna	ETS	3142C	00066460	29-Jun-13	29-Jun-14
SZ185-01	EMI Receiver	R&S	ESCI	100547	10-Mar-14	10-Mar-15
SZ061-07	Pyramidal Horn Antenna	ETS	3160-09	00083067	27-Aug-13	27-Aug-14
SZ061-08	Horn Antenna	ETS	3115	00092346	26-Oct-13	26-Oct-14
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	13-May-13	13-May-14
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	10-Mar-14	10-Mar-15
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	10-Mar-14	10-Mar-15
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	02-Mar-14	02-Mar-15
SZ062-02	RF Cable	RADIALL	RG 213U	--	20-Jan-14	20-Jul-14
SZ062-06	RF Cable	RADIALL	0.04-26.5GHz	--	01-Nov-13	01-May-14
SZ062-12	RF Cable	RADIALL	0.04-26.5GHz	--	17-Oct-13	17-Apr-14
SZ067-04	Notch Filter	Micro-Tronics	BRM5070 2-02	--	21-May-13	21-May-14
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	9-Nov-13	9-Nov-14
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	9-Nov-13	9-Nov-14
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	9-Nov-13	9-Nov-14
SZ188-03	Shielding Room	ETS	RFD-100	4100	23-Aug-13	23-Aug-14