

Typschild-Angaben

T3016

120/230V

Daten abgeleitet aus „Montage-Drucker-Verwaltung“

(extern zur SAP/EDV)

Datenarten	T3016	T3016 C	T3016-2T				
Basisgeräte-Id.Nr.	41943						
Spannung AC V	120/230						
Frequenz Hz	60/50						
Strohm A	0,8/0,4						
Leistung W	45						
Sicherungswert F1	T4,0A/250V						
Modell	T3016	T3016 C	T3016-2T				
Seriennummer	Eingabe Serien-Nr. -Kreis						
Identnummer	Basisgeräte-Nr. aus Feld „Konfiguration“ / Vertriebs-Id.Nr.						
UCL-Nummer	aktueller Stand aus Feld „UCL-Stand“ / Komponenten-Id.Nr.						
FCC ID: EUIT3016	??						

CAUTION: For continued protection against risk of fire, replace only with same type and rating of fuse.

ATTENTION: Pour ne pas compromettre la protection contre les risques d'incendie, remplacer par un fusible de même type et de mêmes caractéristiques nominales.

UCL-N°	0	1	2	3	4	5	6	7	8	9
	10	11	12	13	14	15	16	17	18	19
	20	21	22	23	24	25	26	27	28	29

Tally®

Made in Germany

AC V Model
Hz Ser. No.
A Id. No.
W F1



FCC ID: EUIT3016

This device complies with FCC Rules Part 15. Operation is subject to the following two conditions: (1) This device may not cause harmful interference and (2) this device must accept any interference that may be received, including interference that may cause undesired operation.

Rating Label

Tally	Typenschild-Layout (Laser)				Zeichnungs-Nr.:	Blatt
	T3016	120 / 230V	Standard		60808/11	von Bl.
	20230-00	04.05.1999	ScA			