APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: September 27, 2010

EUT Specification

EUT	Tablet PC
Frequency band	☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz
(Operating)	☐ WLAN: 5.745GHz ~ 5.825GHz
, 1	Others
Device category	Portable (<20cm separation)
	Mobile (>20cm separation)
	Others
Exposure classification	Occupational/Controlled exposure ($S = 5 \text{mW/cm}^2$)
	General Population/Uncontrolled exposure
	$(S=1 \mathrm{mW/cm^2})$
Antenna diversity	Single antenna
	Multiple antennas
	Tx diversity
	Rx diversity
	☐ X/Rx diversity
Max. output power	IEEE 802.11b mode: 16.08 dBm (40.55 mW)
	IEEE 802.11g mode: 25.50dBm (354.81 mW)
	draft 802.11n Standard-20 MHz Channel mode: 25.63 dBm (365.59 mW)
	draft 802.11n Wide-40 MHz Channel mode: 25.52 dBm (356.45 mW)
Antenna gain (Max)	2.41 dBi (Numeric gain: 1.74)
Evaluation applied	MPE Evaluation
	SAR Evaluation*
	□ N/A
Remark:	
1. The maximum output power is 25.63dBm (365.59 mW) at 2437MHz (with 1.74 numeric antenna	
<i>gain</i> .)	
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.	
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power	
density is 1.0 mW/cm2 even if the calculation indicates that the power density would be larger.	

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.

Page 78 Rev. 00