APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: September 27, 2010

EUT Specification

EUT	Tablet PC
Frequency band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5.825GHz ✓ Others: Bluetooth: 2.402GHz ~ 2.480GHz
Device category	 Portable (<20cm separation) Mobile (>20cm separation) Others
Exposure classification	Occupational/Controlled exposure $(S = 5mW/cm^2)$ General Population/Uncontrolled exposure $(S=1mW/cm^2)$
Antenna diversity	 Single antenna Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	3.90 dBm (2.45mW)
Antenna gain (Max)	2.15 dBi (Numeric gain: 1.64)
Evaluation applied	 MPE Evaluation SAR Evaluation N/A*
Remark:	
1. The maximum output power is <u>3.90dBm (2.45mW) at 2480MHz</u> (with <u>1.64 numeric antenna</u>	
gain.) 2. DTS device is not subject to a compliance.	routine RF evaluation; MPE estimate is used to justify the
	transmitters, no SAR consideration applied. The maximum ² even if the calculation indicates that the power density

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)} = 60/2.441 = 24.58 \text{mW}$)

Page 69 Rev. 00