

APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: January 5, 2011

EUT Specification

EUT	Tablet PC
Frequency band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz
Device category	Portable (<20cm separation) Mobile (>20cm separation) Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm²) ☐ General Population/Uncontrolled exposure (S=1mW/cm²)
Antenna diversity	
Max. output power	IEEE 802.11b mode: 17.71 dBm (59.02 mW) IEEE 802.11g mode: 24.99dBm (315.50 mW) IEEE 802.11n HT 20 MHz mode: 24.9 dBm (309.02 mW) IEEE 802.11n HT 40 MHz mode: 25.56 dBm (359.74 mW)
Antenna gain (Max)	0.87 dBi (Numeric gain: 1.22)
Evaluation applied	
Remark:	
1. The maximum output power is <u>25.56dBm (359.74 mW) at 2437MHz (with 1.22 numeric antenna</u> gain.)	
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.	
For mobile or fixed location transmitters, no SAP consideration applied. The maximum nower	

3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm2 even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.

Page 78 Rev. 00