



# FCC TEST REPORT

for

**Notebook PC**

**MODEL: CE261 ;Pegasus**

**Test Report Number:  
KS070608A02-RP**

Issued for

**First International Computer,Inc**  
NO.300, YangGuang St., NeiHu, Taipei,  
Taiwan, 114

Issued by:

**Compliance Certification Services Inc.**  
**Kun shan Laboratory**  
**No.10 Weiye Rd, Innovation park, Eco&Tec,**  
**Development Zone, Kunshan City, Jiangsu, P.R.O.C**  
**TEL: 86-512-57355888**  
**FAX: 86-512-57370818**  
**Issued Date: June 28, 2007**



Lab. Code: 200581-0



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 28, 2007	Initial Issue	ALL	Miro chueh



**TABLE OF CONTENTS**

**1 TEST CERTIFICATION ..... 4**

**2 TEST RESULT SUMMARY ..... 5**

**3 EUT DESCRIPTION..... 6**

**4 TEST METHODOLOGY..... 7**

    4.1. DESCRIPTION OF TEST MODES ..... 7

**5 SETUP OF EQUIPMENT UNDER TEST ..... 8**

    5.1. DESCRIPTION OF SUPPORT UNITS..... 8

    5.2. CONFIGURATION OF SYSTEM UNDER TEST ..... 8

**6 FACILITIES AND ACCREDITATIONS ..... 9**

    6.1. FACILITIES ..... 9

    6.2. ACCREDITATIONS ..... 9

    6.3. MEASUREMENT UNCERTAINTY ..... 9

**7 LIMITS AND RESULTS ..... 10**

    7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT ..... 10

    7.2. SPURIOUS EMISSIONS MEASUREMENT ..... 17

    7.3. 6dB BANDWIDTH MEASUREMENT ..... 35

    7.4. PEAK OUTPUT POWER ..... 40

    7.5. BAND EDGES MEASUREMENT: ..... 45

    7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT ..... 57

**APPENDIX I RADIO FREQUENCY EXPOSURE ..... 62**

**APPENDIX II PHOTOGRAPHS OF THE TEST CONFIGURATION ..... 64**



# 1 TEST CERTIFICATION

**Product:** Notebook PC

**Model:** CE261; Pegasus

**Brand:** FIC; EVEREX; Packard Bell

**Tested:** June 9, 2007-June 28,2007

**Applicant:** First International Computer, Inc

NO.300, YangGuang St., NeiHu, Taipei, Taiwan, 114

**Manufacturer:** First International Computer(suzhou), Inc

Export Processing Zone, No 200, Central Suhong Road, SuZhou Industrial Park JiangSu, P.R.China

## APPLICABLE STANDARDS

Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

## DEVIATION FROM APPLICABLE STANDARD

None

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2003** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

**Approved by:**

Miro Chueh  
Section Manager  
Compliance Certification Service Inc.

**Reviewed by:**

Lin Zhang  
EMC supervisor  
Compliance Certification Service Inc.



## 2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	Spurious Emissions ● Conducted Measurement ● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The test result judgment is decided by the limit of test standard  
2. The information of measurement uncertainty is available upon the customer's request.



### 3 EUT DESCRIPTION

<b>Product</b>	Notebook PC
<b>Trade Name</b>	FIC; EVEREX; Packard Bell
<b>Model Number</b>	CE261; Pegasus
<b>Model Discrepancy</b>	All the above models are identical except the model designation for different market.
<b>Serial Number</b>	N/A
<b>Wireless LAN module Model Number</b>	AW-GU210
<b>Wireless LAN module Brand name</b>	AzureWave
<b>AC Power Cord Type</b>	Unshielded, 1.8m (Detachable) to Power Adapter
<b>DC Power Cable Type</b>	Unshielded, 1.8m (Non-Detachable) at Power Adapter with a core
<b>Frequency Range</b>	2412 ~ 2462 MHz
<b>Transmit Power</b>	IEEE 802.11b:18.01dBm IEEE 802.11g:14.02dBm
<b>Modulation Technique</b>	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: DSSS (CCK, DQPSK, DBPSK) + OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
<b>Transmit Data Rate</b>	IEEE 802.11b: 11, 5.5, 2, 1 Mbps IEEE 802.11g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps
<b>Number of Channels</b>	IEEE 802.11b , IEEE 802.11g :13 Channels
<b>Antenna Specification</b>	PCB antenna with 1.82dBi gain (Max)

**Note:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: **EUNCE261A** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



## **4 TEST METHODOLOGY**

### **4.1. DESCRIPTION OF TEST MODES**

The EUT had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

IEEE802.11b: Channel low(2412MHz), Channel middle(2437MHz) and Channel high (2462MHz) with preliminary test 11, 5.5, 2, and 1, After the preliminary scan , the following test mode 11Mbps highest data rate (the worst case) are chosen for the final testing.

IEEE802.11g: Channel low(2412MHz), Channel middle(2437MHz) and Channel high(2462MHz) with preliminary test 54/48/36/24/18/12/9/6, After the preliminary scan , the following test mode 6Mbps data rate (the worst case) are chosen for the final testing.



## 5 SETUP OF EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	Monitor	CPD-G42 0	2404647	DoC	SONY	Shielded, 1.8m with a Core	Un-Shielded, 1.5m
2	HDD(USB)-9	F12-UF	A0100222-539 0021	DoC	TeraSys	N/A	Shielded, 1.8m
3	HDD(USB)-5	F12-UF	A0100214-4C g0003	DoC	TeraSys	N/A	Shielded, 1.8m
4	Speaker-1	CD-371	N/A	DoC	JINLIAN	Un-Shielded, 2.0m	N/A
5	Notebook	M285	1824064-1B	DoC	LEO	Line cable: Un-Shielded 1.8m LAN cable: Un-Shielded 1.8m	Shielded, 1.8m
6	Mouse(USB)	M-UV83	HCA60406943	DoC	Logitech	Shielded, 1.8m	N/A

**Note:**

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.





## 6 FACILITIES AND ACCREDITATIONS

### 6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

**No.10Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, P.R.O.C**

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC,NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA,
<b>Taiwan</b>	TAF

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsemc.com>.

### 6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETR 028:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	+/- 2.15dB
Radiated emissions	30MHz ~ 200MHz	+/- 2.50dB
	200MHz ~1000MHz	+/- 2.50dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## 7 LIMITS AND RESULTS

### 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

#### 7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### TEST INSTRUMENTS

Conducted Emission Test Site A (10m chamber)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESI26	100068	02/11/2008
EMC Analyzer	Agilent	E7402A	US41160329	02/11/2008
LISN	FCC	FCC-LISN-50-50-2-M	01067	02/11/2008
LISN (EUT)	FCC	FCC-LISN-50-50-2-M	01068	02/11/2008
FOUR BALANCED TELECOM PAIRS ISN	FCC	FCC-TLISN-T8-02	20165	07/30/2007
4-WIRE ISN	R&S	ENY41	830663/024	04/08/2008
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	03/15/2008
EMI Monitor control box	FCC	0-SVDC	N/A	05/11/2008


- NOTE:**
- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  - 2. N.C.R = No Calibration Request.



**7.1.2. TEST PROCEDURES** (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

**7.1.3. TEST SETUP**



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

**7.1.4. Data Sample:**

Frequency (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Correction factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
XXX	37.58	35.11	10.10	47.68	45.21	63.49	53.49	-15.81	-8.28	L1

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer/Receiver reading  
 Correction factor (dB) = Insertion loss of LISN  
 Limit (dBuV) = Limit stated in standard  
 Margin (dB) = Reading (dBuV) – Limit (dBuV)  
 Note = Current carrying line of reading



7.1.5. TEST RESULTS

Adapter :DELTA

Model No.	CE261	Test Mode	Normal Link
Environmental Conditions	25deg.C,43% RH, 991 hPa	6dB BANDWIDTH	9 kHz
Tested by:	healing		


Freq. (MHz)	Q.P. Raw reading (dBuV)	AVG Raw reading (dBuV)	Correction factor(dB)	Q.P. Amptd. (dBuV)	AVG Amptd. (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Line/Neutral
0.204	33.86	33.31	10.39	44.25	43.70	64.47	54.47	-20.22	-10.77	Line
0.270	31.30	29.92	10.30	41.60	40.22	62.56	52.56	-20.96	-12.34	Line
0.339	20.98	20.76	10.24	31.22	31.00	60.61	50.61	-29.39	-19.61	Line
0.405	16.52	18.47	10.19	26.71	28.66	58.71	48.71	-32.00	-20.05	Line
0.540	20.32	19.93	10.10	30.42	30.03	56.00	46.00	-25.58	-15.97	Line
2.311	7.27	6.55	10.98	18.25	17.53	60.00	50.00	-41.75	-32.47	Line
0.202	23.70	24.04	10.29	33.99	34.33	64.52	54.52	-30.53	-20.19	Neutral
0.270	20.24	20.26	10.25	30.49	30.51	62.56	52.56	-32.07	-22.05	Neutral
0.339	12.64	12.53	10.24	22.88	22.77	60.61	50.61	-37.73	-27.84	Neutral
0.410	10.03	10.12	10.24	20.27	20.36	58.56	48.56	-38.29	-28.20	Neutral
0.545	13.21	13.11	10.24	23.45	23.35	56.00	46.00	-32.55	-22.65	Neutral
0.614	2.53	5.82	10.22	12.75	16.04	56.00	46.00	-43.25	-29.96	Neutral

REMARKS: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




**Test Plots**

**Conducted emissions (Line 1)**



**Conducted emissions (Line 2)**





Adapter :LI SHIN

Model No.	CE261	Test Mode	Normal Link
Environmental Conditions	25deg.C,43% RH, 991 hPa	6dB BANDWIDTH	9 kHz
Tested by:	healing		


Freq. (MHz)	Q.P. Raw reading (dBuV)	AVG Raw reading (dBuV)	Correction factor(dB)	Q.P. Amptd. (dBuV)	AVG Amptd. (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Line/Neutral
0.205	28.08	24.97	10.38	38.46	35.35	64.38	54.38	-25.92	-19.03	Line
0.577	8.68	8.72	10.11	18.79	18.83	62.49	52.49	-43.70	-33.66	Line
0.894	22.59	20.55	10.14	32.73	30.69	60.00	50.00	-27.27	-19.31	Line
1.489	18.32	15.28	10.29	28.61	25.57	60.00	50.00	-31.39	-24.43	Line
16.898	17.54	17.54	11.08	28.62	28.62	60.00	50.00	-31.38	-21.38	Line
23.132	27.54	27.41	10.98	38.52	38.39	60.00	50.00	-21.48	-11.61	Line
0.198	20.47	13.23	10.35	30.82	23.58	64.57	54.57	-33.75	-30.99	Neutral
0.270	18.73	18.17	10.26	28.99	28.43	60.00	50.00	-31.01	-21.57	Neutral
0.334	20.21	19.04	10.24	30.45	29.28	60.00	50.00	-29.55	-20.72	Neutral
0.574	10.40	6.49	10.23	20.63	16.72	60.00	50.00	-39.37	-33.28	Neutral
18.245	15.61	16.17	11.03	26.64	27.20	60.00	50.00	-33.36	-22.80	Neutral
23.132	17.21	17.21	10.99	28.20	28.20	60.00	50.00	-31.80	-21.80	Neutral

REMARKS:L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




**Test Plots**

**Conducted emissions (Line 1)**



**Conducted emissions (Line 2)**







## 7.2. SPURIOUS EMISSIONS MEASUREMENT

### 7.2.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### 7.2.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007

### 7.2.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz. Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.




7.2.4. TEST RESULTS

Test Plot (IEEE 802.11b mode)

CH Low

30MHz ~ 2.9GHz


Agilent 11:48:13 Jun 14, 2007



Copyright 2000-2003 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent 11:49:26 Jun 14, 2007




Copyright 2000-2003 Agilent Technologies



**CH Mid**

**30MHz ~ 2.9GHz**

Agilent 11:37:55 Jun 14, 2007



**Marker**

Select Marker 1 2 3 4

Normal

Delta

Delta Pair (Tracking Ref) Ref  $\Delta$

Span Pair Span Center


Off

More 1 of 2

Copyright 2000-2003 Agilent Technologies

**2.9GHz ~ 26.5GHz**

Agilent 11:39:18 Jun 14, 2007



**Marker**

Select Marker 1 2 3 4

Normal

Delta

Delta Pair (Tracking Ref) Ref  $\Delta$

Span Pair Span Center

Off

More 1 of 2


Copyright 2000-2003 Agilent Technologies



**CH High**

**30MHz ~ 2.9GHz**

Agilent 11:55:03 Jun 14, 2007



**Marker**

Select Marker  
1 2 3 4

Normal

Delta

Delta Pair  
(Tracking Ref)  
Ref ▲

Span Pair  
Span Center


Off

More  
1 of 2

Copyright 2000-2003 Agilent Technologies

**2.9GHz ~ 26.5GHz**

Agilent 11:56:25 Jun 14, 2007



**Marker**

Select Marker  
1 2 3 4

Normal

Delta

Delta Pair  
(Tracking Ref)  
Ref ▲

Span Pair  
Span Center

Off

More  
1 of 2

Copyright 2000-2003 Agilent Technologies




Test Plot (IEEE 802.11g mode)

CH Low

30MHz ~ 2.9GHz


Agilent 12:17:55 Jun 14, 2007



Copyright 2000-2003 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent 12:18:48 Jun 14, 2007




Copyright 2000-2003 Agilent Technologies



**CH Mid**

**30MHz ~ 2.9GHz**

Agilent 12:08:49 Jun 14, 2007




Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More			
1 of 2			

Copyright 2000-2003 Agilent Technologies

**2.9GHz ~ 26.5GHz**

Agilent 12:10:09 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More			
1 of 2			


Copyright 2000-2003 Agilent Technologies



**CH High**

**30MHz ~ 2.9GHz**

Agilent 11:59:02 Jun 14, 2007




Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies

**2.9GHz ~ 26.5GHz**

Agilent 12:00:44 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

Copyright 2000-2003 Agilent Technologies



7.2.5. Radiated Emissions

7.2.5.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**NOTE:** (1) The lower limit shall apply at the transition frequencies.  
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).





7.2.5.2. TEST INSTRUMENTS

3M Semi Anechoic Chamber (977)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007
Spectrum Analyzer	Agilent	E4446A	US44300398	07/25/2007
EMI Test Receiver	R&S	ESPI3	101026	11/11/2007
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	12/13/2007
Pre-Amplifier	Miteq	NSP4000-NF	870731	01/28/2008
Bilog Antenna	Sunol	JB1	A110204-2	11/22/2007
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	02/01/2008
PSG Analog Signal Generator	Agilent	E8257C	MY43321570	12/19/2007
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Site NSA	CCS	N/A	N/A	04/06/2008


- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The FCC Site Registration number is 93105,90471.  
 4. N.C.R = No Calibration Required.

7.2.5.3. TEST PROCEDURE (please refer to measurement standard)


- The EUT is placed on a turntable, which is 0.8m above ground plane.
- The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Set the spectrum analyzer in the following setting as:  
 Below 1GHz:  
     RBW=100kHz / VBW=300kHz / Sweep=AUTO  
 Above 1GHz:  
     (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO  
     (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- Repeat above procedures until the measurements for all frequencies are complete.

**7.2.5.4. TEST SETUP**

**Below 1 GHz**



**Above 1 GHz**



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.5.5. Data Sample:

**Below 1 GHz**

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Remark) (dBuV)	Correction Factor (dB/m)	Result (Remark) (dBuV/m)	Limit (Peak) (dBuV/m)	Margin (dB)	Remark
xxx	V	12.12	10.21	22.33	37.00	-14.67	Peak

**Above 1 GHz**

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
xxx	V	65.45	63.00	-11.12	54.33	51.88	74.00	54.00	-2.12	AVG

- Frequency (MHz) = Emission frequency in MHz
- Ant.Pol. (H/V) = Antenna polarization
- Reading (dBuV) = Uncorrected Analyzer / Receiver reading
- Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
- Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
- Limit (dBuV/m) = Limit stated in standard
- Margin (dB) = Remark Result (dBuV/m) – Limit (dBuV/m)
- Peak = Peak Reading
- QP = Quasi-peak Reading
- AVG = Average Reading



7.2.5.6. TEST RESULTS

**Below 1 GHz**

Operation Mode: Normal Link

Test Date: June 12, 2007

Temperature: 26°C

Tested by: healing

Humidity: 50 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
39.15	V	Peak	41.83	-5.88	35.95	40.0	-4.05
46.37	V	Peak	41.15	-5.65	35.50	40.0	-4.50
118.96	V	Peak	41.81	-8.43	33.38	43.5	-10.12
227.51	V	Peak	46.76	-9.94	36.82	46.0	-9.18
552.67	V	Peak	38.89	-1.36	37.53	46.0	-8.47
943.54	V	Peak	35.24	4.13	39.37	46.0	-6.63
91.88	H	Peak	40.49	-3.72	36.77	43.5	-6.73
125.06	H	Peak	44.56	-8.17	36.39	43.5	-7.11
202.33	H	Peak	46.37	-10.35	36.02	46.0	-9.98
228.73	H	Peak	48.19	-9.93	38.26	46.0	-7.74
316.01	H	Peak	46.88	-7.21	39.67	46.0	-6.33
958.44	H	Peak	36.98	4.44	41.42	46.0	-4.58

**REMARKS:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).



Above 1 GHz

Operation Mode: TX / IEEE 802.11b / CH Low

Test Date: June 12, 2007

Temperature: 26°C

Tested by: healing

Humidity: 50% RH

Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant.Pol. (H/V), Reading (Peak) (dBuV), Reading (Average) (dBuV), Correction Factor (dB/m), Result (Peak) (dBuV/m), Result (Average) (dBuV/m), Limit (Peak) (dBuV/m), Limit (Average) (dBuV/m), Margin (dB), Remark. Contains data for frequencies 4825.00 and 7242.35 MHz.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) - Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH Mid

Test Date: June 12, 2007

Temperature: 26°C

Tested by: healing

Humidity: 50% RH

Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant. Pol. (H/V), Reading (Peak) (dBuV), Reading (Average) (dBuV), Correction Factor (dB/m), Result (Peak) (dBuV/m), Result (Average) (dBuV/m), Limit (Peak) (dBuV/m), Limit (Average) (dBuV/m), Margin (dB), Remark. Contains data for frequencies 4875.00 and 7310.33 MHz.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).





Operation Mode: TX / IEEE 802.11g / CH Low
Temperature: 26°C
Humidity: 50 % RH

Test Date: June 12, 2007
Tested by: healing
Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant. Pol. (H/V), Reading (Peak) (dBuV), Reading (Average) (dBuV), Correction Factor (dB/m), Result (Peak) (dBuV/m), Result (Average) (dBuV/m), Limit (Peak) (dBuV/m), Limit (Average) (dBuV/m), Margin (dB), Remark. Contains two data rows and several empty rows.

REMARKS:

- 7. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
8. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
9. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
10. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
11. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).





Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: June 12, 2007

Temperature: 26°C

Tested by: healing

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
4875.00	V	46.56	35.75	11.08	57.64	46.83	74.00	54.00	-7.17	average
7314.33	V	34.4	21.98	18.21	52.61	40.19	74.00	54.00	-13.81	average
4875.00	H	44.74	35.00	11.08	55.82	46.08	74.00	54.00	-7.92	average
7306.67	H	35.55	23.31	18.23	53.78	41.54	74.00	54.00	-12.46	average

REMARKS:

7. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
8. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
9. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
10. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
11. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH High

Test Date: June 12, 2007

Temperature: 26°C

Tested by: healing

Humidity: 50 % RH

Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant. Pol. (H/V), Reading (Peak) (dBuV), Reading (Average) (dBuV), Correction Factor (dB/m), Result (Peak) (dBuV/m), Result (Average) (dBuV/m), Limit (Peak) (dBuV/m), Limit (Average) (dBuV/m), Margin (dB), Remark. It contains two data rows for frequencies 4925.00 and 7379.33 MHz with V and H polarizations.

REMARKS:

- 7. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
8. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
9. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
10. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
11. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**7.3. 6dB BANDWIDTH MEASUREMENT**

**7.3.1. LIMITS**


According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**7.3.2. TEST INSTRUMENTS**

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007

**7.3.3. TEST PROCEDURES** (please refer to measurement standard)

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = 20MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.



**7.3.4. TEST SETUP**



**7.3.5. TEST RESULTS**

*No non-compliance noted*

**Test Data**

**Test mode: IEEE 802.11b**

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	8889	>500	PASS
Mid	2437	8750		PASS
High	2462	8681		PASS

**Test Data**

**Test mode: IEEE 802.11g**


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	15901	>500	PASS
Mid	2437	15126		PASS
High	2462	16048		PASS



**Test Plot (IEEE 802.11b mode)**

**6dB Bandwidth (CH Low)**

Agilent 11:20:27 Jun 14, 2007




Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)	Ref ▲		
Span Pair	Span Center		
Off			
More 1 of 2			

<b>Occupied Bandwidth</b>	<b>Occ BW % Pwr</b>	99.00 %
14.3429 MHz	<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	26.537 kHz	
<b>x dB Bandwidth</b>	8.889 MHz	

File Operation Status, A:\SCREN043.GIF file saved

**6dB Bandwidth (CH Mid)**

Agilent 11:30:13 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)	Ref ▲		
Span Pair	Span Center		
Off			
More 1 of 2			


<b>Occupied Bandwidth</b>	<b>Occ BW % Pwr</b>	99.00 %
14.2985 MHz	<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	23.292 kHz	
<b>x dB Bandwidth</b>	8.750 MHz	

File Operation Status, A:\SCREN054.GIF file saved



### 6dB Bandwidth (CH High)

Agilent 11:22:35 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)	Ref ▲		
Span Pair	Span Center		
Off			
More 1 of 2			


<b>Occupied Bandwidth</b>	<b>Occ BW % Pwr</b>	99.00 %
14.3002 MHz	<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	36.633 kHz	
<b>x dB Bandwidth</b>	8.681 MHz	

File Operation Status, A:\SCREN045.GIF file saved

### Test Plot (IEEE 802.11g mode)

### 6dB Bandwidth (CH Low)

Agilent 11:27:21 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)	Ref ▲		
Span Pair	Span Center		
Off			
More 1 of 2			


<b>Occupied Bandwidth</b>	<b>Occ BW % Pwr</b>	99.00 %
16.2527 MHz	<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	66.607 kHz	
<b>x dB Bandwidth</b>	15.901 MHz	

File Operation Status, A:\SCREN049.GIF file saved



### 6dB Bandwidth (CH Mid)

Agilent 11:26:31 Jun 14, 2007




Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

<b>Occupied Bandwidth</b>		<b>Occ BW % Pwr</b>	99.00 %
16.2551 MHz		<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	56.942 kHz		
<b>x dB Bandwidth</b>	15.126 MHz		

File Operation Status, A:\SCREN048.GIF file saved

### 6dB Bandwidth (CH High)

Agilent 11:28:40 Jun 14, 2007



Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)			
Ref	▲		
Span Pair			
Span	Center		
Off			
More 1 of 2			

<b>Occupied Bandwidth</b>		<b>Occ BW % Pwr</b>	99.00 %
16.2631 MHz		<b>x dB</b>	-6.00 dB
<b>Transmit Freq Error</b>	53.179 kHz		
<b>x dB Bandwidth</b>	16.048 MHz		

File Operation Status, A:\SCREN051.GIF file saved



### 7.4. PEAK OUTPUT POWER

#### 7.4.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


#### 7.4.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007

#### 7.4.3. TEST PROCEDURES (please refer to measurement standard)

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.

#### 7.4.4. TEST SETUP







7.4.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	17.85	0.06095	1	PASS
Mid	2437	18.01	0.06324		PASS
High	2462	17.73	0.05929		PASS

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	13.90	0.02455	1	PASS
Mid	2437	14.02	0.02523		PASS
High	2462	13.82	0.02410		PASS



**Test Plot (IEEE 802.11b mode)**

**Peak Power (CH Low)**

Agilent 09:13:46 Jun 14, 2007




Trace		
1	Trace	3
2		
3		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		

<b>Channel Power</b>	<b>Power Spectral Density</b>
17.85 dBm /20.0000 MHz	-55.16 dBm/Hz

File Operation Status, A:\SCREEN015.GIF file saved

**Peak Power (CH Mid)**

Agilent 09:07:34 Jun 14, 2007



Trace		
1	Trace	3
2		
3		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		


<b>Channel Power</b>	<b>Power Spectral Density</b>
18.01 dBm /20.0000 MHz	-55.01 dBm/Hz

File Operation Status, A:\SCREEN010.GIF file saved



Peak Power (CH High)

Agilent 09:15:32 Jun 14, 2007




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		

Copyright 2000-2003 Agilent Technologies

Test Plot (IEEE 802.11g mode)

Peak Power (CH Low)

Agilent 08:58:52 Jun 14, 2007



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		

File Operation Status, A:\SCREN005.GIF file saved



Peak Power (CH Mid)

Agilent 08:56:54 Jun 14, 2007

Freq/Channel

Ch Freq 2.437 GHz Trig Free


Center Freq 2.43700000 GHz

Channel Power

Start Freq 2.42450000 GHz

Center 2.437000000 GHz

Stop Freq 2.44950000 GHz



CF Step 2.50000000 MHz  
Auto Man

Center 2.437 00 GHz Span 25 MHz  
#Res BW 1 MHz #VBW 3 MHz Sweep 1 ms (601 pts)

Freq Offset 0.00000000 Hz

Channel Power	Power Spectral Density
14.02 dBm /20.0000 MHz	-58.99 dBm/Hz

Signal Track On Off

File Operation Status, A:\SCREEN003.GIF file saved

Peak Power (CH High)

Agilent 09:00:01 Jun 14, 2007

Trace


Ch Freq 2.462 GHz Trig Free

Trace 1 2 3

Channel Power

Sweep Time 1.000 ms

Clear Write



Max Hold

Center 2.462 00 GHz Span 25 MHz  
#Res BW 1 MHz #VBW 3 MHz Sweep 1 ms (601 pts)

Min Hold

Channel Power	Power Spectral Density
13.82 dBm /20.0000 MHz	-59.19 dBm/Hz

View

Blank

File Operation Status, A:\SCREEN007.GIF file saved



7.5. BAND EDGES MEASUREMENT:

7.5.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.5.2. TEST INSTRUMENTS


3M Semi Anechoic Chamber (977)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007
Spectrum Analyzer	Agilent	E4446A	US44300398	07/25/2007
EMI Test Receiver	R&S	ESPI3	101026	11/11/2007
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	12/13/2007
Pre-Amplifier	Miteq	NSP4000-NF	870731	01/28/2008
Bilog Antenna	Sunol	JB1	A110204-2	11/22/2007
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	02/01/2008
PSG Analog Signal Generator	Agilent	E8257C	MY43321570	12/19/2007
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Site NSA	CCS	N/A	N/A	04/06/2008

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The FCC Site Registration number is 93105,90471.  
 4. N.C.R = No Calibration Required.

**7.5.3. TEST PROCEDURES** (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

**7.5.4. TEST SETUP**





**Test Data**

**Test Plot (IEEE 802.11b mode)**

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2390.10	V	44.69	34.15	4.92	49.61	39.07	74	54	-24.39	-14.93
2483.50	V	46.91	34.28	4.92	51.83	39.20	74	54	-22.17	-14.80
2390.10	H	46.39	34.33	4.92	51.31	39.25	74	54	-22.69	-14.75
2483.50	H	44.93	34.37	4.92	49.85	39.29	74	54	-24.15	-14.71



### 7.5.5. TEST RESULTS


#### Test Plot (IEEE 802.11b mode)

#### Band Edges (CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent 19:57:38 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref) Ref $\Delta$				
Span Pair Span Center				
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent 19:58:32 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref) Ref $\Delta$				
Span Pair Span Center				
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies






Detector mode: Peak

Polarity: Horizontal

Agilent 20:01:28 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref	▲			
Span Pair				
Span	Center			
Off				
More				
1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent 20:08:47 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref	▲			
Span Pair				
Span	Center			
Off				
More				
1 of 2				

Copyright 2000-2004 Agilent Technologies




### Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical


Agilent 20:39:47 Jun 11, 2007



Detector mode: Average

Polarity: Vertical

Agilent 20:39:16 Jun 11, 2007






Detector mode: Peak

Polarity: Horizontal

Agilent 20:27:58 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref	▲			
Span Pair				
Span	Center			
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent 20:33:28 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref	▲			
Span Pair				
Span	Center			
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies



**Test Data**

**Test Plot (IEEE 802.11g mode)**

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2390.10	V	45.47	34.38	4.92	50.39	39.30	74	54	-23.61	-14.70
2483.50	V	45.99	34.68	4.92	50.91	39.60	74	54	-23.09	-14.40
2390.10	H	45.44	34.32	4.92	50.36	39.24	74	54	-23.64	-14.76
2483.50	H	45.70	34.38	4.92	50.62	39.30	74	54	-23.38	-14.70




**Test Plot (IEEE 802.11g mode)**  
**Band Edges (CH Low)**

Detector mode: Peak

Polarity: Vertical

Agilent 21:06:33 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				
Span Pair				
Span	Center			
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent 21:07:20 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				
Span Pair				
Span	Center			
Off				
More 1 of 2				


Copyright 2000-2004 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent 21:53:25 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More				
				1 of 2

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent 21:54:28 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More				
				1 of 2

Copyright 2000-2004 Agilent Technologies




### Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical

Agilent 22:18:52 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent 22:19:42 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More 1 of 2				


Copyright 2000-2004 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent 22:11:23 Jun 11, 2007




Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent 22:12:08 Jun 11, 2007



Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref				▲
Span Pair				
Span				Center
Off				
More 1 of 2				

Copyright 2000-2004 Agilent Technologies





## 7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 7.6.1. LIMITS

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


### 7.6.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2007

### 7.6.3. TEST PROCEDURES (please refer to measurement standard)

1. Place the EUT on the table and set it in transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

### 7.6.4. TEST SETUP



r



7.6.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-9.49	8.00	PASS
Mid	2437	-9.44		PASS
High	2462	-9.72		PASS

Test Data

Test mode: IEEE 802.11g

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-16.50	8.00	PASS
Mid	2437	-14.34		PASS
High	2462	-16.18		PASS









# APPENDIX I RADIO FREQUENCY EXPOSURE

## LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

## EUT Specification

<b>EUT</b>	Notebook PC
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> Bluetooth: <u>2.402GHz ~ 2.480 GHz</u>
<b>Device category</b>	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation)
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	IEEE 802.11b: 18.01 dBm (63.24mW) IEEE 802.11g: 14.02 dBm (25.23mW)
<b>Antenna gain (Max)</b>	1.82dBi (Numeric gain: 1.52)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

### Remark:

1. The maximum output power is 18.01dBm (63.24mW) at 2437MHz (with 1.52 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.



**TEST RESULTS**

**Calculation**

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{3770}$

- Where  $E =$  Field strength in Volts / meter
- $P =$  Power in Watts
- $G =$  Numeric antenna gain
- $d =$  Distance in meters
- $S =$  Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$P (mW) = P (W) / 1000$  and  
 $d (cm) = d(m) / 100$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

- Where  $d =$  Distance in cm
- $P =$  Power in mW
- $G =$  Numeric antenna gain
- $S =$  Power density in mW / cm<sup>2</sup>

**Maximum Permissible Exposure**

EUT output power = 63.24mW

Numeric Antenna gain =1.52

Substituting the MPE safe distance using d = 20 cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

- Where  $P =$  Power in mW
- $G =$  Numeric antenna gain
- $S =$  Power density in mW / cm<sup>2</sup>


→ Power density = 0.019mW / cm<sup>2</sup>

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)


## APPENDIX II PHOTOGRAPHS OF THE TEST CONFIGURATION

### Radiated Emissions Setup Photos

*Front of view*



*Back of view*





**Power Line Conducted Emissions Setup Photos**

*Front of view*



*Right of view*

