



FCC TEST REPORT

for

UMPC

MODEL: CE2A1; CW0A1

Test Report Number:
KS080618A01-RP

Issued for

First International Computer, Inc
NO.300, YangGuang St., NeiHu, Taipei,
Taiwan, 114

Issued by:

Compliance Certification Services Inc.
Kun shan Laboratory
No.10 Weiye Rd, Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, P.R.O.C
TEL: 86-512-57355888
FAX: 86-512-57370818
Issued Date: July 19, 2008



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 19, 2008	Initial Issue	ALL	Miro chueh



TABLE OF CONTENTS

1 TEST CERTIFICATION 4

2 TEST RESULT SUMMARY 5

3 EUT DESCRIPTION..... 6

4 TEST METHODOLOGY..... 7

 4.1. DESCRIPTION OF TEST MODES 7

5 SETUP OF EQUIPMENT UNDER TEST 8

 5.1. DESCRIPTION OF SUPPORT UNITS..... 8

 5.2. CONFIGURATION OF SYSTEM UNDER TEST 8

6 FACILITIES AND ACCREDITATIONS 9

 6.1. FACILITIES 9

 6.2. ACCREDITATIONS 9

 6.3. MEASUREMENT UNCERTAINTY 9

7 LIMITS AND RESULTS 10

 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT 10

 7.2. SPURIOUS EMISSIONS MEASUREMENT 17

 7.3. 6dB BANDWIDTH MEASUREMENT 35

 7.4. PEAK OUTPUT POWER 40

 7.5. BAND EDGES MEASUREMENT:..... 45

 7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT 57

APPENDIX I RADIO FREQUENCY EXPOSURE..... 62



1 TEST CERTIFICATION

Product: UNPC

Model: CE2A1; CW0A1

Brand: FIC, EVEREX

Tested: July 9, 2007-July 18,2007

Applicant: First International Computer, Inc
NO.300, YangGuang St., NeiHu, Taipei, Taiwan, 114

Manufacturer: First International Computer(suzhou), Inc
Export Processing Zone, No 200, Central Suhong Road, SuZhou Industrial Park JiangSu,
P.R.China

APPLICABLE STANDARDS

Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	<ul style="list-style-type: none"> ● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

DEVIATION FROM APPLICABLE STANDARD

None

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2003** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

Approved by:

Reviewed by:

Miro Chueh
EMC Manager
Compliance Certification Service Inc.

Lin Zhang
EMC Section Manager
Compliance Certification Service Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	Spurious Emissions ● Conducted Measurement ● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The test result judgment is decided by the limit of test standard
 2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	UMPC
Trade Name	FIC, EVEREX
Model Number	CE2A1; CW0A1
Model Discrepancy	All the above models are identical except the model designation for different market.
Wireless LAN module Model Number	AW-GE703H
Wireless LAN module Brand name	AzureWave
AC Power Cord Type	Unshielded, 1.8m (Detachable) to Power Adapter
DC Power Cable Type	Unshielded, 1.8m (Non-Detachable) at Power Adapter with a core
Frequency Range	2412 ~ 2462 MHz
Transmit Power	IEEE 802.11b:16.66dBm IEEE 802.11g:12.81dBm
Modulation Technique	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: DSSS (CCK, DQPSK, DBPSK) + OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Transmit Data Rate	IEEE 802.11b: 11, 5.5, 2, 1 Mbps IEEE 802.11g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 Mbps
Number of Channels	IEEE 802.11b , IEEE 802.11g :11 Channels
Antenna Specification	0.57dBi gain (Max)

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: **EUNCE2A1A** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

IEEE802.11b: Channel low(2412MHz), Channel middle(2437MHz) and Channel high (2462MHz) with preliminary test 11, 5.5, 2, and 1, After the preliminary scan , the following test mode 11Mbps highest data rate (the worst case) are chosen for the final testing.

IEEE802.11g: Channel low(2412MHz), Channel middle(2437MHz) and Channel high(2462MHz) with preliminary test 54/48/36/24/18/12/9/6, After the preliminary scan , the following test mode 6Mbps data rate (the worst case) are chosen for the final testing.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Trade Name	Data Cable	Power Cord
1	Monitor	CPD-G42 0	2404647	DoC	SONY	Shielded, 1.8m with a Core	Un-Shielded, 1.5m
2	HDD(USB)-9	F12-UF	A0100222-539 0021	DoC	TeraSys	N/A	Shielded, 1.8m
3	HDD(USB)-5	F12-UF	A0100214-4C g0003	DoC	TeraSys	N/A	Shielded, 1.8m
4	Speaker-1	CD-371	N/A	DoC	JINLIAN	Un-Shielded, 2.0m	N/A
5	Notebook PC	M285	1824064-1B	DoC	LEO	Line cable: Un-Shielded 1.8m LAN cable: Un-Shielded 1.8m	Shielded, 1.8m

Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, P.R.O.C

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC,A2LA
Japan	VCCI
Canada	INDUSTRY CANADA,
Taiwan	TAF

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsemc.com>.

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETR 028:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	+/- 1.13dB
Radiated emissions	30MHz ~ 200MHz	+/- 3.84dB
	200MHz ~1000MHz	+/- 3.82dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



7 LIMITS AND RESULTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

TEST INSTRUMENTS

Conducted Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMC Analyzer	Agilent	E7402A	US41160329	03/05/2009
V (V-LISN)	Schwarzbeck	NNLK 8129	8129-143	05/06/2009
LISN (EUT)	FCC	FCC-LISN-50/250-50-2-02	SN:05012	05/06/2009
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	04/18/2009
RF Current Probe	FCC	F-65A	147	05/06/2009


- NOTE:**
- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 - 2. N.C.R = No Calibration Request.



7.1.2. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

7.1.3. TEST SETUP



- For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.1.4. Data Sample:

Frequency (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Correction factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
XXX	37.58	35.11	10.10	47.68	45.21	63.49	53.49	-15.81	-8.28	L1

Frequency (MHz) = Emission frequency in MHz
 Reading (dBuV) = Uncorrected Analyzer/Receiver reading
 Correction factor (dB) = Insertion loss of LISN
 Limit (dBuV) = Limit stated in standard
 Margin (dB) = Reading (dBuV) – Limit (dBuV)
 Note = Current carrying line of reading



7.1.5. TEST RESULTS

Adapter :DELTA

Model No.	CE2A1	Test Mode	Normal Link
Environmental Conditions	25deg.C,43% RH, 991 hPa	6dB BANDWIDTH	9 kHz
Tested by:	healing		


Freq. (MHz)	Q.P. Raw reading (dBuV)	AVG Raw reading (dBuV)	Correction factor(dB)	Q.P. Amptd. (dBuV)	AVG Amptd. (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Line/Neutral
0.183	43.98	26.93	10.84	54.82	37.77	65.07	55.07	-10.25	-17.30	Line
0.242	38.27	20.52	10.33	48.60	30.85	63.37	53.37	-14.77	-22.52	Line
0.883	30.73	17.95	10.09	40.82	28.04	56.00	46.00	-15.18	-17.96	Line
1.289	30.88	17.95	10.17	41.05	28.12	56.00	46.00	-14.95	-17.88	Line
5.884	38.84	30.44	10.53	49.37	40.97	60.00	50.00	-10.63	-9.03	Line
7.956	42.25	35.00	10.43	52.68	45.43	60.00	50.00	-7.32	-4.57	Line
0.186	44.50	30.26	10.73	55.23	40.99	64.98	54.98	-9.75	-13.99	Neutral
0.251	39.51	26.40	10.26	49.77	36.66	63.11	53.11	-13.34	-16.45	Neutral
0.434	35.73	23.01	10.22	45.95	33.23	57.88	47.88	-11.93	-14.65	Neutral
0.881	31.55	18.79	10.11	41.66	28.90	56.00	46.00	-14.34	-17.10	Neutral
5.858	38.81	30.40	10.35	49.16	40.75	60.00	50.00	-10.84	-9.25	Neutral
7.895	42.17	35.16	10.37	52.54	45.53	60.00	50.00	-7.46	-4.47	Neutral

REMARKS: L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





Adapter :LI SHIN

Model No.	CE2A1	Test Mode	Normal Link
Environmental Conditions	25deg.C,43% RH, 991 hPa	6dB BANDWIDTH	9 kHz
Tested by:	healing		


Freq. (MHz)	Q.P. Raw reading (dBuV)	AVG Raw reading (dBuV)	Correction factor(dB)	Q.P. Amptd. (dBuV)	AVG Amptd. (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Line/Neutral
0.187	28.63	27.91	10.72	39.35	38.63	64.94	54.94	-25.59	-16.31	Line
0.566	26.76	17.41	10.07	36.83	27.48	56.00	46.00	-19.17	-18.52	Line
0.761	23.63	6.70	10.09	33.72	16.79	56.00	46.00	-22.28	-29.21	Line
4.752	32.39	25.98	10.50	42.89	36.48	56.00	46.00	-13.11	-9.52	Line
6.429	32.04	23.92	10.50	42.54	34.42	60.00	50.00	-17.46	-15.58	Line
7.765	36.70	30.11	10.44	47.14	40.55	60.00	50.00	-12.86	-9.45	Line
0.194	42.03	32.33	10.46	52.49	42.79	64.73	54.73	-12.24	-11.94	Neutral
0.257	34.56	25.87	10.26	44.82	36.13	62.95	52.95	-18.13	-16.82	Neutral
0.644	29.94	23.86	10.18	40.12	34.04	56.00	46.00	-15.88	-11.96	Neutral
1.554	24.68	16.60	10.24	34.92	26.84	56.00	46.00	-21.08	-19.16	Neutral
6.005	26.33	19.63	10.35	36.68	29.98	60.00	50.00	-23.32	-20.02	Neutral
7.782	34.02	25.19	10.37	44.39	35.56	60.00	50.00	-15.61	-14.44	Neutral

REMARKS:L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.2.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2008

7.2.3. TEST PROCEDURE (please refer to measurement standard)


Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz. Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.



CH Mid

30MHz ~ 2.9GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search


Mkr → CF

More
1 of 2

Unable to save file

2.9GHz ~ 26.5GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

Mkr → CF

More
1 of 2


Copyright 2000-2007 Agilent Technologies



CH High

30MHz ~ 2.9GHz

Agilent




Freq/Channel	
Center Freq	1.46500000 GHz
Start Freq	30.0000000 MHz
Stop Freq	2.90000000 GHz
CF Step	287.000000 MHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

Copyright 2000-2007 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent



Peak Search	
Next Peak	
Next Pk Right	
Next Pk Left	
Min Search	
Pk-Pk Search	
Mkr → CF	
More	1 of 2


Copyright 2000-2007 Agilent Technologies



CH Mid

30MHz ~ 2.9GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search


Mkr → CF

More
1 of 2

Copyright 2000-2007 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

Mkr → CF

More
1 of 2


Copyright 2000-2007 Agilent Technologies



CH High

30MHz ~ 2.9GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search


Mkr → CF

More
1 of 2

Copyright 2000-2007 Agilent Technologies

2.9GHz ~ 26.5GHz

Agilent



Peak Search

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

Mkr → CF

More
1 of 2

Copyright 2000-2007 Agilent Technologies



7.2.5. Radiated Emissions

7.2.5.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE: (1) The lower limit shall apply at the transition frequencies.
(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).



7.2.5.2. TEST INSTRUMENTS

3M Semi Anechoic Chamber (977)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2008
Spectrum Analyzer	Agilent	E4446A	US44300398	07/25/2009
EMI Test Receiver	R&S	ESPI3	101026	11/11/2008
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	12/13/2008
Pre-Amplifier	Miteq	NSP4000-NF	870731	01/28/2009
Bilog Antenna	Sunol	JB1	A110204-2	11/22/2008
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	02/01/2009
PSG Analog Signal Generator	Agilent	E8257C	MY43321570	12/19/2008
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Site NSA	CCS	N/A	N/A	04/06/2009


- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The FCC Site Registration number is 93105,90471.
 4. N.C.R = No Calibration Required.

7.2.5.3. TEST PROCEDURE (please refer to measurement standard)


- The EUT is placed on a turntable, which is 0.8m above ground plane.
- The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Set the spectrum analyzer in the following setting as:
 Below 1GHz:
 RBW=100kHz / VBW=300kHz / Sweep=AUTO
 Above 1GHz:
 (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
- Repeat above procedures until the measurements for all frequencies are complete.

7.2.5.4. TEST SETUP

Below 1 GHz



Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.5.5. Data Sample:

Below 1 GHz

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Remark) (dBuV)	Correction Factor (dB/m)	Result (Remark) (dBuV/m)	Limit (Peak) (dBuV/m)	Margin (dB)	Remark
xxx	V	12.12	10.21	22.33	37.00	-14.67	Peak

Above 1 GHz

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
xxx	V	65.45	63.00	-11.12	54.33	51.88	74.00	54.00	-2.12	AVG

- Frequency (MHz) = Emission frequency in MHz
- Ant.Pol. (H/V) = Antenna polarization
- Reading (dBuV) = Uncorrected Analyzer / Receiver reading
- Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
- Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
- Limit (dBuV/m) = Limit stated in standard
- Margin (dB) = Remark Result (dBuV/m) – Limit (dBuV/m)
- Peak = Peak Reading
- QP = Quasi-peak Reading
- AVG = Average Reading



7.2.5.6. TEST RESULTS

Below 1 GHz

Operation Mode: Normal Link

Test Date: July 16, 2008

Temperature: 25°C

Tested by: healing

Humidity: 42 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
40.01	V	Peak	40.3	-5.89	34.41	40.0	-5.59
49.31	V	Peak	39.15	-5.67	33.48	40.0	-6.52
120.39	V	Peak	46.32	-8.46	37.86	43.5	-5.64
230.95	V	Peak	48.92	-9.92	39	46.0	-7
555.67	V	Peak	40.94	-1.35	39.59	46.0	-6.41
945.00	V	Peak	34.69	4.15	38.84	46.0	-7.16
95.3	H	Peak	42.12	-3.71	38.41	43.5	-5.09
125.96	H	Peak	45.69	-8.16	37.53	43.5	-5.97
210.39	H	Peak	47.39	-10.37	37.02	43.5	-6.48
236.68	H	Peak	49.12	-9.92	39.2	46.0	-6.8
320.75	H	Peak	46.74	-7.24	39.5	46.0	-6.5
950.41	H	Peak	33.64	4.45	38.09	46.0	-7.91

REMARKS:

1. Measuring frequencies from 30 MHz to the 1GHz, No emission found between lowest internal used/generated frequency to 30 MHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH High

Test Date: July 10, 2008

Temperature: 26°C

Tested by: healing

Humidity: 50 % RH

Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant.Pol. (H/V), Reading (Peak/Average) (dBuV), Correction Factor (dB/m), Result (Peak/Average) (dBuV/m), Limit (Peak/Average) (dBuV/m), Margin (dB), Remark. Contains data for frequencies 4925.00 and 7386.67 MHz.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Low
Temperature: 26°C
Humidity: 50 % RH

Test Date: July 10, 2008
Tested by: healing
Polarity: Ver. / Hor.

Table with 11 columns: Frequency (MHz), Ant.Pol. (H/V), Reading (Peak) (dBuV), Reading (Average) (dBuV), Correction Factor (dB/m), Result (Peak) (dBuV/m), Result (Average) (dBuV/m), Limit (Peak) (dBuV/m), Limit (Average) (dBuV/m), Margin (dB), Remark. Contains two data rows and several empty rows.

REMARKS:

- 7. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
8. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
9. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
10. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
11. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
12. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: July 10, 2008

Temperature: 26°C

Tested by: healing

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
4875.00	V	46.56	39.17	11.08	57.64	46.83	74.00	54.00	-7.17	average
7315.82	V	34.4	25.94	18.21	52.61	40.19	74.00	54.00	-13.81	average
4875.00	H	44.74	35.00	11.08	55.82	46.08	74.00	54.00	-7.92	average
7306.67	H	35.55	23.31	18.23	53.78	41.54	74.00	54.00	-12.46	average

REMARKS:

- 7. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 8. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 9. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 10. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 11. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 12. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

7.3. 6dB BANDWIDTH MEASUREMENT

7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


7.3.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2008

7.3.3. TEST PROCEDURES (please refer to measurement standard)

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = 20MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

7.3.4. TEST SETUP





7.3.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	10072	>500	PASS
Mid	2437	10082		PASS
High	2462	10064		PASS

Test Data

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Test Result
Low	2412	16446	>500	PASS
Mid	2437	16448		PASS
High	2462	16428		PASS



Test Plot (IEEE 802.11b mode)

6dB Bandwidth (CH Low)

Agilent




Marker			
Select Marker	1	2	3 4
Normal			
Delta			
Delta Pair (Tracking Ref)	Ref ▲		
Span Pair	Center		
Off			
More 1 of 2			

Occupied Bandwidth	Occ BW % Pwr	99.00 %
14.5644 MHz	x dB	-6.00 dB
Transmit Freq Error	-42.989 kHz	
x dB Bandwidth	10.072 MHz	

Preselector is not available at this frequency

6dB Bandwidth (CH Mid)

Agilent



Meas Setup	
Avg Number	10
On	Off
Avg Mode	Repeat
Exp	
Max Hold	Off
On	
Occ BW % Pwr	99.00 %
OBW Span	20.0000000 MHz
x dB	-6.00 dB
Optimize Ref Level	

Occupied Bandwidth	Occ BW % Pwr	99.00 %
14.5638 MHz	x dB	-6.00 dB
Transmit Freq Error	-36.896 kHz	
x dB Bandwidth	10.082 MHz	

Copyright 2000-2007 Agilent Technologies



6dB Bandwidth (CH High)

Agilent

Ch Freq 2.462 GHz		Trig Free	
Occupied Bandwidth			
Ref 20 dBm Atten 30 dB			
#Peak			
Log			
10			
dB/			
Offst			
1.5			
dB			
Center 2.462 00 GHz		Span 20 MHz	
#Res BW 100 kHz		#VBW 100 kHz Sweep 2.44 ms (601 pts)	
Occupied Bandwidth		Occ BW % Pwr 99.00 %	
14.6084 MHz		x dB -6.00 dB	
Transmit Freq Error			
-4.264 kHz			
x dB Bandwidth			
10.064 MHz			

Meas Setup	
Avg Number	10
On	Off
Avg Mode	Repeat
Exp	
Max Hold	Off
On	
Occ BW % Pwr	99.00 %
OBW Span	20.0000000 MHz
x dB	-6.00 dB
Optimize Ref Level	

Copyright 2000-2007 Agilent Technologies

Test Plot (IEEE 802.11g mode)

6dB Bandwidth (CH Low)

Agilent

Ch Freq 2.412 GHz		Trig Free	
Occupied Bandwidth			
Ref 20 dBm Atten 30 dB			
#Peak			
Log			
10			
dB/			
Offst			
1.5			
dB			
Start 2.402 00 GHz		Stop 2.422 00 GHz	
#Res BW 100 kHz		#VBW 100 kHz Sweep 2.44 ms (601 pts)	
Occupied Bandwidth		Occ BW % Pwr 99.00 %	
16.3302 MHz		x dB -6.00 dB	
Transmit Freq Error			
-30.498 kHz			
x dB Bandwidth			
16.446 MHz			

Meas Setup	
Avg Number	10
On	Off
Avg Mode	Repeat
Exp	
Max Hold	Off
On	
Occ BW % Pwr	99.00 %
OBW Span	20.0000000 MHz
x dB	-6.00 dB
Optimize Ref Level	

Unable to save file



6dB Bandwidth (CH Mid)

Agilent

Ch Freq 2.437 GHz		Trig Free	
Occupied Bandwidth			
Ref 20 dBm Atten 30 dB			
#Peak	→		
Log	→		
10	→		
dB/	→		
Offst	→		
1.5	→		
dB	→		
Center 2.437 00 GHz		Span 20 MHz	
#Res BW 100 kHz	#VBW 100 kHz	Sweep 2.44 ms (601 pts)	
Occupied Bandwidth		Occ BW % Pwr	99.00 %
16.3307 MHz		x dB	-6.00 dB
Transmit Freq Error		-25.888 kHz	
x dB Bandwidth		16.448 MHz	

Marker				
Select Marker	1	2	3	4
Normal				
Delta				
Delta Pair (Tracking Ref)				
Ref	▲			
Span Pair				
Span	Center			
Off				
More				
1 of 2				

File Operation Status, A:\SCREN061.GIF file saved

6dB Bandwidth (CH High)

Agilent

Ch Freq 2.462 GHz		Trig Free	
Occupied Bandwidth			
Ref 20 dBm Atten 30 dB			
#Peak	→		
Log	→		
10	→		
dB/	→		
Offst	→		
1.5	→		
dB	→		
Center 2.462 00 GHz		Span 20 MHz	
#Res BW 100 kHz	#VBW 100 kHz	Sweep 2.44 ms (601 pts)	
Occupied Bandwidth		Occ BW % Pwr	99.00 %
16.3265 MHz		x dB	-6.00 dB
Transmit Freq Error		-26.802 kHz	
x dB Bandwidth		16.428 MHz	

Meas Setup	
Avg Number	10
On	Off
Avg Mode	
Exp	Repeat
Max Hold	
On	Off
Occ BW % Pwr	
99.00 %	
OBW Span	
20.0000000 MHz	
x dB	
-6.00 dB	
Optimize	
Ref Level	

Copyright 2000-2007 Agilent Technologies



7.4. PEAK OUTPUT POWER

7.4.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


7.4.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	08/15/2009

7.4.3. TEST PROCEDURES (please refer to measurement standard)

- 1 Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2 Set RBW = 1 MHz.
- 3 Set VBW ≥ 3 MHz.
- 4 Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode.
- 5 Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to δhichfree runöhich.
- 6 Trace average 100 traces in power averaging mode.
- 7 Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer’s band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

7.4.4. TEST SETUP



7.4.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	15.84	0.03837	1	PASS
Mid	2437	16.27	0.04236		PASS
High	2462	16.66	0.04634		PASS

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	11.96	0.01570	1	PASS
Mid	2437	12.34	0.01714		PASS
High	2462	12.81	0.01910		PASS



Test Plot (IEEE 802.11b mode)

Peak Power (CH Low)

Agilent




Freq/Channel
Center Freq 2.41200000 GHz
Start Freq 2.39950000 GHz
Stop Freq 2.42450000 GHz
CF Step 2.50000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

Channel Power	Power Spectral Density
15.84 dBm /20.0000 MHz	-57.17 dBm/Hz

Copyright 2000-2007 Agilent Technologies

Peak Power (CH Mid)

Agilent



Freq/Channel
Center Freq 2.43700000 GHz
Start Freq 2.42450000 GHz
Stop Freq 2.44950000 GHz
CF Step 2.50000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off


Channel Power	Power Spectral Density
16.27 dBm /20.0000 MHz	-56.74 dBm/Hz

Copyright 2000-2007 Agilent Technologies



Peak Power (CH High)

Agilent




Freq/Channel
Center Freq 2.46200000 GHz
Start Freq 2.44950000 GHz
Stop Freq 2.47450000 GHz
CF Step 2.50000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

Copyright 2000-2007 Agilent Technologies

Test Plot (IEEE 802.11g mode)

Peak Power (CH Low)

Agilent




Freq/Channel
Center Freq 2.41200000 GHz
Start Freq 2.39950000 GHz
Stop Freq 2.42450000 GHz
CF Step 2.50000000 MHz Auto Man
Freq Offset 0.00000000 Hz
Signal Track On Off

Copyright 2000-2007 Agilent Technologies



Peak Power (CH Mid)

Agilent




Freq/Channel	
Center Freq	2.43700000 GHz
Start Freq	2.42450000 GHz
Stop Freq	2.44950000 GHz
CF Step	2.50000000 MHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

Copyright 2000-2007 Agilent Technologies

Peak Power (CH High)

Agilent



BW/Avg	
Res BW	1.0 MHz Auto Man
Video BW	3.0 MHz Auto Man
VBW/RBW	10.00000 Auto Man
Average	100 On Off
Avg/VBW Type	Log-Pwr (Video) Auto Man
Span/RBW	106 Auto Man

Copyright 2000-2007 Agilent Technologies



7.5. BAND EDGES MEASUREMENT:

7.5.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.5.2. TEST INSTRUMENTS


Table with 5 columns: Name of Equipment, Manufacturer, Model, Serial Number, Calibration Due. Title: 3M Semi Anechoic Chamber (977). Rows include Spectrum Analyzer, EMI Test Receiver, Pre-Amplifier, Bilog Antenna, Horn-antenna, PSG Analog Signal Generator, Turn Table, Antenna Tower, Controller, and Site NSA.

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The FCC Site Registration number is 93105,90471.
4. N.C.R = No Calibration Required.

7.5.3. TEST PROCEDURES (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

7.5.4. TEST SETUP





Test Data

Test Plot (IEEE 802.11b mode)

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak	AV				
					(dBuV/m)	(dBuV/m)				
2390.10	V	45.29	34.28	4.92	50.21	39.20	74	54	-23.79	-14.80
2483.50	V	45.27	34.00	4.92	50.19	38.92	74	54	-23.81	-15.08
2390.10	H	46.55	34.35	4.92	51.47	39.27	74	54	-22.53	-14.73
2483.50	H	45.74	35.09	4.92	50.66	40.01	74	54	-23.34	-13.99



7.5.5. TEST RESULTS


Test Plot (IEEE 802.11b mode)

Band Edges (CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent




Freq/Channel	
Center Freq	2.36500000 GHz
Start Freq	2.31000000 GHz
Stop Freq	2.42000000 GHz
CF Step	11.00000000 MHz Auto Man
Freq Offset	0.00000000 Hz
Signal Track	On Off

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent



Trace		
1	2	3
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		


Copyright 2000-2007 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		

Copyright 2000-2007 Agilent Technologies




Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		


Copyright 2000-2007 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More		
1 of 2		

Copyright 2000-2007 Agilent Technologies



Test Data

Test Plot (IEEE 802.11g mode)

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Peak Margin (dB)	AV Margin (dB)
					Peak (dBuV/m)	AV (dBuV/m)				
2390.10	V	46.37	35.18	4.92	51.29	40.10	74	54	-22.71	-13.90
2483.50	V	51.07	37.62	4.92	55.99	42.54	74	54	-18.01	-11.46
2390.10	H	46.67	35.27	4.92	51.59	40.19	74	54	-22.41	-13.81
2483.50	H	56.78	39.89	4.92	61.7	44.81	74	54	-12.30	-9.19




Test Plot (IEEE 802.11g mode)
Band Edges (CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		


Copyright 2000-2007 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

Unable to save file




Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Vertical

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		


Copyright 2000-2007 Agilent Technologies



Detector mode: Peak

Polarity: Horizontal

Agilent




Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

Copyright 2000-2007 Agilent Technologies

Detector mode: Average

Polarity: Horizontal

Agilent



Trace		
1	2	3
Trace		
Clear Write		
Max Hold		
Min Hold		
View		
Blank		
More 1 of 2		

File Operation Status, A:\SCREN056.GIF file saved

7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT

7.6.1. LIMITS

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


7.6.2. TEST INSTRUMENTS

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	11/16/2008

7.6.3. TEST PROCEDURES (please refer to measurement standard)

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.6.4. TEST SETUP



r



7.6.5. TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-14.15	8.00	PASS
Mid	2437	-14.86		PASS
High	2462	-14.06		PASS

Test Data

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2412	-17.31	8.00	PASS
Mid	2437	-16.95		PASS
High	2462	-16.43		PASS



Test Plot (IEEE 802.11b mode)

PPSD (CH Low)


Agilent



Copyright 2000-2007 Agilent Technologies

PPSD (CH Mid)

Agilent




Copyright 2000-2007 Agilent Technologies



PPSD (CH High)

Agilent




Copyright 2000-2007 Agilent Technologies

Test Plot (IEEE 802.11g mode)

PPSD (CH Low)

Agilent




Copyright 2000-2007 Agilent Technologies



PPSD (CH Mid)


Agilent



Copyright 2000-2007 Agilent Technologies

PPSD (CH High)

Agilent



Copyright 2000-2007 Agilent Technologies



APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	UMPC
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> Bluetooth: <u>2.402GHz ~ 2.480 GHz</u>
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11b: 16.66 dBm (46.34mW) IEEE 802.11g: 12.81 dBm (19.10mW)
Antenna gain (Max)	0.57dBi (Numeric gain: 1.14)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

Remark:

1. The maximum output power is 16.66dBm (46.34mW) at 2462MHz (with 1.14 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.



TEST RESULTS

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where $E =$ Field strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d =$ Distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

Maximum Permissible Exposure

EUT output power = 46.34mW

Numeric Antenna gain =1.14

Substituting the MPE safe distance using d = 20 cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

→ Power density =0.011mW / cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)