



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Notebook

Trade Name: FIC

Model: CW001

Issued to

**First International Computer Inc
4FL.,No.300,Yang Guang St., NeiHu,
Taipei, Taiwan, 114**

Issued by

**Compliance Certification Services Inc.
No. 11, Wu-Gong 6th Rd., Wugu Industrial Park,
Taipei Hsien 248, Taiwan (R.O.C.)
<http://www.ccsemc.com.tw>
service@tw.ccsemc.com**



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



TABLE OF CONTENTS

- 1. TEST RESULT CERTIFICATION.....3**
- 2. EUT DESCRIPTION4**
- 3. TEST METHODOLOGY5**
 - 3.1 EUT CONFIGURATION5
 - 3.2 EUT EXERCISE.....5
 - 3.3 GENERAL TEST PROCEDURES.....5
 - 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....6
 - 3.5 DESCRIPTION OF TEST MODES7
- 4. INSTRUMENT CALIBRATION.....8**
 - 4.1 MEASURING INSTRUMENT CALIBRATION.....8
 - 4.2 MEASUREMENT EQUIPMENT USED.....8
 - 4.3 MEASUREMENT UNCERTAINTY9
- 5. FACILITIES AND ACCREDITATIONS10**
 - 5.1 FACILITIES10
 - 5.2 EQUIPMENT.....10
 - 5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....11
- 6. SETUP OF EQUIPMENT UNDER TEST12**
 - 6.1 SETUP CONFIGURATION OF EUT.....12
 - 6.2 SUPPORT EQUIPMENT.....12
- 7. FCC PART 15.247 REQUIREMENTS.....13**
 - 7.1 20 DB BANDWIDTH13
 - 7.2 PEAK POWER.....18
 - 7.3 AVERAGE POWER.....20
 - 7.4 BAND EDGES MEASUREMENT.....21
 - 7.5 PEAK POWER SPECTRAL DENSITY.....30
 - 7.6 FREQUENCY SEPARATION.....36
 - 7.7 NUMBER OF HOPPING FREQUENCY.....39
 - 7.8 TIME OF OCCUPANCY (DWELL TIME).....42
 - 7.9 SPURIOUS EMISSIONS.....55
 - 7.10 POWERLINE CONDUCTED EMISSIONS.....70
- APPENDIX I RADIO FREQUENCY EXPOSURE.....73**
- APPENDIX II PHOTOGRAPHS OF TEST SETUP.....74**



1. TEST RESULT CERTIFICATION

Applicant: First International Computer Inc
4FL.,No.300,Yang Guang St., NeiHu,
Taipei, Taiwan, 114

Equipment Under Test: Notebook

Trade Name: FIC

Model: CW001

Date of Test: November 15 ~ December 4, 2008

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2003** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Rex Lai
Section Manager
Compliance Certification Services Inc.

Amanda Wu
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Notebook		
Trade Name	FIC		
Model Number	CW001		
Model Discrepancy	N/A		
Power Supply	1. VDC from Power Adapter 2. Battery: 14.4V, 2200mAh		
Power Adapter Manufacturer	DELTA	Model	ADP-40MH AD
Power Adapter Power Rating	For ADP-40MH AD I/P: 100-240V~1.2A, 50-60Hz O/P: 20V, 2A		
Frequency Range	2402 ~ 2480 MHz		
Transmit Power	3.13 dBm		
Modulation Technique	GFSK for 1Mbps; $\pi/4$ -DQPSK for 2Mbps; 8DPSK for 3Mbps		
Transmit Data Rate	1, 2, 3Mbps		
Number of Channels	79 Channels		
Antenna Specification	Gain: 2.90 dBi		
Antenna Designation	PIFA Antenna		

Remark:

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: EUNCW001-01 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2003 and FCC CFR 47 Part 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: CW001) had been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting mode was programmed.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

After the preliminary test, the power of the Main antenna is maximal and therefore had been tested under operating condition.

During the preliminary test, GFSK, $\pi/4$ -QPSK & 8DPSK with DH1 were pre-tested and found that 8DPSK emits the highest output power. Then the tests were carried on with DH1 compare to DH3 & DH5 and found that 8DPSK with DH5 emit the highest output power, and therefore had been tested under operating condition.

Following channels were selected for the for radiated emission and conducted emissions testing only as listed below:

Tested Channel	Modulation Type	Packet Type	Date Rate
Low, Mid, High	GFSK	DH 5	1
Low, Mid, High	8DPSK	DH 5	3



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	02/24/2009
Power Meter	Agilent	E4416A	GB41291611	04/06/2009
Power Sensor	Agilent	E9327A	US40441097	06/19/2009

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	10/07/2009
Test Receiver	Rohde&Schwarz	ESCI	100064	11/29/2009
Switch Controller	TRC	Switch Controller	SC94050010	05/03/2009
4 Port Switch	TRC	4 Port Switch	SC94050020	05/03/2009
Horn-Antenna	TRC	HA-0502	06	06/04/2009
Horn-Antenna	TRC	HA-0801	04	10/20/2009
Horn-Antenna	TRC	HA-1201A	01	10/15/2009
Horn-Antenna	TRC	HA-1301A	01	10/15/2009
Bilog- Antenna	Sunol Sciences	JB3	A030205	03/28/2009
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC MRA: TW1039 IC: IC 2324G-1/-2	10/17/2010 11/04/2010
Test S/W	LABVIEW (V 6.1)			

Powerline Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver 9kHz-30MHz	Rohde & Schwarz	ESHS30	828144/003	11/18/2009
Two-Line V-Network 9kHz-30MHz	Schaffner	NNB41	03/10013	06/11/2009
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	04/09/2009
ISN 9kHz-30MHz	FCC	FCC-TLISN-T4	20167	10/16/2009
Test S/W	LABVIEW (V 6.1)			



4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Powerline Conducted Emission	+/- 2.81
3M Semi Anechoic Chamber / 30MHz ~ 1GHz	+/-3.7046
3M Semi Anechoic Chamber / 1GHz Above	+/-3.0958

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.199, Chungshen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4: 2003 and CISPR Publication 22.

5.2 EQUIPMENT




Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	 FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	 Testing Laboratory 1309
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	 IC 2324G-1 IC 2324G-2

** No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.*



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	LCD Monitor	SAMSUNG	959NF	AQ19H2RT706126P	FCC DoC	Shielded, 1.8m with 2 cores	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
2.	PS/2 Mouse	DELL	MO56UC	FOA0094M	FCC DoC	Shielded, 1.8m	N/A
3	USB 2.0 External HDD	TeraSyS	F12-U	A0100214-43b0012	FCC DoC	Shielded, 1.8m	N/A
4	Multimedia Earphone	Labtec	Axis-301	N/A	FCC DoC	Unshielded, 1.8m*2	N/A




7. FCC PART 15.247 REQUIREMENTS

7.120 DB BANDWIDTH

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=10kHz, VBW = 30 kHz, Span = 1.5MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS

No non-compliance noted.

Test Data

For GFSK / DH5

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2402	0.941
Mid	2441	0.947
High	2480	0.941

For 8DPSK / DH5

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
Low	2402	1.270
Mid	2441	1.273
High	2480	1.260



Test Plot


For GFSK / DH5

20dB Bandwidth (CH Low)

Agilent 15:09:32 Nov 28, 2008

R L

Δ Mkr2 941 kHz
-0.63 dB



Center 2.402 000 GHz Span 1.5 MHz
#Res BW 10 kHz #VBW 30 kHz Sweep 14.36 ms (601 pts)


Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.401 997 GHz	-2.69 dBm
2R	(1)	Freq	2.401 539 GHz	-22.14 dBm
2Δ	(1)	Freq	941 kHz	-0.63 dB

20dB Bandwidth (CH Mid)

Agilent 15:12:37 Nov 28, 2008

R L

Δ Mkr2 947 kHz
0.56 dB



Center 2.441 000 GHz Span 1.5 MHz
#Res BW 10 kHz #VBW 30 kHz Sweep 14.36 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.440 997 GHz	-3.23 dBm
2R	(1)	Freq	2.440 534 GHz	-24.28 dBm
2Δ	(1)	Freq	947 kHz	0.56 dB




20dB Bandwidth (CH High)

Agilent 15:11:40 Nov 28, 2008

R T

Δ Mkr2 941 kHz
0.31 dB



Center 2.480 000 GHz

Span 1.5 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 14.36 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 995 GHz	-4.32 dBm
2R	(1)	Freq	2.479 537 GHz	-24.69 dBm
2Δ	(1)	Freq	941 kHz	0.31 dB



For 8DPSK / DH5

20dB Bandwidth (CH Low)

Agilent 15:40:02 Nov 28, 2008


R T

Δ Mkr2 1.270 MHz

0.15 dB

Ref 11 dBm

#Atten 14 dB



Center 2.402 000 GHz

Span 2 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 19.12 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.401 997 GHz	-3.08 dBm
2R	(1)	Freq	2.401 347 GHz	-23.26 dBm
2Δ	(1)	Freq	1.270 MHz	0.15 dB

20dB Bandwidth (CH Mid)

Agilent 15:40:39 Nov 28, 2008


R T

Δ Mkr2 1.273 MHz

-0.19 dB

Ref 11 dBm

#Atten 14 dB



Center 2.441 000 GHz

Span 2 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 19.12 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.440 997 GHz	-3.50 dBm
2R	(1)	Freq	2.440 347 GHz	-23.66 dBm
2Δ	(1)	Freq	1.273 MHz	-0.19 dB




20dB Bandwidth (CH High)

Agilent 15:41:26 Nov 28, 2008

R T

Δ Mkr2 1.260 MHz



Center 2.480 000 GHz Span 2 MHz

#Res BW 10 kHz #VBW 30 kHz Sweep 19.12 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.479 997 GHz	-6.32 dBm
2R	(1)	Freq	2.479 357 GHz	-26.97 dBm
2Δ	(1)	Freq	1.260 MHz	0.76 dB




7.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
3. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted.



Test Data

For GFSK / DH5

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	3.13	0.0021	0.125	PASS
Mid	2441	2.93	0.0020		PASS
High	2480	1.78	0.0015		PASS

For 8DPSK / DH5

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	2.71	0.0019	0.125	PASS
Mid	2441	2.44	0.0018		PASS
High	2480	0.95	0.0012		PASS




7.3 AVERAGE POWER

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted.

Test Data

For GFSK / DH5

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	1.85	0.00153
Mid	2441	1.63	0.00146
High	2480	0.48	0.00112

For 8DPSK / DH5


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-0.78	0.00084
Mid	2441	-1.12	0.00077
High	2480	-2.54	0.00056

7.4 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.



For GFSK / DH5

Band Edges (CH Low)


Detector mode: Peak

Polarity: Vertical

Agilent 14:31:30 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
47.34 dBµV




Detector mode: Average

Polarity: Vertical

Agilent 14:32:01 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
36.30 dBµV





Detector mode: Peak

Polarity: Horizontal

Agilent 14:34:23 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
46.61 dBµV

Ref 117 dBµV


#Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dBµV
LgAv

V1 S2
S3 FC
A AA

£(f):
FTun
Swp



Start 2.310 00 GHz

Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent 14:35:04 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
34.98 dBµV

Ref 117 dBµV


#Atten 20 dB

#Peak
Log
10
dB/

DI
54.0
dBµV
LgAv

M1 S2
S3 FC
A AA

£(f):
FTun
Swp



Start 2.310 00 GHz

Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 7.408 s (601 pts)



Band Edges (CH High)

Detector mode: Peak

Polarity: Vertical


Agilent 14:38:51 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
53.17 dBμV

Ref 117 dBμV

#Atten 20 dB



Start 2.480 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Vertical


Agilent 14:39:20 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
41.27 dBμV

Ref 117 dBμV

#Atten 20 dB



Start 2.480 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 1.56 s (601 pts)



Detector mode: Peak

Polarity: Horizontal

Agilent 14:37:56 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
51.94 dBμV


Ref 117 dBμV

#Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dBμV
LgAv

V1 S2
S3 FC
A AA
£(f):
FTun
Swp



Start 2.480 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent 14:37:29 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
40.58 dBμV


Ref 117 dBμV

#Atten 20 dB

#Peak
Log
10
dB/

DI
54.0
dBμV
LgAv

M1 S2
S3 FC
A AA
£(f):
FTun
Swp



Start 2.480 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 1.56 s (601 pts)



For 8DPSK / DH5

Band Edges (CH Low)


Detector mode: Peak

Polarity: Vertical

Agilent 14:44:31 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
47.14 dBµV




Detector mode: Average

Polarity: Vertical

Agilent 14:44:56 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
35.59 dBµV





Detector mode: Peak

Polarity: Horizontal

Agilent 14:43:43 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
46.95 dBμV


Ref 117 dBμV

#Atten 20 dB

#Peak
Log
10
dB/

DI
74.0
dBμV
LgAv

V1 S2
S3 FC
A AA
£(f):
FTun
Swp



Start 2.310 00 GHz

Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal

Agilent 14:43:17 Nov 15, 2008

R T

Mkr1 2.390 00 GHz
34.74 dBμV


Ref 117 dBμV

#Atten 20 dB

#Peak
Log
10
dB/

DI
54.0
dBμV
LgAv

V1 S2
S3 FC
A AA
£(f):
FTun
Swp



Start 2.310 00 GHz

Stop 2.405 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 7.408 s (601 pts)



Band Edges (CH High)


Detector mode: Peak

Polarity: Vertical

Agilent 14:40:54 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
56.91 dBμV




Detector mode: Average

Polarity: Vertical

Agilent 14:40:25 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
44.08 dBμV






Detector mode: Peak

Polarity: Horizontal

Agilent 14:41:46 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
56.12 dBμV




Detector mode: Average

Polarity: Horizontal

Agilent 14:42:14 Nov 15, 2008

R T

Mkr1 2.483 50 GHz
43.30 dBμV




7.5 PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted



Test Data

For GFSK / DH5

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-8.45	8.00	PASS
Mid	2441	-8.58		PASS
High	2480	-9.88		PASS

For 8DPSK / DH5

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-10.43	8.00	PASS
Mid	2441	-10.63		PASS
High	2480	-11.86		PASS



Test Plot


For GFSK / DH5

PPSD (CH Low)

Agilent 15:25:16 Nov 28, 2008

R T

Mkr1 2.401 975 9 GHz
-8.45 dBm




PPSD (CH Mid)

Agilent 15:29:20 Nov 28, 2008

R T

Mkr1 2.440 976 4 GHz
-8.58 dBm






PPSD (CH High)

Agilent 15:32:09 Nov 28, 2008

R T

Mkr1 2.479 976 4 GHz

-9.88 dBm





For GFSK / DH5


PPSD (CH Low)

Agilent 15:59:18 Nov 28, 2008

R T

Mkr1 2.401 999 0 GHz

-10.43 dBm



Center 2.402 000 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)


PPSD (CH Mid)

Agilent 15:57:18 Nov 28, 2008

R T

Mkr1 2.440 999 5 GHz

-10.63 dBm



Center 2.441 000 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)




PPSD (CH High)

Agilent 15:55:20 Nov 28, 2008

R T

Mkr1 2.479 999 0 GHz

-11.86 dBm






7.6 FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

For GFSK / DH5

Channel Separation (MHz)	Two-thirds of the 20 dB bandwidth	Channel Separation Limit	Result
1.00	631	Two-thirds of the 20 dB bandwidth	Pass

For 8DPSK / DH5

Channel Separation (MHz)	Two-thirds of the 20 dB bandwidth	Channel Separation Limit	Result
1.00	847	Two-thirds of the 20 dB bandwidth	Pass




Test Plot

For GFSK / DH5

Measurement of Channel Separation

Agilent 15:35:32 Nov 28, 2008


R L



Measurement of 20dB Bandwidth

Agilent 15:12:37 Nov 28, 2008

R L






For 8DPSK / DH5

Measurement of Channel Separation

Agilent 16:06:52 Nov 28, 2008

R T

Mkr2 2.441 005 GHz




Measurement of 20dB Bandwidth

Agilent 15:40:39 Nov 28, 2008

R T

Δ Mkr2 1.273 MHz

-0.19 dB






7.7 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = auto and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=510kHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted.

Test Data

For GFSK / 8DPSK

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS




For 8DPSK

2.4 GHz – 2.4415 GHz

Agilent 15:51:02 Nov 28, 2008


R T



2.4415 GHz – 2.4835 GHz

Agilent 15:52:00 Nov 28, 2008

R T




7.8 TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted.



Test Data

For GFSK

DH 1

CH Low: $0.4167 * (1600/2)/79 * 31.6 = 133.344$ (ms)

CH Mid: $0.4167 * (1600/2)/79 * 31.6 = 133.344$ (ms)

CH High: $0.4167 * (1600/2)/79 * 31.6 = 133.344$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.4167	133.344	31.60	400.00	PASS
Mid	0.4167	133.344	31.60		PASS
High	0.4167	133.344	31.60		PASS

DH 3

CH Low: $1.650 * (1600/4)/79 * 31.6 = 264.000$ (ms)

CH Mid: $1.667 * (1600/4)/79 * 31.6 = 266.720$ (ms)

CH High: $1.667 * (1600/4)/79 * 31.6 = 266.720$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.650	264.000	31.60	400.00	PASS
Mid	1.667	266.720	31.60		PASS
High	1.667	266.720	31.60		PASS

DH 5

CH Low: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH Mid: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH High: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.917	311.147	31.60	400.00	PASS
Mid	2.917	311.147	31.60		PASS
High	2.917	311.147	31.60		PASS



Test Plot


DH 1

(CH Low)

Agilent 15:17:04 Nov 28, 2008

R L

Δ Mkr1 416.7 μs
-2.13 dB



Center 2.402 000 GHz

Res BW 1 MHz

#VBW 1 MHz


Span 0 Hz
Sweep 10 ms (601 pts)

(CH Mid)

Agilent 15:16:18 Nov 28, 2008

R T

Δ Mkr1 416.7 μs
-4.97 dB



Center 2.441 000 GHz

Res BW 1 MHz

#VBW 1 MHz

Span 0 Hz
Sweep 10 ms (601 pts)




(CH High)

Agilent 15:16:44 Nov 28, 2008

R T

Δ Mkr1 416.7 μs
-15.25 dB



Center 2.480 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)


DH 3

(CH Low)

Agilent 15:17:57 Nov 28, 2008

R T

Δ Mkr1 1.65 ms
-0.04 dB



Center 2.402 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)




(CH Mid)

Agilent 15:18:22 Nov 28, 2008

R T

Δ Mkr1 1.667 ms
-15.72 dB




Center 2.441 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)

(CH High)

Agilent 15:18:44 Nov 28, 2008

R T

Δ Mkr1 1.667 ms
-2.60 dB



Center 2.480 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)




DH 5

(CH Low)

Agilent 15:20:09 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-10.64 dB



Center 2.402 000 GHz

Res BW 1 MHz

#VBW 1 MHz


Span 0 Hz
Sweep 10 ms (601 pts)

(CH Mid)

Agilent 15:19:47 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-4.63 dB



Center 2.441 000 GHz

Res BW 1 MHz

#VBW 1 MHz

Span 0 Hz
Sweep 10 ms (601 pts)




(CH High)

Agilent 15:19:21 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-9.50 dB





For 8DPSK

DH 1

CH Low: $0.4333 * (1600/2)/79 * 31.6 = 138.656$ (ms)

CH Mid: $0.4333 * (1600/2)/79 * 31.6 = 138.656$ (ms)

CH High: $0.4167 * (1600/2)/79 * 31.6 = 133.344$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.4333	138.656	31.60	400.00	PASS
Mid	0.4333	138.656	31.60		PASS
High	0.4167	133.344	31.60		PASS

DH 3

CH Low: $1.667 * (1600/4)/79 * 31.6 = 266.720$ (ms)

CH Mid: $1.683 * (1600/4)/79 * 31.6 = 269.280$ (ms)

CH High: $1.683 * (1600/4)/79 * 31.6 = 269.280$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.667	266.720	31.60	400.00	PASS
Mid	1.683	269.280	31.60		PASS
High	1.683	269.280	31.60		PASS

DH 5

CH Low: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH Mid: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH High: $2.917 * (1600/6)/79 * 31.6 = 311.147$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.917	311.147	31.60	400.00	PASS
Mid	2.917	311.147	31.60		PASS
High	2.917	311.147	31.60		PASS



Test Plot


DH 1

(CH Low)

Agilent 15:44:13 Nov 28, 2008

R T

Δ Mkr1 433.3 μs
-5.62 dB




(CH Mid)

Agilent 15:44:37 Nov 28, 2008

R T

Δ Mkr1 433.3 μs
2.61 dB






(CH High)

Agilent 15:44:59 Nov 28, 2008

R T

Δ Mkr1 416.7 μs
-3.89 dB



Center 2.480 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)


DH 3

(CH Low)

Agilent 15:46:46 Nov 28, 2008

R T

Δ Mkr1 1.667 ms
-1.44 dB



Center 2.402 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)




(CH Mid)

Agilent 15:46:23 Nov 28, 2008

R T

Δ Mkr1 1.683 ms
-11.96 dB




Center 2.441 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)

(CH High)

Agilent 15:45:55 Nov 28, 2008

R T

Δ Mkr1 1.683 ms
4.36 dB



Center 2.480 000 GHz Span 0 Hz
Res BW 1 MHz #VBW 1 MHz Sweep 10 ms (601 pts)




DH 5

(CH Low)

Agilent 15:47:37 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-0.70 dB




(CH Mid)

Agilent 15:48:09 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-0.99 dB






(CH High)

Agilent 15:48:47 Nov 28, 2008

R T

Δ Mkr1 2.917 ms
-1.34 dB






7.9 SPURIOUS EMISSIONS

7.9.1 Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




Test Plot

For GFSK / DH5

CH Low

Agilent 15:34:24 Nov 28, 2008


R T



CH Mid

Agilent 15:33:50 Nov 28, 2008

R L






CH High

Agilent 15:32:56 Nov 28, 2008

R T

Mkr1 2.50 GHz
-1.01 dBm






For 8DPSK / DH5

CH Low

Agilent 16:02:51 Nov 28, 2008


R T



CH Mid

Agilent 16:03:34 Nov 28, 2008

R T






CH High

Agilent 16:04:35 Nov 28, 2008

R T

Mkr1 2.50 GHz
-2.77 dBm





7.9.2 Radiated Emissions

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.



Below 1 GHz

Operation Mode: Normal Link

Test Date: November 26, 2008

Temperature: 23°C

Tested by: Mimic Yang

Humidity: 53 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
366.27	V	46.64	-7.23	39.41	46.00	-6.59	Peak
405.07	V	43.43	-6.00	37.42	46.00	-8.58	Peak
495.60	V	41.80	-4.27	37.53	46.00	-8.47	Peak
539.25	V	41.23	-3.21	38.01	46.00	-7.99	Peak
584.52	V	41.68	-2.62	39.06	46.00	-6.94	Peak
799.53	V	33.96	0.42	34.37	46.00	-11.63	Peak
299.98	H	42.02	-8.61	33.41	46.00	-12.59	Peak
335.55	H	41.41	-8.04	33.37	46.00	-12.63	Peak
366.27	H	44.51	-7.23	37.27	46.00	-8.73	Peak
405.07	H	39.51	-6.00	33.51	46.00	-12.49	Peak
434.17	H	38.76	-5.74	33.02	46.00	-12.98	Peak
801.15	H	34.61	0.41	35.02	46.00	-10.98	Peak

Remark:

- No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)*
- Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.*
- Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.*
- Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.*
- Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).*



Above 1 GHz

For GFSK / DH5

Operation Mode: TX / CH Low

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	61.96	38.97	-7.52	54.44	31.45	74.00	54.00	-22.55	AVG
1866.67	V	63.36	38.83	-5.29	58.07	33.54	74.00	54.00	-20.46	AVG
4850.00	V	49.11	---	0.29	49.40	---	74.00	54.00	-4.60	Peak
N/A										
1333.33	H	57.26	---	-8.75	48.50	---	74.00	54.00	-5.50	Peak
1600.00	H	56.65	---	-7.52	49.13	---	74.00	54.00	-4.87	Peak
1833.33	H	56.67	49.88	-5.57	51.10	44.31	74.00	54.00	-9.69	AVG
1866.67	H	59.34	38.76	-5.29	54.05	33.47	74.00	54.00	-20.53	AVG
4766.67	H	48.64	---	0.48	49.12	---	74.00	54.00	-4.88	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / CH Mid

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	54.09	---	-7.52	46.57	---	74.00	54.00	-7.43	Peak
1826.67	V	52.87	---	-5.63	47.24	---	74.00	54.00	-6.76	Peak
6383.33	V	49.08	---	1.61	50.70	---	74.00	54.00	-3.30	Peak
N/A										
1600.00	H	54.11	---	-7.52	46.58	---	74.00	54.00	-7.42	Peak
1836.67	H	56.82	43.36	-5.54	51.28	37.82	74.00	54.00	-16.18	AVG
1866.67	H	54.85	---	-5.29	49.56	---	74.00	54.00	-4.44	Peak
4891.67	H	48.68	---	0.20	48.88	---	74.00	54.00	-5.12	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / CH High

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	56.56	---	-7.52	49.03	---	74.00	54.00	-4.97	Peak
1866.67	V	52.93	---	-5.29	47.64	---	74.00	54.00	-6.36	Peak
6133.33	V	48.99	---	1.32	50.31	---	74.00	54.00	-3.69	Peak
N/A										
1600.00	H	52.43	---	-7.52	44.91	---	74.00	54.00	-9.09	Peak
1836.67	H	56.02	---	-5.54	50.48	---	74.00	54.00	-3.52	Peak
4916.67	H	48.45	---	0.15	48.59	---	74.00	54.00	-5.41	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



For 8DPSK / DH5

Operation Mode: TX / CH Low

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	56.68	---	-7.52	49.15	---	74.00	54.00	-4.85	Peak
1866.67	V	65.32	38.99	-5.29	60.03	33.70	74.00	54.00	-20.30	AVG
4458.33	V	48.15	---	1.04	49.19	---	74.00	54.00	-4.81	Peak
5275.00	V	48.62	---	0.19	48.81	---	74.00	54.00	-5.19	Peak
N/A										
1600.00	H	54.76	---	-7.52	47.23	---	74.00	54.00	-6.77	Peak
1836.67	H	56.69	43.24	-5.54	51.14	37.70	74.00	54.00	-16.30	AVG
3958.33	H	47.99	---	0.69	48.69	---	74.00	54.00	-5.31	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / CH Mid

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	56.13	---	-7.52	48.60	---	74.00	54.00	-5.40	Peak
1840.00	V	53.41	---	-5.52	47.89	---	74.00	54.00	-6.11	Peak
1896.67	V	52.67	---	-5.04	47.63	---	74.00	54.00	-6.37	Peak
5633.33	V	49.29	---	0.59	49.88	---	74.00	54.00	-4.12	Peak
N/A										
1600.00	H	54.38	---	-7.52	46.86	---	74.00	54.00	-7.14	Peak
1836.67	H	56.51	---	-5.54	50.97	---	74.00	54.00	-3.03	Peak
4108.33	H	48.16	---	0.85	49.00	---	74.00	54.00	-5.00	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / CH High

Test Date: November 15, 2008

Temperature: 25°C

Tested by: Nan Tsai

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1600.00	V	56.91	---	-7.52	49.39	---	74.00	54.00	-4.61	Peak
1826.67	V	54.07	---	-5.63	48.44	---	74.00	54.00	-5.56	Peak
4908.33	V	49.35	---	0.16	49.52	---	74.00	54.00	-4.48	Peak
N/A										
1600.00	H	56.22	---	-7.52	48.70	---	74.00	54.00	-5.30	Peak
1836.67	H	56.14	---	-5.54	50.60	---	74.00	54.00	-3.40	Peak
4216.67	H	48.41	---	0.91	49.32	---	74.00	54.00	-4.68	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



7.10 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link

Test Date: December 4, 2008

Temperature: 22°C

Tested by: Eddy Chung

Humidity: 45% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.2000	48.53	43.63	0.27	48.80	43.90	63.61	53.61	-14.81	-9.71	L1
0.2650	39.54	35.74	0.26	39.80	36.00	61.27	51.27	-21.47	-15.27	L1
0.3350	37.25	33.55	0.25	37.50	33.80	59.33	49.33	-21.83	-15.53	L1
2.0700	37.13	34.33	0.37	37.50	34.70	56.00	46.00	-18.50	-11.30	L1
4.6050	22.54	14.44	0.76	23.30	15.20	56.00	46.00	-32.70	-30.80	L1
23.5200	25.72	18.62	1.78	27.50	20.40	60.00	50.00	-32.50	-29.60	L1
0.2000	49.23	44.83	0.27	49.50	45.10	63.61	53.61	-14.11	-8.51	L2
0.2650	41.84	36.74	0.26	42.10	37.00	61.27	51.27	-19.17	-14.27	L2
0.3300	38.05	33.25	0.25	38.30	33.50	59.45	49.45	-21.15	-15.95	L2
2.1900	21.71	15.91	0.39	22.10	16.30	56.00	46.00	-33.90	-29.70	L2
4.7150	15.72	6.52	0.78	16.50	7.30	56.00	46.00	-39.50	-38.70	L2
23.2850	26.24	19.54	1.76	28.00	21.30	60.00	50.00	-32.00	-28.70	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Notebook
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Bluetooth: 2.402GHz ~ 2.480GHz
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5mW/cm^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	3.13 dBm (2.056mW)
Antenna gain (Max)	2.90 dBi (Numeric gain: 1.95)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation <input checked="" type="checkbox"/> N/A*

Remark:

- The maximum output power is 3.13 dBm (2.056mW) at 2402MHz (with 1.95 numeric antenna gain.)
- DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
- For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is $1.0 mW/cm^2$ even if the calculation indicates that the power density would be larger.

TEST RESULTS

Not applicable.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58mW$)