



Measurement of MPE

1. Foreword

In adopt with the Human Exposure IEEE C95.1, and according to the FCC 1.1310. The *Maximum Permissible Exposure (MPE)* is obligated to measure in order to prove the safety of radiation harmfulness to the human body.

The *Gain* of the antenna used is measured in an *anechoic chamber*. The *maximum total power to the antenna* is to be recorded. By adopting the ***Friis Transmission Formula*** and the *power gain of the antenna*, we can find the distance right away from the product, where the limit of the MPE is.

2. Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	100	6
3.0-30	1842/f	4.89/f	900/f ²	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	100	30
1.34-30	824/f	2.19/f	180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30



Compliance Certification Services (Kunshan) Inc.

10#Weiye Rd, Innovation Park, Eco. & Tec. Development Zone Kunshan city JiangSu, (215300) CHINA

TEL: 86-512-57355888 FAX: 86-512-57370818

Report No: KS060328A01-RP

FCC ID No.: EUNGE2I

Date of Issue: April 20, 2006

According to **OET BULLETIN 56 Fourth Edition/August 1999, Equation for Predicting RF Fields:**

Power density at the specific separation (portable):
$$S = \frac{PG}{4\pi R^2} = \frac{59.7 \times 1.63}{4\pi(20)^2} = 0.0194 \text{mW} / \text{cm}^2$$

Where: S = *power density* (in appropriate units, e.g. mW/cm²)

P = *power input* to the antenna (in appropriate units, e.g., mW)

G = *power gain* of the antenna in the direction of interest relative to an isotropic radiator

R = *distance* to the center of radiation of the antenna (appropriate units, e.g., cm)

The *Numeric gain* G of antenna with a gain specified in dB is determined by:

$$G = \text{Log}^{-1} (\text{dB antenna gain}/10)$$

$$G = \text{Log}^{-1} (2.13 / 10) = 1.63$$