

Report No: KS060508A02-RP

FCC ID No.: EUNLM7WVL

Date of Issue: May 31, 2006

Measurement of MPE

1. Foreword

In adopt with the Human Exposure IEEE C95.1, and according to the FCC 1.1310. The *Maximum Permissible Exposure (MPE)* is obligated to measure in order to prove the safety of radiation harmfulness to the human body.

The *Gain* of the antenna used is measured in an anechoic chamber. The maximum total power to the antenna is to be recorded. By adopting the *Friis Transmission Formula* and the power gain of the antenna, we can find the distance right away from the product, where the limit of the MPE is.

Frequency Range	Electric Field Strength (V/m)	Magnetic Filed Strength (H)	Power Density	Averaging Time E ² , H ² or S
-	Strength (v/m)	••••	(S)	
(MHz)		(A/m)	(mW/cm2)	(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	100	6
3.0-30	1842/f	4.89/f	900/f ²	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	100	30
1.34-30	824/f	2.19/f	180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

2. Limits for Maximum Permissible Exposure (MPE)



Compliance Certification Services (Kunshan) Inc.

10#Weiye Rd, Innovation Park, Eco. & Tec. Development Zone Kunshan city JiangSu, (215300) CHINA TEL: 86-512-57355888 FAX: 86-512-57370818

Report No: KS060508A02-RP FCC

FCC ID No.: EUNLM7WVL

Date of Issue: May 31, 2006

According to OET BULLETIN 56 Fourth Edition/August 1999, Equation for Predicting RF Fields:

Power density at the specific separation: $S = \frac{PG}{4\pi R^2} = \frac{52.72 \times 1.91}{4\pi (20)^2} = 0.0200 mW / cm^2$

Where: S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

The *Numeric gain G* of antenna with a gain specified in dB is determined by:

 $G = Log^{-1}$ (dB antenna gain/10) $G = Log^{-1} (2.80 / 10) = 1.91$