

Nintendo Co., Ltd.

11-1 Kamitoba Hokotate-cho Minami-ku, Kyoto, Japan Tel: 81 (75) 662-9600

Request for transmitter Limited Modular Approval

Transmitter Module Characteristics

Item Requirements EUT

| | | Requirementes 101 | |
|---|-----|--------------------------------|--------------------------------|
| 1 | Yes | Have its own RF shielding | Device is equipped with Metal |
| | | | shielding to cover RF |
| | | | section. Refer to internal |
| | | | photos of module. |
| 2 | Yes | Have buffered | All inputs to the modules are |
| | | modulation/data inputs (if | buffered through logic |
| | | such | inputs. Refer to Block |
| | | inputs are provided), | Diagram of module. |
| 3 | No | Have it own power supply | 3.3 V and 1.8V regulated DC |
| | | regulation | voltage are fed from the host. |
| | | | Refer to schematics of |
| | | | module. |
| 4 | Yes | Meet the antenna | Device is equipped with |
| | | requirements of Section | unique antenna |
| | | 15.203 | connector(MHFII,producto of |
| | | | I-PEX or U.FL-R-SMT-1(10), |
| | | | product of HIROSE). Refer to |
| | | | external photos and antenna |
| | | | description. |
| 5 | No | Be tested in a stand-alone | The module plugged into the |
| | | configuration, i.e., the | host which is tested together |
| | | antenna, AC or DC power and | for limited modular |
| | | data input/output | approval. Refer to setup |
| | | lines must be connected to the | photos. |
| | | module but, the | |
| | | module must not be inside | |
| | | another case during | |
| | | testing | |

(Nintendo[®])

11-1 Kamitoba Hokotate-cho Minami-ku, Kyoto, Japan Tel: 81 (75) 662-9600

Nintendo Co., Ltd.

| _ | | ······································ | |
|----|-----|--|--------------------------------|
| 67 | Yes | Be labeled with its own FCC ID | Since FCC ID is visible as the |
| | | number, and if | module is not installed |
| | | the FCC ID is not visible when | inside the host, it is not |
| | | the module is | necessary to display |
| | | installed inside another | referring to the enclosed |
| | | device, then the outside | module. |
| | | of the device into which the | |
| | | module is installed | |
| | | must also display a label | |
| | | referring to the | |
| | | enclosed module. | |
| 73 | Yes | The modular transmitter is | Refer to the user manual of |
| | | manufactured so that | module. |
| | | the user cannot influence the | |
| | | operation of the | |
| | | transmitter that will | |
| | | operate outside of the scope | |
| | | of the regulations. | |
| 87 | les | Address compliance with the | Meet RF exposure compliance |
| | | Commission's RF | requirement. Refer to the MPE |
| | | exposure limits in Sections | calculation of test report. |
| | | 1.1310 and 2.1093. | |
| | | In addition, spread spectrum | |
| | | transmitters | |
| | | operating under Section | |
| | | 15.247 are required to | |
| | | address RF exposure | |
| | | compliance in accordance | |
| | | with Section 15.247(b)(4). | |

Taro Kimura Certified By: TARO Kimura Date 10th of April, 2010