

RF exposure statement

To whom it may concern:

ZACTA Technology Corporation
Address: 4149-7 Hachimanpara 5-chome
Yonezawa-shi, Yamagata 992-1128 Japan

is authorized as a test-lab from **Applicant: Mitsumi Electric Co., Ltd.** for testing the device.

The maximum peak output power of the product **FCC ID: EW4DWMW028** is 3.184 mW.

RF exposure calculation

$$S = \frac{PG}{4\pi R^2} \quad [\text{mW/cm}^2] \quad (\text{limit}=1.0\text{mW/cm}^2)$$

where: S = power density

P = power input to the antenna (3.184 mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator (1.83 = 2.62 dBi)

R = distance to the center of radiation of the antenna (20 cm)

[PARTNER-CTR Capture]

Radio	Frequency (MHz)	Output Power to Antenna (mW)	Power density (mW/cm ²)
IEEE802.11b	2412, 2442MHz	3.184	0.00116
IEEE802.11g	2412MHz	3.162	0.00115

Therefore, the product **FCC ID: EW4DWMW028** is deemed to comply with the requirements of FCC 47CFR 2.1091 'Radiofrequency radiation exposure evaluation: mobile devices'.

Regarding product **IC: 4250A-DWMW028**

The IC RF Exposure Evaluation exemption limit is 5W (e.i.r.p) for devices operating above 1.5GHz and having a separation distance to the user greater than 20cm, according to RSS-102 (Issue 4), clause 2.5.2.

The maximum conducted output power of the product is 3.184 mW.

The maximum antenna gain is 2.62 dBi = 1.83.

Therefore the maximum e.i.r.p. output power of the product is 3.184 mW * 1.83 = 5.827 mW.

Conclusion: The product meets the IC RF Exposure Evaluation exemption