



Report No.: HKEM181100090602
Page: 1 of 10
FCC ID: EW780-1368-00
IC: 1135B-80136800

TEST REPORT

Application No.: HKEM1811000906IT
Applicant: VTECH TELECOMMUNICATIONS LTD
Address of Applicant: 23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong
Manufacturer: VTECH TELECOMMUNICATIONS LTD
Address of Manufacturer: 23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong
Factory: VTech (Dongguan) Telecommunications Limited.
Address of Factory: VTech Science Park, Xia Ling Bei Management Zone, Liaobu, Dongguan, Guangdong, China.

Equipment Under Test (EUT):
EUT Name: Full HD Pan & Tilt Camera with Alarm
HVIN: 35-600010BU
Model No.: VC9511 Camera, VC9511-2 Camera, VC9511-3 Camera, VC9511-11 Camera, VC9511-21 Camera, VC951z-abcd Camera ♣
Trade mark: VTech
♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Standard(s): 47 CFR Part 1.1307 (2018)
47 CFR Part 1.1310 (2018)
RSS102 Issue 5 March 2015

Date of Receipt: 2018-11-07
Date of Test: 2018-11-19
Date of Issue: 2018-11-21

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Ivan Toa

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-11-21		Original

Authorized for issue by:			
Tested By			2018-11-19
		_____ Leo Xu /Project Engineer	_____ Date
Checked By			2018-11-21
		_____ Ivan Toa /Reviewer	_____ Date



1 Contents

	Page
1 CONTENTS.....	3
2 GENERAL INFORMATION	4
2.1 DETAILS OF E.U.T.	4
2.2 TEST LOCATION	6
2.3 TEST FACILITY	6
2.4 DEVIATION FROM STANDARDS	6
2.5 ABNORMALITIES FROM STANDARD CONDITIONS	6
2.6 DEVIATION FROM STANDARDS	7
2.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
2.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
3 RF EXPOSURE EVALUATION.....	8
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	8
3.1.1 <i>Limits</i>	8
3.1.2 <i>Test Procedure</i>	9
3.1.3 <i>EUT RF Exposure Evaluation</i>	10

2 General Information

2.1 Details of E.U.T.

Power supply:	AC100-240V, 50/60Hz 0.5A
Adapter	Adapter 1 Model: CS12N05015FUF Input: AC100-240V, 50/60Hz 0.5A output: DC 5.0V, 1.5A Adapter 2 Model: S012CDU0500150 Input: AC100-240V, 50/60Hz 0.4A output: DC 5.0V, 1.5A *Remark: Complete measurement was performed with Adaptor 2
Cable	Adapter 1 & 2, DC cable: 295cm 2-wires unshielded cable
Funtion	Wireless Network camera, Local storage (micro sd card) recording
Test Voltage	AC120V 60 Hz
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Fixed production
Antenna Type:	PIFA Antenna
Antenna Gain:	2 dBi
Frequency List	

Channel list for 802.11b/g/n(HT20)

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Remark: Test frequencies for 20MHz bandwidth are the lowest channel: 1 channel(2412MHz), middle channel: 6 channel (2437 MHz) and highest channel: 11 channel (2462 MHz).



Channel list for 802.11n(HT40)

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
		5	2432	9	2452
		6	2437		
3	2422	7	2442		
4	2427	8	2447		

Test frequencies for 40MHz bandwidth are the lowest channel: 3 channel(2422MHz), middle channel: 6 channel (2437 MHz) and highest channel: 9 channel (2452 MHz).

Model: VC9511 Camera, VC9511-2 Camera, VC9511-3 Camera, VC9511-12 Camera, VC9511-22 Camera, and VC951z-abcd Camera

Suffix (“ a, b, c, d, z” of “VC951z-abcd Camera”) represents

- Color code
- Packing configuration
- (Others, please specify)

z=packaging, can be 0-9, a-z, A-Z

a=number of IP Cam; can be 0-9, a-z, A-Z or blank

b=color options, can be 0-9, a-z, A-Z or blank

c= combinations of sensor types/ other accessory in the bundle, can be 0-9, 00-99 or blank

d= combinations of sensor types/ other accessory in the bundle, can be 0-9, 00-99 or blank

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuit design, PCB layout, electrical components used, internal wiring and function. The differences are only the model and color for trading purpose Therefore only the model VC9511 Camera was tested in this report.



2.2 Test Location

All tests were performed at:

SGS IECC Limited (Member of the SGS Group (SGS SA))
No. 16-B, Yip Wo Street, On Lok Tsuen, Fanling, N.T., Hong Kong
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

2.3 Test Facility

The test facility is recognized or accredited by the following organizations:

• **HOKLAS (Lab Code: 125)**

SGS IECC Limited has been accepted by HKAS Executive, on the recommendation of the Accreditation Advisory Board, as a HOKLAS Accredited Laboratory, this laboratory meets the requirements of ISO/IEC 17025:2005 and it has been accredited for performing specific test as listed in the scope of accreditation within the test category of Electrical and Electronic Products.

• **FCC Recognized Accredited Test Firm (CAB Registration No.: 446297)**

SGS IECC Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0010, Test Firm Registration Number: 446297.

• **Industry Canada (Registration No.: 5193A-2)**

The 3m Alternative Semi-anechoic chamber of SGS IECC Limited has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 5193A-2..

2.4 Deviation from Standards

None

2.5 Abnormalities from Standard Conditions

None



Report No.: HKEM 181100090602
Page: 7 of 10
FCC ID: EW780-1368-00
IC: 1135B-80136800

2.6 Deviation from Standards

None.

2.7 Abnormalities from Standard Conditions

None.

2.8 Other Information Requested by the Customer

None.



3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 FCC Radiofrequency radiation Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

$$\text{Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



3.1.2 IC Radiofrequency radiation

According to RSS-102 Issue 5, section 2.5.2 Exemption.

RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}W$ (adjusted for tune-up tolerance), where f is in MHz;

at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} W$ (adjusted for tune-up tolerance), where f is in MHz;

at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

3.1.3 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



3.1.4 EUT RF Exposure Evaluation

For 2.4G WiFi

Antenna Gain: 2dBi

The maximum Gain measured in fully anechoic chamber is 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance: 20cm

For FCC

SISO mode (Worst case: 802.11b)

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	MPE Ratios	Result
Highest	2462	15.6	57.544	0.0114	1	0.0114	PASS

SISO mode (Worst case: 802.11n(HT40))

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	MPE Ratios	Result
Highest	2452	15	50.118	0.0100	1	0.0100	PASS

For IC

SISO mode (Worst case: 802.11b)

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (W)	Limit (W)	Result
Highest	2462	15.6	0.0575	2.7	PASS

SISO mode (Worst case: 802.11n(HT20))

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (W)	Limit (W)	Result
Highest t	2452	15	0.0501	2.7	PASS

Note: Refer to report No. HKEM181100090601 for EUT test conducted power value. The distancer (5th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

802.11b/g/n cannot be transmitted simultaneous, hence only SISO mode is used in RF Exposure Evaluation This equipment should be installed and operated with minimum 20 cm between the radiator and your body.

Conclusion:

The device is exclusion from SAR test.

- End of the Report -