

# TEST REPORT

**Application No.:** HKEM2209000917AT  
**Applicant:** VTech Telecommunications Ltd.  
**Address of Applicant:** 23/F., Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong  
**Equipment Under Test (EUT):**  
**EUT Name:** Pan & Tilt Video Monitor  
**Model No.:** VM901HD PU, VM901-2HD PU  
**Additional Model:** Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.  
**FCC ID:** EW780-1957-01D  
**IC:** 1135B-80195701D  
**HVIN:** 35-201964PUA  
**Standard(s) :** CFR 47 FCC Part 15, Subpart C  
 RSS-247 Issue 2  
 RSS-Gen Issue 5  
**Date of Receipt:** 2022-09-26  
**Date of Test:** 2022-09-26 to 2022-10-14  
**Date of Issue:** 2022-10-17

<b>Test Result:</b>	The submitted sample was found to comply with the test requirement
---------------------	--



**Law Man Kit**  
**EMC Manager**

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Revision No.	Date	Report superseded	Remark

Authorized for issue by:			
			
		<b>Panny Leung</b> /Project Engineer	
			
		<b>Law Man Kit</b> /Reviewer	

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Disturbance at AC Power Line(150kHz-30MHz)	47 CFR Part 15, Subpart C 15.207	ANSI C63.10: 2013 Section 6.2	47 CFR FCC Part 15, Subpart C 15.207	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.2.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	RSS-Gen Issue 5, Amdt 2021	N/A	RSS-Gen Section 6.8	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	RSS-Gen Issue 5: Amdt 2021	ANSI C63.10 (2013) Section 6.2	RSS-Gen Section 8.8	Pass
99% Bandwidth	RSS-Gen Issue 5: Amdt 2021	ANSI C63.10 Section 6.9.3	RSS-Gen Section 6.7	Pass
Minimum 6dB Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.8.1	RSS-247 Section 5.2(a)	Pass
Conducted Peak Output Power	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.9.1	RSS-247 Section 5.4(d)	Pass
Power Spectrum Density	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.10.2	RSS-247 Clause 5.2(b)	Pass

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Conducted Band Edges Measurement	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.12	RSS-247 Section 5.5	Pass
Spurious Emissions	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.11	RSS-247 Section 5.5	Pass
Radiated Emissions which fall in the restricted bands	RSS-Gen Issue 5: Amdt 2021	ANSI C63.10 (2013) Section 6.4&6.5&6.6	RSS-247 Section Section 3.3 & RSS-Gen Section 8.10	Pass
Frequency stability	RSS-247 Issue 2, February 2017	RSS-Gen Section 6.11	RSS-Gen Section 8.11	Pass

Note: Frequency stability requested in RSS GEN Section 8.1.1 has been complied since the result of band edge can demonstrate.

**Declaration of EUT Family Grouping:**

VM901HD PU, VM901-2HD PU

These models are identical in electronics/electrical designs, including software & firmware, construction design/Physical design/enclosure and PCB layout. The only difference between these models is the model numbers for marketing purpose. Thus, only the model VM901HD PU was tested in this report.

**Abbreviation:**

Tx: In this whole report Tx (or tx) means Transmitter.  
 Rx: In this whole report Rx (or rx) means Receiver.  
 RF: In this whole report RF means Radiated Frequency.  
 CH: In this whole report CH means channel.  
 Volt: In this whole report Volt means Voltage.  
 Temp: In this whole report Temp means Temperature.  
 Humid: In this whole report Humid means humidity.  
 Press: In this whole report Press means Pressure.  
 N/A: In this whole report not application.

### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>5</b>
<b>4 GENERAL INFORMATION .....</b>	<b>7</b>
4.1 DETAILS OF E.U.T. ....	7
4.2 DESCRIPTION OF SUPPORT UNITS .....	8
4.3 MEASUREMENT UNCERTAINTY .....	8
4.4 TEST LOCATION .....	9
4.5 TEST FACILITY .....	9
4.6 DEVIATION FROM STANDARDS .....	9
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	9
<b>5 EQUIPMENT LIST .....</b>	<b>10</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>12</b>
6.1 ANTENNA REQUIREMENT .....	12
6.1.1 <i>Test Requirement:</i> .....	12
6.1.2 <i>Conclusion</i> .....	12
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>13</b>
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) .....	13
7.1.1 <i>E.U.T. Operation</i> .....	14
7.1.2 <i>Test Setup Diagram</i> .....	14
7.1.3 <i>Measurement Procedure and Data</i> .....	14
7.2 99% BANDWIDTH .....	17
7.2.1 <i>E.U.T. Operation</i> .....	17
7.2.2 <i>Test Setup Diagram</i> .....	17
7.2.3 <i>Measurement Procedure and Data</i> .....	17
7.3 MINIMUM 6dB BANDWIDTH .....	18
7.3.1 <i>E.U.T. Operation</i> .....	18
7.3.2 <i>Test Setup Diagram</i> .....	18
7.3.3 <i>Measurement Procedure and Data</i> .....	18
7.4 CONDUCTED PEAK OUTPUT POWER .....	19
7.4.1 <i>E.U.T. Operation</i> .....	19
7.4.2 <i>Test Setup Diagram</i> .....	19
7.4.3 <i>Measurement Procedure and Data</i> .....	19
7.5 POWER SPECTRUM DENSITY .....	20
7.5.1 <i>E.U.T. Operation</i> .....	20
7.5.2 <i>Test Setup Diagram</i> .....	20
7.5.3 <i>Measurement Procedure and Data</i> .....	20
7.6 CONDUCTED BAND EDGES MEASUREMENT .....	21
7.6.1 <i>E.U.T. Operation</i> .....	23
7.6.2 <i>Test Setup Diagram</i> .....	23
7.6.3 <i>Measurement Procedure and Data</i> .....	23
7.7 CONDUCTED SPURIOUS EMISSIONS .....	24
7.7.1 <i>E.U.T. Operation</i> .....	24
7.7.2 <i>Test Setup Diagram</i> .....	24
7.7.3 <i>Measurement Procedure and Data</i> .....	24



7.8	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	26
7.8.1	<i>E.U.T. Operation</i> .....	26
7.8.2	<i>Test Setup Diagram</i> .....	27
7.8.3	<i>Measurement Procedure and Data</i> .....	27
7.9	RADIATED SPURIOUS EMISSIONS .....	29
7.9.1	<i>E.U.T. Operation</i> .....	30
7.9.2	<i>Test Setup Diagram</i> .....	30
7.9.3	<i>Measurement Procedure and Data</i> .....	31
<b>8</b>	<b>PHOTOGRAPHS .....</b>	<b>41</b>
<b>9</b>	<b>APPENDIX.....</b>	<b>42</b>
9.1	99% BANDWIDTH .....	42
9.2	MINIMUM EMISSION BANDWIDTH 6 dB .....	48
9.3	RF OUTPUT POWER .....	54
9.4	BAND EDGE .....	61
9.5	CONDUCTED SPURIOUS EMISSION .....	69

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	Adaptor Model: VT07EUS05200 Input: AC 100 V - 240 V, 50/60 Hz, 0.5 A Output: DC 5.0 V, 2.0 A  or  Battery Model: GSP806090-5Ah-3.7V-1S1P Capacity: 5000mAh, 18.5Wh Voltage: 3.7VDC
Test voltage:	AC 120 V
Cable:	Power Cable: 200 cm unshielded 2-wire DC cable
Antenna Gain:	2 dBi
Antenna Type:	Dipole
Channel Spacing:	5MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Data rate:	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11 Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: 6.5Mbps, 13Mbps, 19.5Mbps, 26Mbps, 39Mbps, 52Mbps, 58.5Mbps, 65Mbps
Number of Channels:	802.11b/g/n(HT20):11
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz
Tested Channels:	2412MHz, 2437MHz, 2462MHz
Version code:	T31N
Series number:	A1
Hardware Version:	35-201964PUA
Software Version:	V1.0.2.0
	Remark: Power level setting was not adjustable and fixed default through SW Version.

#### Frequency List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>1</b>	<b>2412</b>	5	2432	9	2452
2	2417	<b>6</b>	<b>2437</b>	10	2457
3	2422	7	2442	<b>11</b>	<b>2462</b>
4	2427	8	2447		

Remark: 1. Testing Channels are highlighted in **bold**.

## 4.2 Description of Support Units

The EUT has been tested with corresponding accessories as below:

Supplied by client

Description	Manufacturer	Model No.	SN/Certificate NO
Test Software	MicroRidge System	Version 3.0.0.108	N/A

Supplied by SGS:

Description	Manufacturer	Model No.	SN/Certificate NO
NoteBook (EMC4)	Dell	P75F	N/A

## 4.3 Measurement Uncertainty

RF

No.	Item	Measurement Uncertainty
1	Conducted disturbance	2.8dB (150kHz to 30MHz)
2	Radio Frequency	$\pm 7.25 \times 10^{-8}$
3	Duty cycle	$\pm 0.37\%$
4	Occupied Bandwidth	$\pm 3\%$
5	RF conducted power (30MHz-40GHz)	1.7dB
6	RF power density	1.7dB
7	Conducted Spurious emissions	1.7dB
8	RF Radiated power & Radiated Spurious emission test	4.7dB (30MHz-1GHz)
		4.7dB (1GHz-6GHz)
		4.7dB (6GHz-18GHz)
		5.7dB (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$

Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR}}$  (CISPR Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

According to decision rule based on Clause 4.2 of CISPR 16-4-2, the EUT complied with the standards specified above.



#### 4.4 Test Location

All tests were performed at:

SGS Hong Kong Limited  
Unit 2 and 3, G/F, Block A, Po Lung Centre,  
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong  
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

##### **IAS Accreditation (Lab Code: TL-817)**

SGS HONG KONG Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website ([www.iasonline.org](http://www.iasonline.org)).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

##### **FCC Recognized Accredited Test Firm (CAB Registration No.: 514599)**

SGS HONG KONG Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

##### **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS HONG KONG Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

#### 4.6 Deviation from Standards

None

#### 4.7 Abnormalities from Standard Conditions

None

---

## 5 Equipment List

**Minimum 6dB Bandwidth, Conducted Peak Output Power, Power Spectrum Density, Conducted Band Edges Measurement, Conducted Spurious Emissions**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
SMBV100A VECTOR SIGNAL GENERATOR	Rohde & Schwarz	SMBV100A	E234	2022/08/17	2023/08/16
FSV40 SIGNAL ANALYZER 40GHz	Rohde & Schwarz	FSV40	E235	2022/08/17	2023/08/16
Wireless Conn. Tester (CMW)	Rohde & Schwarz	CMW270	E240	2022/08/20	2023/08/19
OSP	Rohde & Schwarz	OSP-B157W8	E242	2022/04/20	2023/04/19
Cable	Rohde & Schwarz	J12J103539-00-2	E239	2022/09/17	2023/09/16
WMS32 Test Software	R&S	Version 10	N/A	--	--

**Conducted Emissions at Mains Terminals (150kHz-30MHz)**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver 9kHz to 3.6GHz	Rohde & Schwarz	ESR3 / 102326	E231	2022/08/17	2023/08/16
Artificial Mains Network (LISN)	Schwarzbeck	NSLK 8127 / 8127312	E005	2022/04/13	2023/04/12
Impulse Limiter	Rohde & Schwarz	ESH-3-Z2 / 357881052	E028	2022/07/15	2023/07/14
EMC32 Test Software	R&S	Version 10	N/A	--	--

**Radiated Spurious Emissions (30MHz-1GHz)**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	ChamPro	N/A	E229	2022/08/08	2023/08/07
Coaxial Cable	SGS	N/A	E167	2022/07/15	2023/07/14
EMI Test Receiver 9kHz to 7GHz	Rohde & Schwarz	ESR7 / 102298	E314	2022/06/29	2023/06/28
TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz	Schwarzbeck	9168-1110	E264	2021/10/18	2023/10/17
EMC32 Test software	Rohde & Schwarz	Version 10	N/A	N/A	N/A
Boresight Mast Controller	ChamPro	AM-BS-4500-E	E237	N/A	N/A
Turntable with Controller	ChamPro	EM1000	E238	N/A	N/A

<b>Radiated Spurious Emissions (above 1GHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
3m Semi-Anechoic Chamber	ChamPro	N/A	E229	2022/08/08	2023/08/07
Coaxial Cable	SGS	N/A	E167	2022/07/15	2023/07/14
EMI Test Receiver 9kHz to 7GHz	Rohde & Schwarz	ESR7 / 102298	E314	2022/06/29	2023/06/28
TRILOG Super Broadb. Test Antenna, (25) 30-1000 MHz	Schwarzbeck	9168-1110	E264	2021/10/18	2023/10/17
Signal and Spectrum Analyzer 2Hz - 26.5GHz	Rohde & Schwarz	FSW26	E296	2022/09/17	2023/09/16
Horn Antenna 1 - 18GHz	Schwarzbeck	BBHA9120D	E211	2022/03/03	2024/03/02
Horn Antenna 15 - 40GHz	Schwarzbeck	BBHA9170	E212	2022/03/16	2024/03/15
Preamplifier 33dB, 1 - 18GHz	Schwarzbeck	BBV9718	E214	2022/01/20	2023/01/19
Preamplifier 33dB, 18 - 26.5GHz	Schwarzbeck	BBV9719	E215	2022/09/17	2023/09/16
Broadband Coaxial Preamplifier typ. 30 dB, 18-40GHz	Schwarzbeck	BBV 9721	E266	2022/09/17	2023/09/16
Band Reject Filter 2.4 -2.5GHz	MICRO-TRONICS	BRM50702	E324	2022/09/17	2023/09/16
RF cable SMA to SMA 10000mm	HUBER+SUHNER	SF104- 26.5/2*11SMA 45	E207-1	2022/09/17	2023/09/16
Boresight Mast Controller	ChamPro	AM-BS-4500-E	E237	N/A	N/A
Turntable with Controller	ChamPro	EM1000	E238	N/A	N/A

<b>General used equipment</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Digital temperature & humidity data logger	SATO	SK-L200TH II	E232	2022/08/16	2023/08/15
Electronic Digital Thermometer with Hygrometer	nil	2074/2075	E159	2022/08/16	2023/08/15
Barometer with digital thermometer	SATO	7612-00	E218	2022/03/29	2023/03/28
Conditional Chamber	Zhong Zhi Testing Instruments	CZ-E-608D	E216	2022/08/17	2023/08/16

## **6 Radio Spectrum Technical Requirement**

### **6.1 Antenna Requirement**

#### **6.1.1 Test Requirement:**

FCC Part 15 Subpart C Section 15.247 & 15.203

RSS-Gen Section 8.3

#### **6.1.2 Conclusion**

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2 dBi.

Photo of antenna refer to Appendix – Internal photo.

---



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207, RSS-Gen Section 8.8  
Test Method: ANSI C63.10 (2013) Section 6.2  
Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 23.0 C Humidity: 52.0 % RH :

Test mode a :TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)..11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram



### 7.1.3 Measurement Procedure and Data


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a (802.11b);

Line: Live Line


Full Spectrum



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Corr. (dB)	Result
0.422000	---	32.9	47.4	14.5	10.9	Pass
0.422000	42.5	---	57.4	14.9	10.9	Pass
0.446000	---	28.9	47.0	18.0	10.9	Pass
0.446000	38.3	---	57.0	18.7	10.9	Pass
0.842000	---	25.4	46.0	20.6	10.7	Pass
0.870000	35.7	---	56.0	20.3	10.6	Pass
1.174000	28.6	---	56.0	27.4	10.5	Pass
1.182000	---	18.6	46.0	27.4	10.5	Pass
1.210000	35.3	---	56.0	20.7	10.5	Pass
1.210000	---	22.4	46.0	23.6	10.5	Pass
1.234000	---	19.7	46.0	26.3	10.5	Pass
4.718000	31.0	---	56.0	25.0	10.3	Pass

Mode: a(802.11b);  
Line: Neutral Line

Full Spectrum



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Corr. (dB)	Result
0.426000	---	34.8	47.3	12.5	10.9	Pass
0.426000	38.8	---	57.3	18.6	10.9	Pass
0.450000	39.2	---	56.9	17.7	10.9	Pass
0.454000	---	32.9	46.8	13.9	10.9	Pass
0.794000	---	29.8	46.0	16.2	10.7	Pass
0.822000	---	30.7	46.0	15.3	10.7	Pass
0.850000	---	30.0	46.0	16.1	10.6	Pass
0.878000	---	29.1	46.0	16.9	10.6	Pass
0.882000	32.3	---	56.0	23.7	10.6	Pass
0.934000	34.1	---	56.0	21.9	10.6	Pass
1.186000	34.1	---	56.0	21.9	10.5	Pass
1.274000	33.2	---	56.0	22.8	10.5	Pass



## 7.2 99% Bandwidth

Test Requirement RSS-Gen Section 6.6  
 Test Method: ANSI C63.10 Section 6.9.3

### 7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 22.5 C Humidity: 53.0 % RH :

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

### 7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
 Test Method: ANSI C63.10 (2013) Section 11.8.1  
 Limit:  $\geq 500$  kHz


#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 C Humidity: 53.0 % RH :

Test mode b:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20)..11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).  
 Only the data of worst case is recorded in the report.

#### 7.3.2 Test Setup Diagram



#### 7.3.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

### 7.4 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247 (b)(1) & 15.247(b)(3), RSS-247 Section 5.4(b)

Test Method: ANSI C63.10 (2013) Section 7.8.5


#### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 C Humidity: 53.0 % RH :

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

#### 7.4.2 Test Setup Diagram



#### 7.4.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

### 7.5 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e), RSS-247 Clause 5.2(b)  
 Test Method: ANSI C63.10 (2013) Section 11.10.2  
 Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission


#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 C Humidity: 53.0 % RH :

Test mode b:TX mode. Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).  
 Only the data of worst case is recorded in the report.

#### 7.5.2 Test Setup Diagram



#### 7.5.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix

### 7.6 Conducted Band Edges Measurement

Test Requirement	47 CFR Part 15, Subpart C 15.247 (d), RSS-247 Section 5.5
Test Method:	ANSI C63.10 (2013) Section 7.8.6
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

FCC Part 15 C Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			

RSS-Gen Section 8.10 Restricted bands of operation.

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

(a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio

apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, *Emergency Position Indicating Radio Beacons (EPIRB)*, *Emergency Locator Transmitters (ELT)*, *Personal Locator Beacons (PLB)*, and *Maritime Survivor Locator Devices (MSLD)*.

(b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.

(c) Unwanted emissions that do not fall within the restricted frequency bands listed in table 7 shall comply either with the limits specified in the applicable RSS or with those specified in table 5 and table 6.

Table 7 – Restricted frequency bands* MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 C Humidity: 53.0 % RH :

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

### 7.6.2 Test Setup Diagram



### 7.6.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix


### 7.7 Conducted Spurious Emissions

Test Requirement	47 CFR Part 15, Subpart C 15.247 (d), RSS-247 Section 5.5
Test Method:	ANSI C63.10 (2013) Section 7.8.8
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

#### 7.7.1 E.U.T. Operation

Operating Environment:	
Temperature:	22.5 C Humidity: 53.0 % RH :
Test mode	a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

#### 7.7.2 Test Setup Diagram



#### 7.7.3 Measurement Procedure and Data

The detailed test data see section 9: Appendix





**Report No.:** HKEM220900091702  
**Page:** 25 of 70

### 7.8 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d), Section 3.3 & RSS-Gen Section 8.9  
 Test Method: ANSI C63.10 (2013) Section 6.10.5  
 Limit:

**Table 5 – General field strength limits at frequencies above 30 MHz**

Frequency (MHz)	Field strength ( $\mu\text{V/m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

**Table 6 – General field strength limits at frequencies below 30 MHz**

Frequency	Magnetic field strength (H-Field) ( $\mu\text{A/m}$ )	Measurement distance (m)
9 - 490 kHz 1	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

#### 7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 21.0 C Humidity: 55.0 % RH :

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).

Only the data of worst case is recorded in the report.

### 7.8.2 Test Setup Diagram



### 7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Worse test result as shown below:

Mode: 802.11b

Frequency (MHz)	Antenna Polarization	Emission Level (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Remark
		Peak	Average	Peak	Average	
2390.000	H	58.4	45.2	74.0	54.0	Pass
2483.500	H	58.7	45.6	74.0	54.0	Pass

Mode: 802.11g

Frequency (MHz)	Antenna Polarization	Emission Level (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Remark
		Peak	Average	Peak	Average	
2390.000	V	57.9	45.4	74.0	54.0	Pass
2483.500	H	58.6	45.7	74.0	54.0	Pass

Mode: 802.11n20

Frequency (MHz)	Antenna Polarization	Emission Level (dB $\mu$ V/m)		Limit (dB $\mu$ V/m)		Remark
		Peak	Average	Peak	Average	
2390.000	H	58.4	45.3	74.0	54.0	Pass
2483.500	V	59.0	46.1	74.0	54.0	Pass

---

### 7.9 Radiated Spurious Emissions

Test Requirement Section 3.3 & RSS-Gen Section 8.9  
 Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6  
 Limit:

**Table 5 – General field strength limits at frequencies above 30 MHz**

Frequency (MHz)	Field strength ( $\mu\text{V/m}$ at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

**Table 6 – General field strength limits at frequencies below 30 MHz**

Frequency	Magnetic field strength (H-Field) ( $\mu\text{A/m}$ )	Measurement distance (m)
9 - 490 kHz 1	$6.37/F$ (F in kHz)	300
490 - 1705 kHz	$63.7/F$ (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

### 7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 21.0 C Humidity: 55.0 % RH :

Test mode a:TX mode\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20).


Only the data of worst case is recorded in the report.

### 7.9.2 Test Setup Diagram



Below 30MHz

30MHz-1GHz



Above 1GHz

### 7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
  - 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
  - 3) Scan from 9kHz to 40GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
  - 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
-

802.11b

**Radiated emission below 1GHz**


Horizontal (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBμV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBμV/m)	Result
30.167500	21.2	H	12.9	18.8	40.0	Pass
132.250000	21.9	H	13.1	21.6	43.5	Pass
247.495000	30.6	H	13.0	15.4	46.0	Pass
270.895000	25.9	H	13.8	20.1	46.0	Pass
360.010000	35.1	H	16.3	10.9	46.0	Pass
857.747500	26.0	H	25.4	20.0	46.0	Pass



Vertical (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBµV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBµV/m)	Result
47.035000	28.1	V	14.4	11.9	40.0	Pass
131.762500	31.5	V	13.1	12.0	43.5	Pass
182.950000	26.6	V	12.5	16.9	43.5	Pass
193.382500	27.0	V	11.0	16.5	43.5	Pass
584.942500	28.3	V	21.3	17.7	46.0	Pass
865.840000	32.5	V	25.4	13.5	46.0	Pass

**Above 1GHz**

Channel:Low

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4789.785	V	52.6	/	74.0	54.0	Pass
4979.821	V	52.7	/	74.0	54.0	Pass
7252.964	H	53.2	/	74.0	54.0	Pass
9646.928	V	54.1	40.0	74.0	54.0	Pass
9687.000	H	53.0	/	74.0	54.0	Pass
12078.535	H	57.3	43.8	74.0	54.0	Pass

Channel:Middle

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4982.250	V	56.3	38.6	74.0	54.0	Pass
4995.607	H	52.2	/	74.0	54.0	Pass
7310.035	V	54.8	43.1	74.0	54.0	Pass
9747.714	H	55.3	44.1	74.0	54.0	Pass
9751.964	V	53.7	/	74.0	54.0	Pass
12179.321	H	57.3	44.4	74.0	54.0	Pass


Channel: High

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4986.500	H	52.5	/	74.0	54.0	Pass
4997.428	V	56.5	38.3	74.0	54.0	Pass
8636.642	V	53.1	/	74.0	54.0	Pass
9102.928	H	53.5	/	74.0	54.0	Pass
11574.607	V	56.2	43.5	74.0	54.0	Pass
11586.750	H	57.5	43.4	74.0	54.0	Pass

802.11g


**Radiated emission below 1GHz**

Horizontal (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBµV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBµV/m)	Result
30.080000	20.8	H	12.9	19.2	40.0	Pass
129.325000	26.7	H	12.9	16.8	43.5	Pass
180.025000	23.5	H	12.9	20.0	43.5	Pass
263.972500	27.8	H	13.5	18.2	46.0	Pass
360.010000	30.7	H	16.3	15.4	46.0	Pass
381.655000	28.4	H	16.9	17.6	46.0	Pass

Vertical (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBµV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBµV/m)	Result
47.035000	28.3	V	14.4	11.7	40.0	Pass
129.325000	33.4	V	12.9	10.1	43.5	Pass
174.565000	23.1	V	13.7	20.4	43.5	Pass
299.950000	31.4	V	14.9	14.6	46.0	Pass
585.040000	30.8	V	21.3	15.2	46.0	Pass
865.840000	31.7	V	25.4	14.3	46.0	Pass

**Above 1GHz**

Channel:Low

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4986.500	V	54.7	38.0	74.0	54.0	Pass
7081.142	V	52.7	/	74.0	54.0	Pass
7218.357	H	53.3	/	74.0	54.0	Pass
9298.428	V	54.0	40.5	74.0	54.0	Pass
9667.571	H	53.2	/	74.0	54.0	Pass
12058.500	H	57.2	43.7	74.0	54.0	Pass

Channel:Middle

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4981.642	V	53.9	/	74.0	54.0	Pass
5312.535	V	55.7	31.9	74.0	54.0	Pass
9305.107	H	54.5	40.6	74.0	54.0	Pass
10929.821	H	58.4	45.4	74.0	54.0	Pass
12125.892	V	57.2	44.2	74.0	54.0	Pass
12214.535	H	57.6	44.4	74.0	54.0	Pass


Channel: High

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
6651.892	V	54.2	37.3	74.0	54.0	Pass
7171.607	H	53.3	/	74.0	54.0	Pass
9720.392	H	53.5	/	74.0	54.0	Pass
9798.714	V	54.2	40.4	74.0	54.0	Pass
12187.214	H	57.5	44.5	74.0	54.0	Pass
12238.821	V	57.5	44.3	74.0	54.0	Pass

802.11n20


**Radiated emission below 1GHz**

Horizontal (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBμV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBμV/m)	Result
30.100000	20.8	H	12.9	19.2	40.0	Pass
129.032500	25.3	H	12.9	18.2	43.5	Pass
180.025000	23.7	H	12.9	19.8	43.5	Pass
263.972500	27.6	H	13.5	18.4	46.0	Pass
360.010000	30.4	H	16.3	15.6	46.0	Pass
381.655000	27.8	H	16.9	18.2	46.0	Pass

Vertical (the worst plot is shown below)



Frequency (MHz)	QuasiPeak (dBµV/m)	Pol.	Corr. (dB/m)	Margin (dB)	Limit (dBµV/m)	Result
46.937500	26.8	V	14.4	13.2	40.0	Pass
129.422500	34.0	V	12.9	9.5	43.5	Pass
179.927500	28.6	V	12.9	14.9	43.5	Pass
299.950000	30.8	V	14.9	15.2	46.0	Pass
585.040000	30.8	V	21.3	15.2	46.0	Pass
865.840000	31.8	V	25.4	14.2	46.0	Pass

**Above 1GHz**

Channel:Low

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
7219.571	V	52.8	/	74.0	54.0	Pass
7220.178	H	53.0	/	74.0	54.0	Pass
9619.607	V	53.5	/	74.0	54.0	Pass
9892.821	H	53.3	/	74.0	54.0	Pass
12054.857	V	57.2	43.7	74.0	54.0	Pass
12119.821	H	57.4	44.1	74.0	54.0	Pass

Channel:Middle

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
7165.535	V	53.9	/	74.0	54.0	Pass
9747.714	H	54.6	43.0	74.0	54.0	Pass
9781.714	V	53.5	/	74.0	54.0	Pass
11099.821	H	58.1	44.5	74.0	54.0	Pass
12154.428	H	57.6	44.5	74.0	54.0	Pass
12204.821	V	57.7	44.4	74.0	54.0	Pass

Channel: High

Frequency (MHz)	Antenna Polarization	Emission Level (dBµV/m)		Limit (dBµV/m)		Remark
		Peak	Average	Peak	Average	
4981.642	V	52.5	/	74.0	54.0	Pass
7184.357	V	53.6	/	74.0	54.0	Pass
9759.857	V	53.6	/	74.0	54.0	Pass
9760.464	H	54.0	40.4	74.0	54.0	Pass
12215.142	V	57.8	44.4	74.0	54.0	Pass
12334.750	H	57.1	44.2	74.0	54.0	Pass





## **8 Photographs**

Remark: Photos refer to Appendix: External Photo, Internal Photo, and Setup Photo


## 9 Appendix

### 9.1 99% Bandwidth


802.11b:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	13.300000	---	---	2405.250000	2418.550000
2437.000000	13.400000	---	---	2430.350000	2443.750000
2462.000000	13.300000	---	---	2455.350000	2468.650000


99 % Bandwidth



99 % Bandwidth



99 % Bandwidth



## Measurement


Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	200.000 kHz	>= 200.000 kHz
VBW	1.000 MHz	>= 600.000 kHz
SweepPoints	400	~ 400
Sweeptime	47.266 us	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.06 dB	0.30 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11g:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	16.700000	---	---	2403.550000	2420.250000
2437.000000	16.800000	---	---	2428.550000	2445.350000
2462.000000	16.600000	---	---	2453.750000	2470.350000


99 % Bandwidth



99 % Bandwidth



99 % Bandwidth



### Measurement


Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	200.000 kHz	>= 200.000 kHz
VBW	1.000 MHz	>= 600.000 kHz
SweepPoints	400	~ 400
Sweptime	47.266 us	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	24 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.10 dB	0.30 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11n20:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	17.700000	---	---	2403.150000	2420.850000
2437.000000	17.700000	---	---	2428.150000	2445.850000
2462.000000	17.700000	---	---	2453.150000	2470.850000


99 % Bandwidth



99 % Bandwidth



99 % Bandwidth



## Measurement

Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	200.000 kHz	>= 200.000 kHz
VBW	1.000 MHz	>= 600.000 kHz
SweepPoints	400	~ 400
Sweeptime	47.266 us	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FET	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	19 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.19 dB	0.30 dB


Remark: Cable loss 0.8dB was considered and set in system configuration.

## 9.2 Minimum Emission Bandwidth 6 dB


802.11b:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	9.100000	---	---	2407.425000	2416.525000
2437.000000	9.100000	---	---	2432.425000	2441.525000
2462.000000	8.150000	---	---	2458.375000	2466.525000

6 dB Bandwidth




6 dB Bandwidth





6 dB Bandwidth



## Measurement


Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	100.000 kHz	100.000 kHz
VBW	300.000 kHz	300.000 kHz
SweepPoints	800	~ 800
SweepTime	94.922 us	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FET	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	10 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.11 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11g:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	16.400000	---	---	2403.775000	2420.175000
2437.000000	16.400000	---	---	2428.775000	2445.175000
2462.000000	16.400000	---	---	2453.775000	2470.175000


6 dB Bandwidth



6 dB Bandwidth



6 dB Bandwidth



## Measurement


Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	800	~ 800
Sweeptime	94.922 us	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	20 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.14 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.


802.11n20:

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2412.000000	17.650000	---	---	2403.175000	2420.825000
2437.000000	17.650000	---	---	2428.175000	2445.825000
2462.000000	17.350000	---	---	2453.475000	2470.825000


6 dB Bandwidth



6 dB Bandwidth



6 dB Bandwidth



## Measurement

Setting	Instrument Value	Target Value
Span	40.000 MHz	40.000 MHz
RBW	100.000 kHz	~ 100.000 kHz
VBW	300.000 kHz	~ 300.000 kHz
SweepPoints	800	~ 800
Sweptime	94.922 us	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamplifier	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	14 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.43 dB	0.50 dB


Remark: Cable loss 0.8dB was considered and set in system configuration.

### 9.3 RF output power

Operation Mode	DUT Frequency (MHz)	Limit Max (dBm)	Gated Level (dBm)	Result
802.11b	2412.000000	30.0	13.3	PASS
802.11b	2437.000000	30.0	11.9	PASS
802.11b	2462.000000	30.0	12.7	PASS
802.11g	2412.000000	30.0	9.6	PASS
802.11g	2437.000000	30.0	8.9	PASS
802.11g	2462.000000	30.0	10.3	PASS
802.11n20	2412.000000	30.0	10.3	PASS
802.11n20	2437.000000	30.0	9.3	PASS
802.11n20	2462.000000	30.0	10.6	PASS


Remark:  
 Cable loss 0.8dB was considered and set in system configuration.

(only the plot of the worst case is shown for each mode)  
 802.11b:



802.11g:


Gated Trace



— Gated Trace — Overall — Limit

802.11n20:

Gated Trace




— Gated Trace — Overall — Limit

Power Spectral Density

802.11b:


DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2412.000000	2412.475000	4.163	8.0	PASS
2437.000000	2436.475000	2.912	8.0	PASS
2462.000000	2461.475000	3.621	8.0	PASS

Peak Power Spectral Density



— Limit    — Sum Level    ◆ PSD


Peak Power Spectral Density



— Limit    — Sum Level    ◆ PSD



Peak Power Spectral Density




— Limit    — Sum Level    ◆ PSD

802.11g:


DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2412.000000	2405.725000	-2.438	8.0	PASS
2437.000000	2444.475000	-3.237	8.0	PASS
2462.000000	2460.725000	-2.025	8.0	PASS

Peak Power Spectral Density




— Limit    — Sum Level    ◆ PSD

Peak Power Spectral Density



— Limit    — Sum Level    ◆ PSD

Peak Power Spectral Density




— Limit    — Sum Level    ◆ PSD

802.11n20:


DUT Frequency (MHz)	Frequency (MHz)	PSD (dBm)	Limit Max (dBm)	Result
2412.000000	2405.725000	-1.693	8.0	PASS
2437.000000	2444.475000	-2.745	8.0	PASS
2462.000000	2466.975000	-1.582	8.0	PASS

Peak Power Spectral Density




— Limit    — Sum Level    ◆ PSD

Peak Power Spectral Density



— Limit    — Sum Level    ◆ PSD

Peak Power Spectral Density



— Limit    — Sum Level    ◆ PSD

### Measurement


Setting	Instrument Value	Target Value
Span	30.000 MHz	30.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	600	~ 600
SweepTime	12.000 ms	12.000 ms
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	45 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.30 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.

### 9.4 Band Edge

802.11b Band Edge Low

Band Edge




— Limit    — Sum Level    × Fail

### Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.575000	-43.5	19.9	-23.7	PASS
2399.525000	-43.6	20.0	-23.7	PASS
2399.875000	-44.7	21.0	-23.7	PASS
2399.475000	-44.8	21.1	-23.7	PASS
2399.925000	-44.9	21.2	-23.7	PASS
2399.975000	-45.4	21.7	-23.7	PASS
2310.525000	-45.5	21.9	-23.7	PASS
2399.625000	-45.8	22.1	-23.7	PASS
2398.475000	-45.9	22.2	-23.7	PASS
2371.725000	-46.0	22.3	-23.7	PASS
2399.075000	-46.0	22.3	-23.7	PASS
2397.975000	-46.0	22.3	-23.7	PASS
2310.575000	-46.1	22.4	-23.7	PASS
2398.575000	-46.1	22.4	-23.7	PASS
2397.725000	-46.2	22.5	-23.7	PASS

Remark: Limit = Inband peak - 30dB

802.11b Band Edge High




**Measurements**

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2492.575000	-46.6	22.3	-24.3	PASS
2489.725000	-47.1	22.8	-24.3	PASS
2488.625000	-47.1	22.8	-24.3	PASS
2493.825000	-47.1	22.8	-24.3	PASS
2483.725000	-47.1	22.8	-24.3	PASS
2492.525000	-47.1	22.8	-24.3	PASS
2490.825000	-47.1	22.8	-24.3	PASS
2494.325000	-47.1	22.8	-24.3	PASS
2483.675000	-47.2	22.9	-24.3	PASS
2493.875000	-47.2	22.9	-24.3	PASS
2496.975000	-47.2	22.9	-24.3	PASS
2484.675000	-47.3	23.0	-24.3	PASS
2484.625000	-47.3	23.0	-24.3	PASS
2489.975000	-47.3	23.0	-24.3	PASS
2490.325000	-47.3	23.0	-24.3	PASS

Remark: Limit = Inband peak - 30dB

802.11g Band Edge Low




**Measurements**

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-38.4	8.1	-30.3	PASS
2399.925000	-38.6	8.2	-30.3	PASS
2399.875000	-40.2	9.9	-30.3	PASS
2399.825000	-41.5	11.2	-30.3	PASS
2399.625000	-41.6	11.2	-30.3	PASS
2399.575000	-41.7	11.4	-30.3	PASS
2399.675000	-42.1	11.7	-30.3	PASS
2399.775000	-42.1	11.8	-30.3	PASS
2399.725000	-42.3	11.9	-30.3	PASS
2399.525000	-42.3	12.0	-30.3	PASS
2399.475000	-42.5	12.2	-30.3	PASS
2399.325000	-43.3	12.9	-30.3	PASS
2399.425000	-43.3	13.0	-30.3	PASS
2399.275000	-43.7	13.4	-30.3	PASS
2399.375000	-44.5	14.1	-30.3	PASS

Remark: Limit = Inband peak - 30dB

802.11g Band Edge High




**Measurements**

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2483.775000	-51.9	22.1	-29.8	PASS
2483.725000	-52.2	22.4	-29.8	PASS
2483.825000	-52.6	22.8	-29.8	PASS
2484.125000	-53.1	23.3	-29.8	PASS
2484.175000	-53.1	23.3	-29.8	PASS
2484.075000	-54.2	24.4	-29.8	PASS
2483.675000	-54.3	24.5	-29.8	PASS
2487.975000	-54.5	24.7	-29.8	PASS
2484.225000	-54.5	24.7	-29.8	PASS
2487.925000	-54.6	24.8	-29.8	PASS
2485.375000	-54.7	24.8	-29.8	PASS
2485.425000	-54.7	24.9	-29.8	PASS
2490.425000	-54.7	24.9	-29.8	PASS
2484.725000	-54.8	25.0	-29.8	PASS
2493.175000	-54.9	25.1	-29.8	PASS

Remark: Limit = Inband peak - 30dB



802.11n20 Band Edge Low




**Measurements**

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-39.5	9.6	-29.8	PASS
2399.925000	-40.3	10.5	-29.8	PASS
2399.875000	-41.1	11.2	-29.8	PASS
2399.825000	-41.3	11.5	-29.8	PASS
2399.775000	-41.8	12.0	-29.8	PASS
2399.625000	-42.3	12.4	-29.8	PASS
2399.725000	-42.4	12.6	-29.8	PASS
2399.675000	-42.4	12.6	-29.8	PASS
2399.575000	-42.5	12.7	-29.8	PASS
2399.525000	-43.2	13.4	-29.8	PASS
2399.425000	-43.3	13.5	-29.8	PASS
2399.475000	-44.1	14.2	-29.8	PASS
2399.325000	-44.3	14.5	-29.8	PASS
2399.375000	-44.3	14.5	-29.8	PASS
2399.275000	-45.2	15.4	-29.8	PASS

Remark: Limit = Inband peak - 30dB

802.11n20 Band Edge High

## Measurements



Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2495.275000	-46.0	16.5	-29.5	PASS
2492.875000	-46.1	16.6	-29.5	PASS
2495.325000	-46.3	16.8	-29.5	PASS
2499.325000	-46.4	16.9	-29.5	PASS
2499.375000	-46.5	17.0	-29.5	PASS
2492.825000	-46.6	17.0	-29.5	PASS
2489.975000	-46.7	17.2	-29.5	PASS
2496.325000	-46.7	17.2	-29.5	PASS
2490.025000	-46.7	17.2	-29.5	PASS
2487.775000	-46.9	17.4	-29.5	PASS
2488.375000	-47.0	17.4	-29.5	PASS
2496.375000	-47.0	17.5	-29.5	PASS
2483.625000	-47.0	17.5	-29.5	PASS
2490.725000	-47.0	17.5	-29.5	PASS
2494.525000	-47.0	17.5	-29.5	PASS

Remark: Limit = Inband peak - 30dB

### Measurement setting

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	1670	~ 1670
SweepTime	1.670 ms	AUTO
Reference Level	10.000 dBm	10.000 dBm
Attenuation	30.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.46 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.




**Report No.:** HKEM220900091702  
**Page:** 68 of 70


### 9.5 Conducted spurious emission

Only the worst case is shown for each mode

802.11b




802.11g



802.11n20

Spurious



— Limit    — Sum Level    — Threshold    × Critical    × Final Critical

Limit=Inband peak-30dB

### Measurement

Setting	Instrument Value	Target Value
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	2601	~ 2601
SweepTime	23.700 ms	AUTO
Reference Level	-10.000 dBm	-30.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	3	3
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	8 / max. 40	max. 40
Stable	3 / 3	3
Max Stable Difference	0.00 dB	0.50 dB

Remark: Cable loss 0.8dB was considered and set in system configuration.

- End of the Report -