



VTech Telecommunications Ltd.

Application
For
Permissive Change Class II

900MHz/5.8GHz 30 Channel Analog Modulation Cordless Phone with
Caller ID and Digital Answering Machine - Base Unit

(FCC ID: EW780-5735-02)

HK08091481-1
KS/ ac
November 8, 2008

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-ettsemko.com

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Letter of Agency
<i>EXHIBIT 9:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

VTech Telecommunications Ltd. - Model: EL42208, EL42108, EL42308,
EL42408, EL42x58

FCC ID: EW780-5735-02

This report concerns (check one:)		Original Grant <input type="checkbox"/>	Class II Change <input checked="" type="checkbox"/>
Equipment Type : <u>DXX - Pt 15 Low Pwr Com. Device TX</u>			
Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?		Yes <input type="checkbox"/>	No <input checked="" type="checkbox"/>
		If yes, defer until : _____ date	
Company Name agrees to notify the Commission by:		_____ date	
of the intended date of announcement of the product so that the grant can be issued on that date.			
Transition Rules Request per 15.37 ?		Yes <input type="checkbox"/>	No <input checked="" type="checkbox"/>
If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-07 Edition] Provision.			
Report prepared by:	Sit Kim Wai, Ken Intertek Testing Services Hong Kong Ltd. 2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. Phone : 852-2173-8538 Fax: 852-2741-1693		

INTERTEK TESTING SERVICES

Table of Contents

1.0 General Description	6
1.1 Product Description	6
1.2 Purpose of Application.....	6
1.3 Test Methodology.....	7
1.4 Test Facility.....	7
2.0 System Test Configuration	9
2.1 Justification	9
2.2 EUT Exercising Software.....	9
2.3 Details of EUT and Description of Peripherals	10
2.4 Measurement Uncertainty	11
2.5 Equipment Modification	11
3.0 Emission Results	13
3.1 Field Strength Calculation.....	14
3.2 Radiated Emission Configuration Photograph - Base Unit.....	15
3.3 Radiated Emission Data - Base Unit.....	16
3.4 Radiated Emission on the Bandedge.....	19
3.5 Line Conducted Configuration Photograph - Base Unit	20
3.6 Line Conducted Emission Data – Base Unit.....	21
4.0 Equipment Photographs	24
5.0 Product Labelling	26
6.0 Technical Specifications	28
7.0 Instruction Manual	30
8.0 Letter of Agency	32
9.0 Confidentiality Request	34

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Operational Description	Technical Description	descri.pdf
Cover Letter	Purpose of Application	product change.pdf
Test Setup Photos	Radiated & Conducted Emission for Base	config photos.pdf
Test Report	Emission Plot	emission.pdf
Test Report	Conducted Emission Test Result	conduct.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location Info	Label Artwork and Location	label.pdf
Users Manual	User Manual	manual 1.pdf manual 2.pdf manual 3.pdf
Cover Letter	Letter of Agency	letter of agency.pdf
Cover Letter	Confidentiality Request	request.pdf

INTERTEK TESTING SERVICES

EXHIBIT 1 GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The EL42208 is a 900MHz/5.8GHz 30 Channel Analog Modulation Cordless Phone with Caller ID and Digital Answering Machine - Base Unit. Operating frequencies of Base Unit and Handset are from 912.750MHz to 917.100MHz, and from 5857.200MHz to 5865.900MHz respectively. The EUT is powered by an AC adaptor 117VAC to 7.5VAC 350mA. The unit is capable of either tone or pulse dialing. The circuit wiring is consistent under the requirement of part 68.

The antennas used in base unit is integral, and the tested sample is a prototype.

The Model: EL42108, EL42308, EL42408 and EL42x58 is the same as the Model: EL42208 in hardware aspect except colour, cosmetic details and model number. "x" indicates different number of same design handset and extra charger. The difference in model number serves as marketing strategy.

The circuit description is saved with filename: descri.pdf

Connection between the base unit and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

1.2 Purpose of Application

The purpose of application is saved with filename: product change.pdf

The RF module of the Base Unit is the same as the previous granted Model: ia5823. Enclosure, baseband circuit and PCB layout are changed.

This is an Application for Certification of a Base Unit of a cordless telephone system. The FCC ID of the associated Handset is EW780-5735-05 and has been granted. A verification report has been prepared for the digital portion. The device is also subject to Part 68 Registration.

INTERTEK TESTING SERVICES

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data and conducted data are located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

INTERTEK TESTING SERVICES

**EXHIBIT 2
SYSTEM TEST CONFIGURATION**

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

For emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

Measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

2.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

2.3 Details of EUT and Description of Peripherals

Details of EUT:

An AC adaptor (provided with the unit) was used to power the device. This description are listed below.

- (1) Base Unit: An AC adaptor (117VAC to 7.5VAC 350mA, Model: UA075035E) (Supplied by Client)

Description of Peripherals:

- (1) Handset: A "Ni-Cd" type rechargeable battery (3.6V 400mAh) (Supplied by Client)
- (2) Handset, Model: EL42208, FCC ID: EW780-5735-05 (Supplied by Client)
- (3) 3m Telephone Line (1m, unshielded, terminated) (Supplied by Intertek)

INTERTEK TESTING SERVICES

2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty test has been considered.

2.5 Equipment Modification

Any modifications installed previous to testing by VTech Telecommunications Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Commercial & Electrical Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 2.0 of this report are confirmed by:

Confirmed by:

*Sit Kim Wai, Ken
Assistant Manager
Intertek Testing Services
Agent for VTech Telecommunications Ltd.*



_____ Signature

November 8, 2008 _____ Date

INTERTEK TESTING SERVICES

**EXHIBIT 3
EMISSION RESULTS**

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:-

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m
 RR = RA - AG in dB μ V
 LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
FS = RR + LF
FS = 23 + 9 = 32 dB μ V/m

RR = 23.0 dB μ V
LF = 9.0 dB

Level in μ V/m = Common Antilogarithm [(32 dB μ V/m)/20] = 39.8 μ V/m

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission

at 1834.200 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.pdf

INTERTEK TESTING SERVICES

3.3 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 5.0 dB margin

TEST PERSONNEL:



Tester Signature

Melvin Nip, Senior Lead Engineer
Typed/Printed Name

November 8, 2008
Date

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: EL42208
Mode : TX-Channel 00

Date of Test: October 27-30, 2008

Table 1, Base unit

Radiated Emissions Pursuant to FCC 15.249: Emissions Requirement

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	912.750	68.8	16	33.0	85.8	94.0	-8.2
H	1825.500	54.1	33	27.2	48.3	54.0	-5.7
H	*2738.250	50.6	33	30.4	48.0	54.0	-6.0
H	*3651.000	46.6	33	33.3	46.9	54.0	-7.1
H	*4563.750	44.1	33	34.9	46.0	54.0	-8.0
H	5476.500	43.1	33	35.7	45.8	54.0	-8.2
H	6389.250	41.4	33	36.9	45.3	54.0	-8.7

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Melvin Nip

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: EL42208
Mode : TX-Channel 29

Date of Test: October 27-30, 2008

Table 2, Base unit

Radiated Emissions Pursuant to FCC 15.249: Emission Requirement

Polarization	Frequency	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	917.100	68.5	16	33.0	85.5	94.0	-8.5
H	1834.200	54.8	33	27.2	49.0	54.0	-5.0
H	*2751.300	51.0	33	30.4	48.4	54.0	-5.6
H	*3668.400	46.9	33	33.3	47.2	54.0	-6.8
H	*4585.500	44.4	33	34.9	46.3	54.0	-7.7
H	5502.600	42.2	33	36.6	45.8	54.0	-8.2
H	6419.700	41.3	33	36.9	45.2	54.0	-8.8

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna is used for the emission over 1000MHz.
 5. Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).
- * Emission within the restricted band meets the requirement of part 15.205.

Test Engineer: Melvin Nip

INTERTEK TESTING SERVICES

3.4 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (902MHz and 928MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

Please refer to the following plots for radiated emission on the bandedge:

Plot B1A: Base Unit - Low Channel Emissions

Plot B1B: Base Unit - High Channel Emissions

For electronic filing, the above plots are saved with filename: emission.pdf

Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

3.5 Line Conducted Configuration Photograph - Base Unit

Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.pdf

INTERTEK TESTING SERVICES

3.6 Line Conducted Emission Data – Base Unit

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

TEST PERSONNEL:



Tester Signature

Melvin Nip, Senior Lead Engineer
Typed/Printed Name

November 8, 2008
Date

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: EL42208

Date of Test: October 27-30, 2008

Conducted Emissions

For electronic filing, the conducted emission test result is saved with filename:
conduct.pdf

INTERTEK TESTING SERVICES

**EXHIBIT 4
EQUIPMENT PHOTOGRAPHS**

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf

INTERTEK TESTING SERVICES

**EXHIBIT 5
PRODUCT LABELLING**

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf

INTERTEK TESTING SERVICES

**EXHIBIT 6
TECHNICAL SPECIFICATIONS**

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

INTERTEK TESTING SERVICES

**EXHIBIT 7
INSTRUCTION MANUAL**

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

The required FCC Information to the User is stated on the Instruction Manual.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

**EXHIBIT 8
LETTER OF AGENCY**

INTERTEK TESTING SERVICES

8.0 Letter of Agency

For electronic filing, a letter of agency is saved with filename: letter of agency.pdf

INTERTEK TESTING SERVICES

**EXHIBIT 9
CONFIDENTIALITY REQUEST**

INTERTEK TESTING SERVICES

9.0 Confidentiality Request

For electronic filing, a preliminary copy of the Confidentiality Request is saved with filename: request.pdf