

# TEST REPORT

Applicant Name: FCC: VTech Telecommunications Ltd  
IC: VTECH TELECOMMUNICATIONS LIMITED  
Address: FCC: 23/F Tai Ping Ind Center Block 1 57 Ting Kok Rd Tai Po  
NT, Hong Kong  
IC: BL.1 23/F Tai Ping Industr Ctr. 57 Ting Kok Road Tai Po,  
NT Hongkong  
Report Number: SZ1240103-00576E-RFA  
FCC ID: EW780-H2B9-43  
IC: 1135B-80H2B943

## Test Standard (s)

FCC PART 15D; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2; RSS-213, ISSUE 3,  
MARCH 2015

## Sample Description

Product Type: SIP cordless hotel phone  
Model No.: PMX-S5410  
Multiple Model(s) No.: PMX-S5420  
Trade Mark: vtech  
Date Received: 2024/01/04  
Issue Date: 2024/04/18

Test Result:	Pass <sup>▲</sup>
--------------	-------------------

▲ In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

*Andy Yu*

Andy Yu  
RF Engineer

## Approved By:

*Nancy Wang*

Nancy Wang  
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

## Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

## TABLE OF CONTENTS

<b>DOCUMENT REVISION HISTORY .....</b>	<b>4</b>
<b>GENERAL INFORMATION.....</b>	<b>5</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE .....	5
TEST METHODOLOGY .....	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY .....	6
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>7</b>
DESCRIPTION OF TEST CONFIGURATION .....	7
EQUIPMENT MODIFICATIONS .....	7
SUPPORT EQUIPMENT LIST AND DETAILS .....	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP .....	8
<b>SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>11</b>
<b>FCC §1.1307(B) &amp; 2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>13</b>
<b>RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION</b>	<b>14</b>
APPLICABLE STANDARD .....	14
<b>§ 15.317, § 15.203 &amp; RSS-GEN §6.8 ANTENNA REQUIREMENT.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
ANTENNA CONNECTOR CONSTRUCTION .....	15
<b>§ 15.315, § 15.207 &amp; RSS-213 §5.4 CONDUCTED EMISSIONS.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
EUT SETUP.....	16
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE .....	17
FACTOR & OVER LIMIT CALCULATION.....	17
TEST DATA .....	18
<b>§ 15.323 (A) &amp; RSS-213 §5.5 EMISSION BANDWIDTH.....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
TEST PROCEDURE .....	23
TEST DATA .....	24
<b>§ 15.319 (C) &amp; RSS-213 §5.6 PEAK TRANSMIT POWER .....</b>	<b>28</b>
APPLICABLE STANDARD .....	28
TEST PROCEDURE .....	28
TEST DATA .....	29
<b>§ 15.319 (D) &amp; RSS-213 §5.7 POWER SPECTRAL DENSITY .....</b>	<b>34</b>
APPLICABLE STANDARD .....	34
TEST PROCEDURE .....	34
TEST DATA .....	35

**§15.319 (G), § 15.323 (D) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND.....39**

    APPLICABLE STANDARD .....39

    TEST PROCEDURE .....40

    SPURIOUS RADIATED EMISSION SET UP:.....41

    EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....42

    TEST PROCEDURE .....42

    FACTOR & OVER LIMIT/MARGIN CALCULATION .....43

    TEST DATA .....43

**§ 15.323 (F) & RSS-213 §5.3 FREQUENCY STABILITY .....70**

    APPLICABLE STANDARD .....70

    TEST PROCEDURE .....70

    TEST DATA .....71

**§ 15.323 (C)(E)§ 15.319 (F) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE .....72**

    APPLICABLE STANDARD .....72

    TEST PROCEDURE .....72

    TEST DATA .....72

    1) AUTOMATIC DISCONTINUATION OF TRANSMISSION.....73

    2) MONITORING TIME .....73

    3) LOWER MONITORING THRESHOLD.....73

    4) MAXIMUM TRANSMIT PERIOD .....74

    5) SYSTEM ACKNOWLEDGEMENT .....74

    6) LEAST INTERFERED CHANNEL (LIC) .....75

    7) RANDOM WAITING .....77

    8) MONITORING BANDWIDTH AND REACTION TIME .....78

    9) MONITORING ANTENNA.....78

    10) MONITORING THRESHOLD RELAXATION .....79

    11) DUPLEX CONNECTIONS.....79

    12) ALTERNATIVE MONITORING INTERVAL .....81

    13) FAIR ACCESS .....82

    14) FRAME REPETITION STABILITY FRAME PERIOD AND JITTER .....82

**EUT PHOTOGRAPHS .....83**

**TEST SETUP PHOTOGRAPHS .....84**

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	SZ1240103-00576E-RFA	Original Report	2024/04/18

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

HVIN	35-400189BS
FVIN	2L-3.3.0.10-0-vseries-2.10.60.29d2
Product	SIP cordless hotel phone
Tested Model	PMX-S5410
Multiple Model(s)	PMX-S5420
Frequency Range	1921.536-1928.448 MHz
Maximum conducted peak output power	20.0dBm
Modulation Technique	GFSK
Antenna Specification <sup>#</sup>	0dBi (It is provided by the applicant)
Voltage Range	DC 5V from adapter or DC 48V from PoE
Sample serial number	2G4S-11 for Conducted and Radiated Emissions Test 2G4S-7 for RF Conducted Test (Assigned by BAACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	Model: VT07EUS05200 Input: AC 100-240V~50/60Hz, 0.5A Output: DC 5.0V, 2.0A, 10.0W
Note: The Multiple models are electrically identical with the test model except for base and model name. Please refer to the declaration letter# for more detail, which was provided by manufacturer.	

### Objective

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.207, 15.315, 15.317, 15.319 and 15.323 rules. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 – 2013 and RSS-213 Issue 3, 2GHz License-Exempt Personal Communications Service Devices (PCS) OF THE Canadian Department of Industry rules and RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2 of the Innovation, Science and Economic Development Canada rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2013, American National Standard Methods of Measurement of the Electromagnetic and Operational Compatibility of Unlicensed Personal Communications Services (UPCS) Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

**Measurement Uncertainty**

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Frequency		213.55 Hz(k=2, 95% level of confidence)
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
Unwanted Emission, conducted		1.75 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured to testing mode which is provided by the manufacturer.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Digital Radio Communication Tester	CMD60	830553/018
HIKVISION	Router	DS-3WR03	10021642429
Unknown	Resistor	Unknown	Unknown
NOKIA	PoE	G0545-530-060-PSE1000	Unknown


### External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Un-detachable AC Cable	1.2	LISN/ AC mains	Receptacle
Unshielded Detachable AC Cable	1.2	AC Power Source	CMD60
Unshielded Un-detachable DC Cable	1.5	Adapter	EUT(Base)
Unshielded Detachable USB Cable	0.2	EUT(Base)	Resistor
Unshielded Detachable RJ45 Cable	5.0	EUT(Base)	Router
Unshielded Detachable AC Cable	1.5	LISN	PoE
Unshielded Detachable AC Cable	1.2	AC mains	PoE
Unshielded Detachable RJ45 Cable	5.0	PoE	Router
Unshielded Detachable RJ45 Cable	5.0	PoE	EUT(Base)


**Block Diagram of Test Setup**

Power by adapter

For Conducted Emission:




For Radiated Emission:






Power by PoE

For Conducted Emission:



For Radiated Emission:



## SUMMARY OF TEST RESULTS

FCC Rules	ISED Rules	Description of Test	Result
§ 1.1310 & §2.1091	RSS-102 § 2.5.2	RF Exposure Evaluation & Exemption Limits For Routine Evaluation-RF Exposure Evaluation	Compliant
§ 15.317, § 15.203	RSS-Gen §6.8	Antenna Requirement	Compliant
§ 15.315, § 15.207	RSS-213 §5.4	Conducted Emission	Compliant
§ 15.323 (a)	RSS-213 §5.5	Emission Bandwidth	Compliant
§ 15.319 (c)	RSS-213 §5.6	Peak Transmit Power	Compliant
§ 15.319 (d)	RSS-213 §5.7	Power Spectral Density	Compliant
§ 15.323 (d)	RSS-213 §5.8	Emission Inside and Outside the sub-band	Compliant
§15.205, §15.209, § 15.319 (g)	RSS-213 §5.8	Radiated Emission	Compliant
§ 15.323 (f)	RSS-213 §5.3	Frequency Stability	Compliant
§ 15.323 (c)(e) § 15.319 (f)	RSS-213 §5.1&§5.2	Specific Requirements for UPCS	Compliant

Note: the EUT has two antennas (ANT 0 and ANT 1), pre-scan the output power of them, the ANT1 is the larger one which was chosen for the full test.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emissions Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/01/16	2025/01/15
Rohde & Schwarz	LISN	ENV216	101613	2024/01/16	2025/01/15
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2023/08/03	2024/08/02
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218	NCR	NCR
<b>Radiated Emission Test</b>					
R&S	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2023/06/08	2024/06/07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2024/07/19
ETS	Passive Loop Antenna	6512	29604	2023/07/07	2024/07/06
Unknown	Cable	Chamber Cable 1	F-03-EM236	2023/08/03	2024/08/02
Unknown	Cable	Chamber Cable 4	EC-007	2023/08/03	2024/08/02
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2023/04/18	2024/04/17
COM-POWER	Pre-amplifier	PA-122	181919	2023/06/29	2024/06/28
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2024/07/25
Unknown	RF Cable	KMSE	0735	2023/10/08	2024/10/07
Unknown	RF Cable	UFA147	219661	2023/10/08	2024/10/07
Unknown	RF Cable	XH750A-N	J-10M	2023/10/08	2024/10/07
A.H.System	Pre-amplifier	PAM-1840VH	190	2023/08/03	2024/08/02
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2023/08/03	2024/08/02
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
MICRO-TRONICS	2.8G Passband filter	HPM50111	F-03-EM217	2023/08/03	2024/08/02
Wainwright Germany	B1(DECT) Pass filter	1920-1980	F-03-EM233	2023/07/04	2024/07/03

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>RF Conducted Test</b>					
R&S	Spectrum analyzer	FSV40	101942	2023/12/18	2024/12/17
R&S	SPECTRUM ANALYZER	FSU26	200120	2024/01/08	2025/01/07
BACL	Temperature & Humidity Chamber	BTH-150-40	30145	2024/01/16	2025/01/15
Rohde & Schwarz	Digital Radio Communication Tester	CMD60	830553/018	2023/06/08	2024/06/07
Keysight	MXG Vector Signal Generator	N5182B	MY53051503	2024/01/08	2025/01/07
Fluke	Digital Multimeter	287	19000011	2023/06/08	2024/06/07
WEINSCHL	3dB Attenuator	Unknown	F-03-EM220	2023/07/04	2024/07/03
WEINSCHL	Power Splitter	1515	RH386	2023/07/04	2024/07/03
Unknown	RF Cable	65475	01670515	2023/07/04	2024/07/03
HELLVIAO	Contact voltage regulator	TDGC2-5KVA	Unknown	NCR	NCR

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC §1.1307(b) & 2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**Result**

**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**Result**

**For worst case:**

Frequency (MHz)	Antenna Gain <sup>#</sup>	Tune up conducted power <sup>#</sup>	Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(dBm)			
1921.536-1928.448	0	20	20	0.02	1.0

Note: The tune-up power and antenna gain was declared by the applicant.

To maintain compliance with the FCC’s RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant.**

## RSS-102 § 2.5.2 –EXEMPTION LIMITS FOR ROUTINE EVALUATION-RF EXPOSURE EVALUATION

### Applicable Standard

According to RSS-102 § (2.5.2):

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance). In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

### Calculated Data:

The max tune-up conducted output power is 20dBm, antenna gain is 0dBi.

So the maximum e.i.r.p. of the device is  $20\text{dBm} + 0\text{dBi} = 20\text{dBm} = 0.1 \text{ W} < 2.3\text{W}$

The worst case is  $f = 1921.536\text{MHz}$ :

The limit is  $1.31 \times 10^{-2} f^{0.6834} \text{ W} = 2.3\text{W}$

To maintain Compliant with the ISEDC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant**

**§ 15.317, § 15.203 & RSS-Gen §6.8 ANTENNA REQUIREMENT**

**Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device’s antenna shall be stated, based on a measurement or on data from the antenna’s manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device’s ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

**Antenna Connector Construction**

The EUT has two integral antenna arrangements which were permanently attached and both the gain# is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna	Type	Antenna Gain#	Impedance
ANT 0	Monopole	0dBi	50 Ω
ANT 1	Monopole	0dBi	50 Ω

## § 15.315, § 15.207 & RSS-213 §5.4 CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.315, an unlicensed PCS device that is designed to be connected to the public utility (AC) power line must meet the limits specified in §15.207.


A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz-30 MHz, shall not exceed the limits in the below table.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in below table. The more stringent limit applies at the frequency range boundaries.

Table - AC Power Lines Conducted Emission Limits		
Frequency range (MHz)	Conducted limit (dBµV)	
	Quasi-Peak	Average**
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Note:** \*Decreases with the logarithm of the frequency  
 \*\* A linear average detector is required

### EUT Setup



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.315, FCC 15.207 and RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

### Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

**Test Data****Environmental Conditions**


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	42 %
<b>ATM Pressure:</b>	101 kPa

*The testing was performed by Macy Shi on 2024-02-24.*

*EUT operation mode: Transmitting (worst case is ANT 1 Low channel)*

**Power by adapter**


AC 120V/60 Hz, Line



Condition: Line  
 Project : SZ1240103-00576E-RF  
 Tester : Macy shi  
 Note : GFSK

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.17	-0.50	20.25	10.60	10.15	55.03	-34.78	Average
2	0.17	3.38	24.13	10.60	10.15	65.03	-40.90	QP
3	0.25	0.02	20.85	10.63	10.20	51.60	-30.75	Average
4	0.25	3.86	24.69	10.63	10.20	61.60	-36.91	QP
5	0.43	15.01	35.89	10.68	10.20	47.20	-11.31	Average
6	0.43	18.71	39.59	10.68	10.20	57.20	-17.61	QP
7	1.22	1.93	22.71	10.73	10.05	46.00	-23.29	Average
8	1.22	5.26	26.04	10.73	10.05	56.00	-29.96	QP
9	2.21	-1.03	19.94	10.77	10.20	46.00	-26.06	Average
10	2.21	3.67	24.64	10.77	10.20	56.00	-31.36	QP
11	5.28	-1.42	19.50	10.70	10.22	50.00	-30.50	Average
12	5.28	2.74	23.66	10.70	10.22	60.00	-36.34	QP

AC 120V/60 Hz, Neutral




Condition: Neutral  
 Project : SZ1240103-00576E-RF  
 Tester : Macy shi  
 Note : GFSK

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	-0.53	20.21	10.59	10.15	55.91	-35.70	Average
2	0.15	2.82	23.56	10.59	10.15	65.91	-42.35	QP
3	0.27	-1.75	18.92	10.50	10.17	51.07	-32.15	Average
4	0.27	0.65	21.32	10.50	10.17	61.07	-39.75	QP
5	0.43	12.18	33.03	10.65	10.20	47.20	-14.17	Average
6	0.43	14.49	35.34	10.65	10.20	57.20	-21.86	QP
7	1.72	-1.69	18.94	10.51	10.12	46.00	-27.06	Average
8	1.72	0.85	21.48	10.51	10.12	56.00	-34.52	QP
9	4.36	-2.23	18.47	10.45	10.25	46.00	-27.53	Average
10	4.36	1.11	21.81	10.45	10.25	56.00	-34.19	QP
11	29.68	-2.92	17.85	10.51	10.26	50.00	-32.15	Average
12	29.68	0.74	21.51	10.51	10.26	60.00	-38.49	QP

**Power by PoE**

**AC 120V/60 Hz, Line**




Condition: Line  
 Project : SZ1240103-00576E-RF  
 Tester : Macy shi  
 Note : GFSK

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.29	14.11	34.56	10.32	10.13	50.46	-15.90	Average
2	0.29	19.66	40.11	10.32	10.13	60.46	-20.35	QP
3	0.37	20.13	40.58	10.26	10.19	48.43	-7.85	Average
4	0.37	25.73	46.18	10.26	10.19	58.43	-12.25	QP
5	0.39	22.57	43.03	10.26	10.20	48.17	-5.14	Average
6	0.39	28.12	48.58	10.26	10.20	58.17	-9.59	QP
7	0.39	23.03	43.49	10.25	10.21	47.99	-4.50	Average
8	0.39	28.73	49.19	10.25	10.21	57.99	-8.80	QP
9	1.02	9.83	30.61	10.59	10.19	46.00	-15.39	Average
10	1.02	16.69	37.47	10.59	10.19	56.00	-18.53	QP
11	4.60	10.52	31.21	10.45	10.24	46.00	-14.79	Average
12	4.60	15.59	36.28	10.45	10.24	56.00	-19.72	QP

AC 120V/60 Hz, Neutral

Date: 2024-02-24



Condition: Neutral  
 Project : SZ1240103-00576E-RF  
 Tester : Macy shi  
 Note : GFSK

	Read Freq	Read Level	LISN Level	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	18.56	38.92	10.21	10.15	55.91	-16.99	Average
2	0.15	25.55	45.91	10.21	10.15	65.91	-20.00	QP
3	0.30	13.40	34.22	10.69	10.13	50.37	-16.15	Average
4	0.30	19.74	40.56	10.69	10.13	60.37	-19.81	QP
5	0.37	20.37	41.28	10.73	10.18	48.52	-7.24	Average
6	0.37	25.67	46.58	10.73	10.18	58.52	-11.94	QP
7	0.39	23.20	44.16	10.75	10.21	48.08	-3.92	Average
8	0.39	28.31	49.27	10.75	10.21	58.08	-8.81	QP
9	1.03	7.90	28.37	10.29	10.18	46.00	-17.63	Average
10	1.03	16.25	36.72	10.29	10.18	56.00	-19.28	QP
11	25.32	9.01	29.51	10.26	10.24	50.00	-20.49	Average
12	25.32	14.28	34.78	10.26	10.24	60.00	-25.22	QP


## § 15.323 (A) & RSS-213 §5.5 EMISSION BANDWIDTH

### Applicable Standard

Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:

Test Setup 1:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

### Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

EBW:

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

OBW:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24.5 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101 kPa

The testing was performed by Hanic Pan on 2024-02-23.


Test mode: Transmitting

Test Result: Compliant

Channel	Center Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.221	1.452	50 kHz ~ 2.5 MHz
Middle	1924.992	1.218	1.452	50 kHz ~ 2.5 MHz
High	1928.448	1.206	1.476	50 kHz ~ 2.5 MHz

**99% Emission Bandwidth**


**Low Channel**



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
 Date: 23.FEB.2024 11:55:04




### Middle Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 23.FEB.2024 11:31:53


### High Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 23.FEB.2024 11:02:23

### 26 dB Emission Bandwidth


#### Low Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan

Date: 23.FEB.2024 11:55:54


#### Middle Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan

Date: 23.FEB.2024 11:32:33

### High Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 23.FEB.2024 11:03:34

## § 15.319 (c) & RSS-213 §5.6 PEAK TRANSMIT POWER

### Applicable Standard

The peak power output as measured over an interval of time equal to the frame rate or transmission burst of the device under all conditions of modulation. Usually this parameter is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used[47 CFR 15, subpart D, 15.303].

The peak transmit power is according to ANSI C63.17-2013 §6.1.2

Per FCC Part15.319 (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Per FCC Part15.319 (e), the peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Calculation of Peak Transmit Power Limit:

$$\text{Peak Transmit Power Limit} = 100\mu\text{W} \times (\text{EBW})^{1/2}$$


EBW is the transmit emission bandwidth in Hz determined in the other test item:

Peak transmit power shall not exceed 100 μW multiplied by the square root of the occupied bandwidth in hertz. The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

### Test Procedure

Using the manufacturer’s information on occupied bandwidth set the spectrum analyzer as follows:

RBW	≥ Emission bandwidth
Video bandwidth	≥ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101 kPa

The testing was performed by Hanic Pan on 2024-03-06.

Test mode: Transmitting:


**Test Result: Compliant**

Please refer to the following table and plots.

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	FCC Limit (dBm)	ISED Limit (dBm)
ANT 0				
Low	1921.536	19.88	20.81	20.43
Middle	1924.992	19.85	20.81	20.43
High	1928.448	19.78	20.85	20.41
ANT 1				
Low	1921.536	20.00	20.81	20.43
Middle	1924.992	20.00	20.81	20.43
High	1928.448	19.96	20.85	20.41
For FCC: EBW <sub>Low channel</sub> = 1452000Hz, EBW <sub>Middle channel</sub> = 1452000 Hz, EBW <sub>High channel</sub> = 1476000 Hz Peak Transmit Power Limit = $100(EBW)^{1/2}$ μW				
For ISED: OBW <sub>Low channel</sub> = 1221000Hz, OBW <sub>Middle channel</sub> = 1218000 Hz, OBW <sub>High channel</sub> = 1206000 Hz Peak Transmit Power Limit = $100(OBW)^{1/2}$ μW				


ANT 0

### Low Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 6.MAR.2024 09:56:06

### Middle Channel




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 6.MAR.2024 09:54:50




ANT 1

### Low Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 6.MAR.2024 02:14:05


### Middle Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 6.MAR.2024 02:13:19



### High Channel



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 6.MAR.2024 02:12:42

**§ 15.319 (d) & RSS-213 §5.7 POWER SPECTRAL DENSITY**

**Applicable Standard**

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.


The power spectral density is measured in accordance with ANSI C63.17-2013 Clause 6.1.5.

The peak-hold power spectral density of transmitters shall not exceed 12 mW per any 3 kHz bandwidth. As an alternative to the peak-hold power spectral density, the time-averaged power spectral density may be measured and it shall not exceed 3 mW per any 3 kHz bandwidth.

**Test Procedure**

Using the manufacturer’s information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	$\geq 3 \times \text{RBW}$
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 $\mu\text{s}$ ). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal



**Test Data****Environmental Conditions**

<b>Temperature:</b>	24.6 °C
<b>Relative Humidity:</b>	54.5 %
<b>ATM Pressure:</b>	101 kPa


*The testing was performed by Bruce Lin on 2024-03-26.*

*Test mode: Transmitting*


***Test Result: Compliant.*** Please refer to following table and plots

Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)
		(dBm/3kHz)	(mW/3kHz)	
Low	1921.536	-4.15	0.385	3
Middle	1924.992	-3.21	0.478	3
High	1928.448	-2.64	0.545	3

### Low Channel




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:29:44




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:31:33

### Middle Channel




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:23:46




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:27:46

### High Channel



ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:20:29



ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:21:54

---

**§15.319 (g), § 15.323 (d) & RSS-213 §5.8 EMISSION INSIDE AND OUTSIDE THE SUB-BAND**

---

**Applicable Standard**

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mw (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

**Emissions outside the 1920-1930 MHz Band**

Emissions outside the 1920-1930 MHz band shall be attenuated below a reference power of 112 milliwatts (-9.5 dBW) by at least:

- 30 dB between the band edges and 1.25 MHz above and below the band edges;
- 50 dB between 1.25 MHz and 2.5 MHz above or below the band edges; and
- 60 dB at 2.5 MHz or greater above or below the band edges.

**Emissions inside the 1920-1930 MHz Band**

Emissions inside the 1920-1930 MHz band shall be attenuated below the transmit power permitted for that device, as follows:

- 30 dB between the frequencies 1B and 2B measured from the centre of the occupied bandwidth;
- 50 dB between the frequencies 2B and 3B measured from the centre of the occupied bandwidth; and
- 60 dB between the frequencies 3B and band edge, where B is the occupied bandwidth in hertz.

**Test Procedure**

According to ANSI C63.17.2013 Clause 6.1.6.

**In-band emission:**


**Spectrum analyzer settings for measuring in-band emission**

RBW	Approximately 1% of the emission bandwidth ( <i>B</i> )
Video bandwidth	3 × RBW
Sweep time	The sweep time shall be sufficiently slow that the swept frequency rate shall not exceed one RBW per three transmit bursts.
Number of sweeps	Sufficient to stabilize the trace
Amplitude scale	Log
Detection	Peak detection and max hold enabled
Span	Approximately equal to 3.5 <i>B</i>

**Out-band emission:**

RBW	30kHz
Video bandwidth	100kHz
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection


**RF Conducted Emission:**






**Spurious radiated emission set up:**


**9 kHz-30MHz:**



**30MHz-1GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site.

**EMI Test Receiver & Spectrum Analyzer Setup**

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK
Above 1 GHz*	1MHz	3 MHz	/	PK
	1MHz	10Hz	/	Average

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

For the average emission of Fundamental and harmonic, it was calculated by the below formula:

Average= Peak Measurement + Duty Cycle Corrected Factor

**Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

**Factor & Over Limit/Margin Calculation**

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level/Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	22~24.7 °C
<b>Relative Humidity:</b>	44~54.5 %
<b>ATM Pressure:</b>	101 kPa

*The testing was performed by Anson Su on 2024-02-23 for below 1GHz, Dylan Yang on 2024-02-06 for above 1GHz, Hanic Pan on 2024-03-01 and Bruce Lin on 2024-03-26 for RF conducted.*

*Test mode: Transmitting*


**Test Result: Compliant**

*Please refer to following plots*

Note: For the spurious emission below 30MHz, the emissions are 20dB below the limit which are not recorded.


FCC:

### Low Channel (Unwanted Emission inside the Sub-band)




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 13:58:09

### Middle Channel (Unwanted Emission inside the Sub-band)



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:46:27


### High Channel (Unwanted Emission inside the Sub-band)



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:31:15


### ISED:

### Low Channel (Unwanted Emission inside the Sub-band)




ProjectNo.:SZ1240103-00576E-RF Tester:Bruce Lin  
Date: 26.MAR.2024 19:33:13

### Middle Channel (Unwanted Emission inside the Sub-band)




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:35:16

### High Channel (Unwanted Emission inside the Sub-band)




ProjectNo.:SZ1240103-00576E-FP Tester:Bruce Lin  
Date: 26.MAR.2024 19:39:19


### Low Channel (Unwanted Emission outside the Sub-band)




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 13:58:50



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 13:59:32




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:00:08




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:00:51






ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
 Date: 1.MAR.2024 14:01:53


### Middle Channel (Unwanted Emission outside the Sub-band)




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
 Date: 1.MAR.2024 14:47:09




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:47:51



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:48:27




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:49:10




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:50:12


### High Channel (Unwanted Emission outside the Sub-band)




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:31:57




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:32:39



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:33:15



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:33:56




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 1.MAR.2024 14:34:58

**30MHz-1GHz:** (Maximum output power mode, ANT 1 Low channel)

Power by adapter


**Horizontal**



Site : chamber  
 Condition : 3m Horizontal  
 Project Number: SZ1240103-00576E-RF  
 Note : GFSK  
 Tester : Anson Su

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	40.93	-10.99	25.58	14.59	40.00	-25.41	QP
2	97.84	-14.34	30.62	16.28	43.50	-27.22	QP
3	150.67	-11.39	48.38	36.99	43.50	-6.51	QP
4	158.53	-11.80	47.60	35.80	43.50	-7.70	QP
5	382.92	-8.21	46.89	38.68	46.00	-7.32	QP
6	401.13	-7.32	38.94	31.62	46.00	-14.38	QP

**Vertical**




Site : chamber  
 Condition : 3m Vertical  
 Project Number: SZ1240103-00576E-RF  
 Note : GFSK  
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	42.17	-13.13	39.27	26.14	40.00	-13.86	QP
2	99.35	-15.37	35.99	20.62	43.50	-22.88	QP
3	151.20	-11.71	46.33	34.62	43.50	-8.88	QP
4	388.67	-8.15	40.19	32.04	46.00	-13.96	QP
5	625.08	-3.65	33.71	30.06	46.00	-15.94	QP
6	750.11	-2.17	32.68	30.51	46.00	-15.49	QP



Power by PoE


**Horizontal**



Site : chamber  
 Condition : 3m Horizontal  
 Project Number: SZ1240103-00576E-RF  
 Note : GFSK  
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.61	-10.78	24.03	13.25	40.00	-26.75	QP
2	94.59	-15.26	30.13	14.87	43.50	-28.63	QP
3	120.65	-10.34	44.87	34.53	43.50	-8.97	QP
4	384.44	-8.13	47.45	39.32	46.00	-6.68	QP
5	402.72	-7.27	37.63	30.36	46.00	-15.64	QP
6	718.88	-1.57	32.11	30.54	46.00	-15.46	QP

**Vertical**



Site : chamber  
 Condition : 3m Vertical  
 Project Number: SZ1240103-00576E-RF  
 Note : GFSK  
 Tester : Anson Su

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	48.95	-16.89	37.13	20.24	40.00	-19.76	QP
2	54.28	-17.53	41.52	23.99	40.00	-16.01	QP
3	120.22	-10.76	39.55	28.79	43.50	-14.71	QP
4	389.01	-8.13	39.14	31.01	46.00	-14.99	QP
5	625.08	-3.65	29.41	25.76	46.00	-20.24	QP
6	750.11	-2.17	31.27	29.10	46.00	-16.90	QP

**Above 1GHz:**

**ANT 0**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	PK/Ave					
Low Channel							
1921.536	117.99	PK	H	-6.39	111.60	/	/
1921.536	114.82	PK	V	-6.39	108.43	/	/
3843.08	65.31	PK	H	-0.78	64.53	74	-9.47
3843.08	62.31	PK	V	-0.78	61.53	74	-12.47
Middle Channel							
1924.992	118.03	PK	H	-6.39	111.64	/	/
1924.992	115.36	PK	V	-6.39	108.97	/	/
3849.98	65.22	PK	H	-0.79	64.43	74	-9.57
3849.98	62.55	PK	V	-0.79	61.76	74	-12.24
High Channel							
1928.448	118.01	PK	H	-6.39	111.62	/	/
1928.448	114.66	PK	V	-6.39	108.27	/	/
3856.90	65.16	PK	H	-0.74	64.42	74	-9.58
3856.90	62.69	PK	V	-0.74	61.95	74	-12.05

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

Average level= Peak level+ Duty Cycle Corrected Factor

All other spurious emission are 20dB below the limit or the noise floor which are not recorded.

Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBµV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15D/RSS-213		
					Limit (dBµV/m)	Margin (dB)	Comment
1921.536MHz							
1921.536	111.6	H	-28	83.6	/	/	Fundamental
1921.536	108.43	V	-28	80.43	/	/	Fundamental
3843.08	64.53	H	-28	36.53	54	-17.47	Harmonic
3843.08	61.53	V	-28	33.53	54	-20.47	Harmonic
1924.992MHz							
1924.992	111.64	H	-28	83.64	/	/	Fundamental
1924.992	108.97	V	-28	80.97	/	/	Fundamental
3849.98	64.43	H	-28	36.43	54	-17.57	Harmonic
3849.98	61.76	V	-28	33.76	54	-20.24	Harmonic
1928.448MHz							
1928.448	111.62	H	-28	83.62	/	/	Fundamental
1928.448	108.27	V	-28	80.27	/	/	Fundamental
3856.90	64.42	H	-28	36.42	54	-17.58	Harmonic
3856.90	61.95	V	-28	33.95	54	-20.05	Harmonic

Duty cycle:  
 Ton =0.4ms  
 Tp = 10.04 ms  
 Duty cycle = Ton/Tp = 0.4/10.04=0.0398  
 Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0398= -28

**ANT1**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	PK/Ave					
Low Channel							
1921.536	117.99	PK	H	-6.39	111.60	/	/
1921.536	114.23	PK	V	-6.39	107.84	/	/
3843.08	64.65	PK	H	-0.78	63.87	74	-10.13
3843.08	61.82	PK	V	-0.78	61.04	74	-12.96
Middle Channel							
1924.992	118.01	PK	H	-6.39	111.62	/	/
1924.992	114.55	PK	V	-6.39	108.16	/	/
3849.98	64.89	PK	H	-0.79	64.10	74	-9.90
3849.98	62.77	PK	V	-0.79	61.98	74	-12.02
High Channel							
1928.448	118.02	PK	H	-6.39	111.63	/	/
1928.448	114.14	PK	V	-6.39	107.75	/	/
3856.90	65.17	PK	H	-0.74	64.43	74	-9.57
3856.90	62.58	PK	V	-0.74	61.84	74	-12.16

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit


Average level= Peak level+ Duty Cycle Corrected Factor

All other spurious emission are 20dB below the limit or the noise floor which are not recorded.


Field Strength of Average							
Frequency (MHz)	Peak Measurement @3m (dBµV/m)	Polar (H/V)	Duty Cycle Correction Factor (dB)	Corrected Amplitude (dBµV/m)	FCC Part 15D/RSS-213		
					Limit (dBµV/m)	Margin (dB)	Comment
1921.536MHz							
1921.536	111.6	H	-28	83.6	/	/	Fundamental
1921.536	107.84	V	-28	79.84	/	/	Fundamental
3843.08	63.87	H	-28	35.87	54	-18.13	Harmonic
3843.08	61.04	V	-28	33.04	54	-20.96	Harmonic
1924.992MHz							
1924.992	111.62	H	-28	83.62	/	/	Fundamental
1924.992	108.16	V	-28	80.16	/	/	Fundamental
3849.98	64.1	H	-28	36.1	54	-17.9	Harmonic
3849.98	61.98	V	-28	33.98	54	-20.02	Harmonic
1928.448MHz							
1928.448	111.63	H	-28	83.63	/	/	Fundamental
1928.448	107.75	V	-28	79.75	/	/	Fundamental
3856.90	64.43	H	-28	36.43	54	-17.57	Harmonic
3856.90	61.84	V	-28	33.84	54	-20.16	Harmonic

Duty cycle:  
 Ton =0.4ms  
 Tp = 10.04 ms  
 Duty cycle = Ton/Tp = 0.4/10.04=0.0398  
 Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0398= -28

### Duty cycle




ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 23.FEB.2024 11:57:11



ProjectNo.:SZ1240103-00576E-RF Tester:Hanic Pan  
Date: 23.FEB.2024 11:57:23


**Test plot with ANT 0:**





**Vertical**

1-3GHz




Project No. : SZ1240103-00576E  
 Tester : Dylan  
 Polarization: Vertical  
 Note : FP\_1921.54

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2841.000	-2.57	32.35	29.78	54.00	-24.22	Average
2	2841.000	-2.57	48.43	45.86	74.00	-28.14	Peak

**Horizontal**

3-18GHz




Project No. : SZ1240103-00576E  
 Tester : Dylan  
 Polarization: Horizontal  
 Note : FP\_1921.54

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3843.080	-0.78	65.31	64.53	74.00	-9.47	Peak
2	17979.380	24.47	37.97	62.44	74.00	-11.56	Peak
3	17979.380	24.47	23.05	47.52	54.00	-6.48	Average

**Vertical**

3-18GHz




Project No. : SZ1240103-00576E  
 Tester : Dylan  
 Polarization: Vertical  
 Note : FP\_1921.54

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3843.080	-0.78	62.31	61.53	74.00	-12.47	Peak
2	17964.380	24.37	38.38	62.75	74.00	-11.25	Peak
3	17964.380	24.37	22.84	47.21	54.00	-6.79	Average

**Horizontal**

18-20GHz




Project No. : SZ1240103-00576E  
 Tester : Dylan  
 Polarization: Horizontal  
 Note : FP\_1921.54

	Read	Limit	Over				
Freq	Factor	Level	Level	Line			
MHz	dB/m	dBuV	dBuV/m	dBuV/m			
1	19908.380	13.84	45.53	59.37	74.00	-14.63	Peak
2	19908.380	13.84	33.67	47.51	54.00	-6.49	Average

**Vertical**

18-20GHz



Project No. : SZ1240103-00576E  
 Tester : Dylan  
 Polarization: Vertical  
 Note : FP\_1921.54

	Read	Limit	Over				
Freq	Factor	Level	Level	Line			
MHz	dB/m	dBuV	dBuV/m	dBuV/m			
1	19463.880	13.86	45.55	59.41	74.00	-14.59	Peak
2	19463.880	13.86	32.67	46.53	54.00	-7.47	Average

**§ 15.323 (f) & RSS-213 §5.3 FREQUENCY STABILITY**

**Applicable Standard**

Per §15.323(f) & ANSI C63.17-2013 Clause 6.2.1, the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ±10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to +50°C or as declared by the manufacturer at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20 °C. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

According to RSS-213 Issue 3 (2015-03) § (5.3):  
 The carrier frequency stability shall be maintained within ±10 ppm (±0.001%).

According to RSS-Gen Issue 5 (2021-02) § (8.11):  
 Transmitter frequency stability for licence-exempt radio apparatus shall be measured in accordance with Section 6.11. For licence-exempt radio apparatus, the frequency stability shall be measured at temperatures of -20°C (-4°F), +20°C (+68°F) and +50°C (+122°F) instead of at the temperatures specified in Section 6.11.


**Test Procedure**

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20°C	85-115% or new batteries
-20°C	Normal
+50°C	Normal

During test, the equipment shall be placed in the boxes and set the temperature to the specified requirement until the thermal balance has been reached.

Using the mean carrier frequency at 20°C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ± 10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20°C) at the two extreme supply voltages. This test does not apply to a EUT that is capable only of operating from a battery.



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24.5 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101 kPa

The testing was performed by Hanic Pan on 2024-02-23.

**Test Result: Compliant**

Test mode: Transmitting

Power by adapter:

Temperature (°C)	Voltage (V <sub>AC</sub> <input checked="" type="checkbox"/> , V <sub>DC</sub> <input type="checkbox"/> )	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	7	3.64	±10
20	102	1924.992	6	3.12	±10
	138	1924.992	6	3.12	±10
50	120	1924.992	7	3.64	±10

Power by PoE:

Temperature (°C)	Voltage (V <sub>AC</sub> <input checked="" type="checkbox"/> , V <sub>DC</sub> <input type="checkbox"/> )	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	120	1924.992	8	4.16	±10
20	102	1924.992	4	2.08	±10
	138	1924.992	5	2.60	±10
50	120	1924.992	6	3.12	±10

Note: the extreme test condition was declared by applicant.

## § 15.323 (c)(e) § 15.319 (f) & RSS-213 §5.1&§5.2 SPECIFIC REQUIREMENTS FOR UPCS DEVICE

### Applicable Standard


FCC§15.323(c)(e) & §15.319(f) Specific Requirements for UPCS device.  
ANSI C63.17 2013 §6.2 Frequency and time stability and §7.Monitoring tests and §8.Time and spectrum window access procedure.

According to RSS-213 §5.1&§5.2 type of modulation and access protocol  
Equipment certified under this standard shall use digital modulation.  
In order to provide equitable access to the radio frequency spectrum, the licence-exempt PCS device must possess an access protocol.

### Test Procedure

Measurement method according to ANSI C63.17- 2013

Test configuration as below



### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	47 %
<b>ATM Pressure:</b>	101 kPa

*The testing was performed by Hanic Pan on 2024-02-23.*

**Test Result: Compliant**

*Please see the below data*



**1) Automatic Discontinuation of Transmission**

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

**Test result:**

The following tests were performed after a connection had been established with Handset.

Test condition	Reaction of EUT	Pass/Fail
Adapter removed from EUT	Connection break down	Pass
Battery remove from Handset	Connection break down	Pass

**2) Monitoring Time**

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

**Test procedure:**

Measurement method is in according to ANSI C63.17 -2013 clause 7.3.3. RF signal generators apply uniform CW interference on all system carriers except two carriers (designated  $f_1$  and  $f_2$ ), each at level  $T_L + U_M$ . EUT can only transmit on these two carriers.

**Test result:**

This requirement is covered by the results of Least Interfered Channel (LIC).

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on $f_1$ at level $T_L + U_M + 20\text{dB}$ and no interference on $f_2$ . Initiate transmission and verify the transmission only on $f_2$ . Then terminate it.	EUT transmits on $f_2$	Pass
b) Apply the interference on $f_2$ at level $T_L + U_M + 20\text{dB}$ and immediately remove all interference from $f_1$ . The EUT should immediately attempt transmission on $f_1$ (but at least 20 ms after the interference on $f_2$ is applied), verify the transmission only on $f_1$ .	EUT transmission $f_1$	Pass

**3) Lower Monitoring Threshold**

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

**Test procedure:**

Measurement method according to ANSI C63.17 -2013 clause 7.3.1

**Test result:**

Not applicable because the EUT has more 40 defined duplex system access channels and meet the provision of the Least Interfered Channel (LIC).

**4) Maximum Transmit Period**

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

**Test procedure:**

The test procedure is as follows:

- a) Activate the EUT and initiate a communication channel with the companion device, and start a timer or frame counter.
- b) The centre frequency of spectrum analyzer was set to the carrier frequency and SPAN was set to ZERO. The spectrum analyzer was used to monitor the time and spectrum window of the communication channel.
- c) Stop the timer at the end of the EUT transmission on the current time and frequency window (measure the time until the EUT changes to a different slot).

**Test result:**

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	18695	28,800	Pass
Second	18684	28,800	Pass

**5) System Acknowledgement**

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

**Test procedure:**

Measurement method according to ANSI C63.17 2013 clause 8.1, 8.2, 8.2.1

During testing initial transmission without acknowledgement, the signal from the EUT to the companion device is blocked by the circulator.

The test of the transmission time after loss of acknowledgements is performed by cutting off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

**Test result:**

Test	Time taken (second)	Limit (second)	Result
Initial Connection acknowledgement	0.43	1	Pass
Change of access criteria for control information	N/A	30	N/A
Transmission cease time after loss of acknowledgement	4.35	30	Pass

Note: N/A=Not Applicable

**6) Least Interfered Channel (LIC)**

If access to spectrum is not available as determined by the above, and a minimum of 20 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level may be accessed.

A device utilizing the provisions of this paragraph (5) must have monitored all access channels defined for its system within the last 10 seconds and must verify, within the 20 milliseconds (40 milliseconds for devices designed to use a 20 millisecond frame period) immediately preceding actual channel access, that the detected power of the selected time and spectrum windows is no higher than the previously detected value.

The power measurement resolution bandwidth for this comparison must be accurate to within 6 dB. No device or group of cooperating devices located within 1 metre of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

Calculation of monitoring threshold limits for isochroous devices:

$$\text{Lower threshold: } T_L = -174 + 10\text{Log}_{10}B + M_L + P_{MAX} - P_{EUT} \text{ (dBm)}$$

Where: B=Emission bandwidth (Hz)

$M_L$  = dB the threshold may exceed thermal noise (30 for  $T_L$ )

$P_{MAX}$  =  $5\text{Log}_{10}B - 10$  (dBm)

$P_{EUT}$  = Transmitted power (dBm)

**Calculated thresholds:**

Monitor Threshold	B(MHz)	M <sub>L</sub> (dB)	P <sub>MAX</sub> (dBm)	P <sub>EUT</sub> (dBm)	Threshold (dBm)
Lower threshold	1.476	30	20.85	20	-81.46

Note: 1.The upper threshold is applicable as the EUT utilizes more than 20 duplex system channels

**Test procedure:**

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3

**C63.17 clause 7.3.2, LIC procedure test:**

- a) Allow EUT transmission on only two carrier frequencies, which will be designated  $f_1$  and  $f_2$ .
- b) Apply interference to the EUT on  $f_1$  at a level of  $TL + UM + 7$  dB and on  $f_2$  at a level of  $TL + UM$ . Initiate transmission. The EUT should transmit on  $f_2$ . Terminate the connection. Repeat five times. If the EUT transmits once on  $f_1$ , the test failed.
- c) Apply interference to the EUT on  $f_1$  at a level of  $TL + UM$  and on  $f_2$  at a level of  $TL + UM + 7$  dB. Initiate transmission. The EUT should transmit on  $f_1$ . Terminate the connection. Repeat five times. If the EUT transmits once on  $f_2$ , the test failed.
- d) Apply interference to the EUT on  $f_1$  at a level of  $TL + UM + 1$  dB and on  $f_2$  at a level of  $TL + UM - 6$  dB. Initiate transmission. If the EUT transmits on  $f_2$ , terminate the connection. Repeat five times. If the EUT transmits once on  $f_1$ , the test failed.
- e) Apply interference to the EUT on  $f_1$  at a level of  $TL + UM - 6$  dB and on  $f_2$  at a level of  $TL + UM + 1$  dB. Initiate transmission. If the EUT transmits on  $f_1$ , terminate the connection. Repeat five times. If the EUT transmits once on  $f_2$ , the test failed.

**C63.17 clause 7.3.3, Selected channel confirmation:**

- a) Allow EUT transmission on only two carrier frequencies, which will be designated  $f_1$  and  $f_2$ . This limitation to carriers  $f_1$  and  $f_2$  is performed preferably by administration commands for the EUT, or alternatively by applying by a multicarrier interference generator uniform interference on all system carriers except  $f_1$  and  $f_2$ , at a level of  $TL + UM + 20$  dB in-band per carrier. Set the interference level to the EUT on  $f_1$  to a level of  $TL + UM + 20$ dB, and let there be no interference applied on  $f_2$ .
- b) Initiate transmission and verify that the EUT transmits on  $f_2$ . If a connection was made, terminate it.
- c) Apply interference on  $f_2$  at a level of  $TL + UM + 20$  dB in-band, and immediately remove all interference from  $f_1$  and immediately (but not sooner than 20 ms after the interference on  $f_2$  is applied) cause the EUT to attempt transmission. The EUT should now transmit on  $f_1$ , if it transmits.
- d) If the EUT transmits on  $f_2$ , it fails.

**Test result:****1) LIC procedure test:**

Interference (Refer to ANSI C63.17 clause 7.3.3)	Reaction of EUT	Results
a) Apply the interference on $f_1$ at level $T_L+U_M+7\text{dB}$ and the interference on $f_2$ at level $T_L+U_M$ . Initiate transmission and verify the transmission only on $f_2$ . Repeat 5 times.	EUT transmits on $f_2$	Pass
b) Apply the interference on $f_1$ at level $T_L+U_M$ and the interference on $f_2$ at level $T_L+U_M+7\text{dB}$ . Initiate transmission and verify the transmission only on $f_1$ . Repeat 5 times.	EUT transmits on $f_1$	Pass
c) Apply the interference on $f_1$ at level $T_L+U_M+1\text{dB}$ the interference on $f_2$ at level $T_L+U_M-6\text{dB}$ . Initiate transmission and verify the transmission only on $f_2$ . Repeat 5 times.	EUT transmits on $f_2$	Pass
d) Apply the interference on $f_1$ at level $T_L+U_M-6\text{dB}$ and the interference on $f_2$ at level $T_L+U_M+1\text{dB}$ . Initiate transmission and verify the transmission only on $f_1$ . Repeat 5 times.	EUT transmits on $f_1$	Pass

**2) Selected channel confirmation:**

Interference (Refer to ANSI C63.17 clause 7.3.4)	Reaction of EUT	Results
a) Apply the interference on $f_1$ at level $T_U+U_M$ and no interference on $f_2$ . Initiate transmission and verify the transmission only on $f_2$ . Then terminate it.	EUT transmits on $f_2$	Pass
b) Apply the interference on $f_2$ at level $T_L+U_M$ and immediately remove all interference from $f_1$ . The EUT should immediately attempt transmission on $f_1$ (but at least 20 ms after the interference on $f_2$ is applied), verify the transmission only on $f_1$ .	EUT transmission $f_1$	Pass

**7) Random waiting**

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

**Test procedure:**

This test is for EUTs that transmit control and signaling channels and that use the provisions of FCC §15.323(c)(6) & IC RSS-213 5.2(6), thus to verify that the EUT (if in deferral) waits for a channel to go clear, then implements a 10 ms to 150 ms hold off prior to using the channel. FCC §15.323(c)(6) is not restrictive for EUTs that use the LIC and offer 20 or more duplex communications channels, as a combined time and spectrum window cannot become unavailable as there is no threshold limit. Test method according to ANSI C63.17 2013 clause 8.1.2 or 8.1.3

- a) Restrict operation of the EUT to a single carrier designated  $f_1$ . For TDMA system, further restrict EUT transmission to a single timeslot of the usable timeslots available in the TDMA frame structure and synchronize the interference so as to occur centered within the timeslot.

- b) Activate the EUT with no interference present. The EUT must transmit on  $f_1$ . Then apply CW interference on  $f_1$ . The interference level shall be at  $TL + UM$  as appropriate for EUTs that do or do not meet the requirements for using the upper threshold. The EUT must stop transmitting within 30 s.
- c) Cancel the interference. Measure the time interval between the end of the interference transmission and the beginning of transmission by the EUT.
- d) Repeat step b) and step c) 100 times. If the measured time intervals vary uniformly between 10 ms and 150 ms, the EUT passes the test.

Note: This is Not Applicable

### 8) Monitoring Bandwidth and Reaction Time

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than  $50 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$  microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

**Note:** Testing of the monitoring system bandwidth is not required if the designed bandwidth from the manufacturer is available and given in the test report.

The maximum reaction time of the monitor shall be less than  $50 \sqrt{1.25/\text{occupied bandwidth in MHz}}$   $\mu\text{s}$  for signals at the applicable threshold level but shall not be required to be less than 50  $\mu\text{s}$ .

If a signal of 6 dB or more above the threshold level is detected, the maximum reaction time shall be  $35 \sqrt{1.25/\text{occupied bandwidth in MHz}}$   $\mu\text{s}$  but shall not be required to be less than 35  $\mu\text{s}$ .

**Test result:**

**1) Monitoring Bandwidth:**

The antenna of the EUT used for monitoring is the same interior antenna that used for transmission, so the monitoring system bandwidth is equal to the emission bandwidth of the intended transmission

**2) Reaction Time Test:**

No.	Interference Pulse width ( $\mu\text{s}$ )	Reaction of EUT	Observing time ( $\mu\text{s}$ )	Result
1	50 $\mu\text{s}$ with level $T_L+U_M$	No transmission	44.24	Pass
2	35 $\mu\text{s}$ with level $T_L+U_M+6\text{dB}$	No transmission	30.21	Pass

### 9) Monitoring Antenna

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

**Test procedure:**

Measurement method according to ANSI C63.17 -2013 paragraph 4

**Test result:**

---

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

### **10) Monitoring threshold relaxation**

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

#### **Test procedure:**

Measurement method according to ANSI C63.17 -2013 clause 7.4 & paragraph 4

#### **Test result:**

This requirement is covered by the results of Least Interfered Channel (LIC).

### **11) Duplex Connections**

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

**Test procedure:**

This test validates proper operation of an EUT that operates according to the provisions of FCC §15.323(c)(10) using a check of both transmit and receive channels on one end of the link to qualify both ends of the link for transmissions. Test method according to ANSI C63.17 clause 8.3.2 Validation of dual access criteria check for EUTs that implement the upper threshold

- a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 40 dB above  $TL + UM$ .
- b) Restrict the EUT and its companion device to operation at a single carrier  $f_1$  for TDMA systems and on  $f_1$  and  $f_2$  and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection on a time/spectrum window on the enabled carrier(s). Terminate the connection.
- c) Apply interference to the EUT on the EUT's *transmit* time/spectrum windows at  $TL + UM$  per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below  $TL$ . Adjust the interference to the EUT on its *receive* time/spectrum windows such that a single time/spectrum window has interference at least 10 dB below  $TL$ , and the interference on the other time/spectrum windows is at  $TL + UM + 7$  dB. The interference to the companion device should be at least 10 dB below  $TL$  on all active time/spectrum windows. The interference-free *receive* time/spectrum window must not be the duplex mate of the interference-free *transmit* time/spectrum window.
- d) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *receive* time/spectrum window and its duplex mate. Otherwise, the EUT fails the test.
- e) If a connection exists, terminate it. Reduce the interference on the EUT's *receive* time/spectrum windows to a level of  $TL + UM$  per carrier on all time/spectrum windows except for one, which has interference at least 10 dB below  $TL$ . Raise the interference on the EUT's *transmit* time/spectrum windows to a level of  $TL + UM + 7$  dB, maintaining one time/spectrum window with interference at least 10 dB below  $TL$ . The interference to the companion device should be at least 10 dB below  $TL$  on all active time/spectrum windows. Again, the interference-free *transmit* and *receive* time/spectrum windows should not constitute a duplex pair if the system designates a specific duplex pairing for time/spectrum windows.
- f) Cause the EUT to attempt to establish a connection. The connection should be made on the interference-free *transmit* time/spectrum window and its duplex mate. Otherwise, the system fails the test.
- g) Terminate the connection and raise the interference to the EUT on all of the EUT's *transmit* and *receive* time/spectrum windows to  $TU + UM$  per carrier on all time/spectrum windows except for a single *transmit* time/spectrum window and a single *receive* time/spectrum window, which shall have interference at least 10 dB below  $TL$ . The low-interference *transmits* and *receives* time/spectrum windows shall not constitute a duplex pair. Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above  $TU$ . Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.



**Test result:**

Interference (Refer to ANSI C63.17 § 8.3& § 8.3.2)	Reaction of EUT	Results
a) Only a single carrier $f_1$ for EUT TDMA systems and on $f_1$ and $f_2$ and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) All Tx windows with level TL+UM except one & Rx windows with level TL+UM+7dB except one, which are not the duplex mate.	Connected on the target Rx window and its duplex mate.	Pass
c) All Tx windows with level TL+UM+7dB except one & Rx windows with level TL+UM except one, which are not duplex mate.	Connected on the target Tx window and its duplex mate.	Pass
d) All Tx & Rx windows with level TU+UM, except one for Tx window & one for Rx window, which are not duplex mate.	No connection possible	Pass

**12) Alternative monitoring interval**

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

**Test procedure:**

This test validates the ability of the EUT to distinguish between same-system and other-system interference for purposes of satisfying the requirement of 47CFR15.323(c) (11). Test method according to ANSI C63.17 2013 clause 8.4

- a) Adjust the path loss between the EUT and its companion device such that the received signal to the EUT from the companion device is at least 30 dB above  $TL$ .
- b) Restrict the EUT and its companion device to operation at a single carrier  $f_1$  for TDMA systems and on  $f_1$  and  $f_2$  and corresponding duplex carriers for FDMA systems. Verify that the EUT and its companion device can establish a connection.
- c) Apply interference at  $TL + UM$  per carrier to the EUT on all *transmit* time/spectrum windows on the enabled carrier(s). The interference must use the same physical layer parameters (modulation, frame format, etc.) as the EUT transmissions, but with a system identifier different from that used by the EUT and the companion device. Ensure that the interference level at the companion device is at least 10 dB below  $TL$ . Apply no interference to the *receive* time/spectrum windows on the enabled carriers.
- d) Cause the EUT to attempt to establish a connection. If a connection is established, the test fails.

**Test result:**

Interference (Refer to ANSI C63.17 § 8.4)	Reaction of EUT	Results
a) Only a single carrier $f_1$ for EUT TDMA systems and on $f_1$ and $f_2$ and corresponding duplex carriers for FDMA systems.	EUT can transmit	Pass
b) Apply interference with same parameters as EUT transmissions on all Tx windows with level TL+UM on the enabled carrier(s) and no interference on the Rx windows on the enabled carriers.	No connection is established	Pass

IC:

Not appropriate, as the system always monitor both the transmit and receive time/spectrum windows, it is not a co-located device.

**13) Fair Access**

The provisions of FCC §15.323 (c) & paragraphs 5.2 (10) or (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

**Test result:**

The manufacturer declares that this device does not use any mechanisms as provided by FCC §15.323(c)(10) or (11) & IC RSS-213 5.2(10) and (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

**14) Frame Repetition Stability Frame Period and Jitter**

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per million (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

**Test procedure:**

Measurement method according to ANSI C63.17 2013 clause 6.2.2, 6.2.3

**Test result:**

Frame Period and Jitter:

Max. pos. Jitter (µs)	Max. neg. Jitter (µs)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (µs)
0.09	-0.06	10.58	20 or 10/X	25

Note: X is a positive whole number.

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment SZ1240103-00576E-RF-FP External photo and SZ1240103-00576E-RF-FP Internal photo.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment SZ1240103-00576E-RF-FP Test Setup photo.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***