



RF Exposure Evaluation Declaration

Product Name : UWB device
Model No. : X4M05V
FCC ID : EW7X4M05V
IC : 1135B-4M05V

Applicant : VTech Telecommunications Ltd
Address : 23/F, Tai Ping Industrial Centre, Block 1, 57
Ting Kok Road, Tai Po, Hong Kong

Date of Receipt : Dec. 04, 2018
Test Date : Dec. 05, 2018 ~ Jan. 20, 2019
Issued Date : Feb. 25, 2019
Report No. : 18C2028R-RF-US-P20V01
Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Feb. 25, 2019

Report No. : 18C2028R-RF-US-P20V01



Product Name : UWB device

Applicant : VTech Telecommunications Ltd

Address : 23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road,
Tai Po, Hong Kong

Manufacturer : VTech Telecommunications Ltd

Address : 23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road,
Tai Po, Hong Kong

Model No. : X4M05V

Brand Name : VTech

FCC ID : EW7X4M05V

IC : 1135B-4M05V


Test Voltage : DC 5V


EUT Voltage : DC 3V~5.5V


Applicable Standard : KDB 447498D01V06
FCC Part1.1310
RSS-102: Issue 5, 2015

Test Result : Complied

Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,
Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199; IC Lab Code: 4075B

Documented By : 
(Project Assistant: Kathy Feng)

Reviewed By : 
(Senior Project Manager: Frank He)

Approved By : 
(Engineer Supervisor: Jack Zhang)

1. RF Exposure Evaluation

1.1.Limits

For FCC:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

For ISED:

According to RSS 102 Issue 5: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in RSS 102 Clause 4

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/ cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	UWB device
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

- **Power Density**

Standalone modes:

The EIRP of RB=3MHz is -24.437 dBm, which convert to RBW 50MHz the EIRP is -30.131dBm.

Test Mode	Frequency Band (MHz)	EIRP (dBm)	Power Density at R = 0.5 cm (mW/cm ²)	Limit of Power Density S(mW/cm ²)
UWB	6000 ~ 8500	-30.131	0.00000019	1

Note1: The limit for ISED/FCC is same for Frequency of 6~8.5GHz.

2: The standalone transmission power density is 0.00000019mW/cm² for UWB device without any other radio equipment.

_____ The End _____