

RF Exposure Evaluation Report

Equipment under Test:Trasceiver

Model No. : 7347V

FCC ID : EZS7347V

IC : 1513A-7347V

Applicant : FCC:Voxx Electronics Corporation

IC: Voxx Electronics

Address : FCC:2365 Pontiac Road, Auburn Hills, Michigan,48326,United States

IC: 2365 Pontiac Road Auburn Hills MI 48326 USA(excluding The states of Alaska)

Date of Receipt : October 23, 2024

Date of Report : November 13, 2024

Prepared by

Central Research Technology Co.



EMC Test Laboratory

No.11, Lane41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.



PREPARED BY : Cathy Chen , **DATE** : November 13, 2024
(Cathy Chen/ Technical Manager)

APPROVED BY : Sam Chien , **DATE** : November 13, 2024
(Sam Chien /Authorized Signatory)

This report shall not be reproduced, except in full, without written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. The test result in this report is based on the information provided by manufacturer and applies only to the sample tested.

1 Requirement for Compliance

According to KDB 447498 D04 v01 and RSS-102 issue 6:

FCC requirement:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption

IC requirement

Frequency (MHz)	≤ 5 mm (mW)	10 mm (mW)	15 mm (mW)	20 mm (mW)	25 mm (mW)	30 mm (mW)	35 mm (mW)	40 mm (mW)	45 mm (mW)	> 50 mm (mW)
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296

2 Calculation

Frequency Range (MHz)	Maximum Power		Limit (mW)	
	(dBm)	(mW)	FCC	IC @5mm
433.92	-15.86	0.03	1	33.39

$P \text{ (dBm)} = E \text{ (dBuV/m)} - 95.2 = 79.34 - 95.2 = -15.86 \text{ dBm}$

IC limit @5mm: 32 mW (450 MHz), 45 mW(300 MHz) use linear interpolation to get limit.

3 Result

According to result, the SAR testing for this device is not required.

~ End of Report ~