ONE WORLD • OUR APPROVAL



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

| Maximum peak output power at device output terminal: | -0.39 dBm |
|--|-----------------------------|
| Cable and Jumper loss: | 0.0 dB |
| Maximum peak output power at antenna input terminal: | -0.39 dBm |
| | <u>0.914113241</u> mW |
| Single Antenna gain (typical): | <u> </u> |
| Number of Antennae: | 1 |
| Total Antenna gain (typical): | <u> </u> |
| | <u>3.16227766</u> (numeric) |
| Prediction distance: | <u>20</u> cm |
| Prediction frequency: | <u>2402</u> MHz |
| MPE limit for uncontrolled exposure at prediction frequency: | 1 mW/cm ² |

| Power density at prediction frequency: | 0.000575 mW/cm ² |
|--|-----------------------------|
| | 0.005751 W/m ² |
| Tx On time: | 1.000000 ms |
| Tx period time: | 1.000000 ms |
| Average Factor: | 100.000000 % |
| Average Power density at prediction frequency: | 0.005751 W/m ² |
| Maximum allowable antenna gain: | 37.40269855 dBi |
| | |

Margin of Compliance: 32.40269855 dB