



August 25, 2016

Compliance Testing LLC  
 1724 S. Nevada Way  
 Mesa, AZ 85204

RE: Maximum Permissible Exposure

**FCC ID: EZZ26075**  
**Model: 3-26075-XX**  
**700MHz Public Safety Class B Signal Booster**

To Whom It May Concern:

The equipment operating in the 700MHz Public Safety Band requires a separation distance of at least 23cm on the Donor antenna. This distance must be maintained between the user and antenna when the product is used with a 0dBi antenna.

The DAS antenna operating in the 700MHz Public Safety Band complies with the FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

This was calculated by the following:

MPE limit according to 47CFR §1.1310

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30

1500–100,000			1.0	30
--------------	--	--	-----	----

The power density can be calculated from the equation below (equation #4 from OET Bulletin 65, 97-01 edition, page 19)

$$S = \frac{P \cdot G}{4 \cdot \pi \cdot R^2}$$

S Power Density (mW/cm<sup>2</sup>)  
P Conducted Power (mW)  
R Distant (cm)  
G Numerical Antenna Gain

From this equation we can calculate the safety distance needed to fulfil the MPE limits  
In the calculations we have assumed no feeder loss and the max antenna gain was calculated based on the noise figure limits.

				G	P	S	S	R
Amplifier	Freq (MHz)	Output power to antenna (dBm)	Antenna gain (max) (dBi)	Antenna Gain Numerical	TX Power conducted (mW)	Power density limit* (mW/cm <sup>2</sup> )	Power density calculated (mW/cm <sup>2</sup> )	Calculated safety distance (cm)
700PS DL	769	32.8	0	1.00	2287	0.51	0.45	18.8
700PS UL	799	34.69	0	1.00	3533	0.53	0.70	23.0

\* Limit for General Population/Uncontrolled Exposure

Please contact me if there is any other information you may need.

Sincerely,



Amy L Sanvido

On behalf of Deltanode Solutions AB, a Bird Technologies Company

30303 Aurora Rd, Solon, OH 44139 | [www.birdrf.com](http://www.birdrf.com)

e: [asanvido@bird-technologies.com](mailto:asanvido@bird-technologies.com)

w: 440.519.2179

f: 440.248.9593

