

Nemko Test Report: 116930-1TRFWL

Applicant: Digital Security Control, a Division of Tyco Safety
Products Canada Ltd.
3301 Langstaff Road
Concord, Ontario
L4K 4L2

Apparatus: Wireless CO Alarm (M/N: WS4913)

FCC ID: F5309WS4913

In Accordance With: FCC Part 15 Subpart C, 15.231
Periodic operation in the band 40.66-40.70MHz and
above 70 MHz.

Authorized By:

A handwritten signature in blue ink, appearing to read 'Andrey Adelberg', is written over a faint, large 'NEMKO' watermark.

Andrey Adelberg, EMC/Wireless Specialist

Date: January 20, 2009

Total Number of Pages: 19

TABLE OF CONTENTS

Section 1 : Report Summary	3
Section 2 : Equipment Under Test.....	4
2.1 Identification of Equipment Under Test (EUT).....	4
2.2 Accessories	4
2.3 EUT Description.....	4
2.4 Technical Specifications of the EUT	5
2.5 EUT Setup diagram	5
2.6 Operation of the EUT during testing	5
2.7 Modifications incorporated in the EUT	5
Section 3 : Test Conditions.....	6
3.1 Specifications	6
3.2 Deviations From Laboratory Test Procedures	6
3.3 Test Environment	6
3.4 Measurement Uncertainty.....	6
3.5 Test Equipment.....	7
Section 4 : Results Summary	8
4.1 FCC Part 15 Subpart C : Test Results	8
Appendix A : Test Results.....	9
Clause 15.209(a) Radiated Emissions within Restricted Bands	9
Clause 15.231(a) Conditions for intentional radiators to comply with periodic operation	11
Clause 15.231(b) Radiated Emissions	13
Clause 15.231(c) 20dB Bandwidth.....	17
Appendix B : Setup Photographs	18
Appendix C : Block Diagram of Test Setups.....	19

Section 1 : Report Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C. Radiated tests were conducted in accordance with ANSI C63.4-2003.

The assessment summary is as follows:

Apparatus Assessed:	Wireless CO Alarm (M/N: WS4913)
Specification:	FCC Part 15 Subpart C, 15.231
Compliance Status:	Complies
Exclusions:	None
Non-compliances:	None
Report Release History:	Original Release
Test Location:	Nemko Canada Inc. 303 River Road Ottawa, Ontario K1V 1H2
Registration Number:	176392 (3m Semi-Anechoic Chamber)
Tests Performed By:	Jason Nixon, Wireless/Telecom Specialist
Test Dates:	December 8 to 10, 2008, January 20, 2009

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.



Section 2 : Equipment Under Test

2.1 Identification of Equipment Under Test (EUT)

The following information identifies the EUT under test:

Type of Equipment:	Wireless CO Alarm
Brand Name:	DSC
Model Name or Number:	WS4913
Serial Number:	T.01, T.04, None
Nemko Sample Number:	1, 2 (CW), 4 (CW)
FCC ID:	F5309WS4913
Date of Receipt:	November 28, 2008

2.2 Accessories

No accessories were used during this testing.


2.3 EUT Description

The EUT is a wireless CO alarm used as part of an alarm system. The EUT will report a tamper alarm of a high CO volume.

2.4 Technical Specifications of the EUT

Operating Frequency:	433.92MHz
Modulation:	On/Off Keying
Occupied Bandwidth:	41kHz
Emission Designator:	K1D
Antenna Data:	Integral antenna
Power Supply Requirements:	CR17345 3VDC battery

2.5 EUT Setup diagram



2.6 Operation of the EUT during testing

A modified sample was provided for CW transmission to complete radiated measurements and a normal sample for occupied bandwidth and timing requirements. Pressing and releasing the tamper switch triggered the normal operating sample.

2.7 Modifications incorporated in the EUT

The following modifications were performed to lower the Fundamental emission:

- 1) Change C12 from NU to 2pF(DSC#03-785)
- 2) Change C2 from 18pF to 15pF(DSC#03-734)
- 3) Change R1 from 100ohm to 33ohm(DSC#01-1119)
- 4) Change R20 from NU to 1uF(DSC#03-923)
- 5) Change R19 from 1Kohm to 0ohm(DSC#01-926)
- 6) Change C5 from 220nF to 1uF(DSC#03-923)
- 7) Change C9 from 15pF to 18pF(DSC#03-632)
- 8) Change C10 from 0ohm to 22ohm(DSC#01-0954)
- 9) Change C22 from 0ohm to 220pF(DSC#03-684)

Section 3 : Test Conditions

3.1 Specifications

The apparatus was assessed against the following specifications:

FCC Part 15 Subpart C, 15.231

Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

3.2 Deviations From Laboratory Test Procedures

No deviations were made from laboratory test procedures.

3.3 Test Environment

All tests were performed under the following environmental conditions:

Temperature range	:	15 – 30 °C
Humidity range	:	20 - 75 %
Pressure range	:	86 - 106 kPa
Power supply range	:	+/- 5% of rated voltages

3.4 Measurement Uncertainty

Nemko Canada measurement uncertainty has been calculated using guidance of UKAS LAB 34:2003 and TIA-603-B Nov 7, 2002. All calculations have been performed to provide a confidence level of 95% and can be found in Nemko Canada document MU-003.

3.5 Test Equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Cal. Date	Next Cal.
Spectrum Analyzer	Rohde & Schwarz	FSP40	FA001920	April 14/08	April 14/09
3m EMI Test Chamber	TDK	SAC-3	FA002047	May 06/08	May 06/09
Bilog	Sunol	JB3	FA002108	Jan. 21/08	Jan. 21/09
Flush Mount Turntable	Sunol	FM2022	FA002082	NCR	NCR
Controller	Sunol	SC104V	FA002060	NCR	NCR
Mast	Sunol	TLT2	FA002061	NCR	NCR
Receiver/Spectrum Analyzer	Rohde & Schwarz	ESU 40	FA002071	Nov. 25/08	Nov. 25/09
50 Coax cable	HUBER + SUHNER	None	FA002015	Aug. 05/08	Aug. 05/09
50 Coax cable	HUBER + SUHNER	None	FA002022	July 07/08	July 07/09
50 Coax cable	HUBER + SUHNER	None	FA002074	July 07/08	July 07/09
Horn Antenna #1	EMCO	3115	FA000649	Feb. 13/08	Feb. 13/09
1 – 18 GHz Amplifier	JCA	JCA118-503	FA002091	Oct 2/08	Oct 2/09

COU – Calibrate on Use

NCR – No Calibration Required

Section 4 : Results Summary

This section contains the following:

FCC Part 15 Subpart C : Test Results

The column headed 'Required' indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

- N No : not applicable / not relevant.
- Y Yes : Mandatory i.e. the apparatus shall conform to these tests.
- N/T Not Tested, mandatory but not assessed. (See Report Summary)

4.1 FCC Part 15 Subpart C : Test Results

Part 15	Test Description	Required	Result
15.31(e)	Variation of Power source	N	
15.207(a)	Powerline Conducted Emissions	N	
15.209(a)	Radiated Emissions within Restricted Bands	Y	PASS
15.231(a)(1)	Manually operated transmitter	N	
15.231(a)(2)	Automatically activated transmitter	Y	PASS
15.231(a)(3)	Periodic transmissions at regular predetermined intervals	N	
15.231(a)(4)	Radiators used in cases of emergency	N	
15.231(a)(5)	Set-up information for security systems	N	
15.231(b)	Radiated Emissions	Y	PASS
15.231(c)	20dB Bandwidth	Y	PASS
15.231(d)	Devices operating within the frequency band 40.66-40.70 MHz	N	
15.231(e)	Radiated emissions for Periodic radiators	N	

Notes:

Appendix A : Test Results

Clause 15.209(a) Radiated Emissions within Restricted Bands

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvoltsmeter) (kHz)	Measurement Distance (meters)
0.009-0.490	2400/F	300
0.490-1.705	24000/F	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Results: Pass

Additional Observations:

The Spectrum was searched from 30MHz to the 10th Harmonic.

These results apply to emissions found in the Restricted bands defined in FCC Part 15 Subpart C, 15.205.

The EUT was measured on three orthogonal axis with a fresh new battery.

All measurements were performed using a Peak Detector with 100kHz RBW/VBW below 1GHz and a 1MHz RBW/VBW above 1GHz at a distance of 3 meters.

Peak Detector

Freq. (MHz)	Pol. V/H	RCVD Signal (dBμV)	Ant. Factor (dB)	Cable Loss (dB)	Amp. gain (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)
1301.76	V	81.95	24.8	3.2	46.3	63.65	74	10.35
1301.76	H	78.13	25	3.2	46.3	60.03	74	13.97
3905.28	V	57.55	32.3	5.9	45.9	49.85	74	24.15
3905.28	H	59.14	32.5	5.9	45.9	51.64	74	22.36
Level (peak) = RCVD + Ant factor + Cable loss – Amp Gain								

Average Detector

Freq. (MHz)	Pol. V/H	Peak Level (dBμV)	Duty Cycle Corr. (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)
1301.76	V	63.65	16.77	46.88	54	7.12
1301.76	H	60.03	16.77	43.26	54	10.74
3905.28	V	49.85	16.77	33.08	54	20.92
3905.28	H	51.64	16.77	34.87	54	19.13
Level (Avg) = Level (Peak) –duty cycle corr						

Clause 15.231(a) Conditions for intentional radiators to comply with periodic operation


The provisions of this section are restricted to periodic operation within the band 40.66-40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Continuous transmissions, voice, video and the radio control of toys are not permitted. Data is permitted to be sent with a control signal. The following conditions shall be met to comply with the provisions for this periodic operation:

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- (4) Intentional radiators, which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in paragraphs (a)(1) and (a)(2) of this section, provided such transmissions are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

Test Results: Pass

- (1) The EUT is not manually triggered.
- (2) The EUT is automatically triggered and ceases transmission within 3.005sec, see attached plot.
- (3) The EUT does not periodically transmit.
- (4) The EUT is used in security systems but complies with the automatically triggered device requirements.
- (5) The EUT does not have an installer mode.

Transmission Time



Date: 9.DEC.2008 13:06:04



Clause 15.231(b) Radiated Emissions

In addition to the provisions of 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750	125 to 375
174-260	3,750	375
260-470	3,750 to 12,500	375 to 1,250
Above 470	12,500	1,250

Test Results: Pass

Additional Observations:

The Spectrum was searched from 30MHz to the 10th Harmonic.

The EUT was measured on three orthogonal axis with a fresh new battery.

All measurements were performed using a Peak Detector with 100kHz RBW/VBW below 1GHz and a 1MHz RBW/VBW above 1GHz at a distance of 3 meters.

Peak Detector

Freq. (MHz)	Pol. V/H	RCVD Signal (dBμV)	Ant. Factor (dB)	Cable Loss (dB)	Amp. gain (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)
433.92	V	78.48	16.4	1.8	0.0	94.56	100.8	6.24
433.92	H	80.08	16.7	1.8	0.0	94.62	100.8	6.18
867.84	V	34.76	21.7	2.6	0.0	59.06	80.8	21.74
867.84	H	36.74	22.3	2.6	0.0	61.64	80.8	19.16
1735.68	V	81.67	26.2	3.8	46.4	65.27	80.8	15.53
1735.68	H	80.27	26.2	3.8	46.4	63.87	80.8	16.93
2169.6	V	77.34	27.6	4.2	46.1	63.04	80.8	17.76
2169.6	H	77.17	27.8	4.2	46.1	63.07	80.8	17.73
2603.52	V	64.72	28.5	4.7	45.7	52.22	80.8	28.58
2603.52	H	64.58	28.9	4.7	45.7	52.48	80.8	28.32
3037.44	V	59.27	29.9	5.0	45.8	48.37	80.8	32.43
3037.44	H	57.83	30.0	5.0	45.8	47.03	80.8	33.77
3471.36	V	63.87	31.2	5.4	45.9	54.57	80.8	26.23
3471.36	H	63.67	31.2	5.4	45.9	54.37	80.8	26.43


Level (peak) = RCVD + Ant factor + Cable loss – Amp Gain

Average Detector


Freq. (MHz)	Pol. V/H	Peak Level (dBμV)	Duty Cycle Corr. (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)
433.92	V	94.56	16.77	77.79	80.8	3.01
433.92	H	94.62	16.77	77.85	80.8	2.95
867.84	V	59.06	16.77	42.29	60.8	12.3
867.84	H	61.64	16.77	44.87	60.8	13.7
1735.68	V	65.27	16.77	48.5	60.8	14.53
1735.68	H	63.87	16.77	47.1	60.8	14.5
2169.6	V	63.04	16.77	46.27	60.8	25.35
2169.6	H	63.07	16.77	46.3	60.8	25.09
2603.52	V	52.22	16.77	35.45	60.8	29.2
2603.52	H	52.48	16.77	35.71	60.8	30.54
3037.44	V	48.37	16.77	31.6	60.8	23
3037.44	H	47.03	16.77	30.26	60.8	23.2
3471.36	V	54.57	16.77	37.8	60.8	12.3
3471.36	H	54.37	16.77	37.6	60.8	13.7

Level (Avg) = Level (Peak) –duty cycle corr


Duty Cycle:



Date: 9.DEC.2008 13:07:01



Date: 9.DEC.2008 13:16:48



Date: 9.DEC.2008 13:18:08

Worst-case on-time = 2.5msec header + 48bits *250usec = 14.5msec

Duty cycle correction = $20\log(14.5/100) = -16.77\text{dB}$




Nemko Canada Inc.

Clause 15.231(c) 20dB Bandwidth

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test Results: Pass

20dB Bandwidth:



Date: 9.DEC.2008 13:03:58

Appendix B : Setup Photographs

Spurious Emissions Setup:



Appendix C : Block Diagram of Test Setups

Radiated Emissions above 30MHz Test Site

