

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : OT-214-RWD-081

**Reception No.** : 2104001725

**Applicant** : InBody Co., Ltd.

**Address** : InBody Bldg., 625, Eonju-ro, Gangnam-gu, Seoul, 06106, South Korea

**Manufacturer** : InBody Co., Ltd.

**Address** : 15, Heugam-gil, Ipjang-myeon, Seobuk-gu, Cheonan-si, Chungcheongnam-do 31025  
KOREA

**Type of Equipment** : Body Composition Analyzer

**FCC ID.** : F6OH60NWI

**Model Name** : H60NWi

**Serial number** : N/A

**Total page of Report** : 32 pages (including this page)

**Date of Incoming** : April 19, 2021

**Date of issue** : April 28, 2021


## SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.





Tested by  
Hyung-Kwon, Oh / Manager  
ONETECH Corp.

Reviewed by  
Tae-Ho, Kim / Senior Manager  
ONETECH Corp.

Approved by  
Ki-Hong, Nam / General Manager  
ONETECH Corp.

## CONTENTS

**PAGE**


<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>5</b>
<b>2. TEST SUMMARY.....</b>	<b>6</b>
<b>2.1 TEST ITEMS AND RESULTS FOR BLUETOOTH LE .....</b>	<b>6</b>
<b>2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....</b>	<b>6</b>
<b>2.3 RELATED SUBMITTAL(S) / GRANT(S) .....</b>	<b>6</b>
<b>2.4 PURPOSE OF THE TEST .....</b>	<b>6</b>
<b>2.5 TEST METHODOLOGY.....</b>	<b>6</b>
<b>2.6 TEST FACILITY.....</b>	<b>6</b>
<b>3. GENERAL INFORMATION.....</b>	<b>7</b>
<b>3.1 PRODUCT DESCRIPTION.....</b>	<b>7</b>
<b>3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....</b>	<b>7</b>
<b>4. EUT MODIFICATIONS.....</b>	<b>7</b>
<b>5. SYSTEM TEST CONFIGURATION.....</b>	<b>8</b>
<b>5.1 JUSTIFICATION.....</b>	<b>8</b>
<b>5.2 PERIPHERAL EQUIPMENT .....</b>	<b>8</b>
<b>5.3 MODE OF OPERATION DURING THE TEST .....</b>	<b>8</b>
<b>5.4 CONFIGURATION OF TEST SYSTEM.....</b>	<b>10</b>
<b>6. PRELIMINARY TEST .....</b>	<b>10</b>
<b>6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....</b>	<b>10</b>
<b>6.2 GENERAL RADIATED EMISSIONS TESTS .....</b>	<b>10</b>
<b>7. MINIMUM 6 DB BANDWIDTH.....</b>	<b>11</b>
<b>7.1 OPERATING ENVIRONMENT .....</b>	<b>11</b>
<b>7.2 TEST SET-UP .....</b>	<b>11</b>
<b>7.3 TEST DATE .....</b>	<b>11</b>
<b>7.4 TEST DATA FOR 1 MBPS.....</b>	<b>12</b>
<b>8. MAXIMUM PEAK OUTPUT POWER.....</b>	<b>14</b>
<b>8.1 OPERATING ENVIRONMENT .....</b>	<b>14</b>
<b>8.2 TEST SET-UP .....</b>	<b>14</b>
<b>8.3 TEST DATE .....</b>	<b>14</b>
<b>8.4 TEST DATA FOR 1 MBPS.....</b>	<b>15</b>
<b>9. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND.....</b>	<b>17</b>
<b>9.1 OPERATING ENVIRONMENT .....</b>	<b>17</b>

9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT .....	17
9.3 TEST SET-UP FOR RADIATED MEASUREMENT.....	17
9.4 TEST DATE .....	17
9.5 TEST DATA FOR CONDUCTED EMISSION .....	18
9.5.1 Test data for 1 Mbps .....	18
9.6 TEST DATA FOR RADIATED EMISSION .....	23
9.6.1 Radiated Emission which fall in the Restricted Band.....	23
9.6.2 Spurious & Harmonic Radiated Emission.....	24
10. PEAK POWER SPECTRAL DENSITY .....	25
10.1 OPERATING ENVIRONMENT .....	25
10.2 TEST SET-UP .....	25
10.3 TEST DATE .....	25
10.4 TEST DATA FOR 1 MBPS .....	26
11. RADIATED EMISSION TEST .....	28
11.1 OPERATING ENVIRONMENT .....	28
11.2 TEST SET-UP .....	28
11.3 TEST DATE .....	29
11.4 TEST DATA FOR 30 MHZ ~ 1 GHZ.....	30
11.4.1 Test data for Bluetooth LE .....	30
11.5 Test data for Below 30 MHz.....	31
11.6 TEST DATA FOR ABOVE 1 GHZ .....	31
12. LIST OF TEST EQUIPMENT .....	32

**Revision History**

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-214-RWD-081	April 28, 2021	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

Applicant : InBody Co., Ltd.  
 Address : InBody Bldg., 625, Eonju-ro, Gangnam-gu, Seoul, 06106, South Korea  
 Contact Person : Kyung Keun, Kim / Manager  
 Telephone No. : +82-2-300-2241  
 FCC ID : F6OH60NWI  
 Model Name : H60NWi  
 Brand Name :   
 Serial Number : N/A  
 Date : April 28, 2021

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Body Composition Analyzer
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2020
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. TEST SUMMARY

### 2.1 Test items and results for Bluetooth LE

SECTION	TEST ITEMS	RESULTS
15.247 (a) (2)	Minimum 6 dB Bandwidth	Met the Limit / PASS
15.247 (b) (3)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.247 (e)	Peak Power Spectral Density	Met the Limit / PASS
15.209	Radiated Emission Limits	Met the Limit / PASS
15.207	Conducted Limits	N/A (See Note)
15.203	Antenna Requirement	Met requirement / PASS

Note: This test is not performed because the EUT is operated by DC Power.

### 2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

### 2.3 Related Submittal(s) / Grant(s)

Original submittal only

### 2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247.

### 2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2020. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

### 2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea.

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-20122/ C-14617/ G-10666/ T-11842

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

### 3. GENERAL INFORMATION

#### 3.1 Product Description

The InBody Co., Ltd., Model H60NWi (referred to as the EUT in this report) is a Body Composition Analyzer. The product specification described herein was obtained from product data sheet or user’s manual.

DEVICE TYPE	Body Composition Analyzer
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
MODULATION TYPE	GFSK
RF OUTPUT POWER	-4.71 dBm
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	3.70 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32.768 kHz, 38.4 MHz

#### 3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

### 4. EUT MODIFICATIONS

-. None

## 5. SYSTEM TEST CONFIGURATION

### 5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	InBody Co., Ltd.	INBODY_BOARD_MAIN_H60(H30)_B0821	N/A
Sub Board	InBody Co., Ltd.	INBODY_BOARD_WIFI_H60(H30)_B1621	N/A
WIFI Module	I&C Technology Co., Ltd.	N/A	2ADXS-WFM60-SFP2501

### 5.2 Peripheral equipment

-. None

### 5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at 2 402 MHz, 2 440 MHz, and 2 480 MHz to get a maximum emission levels from the EUT. The EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis, but the worst data was recorded in this report.

#### -. Channel List (Bluetooth LE)

Channel	Frequency[MHz]	Channel	Frequency[MHz]	Channel	Frequency[MHz]
0	2 402.00	14	2 430.00	28	2 458.00
1	2 404.00	15	2 432.00	29	2 460.00
2	2 406.00	16	2 434.00	30	2 462.00
3	2 408.00	17	2 436.00	31	2 464.00
4	2 410.00	18	2 438.00	32	2 466.00
5	2 412.00	19	2 440.00	33	2 468.00
6	2 414.00	20	2 442.00	34	2 470.00
7	2 416.00	21	2 444.00	35	2 472.00
8	2 418.00	22	2 446.00	36	2 474.00
9	2 420.00	23	2 448.00	37	2 476.00
10	2 422.00	24	2 450.00	38	2 478.00
11	2 424.00	25	2 452.00	39	2 480.00
12	2 426.00	26	2 454.00		
13	2 428.00	27	2 456.00		




- Duty Cycle

Mode	Tx On Time [ ms ]	Tx Off Time [ ms ]	Duty Cycle [ % ]	Correction Factor [ dB ]
Bluetooth LE	2.14	0.36	85.60	0.68

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) \* 100

Correction Factor : 10 \* Log(1 / (Duty Cycle / 100))

- Test Plot



Bluetooth LE\_1 Mbps

### 5.4 Configuration of Test System

**Line Conducted Test:** It is not need to test this requirement, because the EUT shall be operated by DC Power.

**Radiated Emission Test:** Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2020 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meter Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

### 5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

**Antenna Construction:**

The antenna of the EUT is a Chip Antenna on the main board in the EUT, so no consideration of replacement by the user.

## 6. PRELIMINARY TEST

### 6.1 AC Power line Conducted Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied by DC Power.	

### 6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

## 7. MINIMUM 6 dB BANDWIDTH


### 7.1 Operating environment

Temperature : 23 °C

Relative humidity : 45 % R.H.

### 7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.




### 7.3 Test Date


April 19, 2021 ~ April 26, 2021

### 7.4 Test data for 1 Mbps


CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (kHz)	LIMIT (kHz)	MARGIN (kHz)
Low	2 402.00	654.30	500.00	154.30
Middle	2 440.00	664.30	500.00	164.30
High	2 480.00	644.40	500.00	144.40

Remark. Margin = Measured Value - Limit





Middle Channel



High Channel

## 8. MAXIMUM PEAK OUTPUT POWER


### 8.1 Operating environment

Temperature : 23 °C  
 Relative humidity : 45 % R.H.

### 8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to  $\geq$  DTS Bandwidth, the video bandwidth is set to 3 times the resolution bandwidth.



### 8.3 Test Date


April 19, 2021 ~ April 26, 2021


### 8.4 Test data for 1 Mbps

-. Test Result : Pass


CHANNEL	FREQUENCY (MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402.00	-4.71	30.00	34.71
MIDDLE	2 440.00	-5.17	30.00	35.17
HIGH	2 480.00	-4.74	30.00	34.74

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)





Middle Channel



High Channel




## 9. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

### 9.1 Operating environment

Temperature : 23 °C  
 Relative humidity : 45 % R.H.

### 9.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, the video bandwidth is set to 3 times the resolution bandwidth and peak detection was used.



### 9.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m semi anechoic chamber. The EUT was placed on turntable approximately 1.5 m above the ground plane.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

### 9.4 Test Date


April 19, 2021 ~ April 26, 2021

9.5 Test data for conducted emission


9.5.1 Test data for 1 Mbps




Low Channel




Middle Channel




High Channel




Low Channel




Low Channel




Middle Channel



Middle Channel



High Channel



High Channel

**9.6 Test data for radiated emission**

**9.6.1 Radiated Emission which fall in the Restricted Band**

- Resolution bandwidth : 1 MHz and Peak Detector for Peak Mode  
1 MHz and RMS Detector for Average Mode
- Video bandwidth : 3 MHz for Peak and Average Mode
- Measurement distance : 3 m
- Duty Cycle : 85.60 %
- Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	C.F (dB)	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)
<b>Test Data for Low Channel</b>										
2 341.449	48.02	Peak	H	28.30	8.20	45.30	-	39.22	74.00	34.78
2 340.809	38.02	Average	H				0.68	29.90	54.00	24.10
2 330.100	50.55	Peak	V				-	41.75	74.00	32.25
2 320.669	41.51	Average	V				0.68	33.39	54.00	20.61
<b>Test Data for High Channel</b>										
2 484.843	58.25	Peak	H	28.70	8.35	45.50	-	49.80	74.00	24.20
2 484.500	50.17	Average	H				0.68	42.40	54.00	11.60
2 484.745	61.48	Peak	V				-	53.03	74.00	20.97
2 484.629	52.12	Average	V				0.68	44.35	54.00	9.65

Tabulated test data for Restricted Band

Remark: “H”: Horizontal, “V”: Vertical

$$\text{Margin (dB)} = \text{Limits (dBµV/m)} - \text{Total Level (dBµV/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Correction Factor} - \text{AMP Factor}$$

### 9.6.2 Spurious & Harmonic Radiated Emission

- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,  
1 MHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Duty Cycle : 85.60 %
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	AMP Factor	C.F (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>										
4 804.00	51.35	Peak	H	33.40	11.21	46.30	-	49.66	74.00	24.34
	43.24	Average	H				0.68	42.23	54.00	11.77
	51.40	Peak	V				-	49.71	74.00	24.29
	43.31	Average	V				0.68	42.30	54.00	11.70
<b>Test Data for Middle Channel</b>										
4 880.00	51.26	Peak	H	33.50	11.23	46.33	-	49.66	74.00	24.34
	43.18	Average	H				0.68	42.26	54.00	11.74
	51.34	Peak	V				-	49.74	74.00	24.26
	43.35	Average	V				0.68	42.43	54.00	11.57
<b>Test Data for High Channel</b>										
4 960.00	51.29	Peak	H	33.40	11.31	46.35	-	49.65	74.00	24.35
	43.32	Average	H				0.68	42.36	54.00	11.64
	51.30	Peak	V				-	49.66	74.00	24.34
	43.24	Average	V				0.68	42.28	54.00	11.72

Remark: "H": Horizontal, "V": Vertical

$$\text{Margin (dB)} = \text{Limits (dB}\mu\text{V/m)} - \text{Total Level (dB}\mu\text{V/m)}$$

$$\text{Total Level} = \text{Reading} + \text{Antenna Factor} + \text{Cable Loss} + \text{Correction Factor} - \text{AMP Factor}$$



## 10. PEAK POWER SPECTRAL DENSITY


### 10.1 Operating environment

Temperature : 23 °C  
Relative humidity : 45 % R.H.

### 10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer.

The resolution bandwidth is set to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ , the video bandwidth is set to 3 times the resolution bandwidth.



### 10.3 Test Date

April 19, 2021 ~ April 26, 2021


**10.4 Test data for 1 Mbps**

-. Test Result : Pass


-. Operating Condition : Continuous transmitting mode

CHANNEL	FREQUENCY(MHz)	MEASURED VALUE (dBm)	LIMIT (dBm)	MARGIN (dB)
Low	2 402.00	-21.28	8.00	29.28
Middle	2 440.00	-21.28	8.00	29.28
High	2 480.00	-21.32	8.00	29.32


Remark. Margin = Limit – Measured value



Low Channel



Middle Channel



High Channel

## 11. RADIATED EMISSION TEST

### 11.1 Operating environment

Temperature : 23 °C  
 Relative humidity : 45 % R.H.


### 11.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.


The frequency spectrum from 30 MHz to 26.5 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

#### - Test Configuration


1. Below 30 MHz



2. 30 MHz - 1 GHz



3. Above 1 GHz



**11.3 Test Date**

April 19, 2021 ~ April 26, 2021

### 11.4 Test data for 30 MHz ~ 1 GHz


#### 11.4.1 Test data for Bluetooth LE

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : Body Composition Analyzer

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
---- Horizontal ----										
1	46.490	44.3	14.6	0.7	32.1	27.5	40.0	12.5	400	49
2	66.860	41.8	12.6	0.9	32.1	23.2	40.0	16.8	300	142
3	101.780	52.4	15.6	1.1	32.0	37.1	43.5	6.4	300	100
4	115.360	44.8	17.8	1.2	32.0	31.8	43.5	11.7	300	0
5	148.340	39.7	18.8	1.4	32.0	27.9	43.5	15.6	200	78
6	247.280	37.1	17.7	1.9	32.0	24.7	46.0	21.3	200	359
---- Vertical ----										
7	39.700	45.2	17.4	0.7	32.0	31.3	40.0	8.7	100	359
8	46.490	50.6	14.6	0.7	32.1	33.8	40.0	6.2	100	142
9	66.860	43.8	12.6	0.9	32.1	25.2	40.0	14.8	100	359
10	101.780	47.6	15.6	1.1	32.0	32.3	43.5	11.2	300	193
11	149.310	37.5	18.8	1.4	32.0	25.7	43.5	17.8	100	359
12	831.211	30.9	27.2	4.1	31.9	30.3	46.0	15.7	100	27

**11.5 Test data for Below 30 MHz**

- Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)
- Frequency range : 9 kHz ~ 30 MHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

**11.6 Test data for above 1 GHz**

- Resolution bandwidth : 1 MHz for Peak and Average Mode for the emissions fall in restricted band,  
1 MHz for Peak Mode for the emissions outside restricted band
- Video bandwidth : 3 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 26.5 GHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
Emission from the EUT more than 20 dB below the limit in each frequency range.									

## 12. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal.(Interval)
FSV40-N	Rohde & Schwarz	Signal Analyzer	101457	Apr. 16, 2021 (1Y)
ESR7	Rohde & Schwarz	EMI Test Receiver	102190	Oct. 14, 2020 (1Y)
310N	Sonoma Instrument	AMPLIFIER	392756	Oct. 16, 2020 (1Y)
PAM-840A	Com-Power	Pre-Amplifer	461339	Oct. 16, 2020 (1Y)
PAM-118A	Com-Power	Pre-Amplifer	18040081	Oct. 12, 2020 (1Y)
DT2000-2t	Innco Systems GmbH	Turn Table	N/A	N/A
CO3000	Innco Systems GmbH	Controller	1026/40960617/P	N/A
MA-4640-XPET	Innco Systems GmbH	Antenna Master	MA4640/652/43100318/P	N/A
HLP-2008	TDK RF Solutions	Hybrid Antenna	131316	Feb. 27, 2020 (2Y)
BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Jan. 07, 2021(1Y)
AH-118	Com-Power	Horn Antenna	10050061	Oct. 15, 2020 (1Y)
FMZB 1513	Schwarzbeck	Loop Antenna	1513-235	Mar. 24, 2020(2Y)
HPF 3GHz	Rohde & Schwarz	High Pass Filter (1-3 GHz)	N/A	Feb. 08, 2021 (1Y)
GP-4303D	LG Precision Co.,Ltd	DC POWER SUPPLY	5071069	Jan. 06, 2021 (1Y)