



July 14, 2014

Attn: Application Examiner, Reviewing Engineer

The following is the SAR calculation for the FlexWave™ Prism – HDM 850 MIMO, FCC ID: F8I-PSM0850M, using the system's maximum RF emission. The calculation is based on FCC 47CFR Part 2 and OET 65.

Per OET 65:

Maximum Permissible Exposure is $\text{Freq. (MHz)}/1500 = \text{MPE mW/cm}^2$
 $881.5 \text{ MHz}/1500 = 0.5877 \text{ mW/cm}^2$

The following equations determine the distance from the antenna that the power density is $\leq 0.5877 \text{ mW/cm}^2$.

+47.10 dBm Transmitter Power (Max)
12.90 dBi Antenna Gain (Max)
 $47.10 \text{ dBm} + 12.90 \text{ dBi} = +60 \text{ dBm EIRP}$
 $+60 \text{ dBm EIRP} = 1000 \text{ Watts EIRP}$
 $1000 \text{ Watts EIRP} = 1000 * 10^3 \text{ mWatts EIRP}$
 $0.5877 \text{ mW/cm}^2 = 1000 * 10^3 \text{ mW}/(4 * \pi * r^2)$
 $r = \text{SQRT}(1000 * 10^3 / (4 * \pi * 0.5877))$
 $r = 368.06 \text{ cm or } 3.68 \text{ Meters}$

In addition, the following statement will be added to our installation/operation manual:

To comply with Maximum Permissible Exposure (MPE) requirements, the maximum composite output from the antenna cannot exceed 1000 Watts EIRP and the antenna must be permanently installed in a fixed location that provides at least 6 meters (20 feet) of separation from all persons.

Sincerely,

A handwritten signature in black ink, appearing to read 'Joshua J. Wittman', is written over a horizontal line.

Joshua J. Wittman
Compliance Engineer
Tele: 952 403-8322
Fax: 952 403-8858
Email: joshua.wittman@te.com