

# TEST REPORT

**Application No.:** HKEM2304000316PF  
**Applicant:** Kingtronics Industrial Co Ltd  
**Address of Applicant:** Penthouse, Century Centre, 44-46 Hung To Road, Kwun Tong, Kowloon, Hong Kong

**Equipment Under Test (EUT):**  
**Model No.:** CL4510 BS, CL4XYY ZZ, CL5XYY ZZ  
**Additional Model:** Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

**FCC ID:** FA5CL5500CL4500  
**Standard(s) :** 47 CFR Part 1.1307;  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06

**Date of Receipt:** 2023-05-23  
**Date of Test:** 2023-05-23 to 2023-05-30  
**Date of Issue:** 2023-06-19

<b>Test Result:</b>	The submitted sample was found to comply with the test requirement
---------------------	--





**Law Man Kit**  
EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at <http://www.sgs.com/en/Terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Revision No.	Date	Report superseded	Remark

<b>Authorized for issue by:</b>			
			
		<b>Chan Chun Lok /Project Engineer</b>	Date: 2023-06-14
			
		<b>Law Man Kit /Reviewer</b>	Date: 2023-06-19

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
RF Exposure	47 CFR Part 1.1307, 47 CFR Part 2.1093, KDB 447498 D01	KDB447498D01	KDB447498D01	PASS

### Declaration of EUT Family Grouping:

Item no.: CL4510 BS, CL4XYZ ZZ, CL5XYZ ZZ

According to the confirmation from the applicant, the above models are identical in all electrical aspects in relating to the circuitry design, PCB layout, electrical components used, internal wiring and functions. The differences are only product outlook and colour.

Digit	Combination	Meaning
X	0-9	N/A
YY	00-99	N/A
ZZ	BS	Brushed Steel
	SS	Stainless Steel
	MG	Marine Grade
	BK	Black
	PB	Polished Brass

Therefore, only the model CL4510 BS was tested in this report.

### Note:

This is a report for the host product (Model: CL4510 BS), which embedded with certified module (Model: BM833F, FCC ID:X8WBM833) without any changes to the RF circuit. Thus, the RF output power was derived from original certified module reports (ISL-19LR247FC) issued on 2019-10-21.

### Abbreviation:

- Tx: In this whole report Tx (or tx) means Transmitter.
- Rx: In this whole report Rx (or rx) means Receiver.
- RF: In this whole report RF means Radiated Frequency.
- CH: In this whole report CH means channel.
- Volt: In this whole report Volt means Voltage.
- Temp: In this whole report Temp means Temperature.
- Humid: In this whole report Humid means humidity.
- Press: In this whole report Press means Pressure.
- N/A: In this whole report not application.

### 3 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>2 TEST SUMMARY</b> .....	<b>3</b>
<b>3 CONTENTS</b> .....	<b>4</b>
<b>4 GENERAL INFORMATION</b> .....	<b>5</b>
4.1 DETAILS OF E.U.T. ....	5
4.2 TEST LOCATION.....	6
4.3 TEST FACILITY.....	6
4.4 DEVIATION FROM STANDARDS.....	6
4.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	6
<b>5 RADIO SPECTRUM TECHNICAL REQUIREMENT</b> .....	<b>7</b>
5.1 RF EXPOSURE .....	7
5.1.1 <i>Test Requirement:</i> .....	7
5.1.1 <i>EUT RF Exposure Evaluation</i> .....	8
<b>6 PHOTOGRAPHS</b> .....	<b>9</b>
6.1 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	9

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 6 V ('AA' size battery x 4)
Test voltage:	DC 6 V
Cable:	N/A
Antenna Gain:	-0.56 dBi
Antenna Type:	PCB Antenna
Bluetooth Version:	V5.1 BLE
Channel Separation:	2MHz
Modulation Type:	GFSK
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz

Frequency List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>0</b>	<b>2402</b>	<b>20</b>	<b>2442</b>
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2402	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2480
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	<b>39</b>	<b>2480</b>

The frequencies under test are bolded.

## 4.2 Test Location

All tests were performed at:

SGS Hong Kong Limited  
Unit 2 and 3, G/F, Block A, Po Lung Centre,  
11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong  
Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

## 4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IAS Accreditation (Lab Code: TL-817)**

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website ([www.iasonline.org](http://www.iasonline.org)).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

- **FCC Recognized Accredited Test Firm(CAB Registration No.: 514599)**

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

- **Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)**

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

## 4.4 Deviation from Standards

None

## 4.5 Abnormalities from Standard Conditions

None

---

## 5 Radio Spectrum Technical Requirement

### 5.1 RF Exposure

#### 5.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

*S* = power density (mW/cm<sup>2</sup>)  
*P* = the net power delivered to the antenna (mW)  
*G* = gain of the antenna in linear scale  
*d* = distance between observation point and center of the radiator (cm)

### 5.1.1 EUT RF Exposure Evaluation

Antenna Gain: -0.56 dBi for BLE.

The maximum Gain measured in fully anechoic chamber is 0.88 (BLE) in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

BLE:

Operation mode	Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
GFSK	Low	2402	7.5	5.623	0.00098	1	Pass
GFSK	Middle	2442	7.7	5.888	0.00103	1	Pass
GFSK	High	2480	8.2	6.607	0.00116	1	Pass

Note:

This is a report for the host product (Model: CL4510 BS), which embedded with certified module (Model: BM833F, FCC ID:X8WBM833) without any changes to the RF circuit. Thus, the RF output power was derived from original certified module reports (ISL-19LR247FC) issued on 2019-10-21.





## **6 Photographs**

### **6.1 EUT Constructional Details (EUT Photos)**

Refer to the appendices external, internal and setup photos.

- End of the Report -

---