



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	<b>BUFFALO INC.</b>
Applicant Address	Akamon-dori Bldg 30-20, Ohsu 3-chome Naka-ku, Nagoya 460-8315 Japan
FCC ID	<b>FDI000000015</b>
Manufacturer's company	<b>BUFFALO INC.</b>
Manufacturer Address	Akamon-dori Bldg 30-20, Ohsu 3-chome Naka-ku, Nagoya 460-8315 Japan

Product Name	AirStation
Brand Name	BUFFALO INC.
Model No.	WZR-1166DHP
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Feb. 21, 2013
Final Test Date	May 08, 2013
Submission Type	Original Equipment



### Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a/ac (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009**,

**47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03 and KDB 662911 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE</b> .....	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT</b> .....	<b>2</b>
<b>3. GENERAL INFORMATION</b> .....	<b>3</b>
3.1. Product Details .....	3
3.2. Accessories .....	5
3.3. Table for Filed Antenna .....	6
3.4. Table for Carrier Frequencies .....	7
3.5. Table for Test Modes .....	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units .....	10
3.8. Table for Parameters of Test Software Setting .....	11
3.9. EUT Operation during Test.....	12
3.10. Duty Cycle.....	13
3.11. Test Configurations.....	17
<b>4. TEST RESULT</b> .....	<b>21</b>
4.1. AC Power Line Conducted Emissions Measurement .....	21
4.2. Maximum Conducted Output Power Measurement.....	25
4.3. Power Spectral Density Measurement.....	29
4.4. 6dB Spectrum Bandwidth Measurement .....	39
4.5. Radiated Emissions Measurement.....	48
4.6. Emissions Measurement.....	75
4.7. Antenna Requirements .....	104
<b>5. LIST OF MEASURING EQUIPMENTS</b> .....	<b>105</b>
<b>6. TEST LOCATION</b> .....	<b>107</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT</b> .....	<b>A1 ~ A17</b>
<b>APPENDIX B. TEST PHOTOS</b> .....	<b>B1 ~ B5</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE</b> .....	<b>C1 ~ C3</b>
<b>APPENDIX D. CO-LOCATION REPORT</b> .....	<b>D1 ~ D3</b>



## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR322115AB	Rev. 01	Initial issue of report	May 16, 2013



## 1. CERTIFICATE OF COMPLIANCE

**Product Name** : AirStation  
**Brand Name** : BUFFALO INC.  
**Model No.** : WZR-1166DHP  
**Applicant** : BUFFALO INC.  
**Test Rule Part(s)** : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 21, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'. The signature is written in a cursive style and is positioned above a horizontal line.

**Sam Chen**  
**SPORTON INTERNATIONAL INC.**

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.10 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	1.72 dB
4.3	15.247(e)	Power Spectral Density	Complies	4.24 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.26 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.20 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1GHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n/ac

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 17.60 MHz ; MCS0 (40MHz): 36.00 MHz For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 23.04 MHz ; 802.11ac MCS0/Nss1 (40MHz): 41.44 MHz ; 802.11ac MCS0/Nss1 (80MHz): 75.84 MHz
Maximum Conducted Output Power	For 2.4GHz Band: MCS0 (20MHz): 26.73 dBm ; MCS0 (40MHz): 22.76 dBm For 5GHz Band: 802.11ac MCS0/Nss1 (20MHz): 28.28 dBm ; 802.11ac MCS0/Nss1 (40MHz): 27.65 dBm ; 802.11ac MCS0/Nss1 (80MHz): 23.77 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**802.11a/b/g**

Items	Description
Product Type	802.11b: WLAN (1TX, 1RX) 802.11a/g/n/ac: WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 10.08 MHz ; 11g: 16.32 MHz ; 11a: 23.60 MHz
Maximum Conducted Output Power	11b: 22.11 dBm ; 11g: 26.55 dBm ; 11a: 27.71 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note: The product has beamforming function for 802.11a/n/ac in 5150-5250MHz and 5725-5850MHz.

**Antenna & Band width**

Antenna	Single (TX)			Two (TX)		
	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz
IEEE 802.11a	X	X	X	V	X	X
IEEE 802.11b	V	X	X	X	X	X
IEEE 802.11g	X	X	X	V	X	X
IEEE 802.11n	X	X	X	V	V	X
IEEE 802.11ac	X	X	X	V	V	V

Note : It supports the beamforming function for 802.11a/n/ac mode only.

**IEEE 11n/ac Spec.**

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	M0-15
802.11n (HT40)	2	M0-15
802.11ac (VHT20)	2	MCS 0-9/Nss1-2
802.11ac (VHT40)	2	MCS 0-9/Nss1-2
802.11ac (VHT80)	2	MCS 0-9/Nss1-2

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:

11a: IEEE 802.11a, HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

**3.2. Accessories**

Power	Brand	Model	Rating
Adapter	Asian Power Devices Inc.	WA-36A12U	Input: 100-240VAC, 50-60Hz, 0.9A Output: 12VDC, 3A
<b>Others</b>			
Cradle*1			



### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	Arcadyan	120300037100J	PIFA Antenna	I-PEX	-	0.43
2	Arcadyan	120300037200J	PIFA Antenna	I-PEX	-	0.67
3	Arcadyan	120800010200J	PIFA Antenna	I-PEX	-1.24	-
4	Arcadyan	120800010800J	PIFA Antenna	I-PEX	-0.99	-

Note: The EUT has four antennas.


**For IEEE 802.11b mode (1TX/1RX):**

Only Ant. 3 can be used as transmitting/receiving antenna.

**For IEEE 802.11a/g/n/ac mode (2TX/2RX):**

Both Ant. 1 and Ant. 2 can be used as transmitting/receiving antennas.

Ant. 1 and Ant. 2 could transmit/receive signal simultaneously.



### 3.4. Table for Carrier Frequencies

#### For 2.4GHz Band:

There are two bandwidth systems.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

#### For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

#### For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	1/6/11	3+4
	11n 40MHz	MCS0	3/6/9	3+4
	11b/CCK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3+4
Power Spectral Density	11n 20MHz	MCS0	1/6/11	3, 4
	11n 40MHz	MCS0	3/6/9	3, 4
	11b/CCK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3, 4
6dB Spectrum Bandwidth	11n 20MHz	MCS0	1/6/11	3+4
	11n 40MHz	MCS0	3/6/9	3+4
	11b/CCK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3+4
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	1/6/11	3+4
	11n 40MHz	MCS0	3/6/9	3+4
	11b/CCK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3+4
Band Edge Emissions	11n 20MHz	MCS0	1/6/11	3+4
	11n 40MHz	MCS0	3/6/9	3+4
	11b/CCK	1 Mbps	1/6/11	3
	11g/BPSK	6 Mbps	1/6/11	3+4

**For 5GHz Band**

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Conducted Output Power	11ac 20MHz	MCS0/Nss1	149/157/165	1+2
	11ac 40MHz	MCS0/Nss1	151/159	1+2
	11ac 80MHz	MCS0/Nss1	155	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Power Spectral Density	11ac 20MHz	MCS0/Nss1	149/157/165	1, 2
	11ac 40MHz	MCS0/Nss1	151/159	1, 2
	11ac 80MHz	MCS0/Nss1	155	1, 2
	11a/BPSK	6 Mbps	149/157/165	1, 2
6dB Spectrum Bandwidth	11ac 20MHz	MCS0/Nss1	149/157/165	1+2
	11ac 40MHz	MCS0/Nss1	151/159	1+2
	11ac 80MHz	MCS0/Nss1	155	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11ac 20MHz	MCS0/Nss1	149/157/165	1+2
	11ac 40MHz	MCS0/Nss1	151/159	1+2
	11ac 80MHz	MCS0/Nss1	155	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Band Edge Emissions	11ac 20MHz	MCS0/Nss1	149/157/165	1+2
	11ac 40MHz	MCS0/Nss1	151/159	1+2
	11ac 80MHz	MCS0/Nss1	155	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2

The following test modes were performed for Conducted Emission test and Radiated Emission below 1GHz test:

Mode 1. EUT with AP function

Mode 2. EUT with repeater function (WLAN 2.4GHz function)

Mode 3. EUT with repeater function (WLAN 5GHz function)

**For Conducted Emission test:**

Mode 1 generated the worst test result, so it was recorded in the report.

**Radiated Emission below 1GHz test:**

Mode 3 generated the worst test result, so it was recorded in the report.

**<For MPE and Co-location Test>:**

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix C) and Co-location (please refer to Appendix D) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).  
Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	QDS-BRCM1049LE
Notebook	DELL	E6430	QDS-BRCM1049LE
Notebook	DELL	E6430	QDS-BRCM1049LE
Notebook	DELL	E6430	QDS-BRCM1049LE
Flash Disk	ADATA	C103	DoC
Flash Disk	WD	WDBACY5000AWT	DoC
AP Router	Buffalo	WZR-1166DHP	PY312100188
Wifi Dongle	Netgear	A6200	PY312200200
Notebook	DELL	E4300	QDS-BRCM1049LE

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### For 2.4GHz Band

##### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	Manual Tool v1.0.0.10		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	80	98	76

##### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	Manual Tool v1.0.0.10		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	67	84	64

##### Power Parameters of IEEE 802.11b/g

Test Software Version	Manual Tool v1.0.0.10		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	98	98	98
IEEE 802.11g	85	98	80

### For 5GHz Band

#### Power Parameters of IEEE 802.11ac MCS0/Nss1 20MHz

Test Software Version	Telnet		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0/Nss1 20MHz	98	100	100

#### Power Parameters of IEEE 802.11ac MCS0/Nss1 40MHz

Test Software Version	Telnet	
Frequency	5755 MHz	5795 MHz
MCS0/Nss1 40MHz	94	100

#### Power Parameters of IEEE 802.11ac MCS0/Nss1 80MHz

Test Software Version	Telnet
Frequency	5775 MHz
MCS0/Nss1 80MHz	86

#### Power Parameters of IEEE 802.11a

Test Software Version	Telnet		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	100	99	96

### 3.9. EUT Operation during Test

#### For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

#### For beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.


The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Latest.exe " to link with the remote workstation to receive and transmit packet by Wireless AP and transmit duty cycle no less 98%

### 3.10. Duty Cycle


For non-beamforming mode:

IEEE 802.11n MCS0 20MHz / For 2.4GHz Band



Date: 28.MAR.2013 21:58:47


IEEE 802.11n MCS0 40MHz / For 2.4GHz Band



Date: 28.MAR.2013 21:57:58




IEEE 802.11b



Date: 28.MAR.2013 21:53:57


IEEE 802.11g



Date: 28.MAR.2013 21:54:51


**For beamforming mode:**

**IEEE 802.11ac MCS0/Nss1 20MHz**




Date: 28.MAR.2013 22:01:34

**IEEE 802.11ac MCS0/Nss1 40MHz**




Date: 28.MAR.2013 22:02:26

IEEE 802.11ac MCS0/Nss1 80MHz



Date: 28.MAR.2013 22:03:14

IEEE 802.11a




Date: 28.MAR.2013 22:00:47

### 3.11. Test Configurations

#### 3.11.1. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1




Item	Connection	Shield	Length	Remark
1	Power cable	No	1.5m	-
2	RJ-45 cable	No	10m	-
3	RJ-45 cable	No	10m	-
4	RJ-45 cable*3	No	0.7m	-

### 3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz


Test Mode: Mode 3



Item	Connection	Shield	Length	Remark
1	Power cable	No	1.5m	-
2	RJ-45 cable*3	No	0.7m	-
3	RJ-45 cable	No	10m	-
4	RJ-45 cable	No	10m	-


Test Configuration: above 1GHz

**For non-beamforming mode:**



Item	Connection	Shield	Length	Remark
1	Power cable	No	1.5m	-
2	RJ-45 cable	No	10m	-

For beamforming mode:



Item	Connection	Shield	Length	Remark
1	AC Power cable	No	1.8m	-
2	RJ-45	No	10m	-

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.






4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	48%
Test Engineer	Sin Chang	Phase	Line
Configuration	Normal link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15650	49.15	-16.50	65.65	48.81	0.16	0.18	QP
2	0.15650	38.59	-17.06	55.65	38.25	0.16	0.18	AVERAGE
3	0.18152	44.26	-20.15	64.42	43.92	0.15	0.19	QP
4	0.18152	33.51	-20.90	54.42	33.17	0.15	0.19	AVERAGE
5	0.38263	36.38	-21.84	58.22	36.03	0.15	0.20	QP
6	0.38263	36.12	-12.10	48.22	35.77	0.15	0.20	AVERAGE
7	1.734	23.11	-32.89	56.00	22.70	0.19	0.22	QP
8	1.734	22.87	-23.13	46.00	22.46	0.19	0.22	AVERAGE
9	5.112	16.74	-33.26	50.00	16.18	0.24	0.32	AVERAGE
10	5.112	22.83	-37.17	60.00	22.27	0.24	0.32	QP
11	13.479	30.87	-29.13	60.00	30.08	0.39	0.40	QP
12	13.479	23.93	-26.07	50.00	23.14	0.39	0.40	AVERAGE

Temperature	23°C	Humidity	48%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	Normal link	Test Mode	Mode 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15650	48.97	-16.68	65.65	48.71	0.08	0.18	QP
2	0.15650	36.75	-18.90	55.65	36.49	0.08	0.18	AVERAGE
3	0.17866	31.78	-22.77	54.55	31.51	0.08	0.19	AVERAGE
4	0.17866	44.55	-20.00	64.55	44.28	0.08	0.19	QP
5	0.83047	21.08	-34.92	56.00	20.79	0.09	0.20	QP
6	0.83047	13.45	-32.55	46.00	13.16	0.09	0.20	AVERAGE
7	1.824	15.86	-40.14	56.00	15.53	0.11	0.23	QP
8	1.824	15.00	-31.00	46.00	14.67	0.11	0.23	AVERAGE
9	4.874	16.39	-29.61	46.00	15.93	0.15	0.32	AVERAGE
10	4.874	25.44	-30.56	56.00	24.98	0.15	0.32	QP
11	13.479	29.57	-30.43	60.00	28.88	0.29	0.40	QP
12	13.479	21.96	-28.04	50.00	21.27	0.29	0.40	AVERAGE

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 9.2.2. Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Denis Su	Configurations	IEEE 802.11n/ac
Test Date	Mar. 28, 2013		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 3	Ant. 4			
1	2412 MHz	17.58	20.24	22.12	30.00	Complies
6	2437 MHz	22.13	24.88	26.73	30.00	Complies
11	2462 MHz	17.52	19.89	21.88	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 3	Ant. 4			
3	2422 MHz	14.31	16.72	18.69	30.00	Complies
6	2437 MHz	17.92	21.04	22.76	30.00	Complies
9	2452 MHz	14.03	16.21	18.27	30.00	Complies

## For 5GHz Band

## Configuration IEEE 802.11ac MCS0/Nss1 20MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	23.67	24.79	27.28	30.00	Complies
157	5785 MHz	24.76	25.72	28.28	30.00	Complies
165	5825 MHz	24.73	25.61	28.20	30.00	Complies

Note: Directional gain= $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 3.56\text{dBi} < 6\text{dBi}$ , so the limit doesn't reduce.

## Configuration IEEE 802.11ac MCS0/Nss1 40MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
151	5755 MHz	22.10	23.33	25.77	30.00	Complies
159	5795 MHz	24.18	25.06	27.65	30.00	Complies

Note: Directional gain= $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 3.56\text{dBi} < 6\text{dBi}$ , so the limit doesn't reduce.

## Configuration IEEE 802.11ac MCS0/Nss1 80MHz

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
155	5775 MHz	20.00	21.41	23.77	30.00	Complies

Note: Directional gain= $G_{ANT} + 10\log(N_{ANT}/N_{ss}) = 3.56\text{dBi} < 6\text{dBi}$ , so the limit doesn't reduce.

Temperature	23°C	Humidity	63%
Test Engineer	Denis Su	Configurations	IEEE 802.11a/b/g
Test Date	Mar. 28, 2013		

**Configuration IEEE 802.11b / Ant. 3**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.36	30.00	Complies
6	2437 MHz	21.73	30.00	Complies
11	2462 MHz	22.11	30.00	Complies

**Configuration IEEE 802.11g**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 3	Ant. 4			
1	2412 MHz	18.54	21.06	22.99	30.00	Complies
6	2437 MHz	22.12	24.61	26.55	30.00	Complies
11	2462 MHz	18.12	20.46	22.46	30.00	Complies

**Configuration IEEE 802.11a**

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
149	5745 MHz	24.16	25.18	27.71	30.00	Complies
157	5785 MHz	23.89	24.87	27.42	30.00	Complies
165	5825 MHz	23.18	24.12	26.69	30.00	Complies

Note: Directional gain= $G_{ANT} + 10 \log(N_{ANT}/N_{SS}) = 3.56 \text{dBi} < 6 \text{dBi}$ , so the limit doesn't reduce.

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

#### 4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add  $10 \log(\text{NANT})$  dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be  $\leq 8$  dBm.

#### 4.3.4. Test Setup Layout





#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Denis Su	Configurations	IEEE 802.11n/ac
Test Date	Mar. 28, 2013		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 3	Ant. 4		
1	2412 MHz	-8.91	-5.92	4.99	Complies
6	2437 MHz	-3.36	-1.29	4.99	Complies
11	2462 MHz	-8.62	-5.49	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 3	Ant. 4		
3	2422 MHz	-14.84	-12.52	4.99	Complies
6	2437 MHz	-10.78	-7.50	4.99	Complies
9	2452 MHz	-14.30	-14.95	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

**For 5GHz Band**
**Configuration IEEE 802.11ac MCS0/Nss1 20MHz**

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
149	5745 MHz	-0.48	0.11	4.99	Complies
157	5785 MHz	-1.47	-0.52	4.99	Complies
165	5825 MHz	-0.76	0.41	4.99	Complies

Note: Directional gain=GANT+10log(NANT/Nss) =3.56dBi <6dBi, so the limit doesn't reduce.

$$\text{PSD Limit} = (8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$$

**Configuration IEEE 802.11ac MCS0/Nss1 40MHz**

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
151	5755 MHz	-5.61	-5.77	4.99	Complies
159	5795 MHz	-3.92	-2.12	4.99	Complies

Note: Directional gain=GANT+10log(NANT/Nss) =3.56dBi <6dBi, so the limit doesn't reduce.

$$\text{PSD Limit} = (8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$$

**Configuration IEEE 802.11ac MCS0/Nss1 80MHz**

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
155	5775 MHz	-11.22	-9.41	4.99	Complies

Note: Directional gain=GANT+10log(NANT/Nss) =3.56dBi <6dBi, so the limit doesn't reduce.

$$\text{PSD Limit} = (8\text{dBm}/3\text{kHz} - (10\log(2))) = 4.99\text{dBm}/3\text{kHz}$$

Temperature	23°C	Humidity	63%
Test Engineer	Denis Su	Configurations	IEEE 802.11a/b/g
Test Date	Mar. 28, 2013		

**Configuration IEEE 802.11b / Ant. 3**

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-1.60	8.00	Complies
6	2437 MHz	-2.23	8.00	Complies
11	2462 MHz	-1.01	8.00	Complies

**Configuration IEEE 802.11g**

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 3	Ant. 4		
1	2412 MHz	-7.29	-5.30	4.99	Complies
6	2437 MHz	-3.23	-1.50	4.99	Complies
11	2462 MHz	-7.85	-4.60	4.99	Complies

**Configuration IEEE 802.11a**

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		
149	5745 MHz	-0.13	0.29	4.99	Complies
157	5785 MHz	-0.10	0.75	4.99	Complies
165	5825 MHz	-1.31	-0.12	4.99	Complies


Note: Directional gain= $G_{ANT} + 10 \log(N_{ANT}/N_{SS}) = 3.56 \text{dBi} < 6 \text{dBi}$ , so the limit doesn't reduce.

$$\text{PSD Limit} = (8 \text{dBm}/3\text{kHz} - (10 \log(2))) = 4.99 \text{dBm}/3\text{kHz}$$

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 4 / 2437 MHz




Date: 28.MAR.2013 21:29:52

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 4 / 2437 MHz




Date: 28.MAR.2013 21:24:37

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 2 / 5825 MHz




Date: 28.MAR.2013 19:43:35

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 2 / 5795 MHz




Date: 28.MAR.2013 19:41:52

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 2 / 5775 MHz




Date: 28.MAR.2013 19:40:57

Power Density Plot on Configuration IEEE 802.11b / Ant. 3 / 2462 MHz



Date: 28.MAR.2013 21:14:41


Power Density Plot on Configuration IEEE 802.11g / Ant. 4 / 2437 MHz



Date: 28.MAR.2013 21:32:08



### Power Density Plot on Configuration IEEE 802.11a / Ant. 2 / 5785 MHz



Date: 28.MAR.2013 19:46:30

## 4.4. 6dB Spectrum Bandwidth Measurement

### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100kHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v01r02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

### 4.4.4. Test Setup Layout



### 4.4.5. Test Deviation

There is no deviation with the original standard.

### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Denis Su	Configurations	IEEE 802.11n/ac

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 + Ant. 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.24	17.60	500	Complies
6	2437 MHz	16.24	17.52	500	Complies
11	2462 MHz	16.16	17.52	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 + Ant. 4

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.84	36.00	500	Complies
6	2437 MHz	35.84	36.00	500	Complies
9	2452 MHz	35.84	36.00	500	Complies

**For 5GHz Band**
**Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1 + Ant. 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.60	20.88	500	Complies
157	5785 MHz	17.68	23.04	500	Complies
165	5825 MHz	17.60	22.32	500	Complies

**Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1 + Ant. 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.48	36.64	500	Complies
159	5795 MHz	36.48	41.44	500	Complies

**Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1 + Ant. 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	75.84	75.84	500	Complies

Temperature	23°C	Humidity	64%
Test Engineer	Denis Su	Configurations	IEEE 802.11a/b/g

**Configuration IEEE 802.11b / Ant. 3**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.08	10.08	500	Complies
6	2437 MHz	8.08	10.08	500	Complies
11	2462 MHz	7.68	10.08	500	Complies

**Configuration IEEE 802.11g / Ant. 3 + Ant. 4**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.20	16.32	500	Complies
6	2437 MHz	15.68	16.32	500	Complies
11	2462 MHz	15.68	16.24	500	Complies


**Configuration IEEE 802.11a / Ant. 1 + Ant. 2**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.08	23.60	500	Complies
157	5785 MHz	16.32	23.60	500	Complies
165	5825 MHz	16.32	23.12	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 + Ant. 4 / 2462 MHz




Date: 28.MAR.2013 18:17:16

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 + Ant. 4 / 2437 MHz




Date: 28.MAR.2013 18:18:47

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Ant. 1 + Ant. 2 / 5825 MHz




Date: 28.MAR.2013 18:02:48

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Ant. 1+ Ant. 2 / 5795 MHz



Date: 28.MAR.2013 17:59:43


6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Ant. 1 + Ant. 2 / 5775 MHz



Date: 28.MAR.2013 17:58:39




### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 3 / 2462 MHz




Date: 28.MAR.2013 18:13:29

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 3 + Ant. 4 / 2412 MHz



Date: 28.MAR.2013 18:14:40

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 / 5745 MHz



Date: 28.MAR.2013 18:04:34

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

##### For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

##### For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Test Date	Apr. 25, 2013
Configurations	Normal link	Test Mode	Mode 3

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	Normal Link
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	pk	30.00	35.21	40.00	-4.79	48.40	0.64	17.98	31.81	125	147 HORIZONTAL Peak
2	pp	36.79	36.85	40.00	-3.15	53.82	0.71	14.20	31.88	150	142 HORIZONTAL QP
3		288.99	37.18	46.00	-8.82	53.97	2.07	12.67	31.53	125	82 HORIZONTAL Peak
4		299.66	37.00	46.00	-9.00	53.27	2.13	13.02	31.42	150	272 HORIZONTAL Peak
5		424.79	32.28	46.00	-13.72	44.58	2.57	16.35	31.22	100	110 HORIZONTAL Peak
6		675.05	32.58	46.00	-13.42	41.83	3.33	18.78	31.36	200	44 HORIZONTAL Peak

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	142.52	31.09	43.50	-12.41	50.54	1.42	10.66	31.53	100	36 VERTICAL	Peak
2	293.84	38.11	46.00	-7.89	54.71	2.10	12.79	31.49	150	0 VERTICAL	Peak
3	424.79	35.11	46.00	-10.89	47.41	2.57	16.35	31.22	125	355 VERTICAL	Peak
4	600.36	37.87	46.00	-8.13	47.54	3.12	18.45	31.24	100	71 VERTICAL	Peak
5 pp	624.61	42.87	46.00	-3.13	52.48	3.18	18.61	31.40	100	71 VERTICAL	Peak
6	974.78	42.53	54.00	-11.47	48.32	4.13	21.17	31.09	125	71 VERTICAL	Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

*Horizontal*

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4819.64	30.27	54.00	-23.73	28.93	3.31	33.06	35.03	Average	100	145	HORIZONTAL
2	4826.34	42.83	74.00	-31.17	41.49	3.31	33.06	35.03	Peak	100	145	HORIZONTAL

*Vertical*

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4816.98	29.87	54.00	-24.13	28.58	3.31	33.02	35.04	Average	100	252	VERTICAL
2	4822.91	42.46	74.00	-31.54	41.12	3.31	33.06	35.03	Peak	100	252	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4875.54	42.29	74.00	-31.71	40.83	3.33	33.16	35.03	Peak	100	218	HORIZONTAL
2	4880.86	29.48	54.00	-24.52	28.02	3.33	33.16	35.03	Average	100	218	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4871.31	42.52	74.00	-31.48	41.06	3.33	33.16	35.03	Peak	100	345	VERTICAL
2	4878.74	29.73	54.00	-24.27	28.27	3.33	33.16	35.03	Average	100	345	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4915.38	42.47	74.00	-31.53	40.91	3.35	33.23	35.02	Peak	100	238	HORIZONTAL
2	4928.68	29.82	54.00	-24.18	28.22	3.35	33.26	35.01	Average	100	238	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4918.71	29.84	54.00	-24.16	28.28	3.35	33.23	35.02	Average	100	138	VERTICAL
2	4930.25	42.74	74.00	-31.26	41.14	3.35	33.26	35.01	Peak	100	138	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4837.17	41.94	74.00	-32.06	40.57	3.31	33.09	35.03	Peak	100	136	HORIZONTAL
2	4842.81	29.70	54.00	-24.30	28.32	3.32	33.09	35.03	Average	100	136	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4843.10	29.43	54.00	-24.57	28.05	3.32	33.09	35.03	Average	100	276	VERTICAL
2	4850.15	41.87	74.00	-32.13	40.49	3.32	33.09	35.03	Peak	100	276	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4869.99	41.97	74.00	-32.03	40.55	3.33	33.12	35.03	Peak	100	57	HORIZONTAL
2	4879.55	29.42	54.00	-24.58	27.96	3.33	33.16	35.03	Average	100	57	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4875.06	42.15	74.00	-31.85	40.69	3.33	33.16	35.03	Peak	100	185	VERTICAL
2	4883.55	29.24	54.00	-24.76	27.78	3.33	33.16	35.03	Average	100	185	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4904.00	29.46	54.00	-24.54	27.95	3.34	33.19	35.02	Average	100	205	HORIZONTAL
2	4906.02	41.72	74.00	-32.28	40.17	3.34	33.23	35.02	Peak	100	205	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4903.01	42.04	74.00	-31.96	40.53	3.34	33.19	35.02	Peak	100	303	VERTICAL
2	4903.87	29.48	54.00	-24.52	27.97	3.34	33.19	35.02	Average	100	303	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 149 / Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11490.10	39.88	54.00	-14.12	31.27	5.11	38.78	35.28	Average	100	87	HORIZONTAL
2	11490.46	53.19	74.00	-20.81	44.58	5.11	38.78	35.28	Peak	100	87	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.66	59.44	74.00	-14.56	50.83	5.11	38.78	35.28	Peak	102	325	VERTICAL
2	11489.79	45.84	54.00	-8.16	37.23	5.11	38.78	35.28	Average	102	325	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 157 / Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11567.76	52.50	74.00	-21.50	43.84	5.13	38.83	35.30	Peak	100	78	HORIZONTAL
2	11569.66	39.42	54.00	-14.58	30.76	5.13	38.83	35.30	Average	100	78	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.90	59.06	74.00	-14.94	50.39	5.14	38.83	35.30	Peak	102	328	VERTICAL
2	11570.02	46.00	54.00	-8.00	37.33	5.14	38.83	35.30	Average	102	328	VERTICAL



Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 20MHz CH 165 / Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11649.90	39.84	54.00	-14.16	31.12	5.16	38.86	35.30	Average	100	77	HORIZONTAL
2	11649.94	52.85	74.00	-21.15	44.13	5.16	38.86	35.30	Peak	100	77	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11647.55	58.71	74.00	-15.29	49.99	5.16	38.86	35.30	Peak	100	357	VERTICAL
2	11649.81	45.61	54.00	-8.39	36.89	5.16	38.86	35.30	Average	100	357	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 151 /Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.22	36.61	54.00	-17.39	27.98	5.12	38.79	35.28	Average	100	86	HORIZONTAL
2	11510.34	50.95	74.00	-23.05	42.32	5.12	38.79	35.28	Peak	100	86	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11509.89	42.37	54.00	-11.63	33.74	5.12	38.79	35.28	Average	101	325	VERTICAL
2	11510.05	59.49	74.00	-14.51	50.86	5.12	38.79	35.28	Peak	101	325	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 40MHz CH 159 / Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11589.84	51.79	74.00	-22.21	43.12	5.14	38.83	35.30	Peak	100	260	HORIZONTAL
2	11593.40	37.41	54.00	-16.59	28.74	5.14	38.83	35.30	Average	100	260	HORIZONTAL

#### Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11591.28	42.26	54.00	-11.74	33.59	5.14	38.83	35.30	Average	130	323	VERTICAL
2	11593.75	56.30	74.00	-17.70	47.63	5.14	38.83	35.30	Peak	130	323	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 80MHz CH 155 / Ant. 1 + Ant. 2
Test Date	Mar. 21, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5133.39	50.66	54.00	-3.34	48.62	3.43	33.64	35.03	Average	179	257	HORIZONTAL
2	5133.44	57.10	74.00	-16.90	55.06	3.43	33.64	35.03	Peak	179	257	HORIZONTAL
3	11547.23	50.10	74.00	-23.90	41.46	5.13	38.81	35.30	Peak	100	57	HORIZONTAL
4	11552.72	36.04	54.00	-17.96	27.39	5.13	38.82	35.30	Average	100	57	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5133.26	51.60	54.00	-2.40	49.56	3.43	33.64	35.03	Average	100	275	VERTICAL
2	5133.46	57.24	74.00	-16.76	55.20	3.43	33.64	35.03	Peak	100	275	VERTICAL
3	11549.50	40.21	54.00	-13.79	31.57	5.13	38.81	35.30	Average	100	321	VERTICAL
4	11554.46	54.01	74.00	-19.99	45.36	5.13	38.82	35.30	Peak	100	321	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 1 / Ant. 3
Test Date	Mar. 15, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.00	29.97	54.00	-24.03	28.63	3.31	33.06	35.03	Average	100	298	HORIZONTAL
2	4824.00	39.75	74.00	-34.25	38.41	3.31	33.06	35.03	Peak	100	298	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4824.00	30.09	54.00	-23.91	28.75	3.31	33.06	35.03	Average	100	134	VERTICAL
2	4824.00	40.92	74.00	-33.08	39.58	3.31	33.06	35.03	Peak	100	134	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 6 / Ant. 3
Test Date	Mar. 15, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.00	29.12	54.00	-24.88	27.66	3.33	33.16	35.03	Average	100	64	HORIZONTAL
2	4874.00	41.17	74.00	-32.83	39.71	3.33	33.16	35.03	Peak	100	64	HORIZONTAL
3	7311.00	32.30	54.00	-21.70	27.68	4.06	35.96	35.40	Average	100	145	HORIZONTAL
4	7311.00	42.30	74.00	-31.70	37.68	4.06	35.96	35.40	Peak	100	145	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4874.00	32.18	54.00	-21.82	30.72	3.33	33.16	35.03	Average	100	274	VERTICAL
2	4874.00	41.67	74.00	-32.33	40.21	3.33	33.16	35.03	Peak	100	274	VERTICAL
3	7311.00	32.81	54.00	-21.19	28.19	4.06	35.96	35.40	Average	100	201	VERTICAL
4	7311.00	43.42	74.00	-30.58	38.80	4.06	35.96	35.40	Peak	100	201	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 11 / Ant. 3
Test Date	Mar. 15, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4924.00	29.45	54.00	-24.55	27.85	3.35	33.26	35.01	Average	100	214	HORIZONTAL
2	4924.00	39.72	74.00	-34.28	38.12	3.35	33.26	35.01	Peak	100	214	HORIZONTAL
3	7385.30	32.43	54.00	-21.57	27.68	4.06	36.09	35.40	Average	100	112	HORIZONTAL
4	7385.30	43.69	74.00	-30.31	38.94	4.06	36.09	35.40	Peak	100	112	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.90	31.01	54.00	-22.99	29.41	3.35	33.26	35.01	Average	100	263	VERTICAL
2	4923.90	39.11	74.00	-34.89	37.51	3.35	33.26	35.01	Peak	100	263	VERTICAL
3	7385.30	33.79	54.00	-20.21	29.04	4.06	36.09	35.40	Average	100	173	VERTICAL
4	7385.30	44.19	74.00	-29.81	39.44	4.06	36.09	35.40	Peak	100	173	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 1 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4817.01	30.07	54.00	-23.93	28.78	3.31	33.02	35.04	Average	100	203	HORIZONTAL
2	4819.74	42.70	74.00	-31.30	41.36	3.31	33.06	35.03	Peak	100	203	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4816.98	30.16	54.00	-23.84	28.87	3.31	33.02	35.04	Average	100	327	VERTICAL
2	4817.65	43.63	74.00	-30.37	42.34	3.31	33.02	35.04	Peak	100	327	VERTICAL



Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 6 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4869.32	41.82	74.00	-32.18	40.40	3.33	33.12	35.03	Peak	100	151	HORIZONTAL
2	4881.66	29.53	54.00	-24.47	28.07	3.33	33.16	35.03	Average	100	151	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4876.34	29.69	54.00	-24.31	28.23	3.33	33.16	35.03	Average	100	234	VERTICAL
2	4880.67	42.05	74.00	-31.95	40.59	3.33	33.16	35.03	Peak	100	234	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 11 / Ant. 3 + Ant. 4
Test Date	Mar. 17, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4920.73	29.89	54.00	-24.11	28.32	3.35	33.23	35.01	Average	100	49	HORIZONTAL
2	4926.98	42.27	74.00	-31.73	40.67	3.35	33.26	35.01	Peak	100	49	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4918.01	29.80	54.00	-24.20	28.24	3.35	33.23	35.02	Average	100	146	VERTICAL
2	4928.65	42.55	74.00	-31.45	40.95	3.35	33.26	35.01	Peak	100	146	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 149 / Ant. 1 + Ant. 2
Test Date	May 08, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11490.91	53.54	54.00	-0.46	43.12	6.74	34.82	38.50	Average	251	102	HORIZONTAL
2 p	11491.67	69.92	74.00	-4.08	59.50	6.74	34.82	38.50	Peak	251	102	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11489.47	45.71	54.00	-8.29	35.29	6.74	34.82	38.50	Average	266	100	VERTICAL
2 p	11493.85	60.04	74.00	-13.96	49.62	6.74	34.82	38.50	Peak	266	100	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 157 / Ant. 1 + Ant. 2
Test Date	May 08, 2013		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11571.04	53.74	54.00	-0.26	43.32	6.77	34.85	38.50	Average	251	100	HORIZONTAL
2 p	11571.68	70.05	74.00	-3.95	59.63	6.77	34.85	38.50	Peak	251	100	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11569.04	44.88	54.00	-9.12	34.45	6.77	34.84	38.50	Average	258	104	VERTICAL
2 p	11569.60	60.23	74.00	-13.77	49.80	6.77	34.84	38.50	Peak	258	104	VERTICAL

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 165 / Ant. 1 + Ant. 2
Test Date	May 08, 2013		

#### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11651.04	53.66	54.00	-0.34	43.23	6.80	34.87	38.50	Average	249	103	HORIZONTAL
2 p	11651.79	68.88	74.00	-5.12	58.45	6.80	34.87	38.50	Peak	249	103	HORIZONTAL

#### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 a	11649.05	46.19	54.00	-7.81	35.76	6.80	34.87	38.50	Average	258	100	VERTICAL
2 p	11650.05	55.20	74.00	-18.80	44.77	6.80	34.87	38.50	Peak	258	100	VERTICAL

#### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

### 4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure

2. The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.

Only worst data of each operating mode is presented.

#### 4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

#### 4.6.5. Test Deviation

There is no deviation with the original standard.

#### 4.6.6. EUT Operation during Test

**For non-beamforming mode:**

The EUT was programmed to be in continuously transmitting mode.

**For beamforming mode:**

The EUT was programmed to be in beamforming transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 3 + Ant. 4
Test date	Mar. 13, 2013		

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.68	69.05	74.00	-4.95	38.67	2.21	28.17	0.00	Peak	100	349	HORIZONTAL
2	2389.84	53.80	54.00	-0.20	23.41	2.22	28.17	0.00	Average	100	349	HORIZONTAL
3	2409.60	102.90			72.47	2.22	28.21	0.00	Average	100	349	HORIZONTAL
4	2409.60	115.03			84.60	2.22	28.21	0.00	Peak	100	349	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.40	65.34	74.00	-8.66	34.96	2.21	28.17	0.00	Peak	122	342	HORIZONTAL
2	2390.00	51.48	54.00	-2.52	21.09	2.22	28.17	0.00	Average	122	342	HORIZONTAL
3	2434.12	119.28			88.76	2.23	28.29	0.00	Peak	122	342	HORIZONTAL
4	2434.44	108.40			77.88	2.23	28.29	0.00	Average	122	342	HORIZONTAL
5	2483.50	51.54	54.00	-2.46	20.90	2.26	28.38	0.00	Average	122	342	HORIZONTAL
6	2485.42	67.28	74.00	-6.72	36.60	2.26	28.42	0.00	Peak	122	342	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2459.60	103.84			73.27	2.24	28.33	0.00	Average	121	347	HORIZONTAL
2	2467.13	115.25			84.66	2.26	28.33	0.00	Peak	121	347	HORIZONTAL
3	2484.14	53.44	54.00	-0.56	22.80	2.26	28.38	0.00	Average	121	347	HORIZONTAL
4	2484.14	71.93	74.00	-2.07	41.29	2.26	28.38	0.00	Peak	121	347	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.



Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 3 + Ant. 4
Test date	Mar. 13, 2013		

**Channel 3**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.72	65.69	74.00	-8.31	35.31	2.21	28.17	0.00	Peak	118	342	HORIZONTAL
2	2389.36	52.96	54.00	-1.04	22.58	2.21	28.17	0.00	Average	118	342	HORIZONTAL
3	2417.19	109.06			78.58	2.23	28.25	0.00	Peak	118	342	HORIZONTAL
4	2427.13	97.32			66.84	2.23	28.25	0.00	Average	118	342	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	50.83	54.00	-3.17	20.44	2.22	28.17	0.00	Average	103	281	VERTICAL
2	2390.00	66.01	74.00	-7.99	35.62	2.22	28.17	0.00	Peak	103	281	VERTICAL
3	2432.19	99.91			69.43	2.23	28.25	0.00	Average	103	281	VERTICAL
4	2432.83	112.47			81.99	2.23	28.25	0.00	Peak	103	281	VERTICAL
5	2485.42	53.67	54.00	-0.33	23.00	2.26	28.41	0.00	Average	103	281	VERTICAL
6	2486.06	68.93	74.00	-5.07	38.26	2.26	28.41	0.00	Peak	103	281	VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

**Channel 9**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2446.87	97.55			67.02	2.24	28.29	0.00	Average	119	344	HORIZONTAL
2	2457.13	109.48			78.91	2.24	28.33	0.00	Peak	119	344	HORIZONTAL
3	2484.14	53.13	54.00	-0.87	22.49	2.26	28.38	0.00	Average	119	344	HORIZONTAL
4	2484.78	65.58	74.00	-8.42	34.94	2.26	28.38	0.00	Peak	119	344	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 3 + Ant. 4
Test Date	Mar. 15, 2013		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.08	64.11	74.00	-9.89	33.73	2.21	28.17	0.00	Peak	105	73	VERTICAL
2	2390.00	51.85	54.00	-2.15	21.46	2.22	28.17	0.00	Average	105	73	VERTICAL
3	2411.04	108.66			78.23	2.22	28.21	0.00	Average	105	73	VERTICAL
4	2411.04	112.40			81.97	2.22	28.21	0.00	Peak	105	73	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2383.27	61.44	74.00	-12.56	31.06	2.21	28.17	0.00	Peak	101	284	HORIZONTAL
2	2390.00	48.42	54.00	-5.58	18.03	2.22	28.17	0.00	Average	101	284	HORIZONTAL
3	2436.04	111.94			81.42	2.23	28.29	0.00	Peak	101	284	HORIZONTAL
4	2436.52	108.03			77.51	2.23	28.29	0.00	Average	101	284	HORIZONTAL
5	2483.50	46.02	54.00	-7.98	15.38	2.26	28.38	0.00	Average	101	284	HORIZONTAL
6	2483.50	57.18	74.00	-16.82	26.54	2.26	28.38	0.00	Peak	101	284	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.20	107.91			77.34	2.24	28.33	0.00	Average	100	76	HORIZONTAL
2	2462.96	111.78			81.21	2.24	28.33	0.00	Peak	100	76	HORIZONTAL
3	2483.50	49.53	54.00	-4.47	18.89	2.26	28.38	0.00	Average	100	76	HORIZONTAL
4	2483.50	61.25	74.00	-12.75	30.61	2.26	28.38	0.00	Peak	100	76	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	60%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 3 + Ant. 4
Test Date	Mar. 13, 2013		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2388.72	71.17	74.00	-2.83	40.79	2.21	28.17	0.00	Peak	123	347	HORIZONTAL
2	2390.00	53.53	54.00	-0.47	23.14	2.22	28.17	0.00	Average	123	347	HORIZONTAL
3	2407.51	104.99			74.56	2.22	28.21	0.00	Average	123	347	HORIZONTAL
4	2407.83	115.78			85.35	2.22	28.21	0.00	Peak	123	347	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2386.80	65.95	74.00	-8.05	35.57	2.21	28.17	0.00	Peak	121	342	HORIZONTAL
2	2390.00	51.50	54.00	-2.50	21.11	2.22	28.17	0.00	Average	121	342	HORIZONTAL
3	2431.87	109.12			78.64	2.23	28.25	0.00	Average	121	342	HORIZONTAL
4	2432.51	120.24			89.76	2.23	28.25	0.00	Peak	121	342	HORIZONTAL
5	2483.50	51.73	54.00	-2.27	21.09	2.26	28.38	0.00	Average	121	342	HORIZONTAL
6	2483.50	66.11	74.00	-7.89	35.47	2.26	28.38	0.00	Peak	121	342	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2467.45	101.91			71.32	2.26	28.33	0.00	Average	117	28	HORIZONTAL
2	2467.45	113.55			82.96	2.26	28.33	0.00	Peak	117	28	HORIZONTAL
3	2483.50	53.06	54.00	-0.94	22.42	2.26	28.38	0.00	Average	117	28	HORIZONTAL
4	2483.50	73.61	74.00	-0.39	42.97	2.26	28.38	0.00	Peak	117	28	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.






Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:48:52

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 28.MAR.2013 16:51:36

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 28.MAR.2013 16:52:24

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)



Date: 28.MAR.2013 16:52:51


Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 28.MAR.2013 16:53:54




Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:53:30

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / Reference Level




Date: 28.MAR.2013 17:34:33

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 28.MAR.2013 17:35:55

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 28.MAR.2013 17:36:30

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 28.MAR.2013 17:38:03

Plot on Configuration IEEE 802.11ac MCS0/Nss1 20MHz / CH 165 / 5850MHz~4000MHz (down 30dBc)




Date: 28.MAR.2013 17:37:24

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / Reference Level




Date: 28.MAR.2013 17:27:57

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 28.MAR.2013 17:31:21

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 28.MAR.2013 17:32:16

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 28.MAR.2013 17:29:46

Plot on Configuration IEEE 802.11ac MCS0/Nss1 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 28.MAR.2013 17:28:39

Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / Reference Level



Date: 28.MAR.2013 17:04:29


Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / CH 155 / 30MHz~5725MHz (down 30dBc)



Date: 28.MAR.2013 17:05:03




Plot on Configuration IEEE 802.11ac MCS0/Nss1 80MHz / CH 155 / 5850MHz~40000MHz (down 30dBc)



Date: 28.MAR.2013 17:06:47




Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:44:14

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 28.MAR.2013 16:45:30

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:44:14

Plot on Configuration IEEE 802.11g / Reference Level




Date: 28.MAR.2013 16:37:30

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 28.MAR.2013 16:38:12

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:41:22

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 28.MAR.2013 16:40:12

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 28.MAR.2013 16:39:08

Plot on Configuration IEEE 802.11a / Reference Level



Date: 28.MAR.2013 17:39:26


Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)



Date: 28.MAR.2013 17:40:08




Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 28.MAR.2013 17:40:39

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)



Date: 28.MAR.2013 17:42:02

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)



Date: 28.MAR.2013 17:41:34

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Apr. 15, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“\*” Calibration Interval of instruments listed above is two years.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085