



RF EXPOSURE REPORT

REPORT NO.: SA120607C19
MODEL NO.: BSHSBE20
FCC ID: FDIBSHSBE20-0
RECEIVED: Jun. 07, 2012
TESTED: Jul. 11 ~ Aug. 07, 2012
ISSUED: Aug. 20, 2012

APPLICANT: BUFFALO INC.

ADDRESS: AKAMONDORI Bldg., 30-20, Ohsu 3-chome,
Naka-ku, Nagoya 460-8315, Japan

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. REDUCED CONDITION FOR SAR	5
3. MAXIMUM MEASURED POWER OF EUT	5
4. CONCLUSION	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA120607C19	Original release	Aug. 20, 2012

2. REDUCED CONDITION FOR SAR

When output power is $\leq 60/f(\text{GHz})$ mW, SAR evaluation is not required.

3. MAXIMUM MEASURED POWER OF EUT

Maximum measured transmitter power:

Bluetooth EDR

	Pout (dBm)	Pout (mW)
Bluetooth		
Conducted Power	4.33	2.71
EIRP Power	4.33	2.71

***Note:** The antenna type is Chip antenna with 0dBi gain.

Bluetooth LE 4.0

	Pout (dBm)	Pout (mW)
Bluetooth		
Conducted Power	4.82	3.03
EIRP Power	4.82	3.03

***Note:** The antenna type is Chip antenna with 0dBi gain.

4. CONCLUSION

No SAR evaluation is required since output power of EUT is less than threshold of SAR.