CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA Phone: +1 408 586 6200 Fax: +1 408 586 6299

www.cetecom.com



Issued test report consists of 59 Pages

FCC LISTED, REG. NO.: 101450 &
RECOGNIZED BY INDUSTRY CANADA
IC – 3925

Test report no.:155 FCC/2001 FCC Part 15.247 PCMCIA Card - LW1100N

(FCC ID: FFMLW1100N)



Table of Contents

- 1 General information
- 1.1 Notes
- 1.2 Testing laboratory
- 1.3 Details of applicant
- 1.4 Application details
- 1.5 Test item
- 1.6 Test standards
- 2 Technical test
- 2.1 Summary of test results
- 2.2 Test report
- 1 General information
- 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc. USA.

TEST REPORT PREPARED BY:

EMC & Radio Engineer: Harpreet Sidhu



1.2 Testing laboratory

CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.com

Internet: www.cetecom.com

1.3 Details of applicant

Name : LG Electronics Inc.

Street: 60-39 Kasan-dong, Kumchon-gu

City : Seoul 153-023

Country : Korea

Telephone : +82 2 3289 3117 Telefax : +82 2 3289 3200 Contact : Mr. William KS. Oh

e-mail : ksoh@lge.com

1.4 Application details

Date of receipt of application : 2001-05-15

Date of receipt of test item: 2001-05-21

Date of test : 2001-05-22/23/29

1.5 Test item

Manufacturer : LG Electronics Inc.

Address : See above Name of EUT : PCMCIA Card

Descriptin : PCMCIA Card for laptop computer

Model No. : LW1100N FCC ID : FFMLW1100N

Additional informations:

Frequency : 2412 – 2483.5 MHz

Type of modulation : DSSS

Number of channels : 11 Channels in US

Antenna : Internal Power supply : +3VDC

Temperature range : $-10^{\circ}\text{C} - +50^{\circ}\text{C}$



1.6 Test standards FCC Part 15 §15.247

The tests were done following the public notice DA 00-705 released March 30, 2000



2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

Technical responsibility for area of testing:

	Radio	Schmidt	ldun: de
Date	Section	Name	Signature



2.2 Testreport

TEST REPORT

Testreport no.: 155 FCC/2001 PCMCIA Card - LW1100N FCC ID: FFMLW1100N



TEST REPORT REFERENCE

LIST OF MEASUREMENTS

Paragraph	PARAMETER TO BE MEASURED PARAMETER TO BE MEASURED	AGE	
	Transmitter parameters		
§ 15.247 (a)(2)	Spectrum Bandwith of a DSSS System	7	
§ 15.247 (b)(1)	Maximum peak output power	11	
§ 15.247 (c)(1)	Emission limitations	16	
§ 15.247 (d)	Power Spectral Density	35	
§ 15.247 (e)	Processing Gain of DSSS System	39	
§ 15.107	Conducted emissions		42
	Receiver parameters		
§ 15.209	Receiver Spurious Radiation	44	
	Test equipment listing	52	
	Test Site		53
	Photographs of the equipment	56	

ANNEX: Details about processing gain.



SPECTRUM BANDWITH OF DSSS-SYSTEM

SUBCLAUSE § 15.247 (a)(2)

TEST CONDITIONS		6 dB BANDWIDTH (kHz)				
Frequency (MHz)		2412	2412 2437			
T _{nom} (23)°C	$V_{nom}(3.0)V$	11072	11422	11322		
Measurement uncertainty			±3dB	1		

LIMIT

SUBCLAUSE §15.247(a) (2)


The minimum 6dB bandwith shall shall be at least 500 KHz



SPECTRUM BANDWITH OF DSSS-SYSTEM

SUBCLAUSE § 15.247 (a)(2)

Lowest Channel: 2412 MHz



LIMIT

SUBCLAUSE §15.247(a) (2)

The minimum 6dB bandwith shall shall be at least 500 KHz, here 10.02 MHz




ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz



SPECTRUM BANDWITH OF DSSS-SYSTEM

SUBCLAUSE § 15.247 (a)(2)

Mid Channel: 2437 MHz



LIMIT

SUBCLAUSE §15.247(a) (2)

The minimum 6dB bandwith shall shall be at least 500 KHz, here 11.42 MHz




ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz



SPECTRUM BANDWITH OF DSSS-SYSTEM

SUBCLAUSE § 15.247 (a)(2)

Highest Channel: 2462 MHz



LIMIT

SUBCLAUSE §15.247(a) (2)

The minimum 6dB bandwith shall shall be at least 500 KHz, here 10.02 MHz



ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz



MAXIMUM PEAK OUTPUT POWER (CONDUCTED)

SUBCLAUSE § 15.247 (b) (1)

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)					
Frequency (MHz)		2412		2437		2462	
T _{nom} (23)°C	$V_{nom}(3.0)V$	Pk	13.03	Pk	12.40	Pk	12.20
		Av	7.84	Av	7.29	Av	7.13
Measurement uncertainty				•	±3dB	•	

LIMIT

SUBCLAUSE § 15.247 (b) (1)

F	RF power output	
2400-2483.5	5 MHz / 5725 – 5850 MHz	1.0 Watt



MAXIMUM PEAK OUTPUT POWER (EIRP) (RADIATED)

SUBCLAUSE § 15.247 (b) (1)


TEST CONDITIONS		M	MAXIMUM PEAK OUTPUT POWER (dBm)					
Frequency (MHz)		2412		2437		2462		
T _{nom} (23)°C	V _{nom} (3.0)V	Pk	20.07	Pk	18.72	Pk	19.18	
		Av	14.88	Av	13.61	Av	13.99	
Measurement uncertainty				1	±3dB	1		

LIMIT SUBCLAUSE § 15.247 (b) (1)

Frequency range	RF power output		
2400-2483.5 MHz / 5725 – 5850 MHz	1.0 Watt		




EIRP - Lowest Channel: 2412 MHz






EIRP - Mid Channel: 2437 MHz





EIRP – Highest Channel: 2462 MHz






EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

conducted

2412 MHz up to 25 GHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz


NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.



EMISSION LIMITATIONS (Transmitter) conducted

SUBCLAUSE § 15.247 (c) (1)

2437 MHz up to 25 GHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz

NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact



frequency of the carrier, refer to plots under EIRP.




EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

conducted

2462 MHz up to 25 GHz



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in \$15.209(a) (see \$15.205(c)).

ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz

NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact




frequency of the carrier, refer to plots under EIRP.



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Conducted

30 MHz up to 25 GHz (This plot is valid for all three channels)



LIMITS

SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS: RBW=100KHz, VBW=1MHz

NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.




EMISSION LIMITATIONS (Transmitter)

SUBCLAUSE § 15.247 (c) (2)

conducted

spurious in the restricted band 2483.5 – 2500 MHz (Higher Band Edge)




Date: 31.MAY.01 2D:46:19





Lower Band Edge

conducted



Date: 31.MAY.01 20:51:43






EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

The spurious emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 26 GHz very short cable connections to the antenna was used to minimize the noise level. Channel 1: 2412 MHz; Channel 2: 2437 MHz; Channel 3: 2462 MHz.

All emission measurements were done in Peak mode to reduce measurement time. In case limits are exceeded the measurements will be repeated and documented in the test report either with Quasi Peak ar average detector depending on the frequency range specified in FCC 15 and/or DA00-705. Bandwidth, sweeptime etc. were set according DA00-705 and recorded

Lowest Channel(2412MHz): 30MHz-1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no. 34



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2412MHz): 1GHz-8GHz



NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.

LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2412MHz): 8GHz -18GHz



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2412MHz): 18GHz -26GHz



LIMITS

SUBCLAUSE § 15.247 (c)


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in \$15.209(a) (see \$15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2437MHz): 30MHz -1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no. 34



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in \$15.209(a) (see \$15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2437MHz): 1GHz -8GHz



NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.

LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2437MHz): 8GHz -18GHz



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2437MHz): 18GHz -26GHz



LIMITS

SUBCLAUSE § 15.247 (c)


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2462MHz): 30MHz -1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no. 34



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in \$15.209(a) (see \$15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2462MHz): 1GHz -8GHz



NOTE: The marked peak is the carrier frequency. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.

LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2462MHz): 8GHz -18GHz



LIMITS

SUBCLAUSE § 15.247 (c)


In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

ANALYZER SETTINGS: f < 1 GHz: RBW/VBW: 100 kHz $f^3 1 \text{GHz}$: RBW/VBW: 1 MHz



EMISSION LIMITATIONS (Transmitter) SUBCLAUSE § 15.247 (c) (1)

Highest Channel(2462MHz): 18GHz -26GHz



LIMITS


SUBCLAUSE § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in \$15.205(a), must also comply with the radiated emission limits specified in \$15.209(a) (see \$15.205(c)).

ANALYZER SETTINGS: f < 1 GHz: RBW/VBW: 100 kHz $f^3 1 \text{GHz}$: RBW/VBW: 1 MHz



Emissions from Laptop: 30MHz - 1GHz





POWER SPECTRAL DENSITY

SUBCLAUSE § 15.247 (d)

TEST CONDITIONS		RF POWER LEVEL IN 3 kHz BW		
Frequency (MHz)		2412	2437	2462
T _{nom} (23)°C	$V_{nom}(3.0)V$	-10.14 dBm	-10.70dBm	-10.92 dBm
Measurement uncertainty			±3dB	

LIMIT

SUBCLAUSE §15.247(d)

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band


ANALYZER SETTINGS: RBW=3KHz, VBW=3KHz



POWER SPECTRAL DENSITY

SUBCLAUSE § 15.247 (d)

Lowest Channel: 2412 MHz



LIMIT

SUBCLAUSE §15.247(d)




The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band



POWER SPECTRAL DENSITY

SUBCLAUSE § 15.247 (d)

Mid Channel: 2437 MHz



LIMIT

SUBCLAUSE §15.247(d)


The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band



POWER SPECTRAL DENSITY

SUBCLAUSE § 15.247 (d)

Highest Channel: 2462 MHz



LIMIT

SUBCLAUSE §15.247(d)

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band



PROCESSING GAIN OF DSSS SYSTEMS SUBCLAUSE §15.247 (e)

(NOTE:The processing gain data is provided by Chip Set Manufacturer)





1				•	




CONDUCTED EMISSIONS

§ 15.107/207

Measured with AC/DC power adapter plugged in LISN

Phase: Line



Date: 19.JUN.01 21:20:16

Technical specification : 15.107 / 15.207 (Revised as of October 1, 1991) Limit




0.45 to 30 MHz	250 μV / 47.96 dBμV

-



Phase: Neutral



Technical specification : 15.107 / 15.207 (Revised as of October 1, 1991) Limit

0.45 to 30 MHz	250 µV / 47.96 dBµV
0.43 to 30 MHZ	230 μ V / 47.90 αδμ V
0.10 00 00 1.2122	200 61 7 171 9 622 61 7

-






RECEIVER SPURIOUS RADIATION

§ 15.209

Lowest Channel(2412MHz): 30MHz – 1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)




RECEIVER SPURIOUS RADIATION

§ 15.209

Lowest Channel(2412MHz): 1GHz - 8GHz

NOTE: The peak above the limit is the carrier frequency.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)




RECEIVER SPURIOUS RADIATION

§ 15.209

Mid Channel(2437MHz): 30MHz – 1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)




RECEIVER SPURIOUS RADIATION

§ 15.209

Mid Channel(2437MHz): 1GHz – 8GHz

NOTE: The peak above the limit is the carrier frequency.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)




RECEIVER SPURIOUS RADIATION

§ 15.209

Highest Channel(2462MHz): 30MHz – 1GHz

NOTE: The peaks closer to limit are coming from laptop, for confirmation see page no.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3


(NOTE: All measurements were done in peak mode)



RECEIVER SPURIOUS RADIATION

§ 15.209

Highest Channel(2462MHz): 1GHz – 8GHz NOTE: The peak above the limit is the carrier frequency.



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

(NOTE: All measurements were done in peak mode)




RECEIVER SPURIOUS RADIATION

§ 15.209

8GHz – 18GHz

(NOTE: This plot is applicable for all three channels)



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)	
0.009 - 0.490	2400/F(kHz)	300	
0.490 - 1.705	24000/F(kHz)	30	
1.705 - 30.0	30	30	
30 - 88	100	3	
88 - 216	150	3	
216 - 960	200	3	
above 960	500	3	

(NOTE: All measurements were done in peak mode)






RECEIVER SPURIOUS RADIATION

§ 15.209

18GHz - 26GHz

(NOTE: This plot is applicable for all three channels)



Limits

SUBCLAUSE § 15.209

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)	
0.009 - 0.490	2400/F(kHz)	300	
0.490 - 1.705	24000/F(kHz)	30	
1.705 - 30.0	30	30	
30 - 88	100	3	
88 - 216	150	3	
216 - 960	200	3	
above 960	500	3	

(NOTE: All measurements were done in peak mode)





TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
02	Signal Generator	SMY0	Rohde & Schwarz	836878/011
03	Power-Meter	NRVD	Rohde & Schwarz	0857.8008.02
04	Power Amlifier	250W1000	Amplifier Research	300031
05	Biconilog Antenna	3141	EMCO	0005-1186
06	Horn Antenna	SAS-200/571	AH Systems	325
07	Power Splitter	11667B	Hewlett Packard	645348
08	Climatic Chamber	VT4004	Votch	G1115
09	Pre-Amplifier	JS4-00102600	Miteq	00616
10	Power Sensor	URV5-Z2	Rohde & Schwarz	DE30807
11	Power Sensor	URV5-Z2	Rohde & Schwarz	DE30808



TEST SITE Radiated Emissions






Test set up for radiated emissions:





Conducted Emissions







PHOTOGRAPHS OF THE EQUIPMENT

Photograph No.1: PCMCIA Card with shielding





Photograph No.2: PCMCIA Card with RF connector & shielding





Photograph No.3: PCMCIA Card (Top view)





Photograph No.4: PCMCIA Card (Bottom view)

