

EMC TEST REPORT

No. 2010264STO-101

Electromagnetic disturbances

EQUIPMENT UNDER TEST

Equipment: Decoration lamp with LED
Type/Model: J1829 Stråla
Manufacturer: IKEA of Sweden AB
Tested by request of: IKEA of Sweden AB

SUMMARY

Referring to the emission limits, and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards:

FCC 47 CFR Part 15: Radio frequency device, Subpart B: Unintentional radiators. Class B equipment.

ICES-005 Issue 4: Lighting Equipment, Class B.
ICES-005 Issue 5: Lighting Equipment, Class B.

For details, see clause 2 – 4.

Date of issue: February 4, 2020

Tested by:



Anna Näslund

Approved by:



Per Granberg

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No	Date	Description	Changes
1817142STO-001, Ed. 1	2018-12-13	First release	
1817142STO-001, Ed. 2	2019-08-23	Second release	<p>The report was updated according to order number 1914417.</p> <p>Standard issue ICES-005 Issue 5 is added as there are no differences compared to ICES-005 Issue 4 that affect the tests performed.</p> <p>Clause 2.4 Opinions and interpretations added.</p>
2010264STO-101	2020-02-04	Third release	<p>Pictures of EUT moved to Annex 2010264STO-102</p>

CONTENTS

	Page
1. Client Information	4
2. Equipment under test (EUT).....	4
2.1 Identification of the EUT	4
2.2 Test set up and EUT photos	4
2.3 Additional information about the EUT	5
2.4 Opinions and interpretations	5
3. Test Specifications	6
3.1 Standards	6
3.2 Additions, deviations and exclusions from standards and accreditation	6
3.3 Test site	6
3.4 Mode of operation during the test	6
3.5 Compliance	7
4. Test Summary	8
5. Conducted continuous disturbances	9
5.1 Operating environment.....	9
5.2 Test setup and test procedure	9
5.3 Measurement uncertainty.....	9
5.4 Test results, AC Power input port, Class B.....	10
5.5 Test equipment	11
6. Radiated rf Emission in the frequency-range 30 MHz – 1 GHz	12
6.1 Operating environment.....	12
6.2 Test setup and test procedure	12
6.3 Test conditions	12
6.4 Measurement uncertainty.....	12
6.5 Test results, 30 – 1000 MHz, FCC, Class B	13
6.6 Test equipment	14

1. CLIENT INFORMATION

The EUT has been tested by request of

Company	IKEA of Sweden AB Box 702 343 81 Älmhult SVERIGE
---------	---

Name of contact	Jianqiu Chen
-----------------	--------------

2. EQUIPMENT UNDER TEST (EUT)

2.1 Identification of the EUT

Equipment	Decoration lamp with LED
Type/Model	J1829 Stråla
Brand name	IKEA
Serial Number	-
Manufacturer	IKEA of Sweden AB
Rating	4 V DC, 2.2 W
Class	III
Highest clock frequency	-
Software version	-



Conforms to:
UL Std 588
Certified to:
CSA Std C22.2 No. 37 CAN
ICES-005 (B) / NMB-005 (B)

Type No. J1829
Stråla
Made in



TYP J1829 NA Version 1

Rating plate

2.2 Test set up and EUT photos

Test set up and EUT photos are enclosed in Annex 1 to this test report.

2.3 Additional information about the EUT

The EUT was tested in a tabletop standing configuration.

2.4 Opinions and interpretations

The change of standard from ICES-005 Issue 4 to ICES-005 Issue 5 does not affect the measurements performed in this report. The tests performed according to ICES-005 Issue 4 fulfils the requirements of ICES-005 Issue 5.

3. TEST SPECIFICATIONS

3.1 Standards

Requirements:

FCC 47 CFR Part 15: Radio frequency device, Subpart B: Unintentional radiators.

ICES-005 Issue 4: Lighting Equipment.

ICES-005 Issue 5: Lighting Equipment.

Test methods:

ANSI C63.4: 2014: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Additions, deviations and exclusions from standards and accreditation

No additions, deviations or exclusions have been made from standards and accreditation.

3.3 Test site

Measurements were performed at:

Intertek Semko AB.
Torshamnsgatan 43,
P.O. Box 1103
SE-164 22 Kista

Intertek Semko AB is a FCC listed test site with site registration number 90913

Intertek Semko AB is a FCC accredited conformity assessment body with designation number SE0002

Intertek Semko AB is an Industry Canada listed test facility with IC assigned code 2042G

Measurement chambers

Measurement Chamber	Type of chamber	IC Site filing #
BJÖRKHALLEN	Semi-anechoic 3 m	2042G-1

3.4 Mode of operation during the test

The EUT was tested with 120 V, 60 Hz.

The EUT was tested with light on.

3.5 Compliance

The EUT shall comply with the emission limits according to the standards as listed below

Conducted emission requirements:

The EUT shall meet the limits for the standards.

Reference: 47 CFR §15.107
ICES-005, section 4.5.1

Limits for conducted emission according to FCC and ICES-005

Class B

Frequency range [MHz]	Limits [dBµV]	
	Quasi-Peak	Average
0.15 – 0.50	66 – 56	56 – 46
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Radiated Emission requirements:

The EUT shall meet the limits for the standards.

Reference: 47 CFR §15.109
ICES-005, section 4.5.2

Limits for radiated emission according to FCC and ICES-005

Class B

Frequency range [MHz]	Field strength at 3 m (dBµV/m)	Field strength at 10 m (dBµV/m)	Detector
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.0	Quasi Peak
216 – 960	46.0	35.5	Quasi Peak
960 – 1000	54.0	43.5	Quasi Peak
Above 1000	54.0 / 74.0	43.5 / 63.5	Average / Peak

The values for 10 m measuring distance are calculated by subtracting 10.5 dB from the 3 m limit. (i.e. an extrapolation factor of 20 dB/decade according to §15.31(f)(1))

4. TEST SUMMARY

The results in this report apply only to sample tested:

Standard	Description	Result
	Emission	
FCC Part 15 subpart B ICES-005	Conducted continuous emission in the frequency range 0.150 – 30 MHz, AC Power input port The EUT complies with the Class B limits. The margin to the limit was at least 12.0 dB at 0.154 MHz See clause 5.4.	PASS
FCC Part 15 subpart B ICES-005	Radiated emission of electromagnetic fields in the frequency range 30 – 1000 MHz The EUT complies with the Class B limits. The margin to the limit was at least 11.9 dB at 927.414 MHz See clause 6.5.	PASS

**5. CONDUCTED CONTINUOUS DISTURBANCES
in the frequency-range 0.15 – 30 MHz**

5.1 Operating environment

Date of test:	Temperature:	Relative Humidity:
2018-10-22	22 [°C]	27 [%]

5.2 Test setup and test procedure

The test method is in accordance with ANSI C63.4.

The EUT was connected to the power via Artificial Mains Networks AMN.

EUT was placed on reference ground plane (RGP) 0.8 m from the AMN/ISN.

Overview sweeps were performed for each lead.

During the tests the EUT was operated according to the mode of operation mentioned in clause 3


5.3 Measurement uncertainty

Continuous conducted disturbances with AMN
in the frequency range 150 kHz to 30 MHz

± 3.3 dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2:2011.
The measurement uncertainty is given with a confidence of 95 %.

5.4 Test results, AC Power input port, Class B



Diagram, Peak and Average overview sweep

Measurement results, Quasi-peak, Class B

Frequency [MHz]	Result [dBµV]	Limit [dBµV]	Line L/N	Margin [dB]
0.336	37.4	59.3	N	21.9
0.560	34.6	56.0	L	21.4
0.764	32.8	56.0	L	23.2
25.304	38.6	60.0	N	21.4
25.476	38.4	60.0	L	21.6

Measurement results, Average, Class B

Frequency [MHz]	Result [dBµV]	Limit [dBµV]	Line L/N	Margin [dB]
0.154	43.8	55.8	N	12.0
0.288	27.2	50.6	N	23.4
1.352	20.3	46.0	L	25.7
25.129	30.6	50.0	L	19.4
25.272	30.7	50.0	L	19.3
25.448	30.3	50.0	N	19.7

Result [dBµV] = Analyser reading [dBµV] + cable loss [dB] + LISN insertion loss [dB]

5.5 Test equipment

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 -9	--	--	--
Receiver	Rohde & Schwarz	ESCI	12804	2018-07-04	1 year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	32455	2018-07-04	1 year
AMN	Rohde & Schwarz	ESH3-Z5	2728	2018-07-09	1 year
Coaxial cable	Suhner	RG 58	9728	2018-01-18	1 year
Coaxial cable	Suhner	G03232 D-01	9701	2018-08-01	1 year

6. RADIATED RF EMISSION IN THE FREQUENCY-RANGE 30 MHZ – 1 GHZ

6.1 Operating environment

Date of test:	Temperature:	Relative Humidity:
2018-12-07	23 [°C]	31 [%]

6.2 Test setup and test procedure

The test method is in accordance with ANSI C63.4.

The EUT was set up in order to emit maximum disturbances.

The EUT was placed on an insulating support 0.8 m above the turntable which is part of the reference ground plane.

Overview sweeps were performed with the measurement receiver in max-hold mode and the peak detector activated in the frequency-range 30 – 1000 MHz

6.3 Test conditions

Test set-up:	30 – 1000 MHz		
Test receiver set-up:			
Preview test:	Peak,	RBW 120 kHz	VBW 1 MHz
Final test:	Quasi-Peak,	RBW 120 kHz	
Measuring distance:	3 m		
Measuring angle:	0 – 359°		
Antenna			
Height above ground plane:	1 – 4 m		
Polarisation:	Vertical and Horizontal		
Type:	Bilog		

6.4 Measurement uncertainty

Measurement uncertainty for radiated disturbance


 Uncertainty for the frequency range 30 to 1000 MHz at 3 m ± 5.1 dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2: 2011.

The measurement uncertainty is given with a confidence of 95 %.

6.5 Test results, 30 – 1000 MHz, FCC, Class B

Full Spectrum



Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance.

Measurement results, Quasi Peak, Class B

Frequency [MHz]	Result [dBµV/m]	Limit [dBµV/m]	Polarization H/V	Margin [dB]
30.140	27.5	40.0	V	12.5
50.940	17.8	40.0	V	22.2
76.451	21.6	40.0	V	18.4
121.604	19.9	43.5	V	23.6
695.030	30.1	46.0	H	15.9
927.414	34.1	46.0	H	11.9

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

6.6 Test equipment

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - 9	--	--	--
Measurement Receiver	Rohde & Schwarz	ESIB26	32288	2018-07-04	1 year
Antenna	Rohde & Schwarz	HL562	30711	2018-01-25	3 year
Transformer	Tufvassons	AFM1500	30317	--	--
Measurement cable	Radiall	SHF8M	9975	2018-08-03	1 year
Measurement cable	Rosenberger	UFB311A	39055	2018-05-02	1 year