

J2301 Solvinden

FCC ID: FHO-J2301



120V~, 60Hz, 1.4W
Conforms to: UL Std 153 Certified to: CSA Std C22.2 No. 250.4
CAN ICES-005 (B) / NMB-005 (B)

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Type No. J2301

Solvinden

Made in China

CAUTION: RISK OF ELECTRIC SHOCK, Do not use with extension cord near water or where water may accumulate. Keep lamp at least 16 feet from pools and spas. Keep plugs and receptacles dry.

For use only on GFCI protected circuits

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
DO NOT SUBMERSE
NE PAS IMMERGER


Sup. No.00000







LED driver

CLASS 2 POWER SUPPLY

MODEL: ICPSW24-3.6-IL-1
IKEA of Sweden AB SE-343 81 Älmhult
INPUT: 100-240V~ 50/60Hz Max. 0.05A
OUTPUT: 24.0V \equiv Max.0.15A 3.6W

3445 
Design and Quality
IKEA of Sweden



Intertek
3167844
MADE IN CHINA

FCC ID: FHO-ICPSW24-36-1
CONFORMS TO UL STD.1310
CERTIFIED TO CSA STD. C22.2 NO.223
CAN ICES-005(B)/NMB-005(B)

YYWW



Do not remove this tag

Rainproof

See instruction manual for use in countries other than the U.S.A

WARNING: RISK OF ELECTRIC SHOCK. Install only to a covered Class A GFCI receptacle that has an enclosure that is weatherproof with the attachment plug cap inserted or removed.

AVERTISSEMENT: RISQUE DE CHOC ÉLECTRIQUE. Installez uniquement sur un réceptacle couvert GFCI de classe A qui possède une ouverture étanche et un bouchon de fiche de branchement inséré ou enlevé.

40 mm

120 mm

Label artwork



Label location for J2301 Solvinden