


<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	<b>CN23IUy8 001</b>	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	<b>244555493</b>	<b>Seite 1 von 28</b> <i>Page 1 of 28</i>
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	<b>1288983</b>	<b>Auftragsdatum:</b> <i>Order date:</i>	<b>2023-11-01</b>	
<b>Auftraggeber:</b> <i>Client:</i>	<b>IKEA of Sweden AB</b> Box 702, SE-343 81 Älmhult, Sweden			
<b>Prüfgegenstand:</b> <i>Test item:</i>	<b>Light Chain</b>			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	<b>J2324</b>			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	<b>TÜV Rheinland EMC service</b>			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	<b>FCC 47 CFR Part 15, Subpart B:2021 Class B</b> <b>ICES-005:2018</b>			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	<b>2023-12-19</b>	Refer to the EUT photos file		
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	<b>A003627301-001</b>			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	<b>Refer to test report</b>			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	<b>Refer to clause 1.1</b>			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	<b>TÜV Rheinland (Suzhou) Co., Ltd.</b>			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	<b>Pass</b>			
<b>geprüft von:</b> <i>tested by:</i>	<b>genehmigt von:</b> <i>authorized by:</i>			
<b>Datum:</b> <i>Date:</i>	<b>Ausstellungsdatum:</b> <i>Issue date:</i>			
<b>Stellung / Position:</b>	<b>Project engineer</b>	<b>Stellung / Position:</b>	<b>Reviewer</b>	
<b>Sonstiges /</b> <i>Other:</i>	<b>FCC ID: FHO-J2324</b> Test Firm Name: TÜV Rheinland (Suzhou) Co., Ltd. Test Firm Registration Number: 251781 Designation Number: CN1370			
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	<b>Prüfmuster vollständig und unbeschädigt</b> <i>Test item complete and undamaged</i>			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

v05

Prüfbericht-Nr.: CN23IU8 001  
Test report no.:

Seite 2 von 28  
Page 2 of 28

**Anmerkungen**  
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

## TEST SUMMARY

5.1.1 CONDUCTED EMISSION

*Result:*

*Passed*

5.2.1 RADIATED EMISSION (30-1000 MHz)

*Result:*

*Passed*

# Contents

<b>1</b>	<b>TEST SITES</b> .....	<b>5</b>
1.1	TEST FACILITIES.....	5
<b>2</b>	<b>GENERAL PRODUCT INFORMATION</b> .....	<b>6</b>
2.1	PRODUCT FUNCTION AND INTENDED USE.....	6
2.2	RATINGS AND SYSTEM DETAILS.....	6
2.3	INDEPENDENT OPERATION MODES.....	6
2.4	DESCRIPTION OF INTERCONNECTING CABLES .....	6
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS .....	6
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES .	6
2.7	SUBMITTED DOCUMENTS.....	6
<b>3</b>	<b>TEST SET-UP AND OPERATION MODES</b> .....	<b>7</b>
3.1	PRINCIPLE OF CONFIGURATION SELECTION .....	7
3.2	EQUIPMENT AND CABLE ARRANGEMENT.....	7
3.3	TEST SOFTWARE .....	8
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....	8
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	8
<b>4</b>	<b>CONFORMITY DECISION RULE</b> .....	<b>9</b>
<b>5</b>	<b>TEST RESULTS EMISSION</b> .....	<b>10</b>
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHz .....	10
5.1.1	Conducted emission .....	10
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz.....	18
5.2.1	Radiated emission (30-1000 MHz).....	18
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP</b> .....	<b>26</b>
<b>7</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS</b> .....	<b>27</b>
<b>8</b>	<b>LIST OF FIGURES</b> .....	<b>28</b>

# 1 Test Sites

## 1.1 Test Facilities

**Laboratory:** TÜV Rheinland (Suzhou) Co., Ltd.

**Address:** No.14 building and north half of No.10 workshop building, No.525, Yuewang Lingang South Road, Pingqian (Taicang) Modern Industrial Park, Shaxi Town, Taicang City, Jiangsu Province, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 7 for test and measurement instruments.

## 2 General Product Information

### 2.1 Product Function and Intended Use

The EUT (equipment under test) is an ordinary outdoor light chain for lighting and similar use. For the further information, refer to the user's manual.

### 2.2 Ratings and System Details

System input : AC 120 V, 60 Hz

Rated power : 4 W

LED driver information: ICPSW-24-3.6-IL-1, Input: AC 100-240 V, 50/60 Hz, Max. 0,05 A;  
Output: DC 24.0 V, Max.0.15 mA, 3.6W.

### 2.3 Independent Operation Modes

The basic operation modes are: "ON" and "OFF".

### 2.4 Description of interconnecting cables

No.	Interface and name	Shielded or not	Specified length (mm)
1	AC power line	Unshielded	950
2	DC Power supply line	Unshielded	4800

### 2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

### 2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is 24 MHz.

### 2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

### 3 Test Set-up and Operation Modes

#### 3.1 Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:


1. Radiated emission tests were performed on 2023-12-27.
2. Conducted emission tests were performed on 2023-12-28.

#### 3.2 Equipment and cable arrangement

Block diagram for both conducted emission and radiated emission tests is as follows:



(Conducted emission)



(Radiated emission 30-1000 MHz)

Also refer to photographs on clause 6 for test setups for both conducted emission test and radiated emission test.

### **3.3 Test Software**

No special test software was used during the tests.

### **3.4 Special Accessories and Auxiliary Equipment**

None.

### **3.5 Countermeasures to achieve EMC Compliance**

No other special measure is employed to achieve the requirement.



## 4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values  $U_{\text{CISPR}}$  given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

## 5 Test Results EMISSION

### 5.1 Emission in the Frequency Range up to 30 MHz

#### 5.1.1 Conducted emission

Result:	Passed
Date of testing	: 2023-12-28
Test procedure	: FCC 47 CFR Part 15, Subpart B:2021, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-1
Frequency range	: 0.15 – 30 MHz
Limits	: Quasi-peak limit: 0.15 – 0.5 MHz, 66 to 56 dB $\mu$ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 56 dB $\mu$ V; 5 – 30 MHz, 60 dB $\mu$ V Average limit: 0.15 – 0.5 MHz, 56 to 46 dB $\mu$ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dB $\mu$ V; 5 – 30 MHz, 50 dB $\mu$ V
Bandwidth of EMI receiver for final measurement	: 9 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Shielded room
Input voltage	: AC 120 V, 60 Hz with LED driver
Operational mode	: Mode 1: lighting on mode Mode 2: flashing mode Mode 3: sensor mode
Ambient condition	: Temperature: 21.1 °C; Relative humidity: 45.7 %
Expanded measurement uncertainty ( $k=2$ )	: 2.33 dB The minimum margin to the limit is 2.59 dB at 0.166875 MHz. The margin is higher than expanded measurement uncertainty.

The measurement setup was made according to ANSI C63.4-2014 in a shielded room.

The measurement equipment like test receivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.

The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m.

The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

**Prüfbericht - Nr.:** CN23IU8 001

Test Report No.:

**Seite 11 von 28**

Page 11 of 28


The following figures and tables were those measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, “♦” means Quasi-Peak Value and “◆” means Average Value results.

Notes on following tables of conducted emission results and conversions:

Level (dB $\mu$ V): final measurement results by using quasi-peak detector and average detector

Transd (dB): transducer factor including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)


Margin: Limit (dB $\mu$ V) - Level (dB $\mu$ V)

**Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 1**

**Final Quasi-peak measurement result:**

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	56.20	65.12	8.91	1000.0	9.000	L1	10.4
0.583125	42.66	56.00	13.34	1000.0	9.000	L1	10.5
1.168125	38.84	56.00	17.16	1000.0	9.000	L1	10.8
2.394375	39.86	56.00	16.14	1000.0	9.000	L1	10.3
12.508125	39.22	60.00	20.78	1000.0	9.000	L1	11.0
15.399375	40.98	60.00	19.02	1000.0	9.000	L1	11.1

**Final Average measurement result:**

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	46.11	55.12	9.01	1000.0	9.000	L1	10.4
0.594375	31.62	46.00	14.38	1000.0	9.000	L1	10.5
2.056875	29.62	46.00	16.38	1000.0	9.000	L1	10.3
2.574375	30.73	46.00	15.27	1000.0	9.000	L1	10.3
12.451875	31.35	50.00	18.65	1000.0	9.000	L1	11.0
15.466875	32.33	50.00	17.67	1000.0	9.000	L1	11.1


**Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 1**


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	56.25	65.12	8.87	1000.0	9.000	N	10.6
0.594375	42.03	56.00	13.97	1000.0	9.000	N	10.5
2.056875	39.03	56.00	16.97	1000.0	9.000	N	10.7
2.788125	39.85	56.00	16.15	1000.0	9.000	N	10.8
12.440625	39.06	60.00	20.94	1000.0	9.000	N	11.3
15.433125	41.97	60.00	18.03	1000.0	9.000	N	11.4

Final Average measurement result:


Frequency (MHz)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	46.27	55.12	8.84	1000.0	9.000	N	10.6
0.594375	28.89	46.00	17.11	1000.0	9.000	N	10.5
2.101875	30.35	46.00	15.65	1000.0	9.000	N	10.7
2.844375	31.81	46.00	14.19	1000.0	9.000	N	10.8
12.440625	30.84	50.00	19.16	1000.0	9.000	N	11.3
15.433125	33.13	50.00	16.87	1000.0	9.000	N	11.4

**Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 2**

**Final Quasi-peak measurement result:**

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	61.01	65.12	4.10	1000.0	9.000	L1	10.4
0.594375	45.52	56.00	10.48	1000.0	9.000	L1	10.5
0.999375	40.06	56.00	15.94	1000.0	9.000	L1	10.9
2.495625	37.55	56.00	18.45	1000.0	9.000	L1	10.3
12.395625	36.82	60.00	23.18	1000.0	9.000	L1	11.0
15.365625	40.76	60.00	19.24	1000.0	9.000	L1	11.1

**Final Average measurement result:**

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	45.89	56.00	10.11	1000.0	9.000	L1	10.4
0.594375	35.26	46.00	10.74	1000.0	9.000	L1	10.5
0.999375	32.16	46.00	13.84	1000.0	9.000	L1	10.9
2.169375	31.42	46.00	14.58	1000.0	9.000	L1	10.3
12.373125	25.91	50.00	24.09	1000.0	9.000	L1	11.0
15.365625	29.85	50.00	20.15	1000.0	9.000	L1	11.1


**Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 2**


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	62.53	65.12	2.59	1000.0	9.000	N	10.6
0.594375	44.34	56.00	11.66	1000.0	9.000	N	10.5
1.989375	39.17	56.00	16.83	1000.0	9.000	N	10.7
2.473125	39.32	56.00	16.68	1000.0	9.000	N	10.8
12.384375	37.13	60.00	22.87	1000.0	9.000	N	11.3
15.433125	33.03	60.00	26.97	1000.0	9.000	N	11.4

Final Average measurement result:

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	46.23	56.00	9.77	1000.0	9.000	N	10.4
0.594375	35.49	46.00	10.51	1000.0	9.000	N	10.5
1.989375	29.31	46.00	16.69	1000.0	9.000	N	10.7
2.473125	29.79	46.00	16.21	1000.0	9.000	N	10.8
12.395625	30.86	50.00	19.14	1000.0	9.000	N	11.3
15.376875	29.55	50.00	20.45	1000.0	9.000	N	11.4

**Figure 5: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 3**



Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	56.49	65.12	8.63	1000.0	9.000	L1	10.4
0.594375	43.69	56.00	12.31	1000.0	9.000	L1	10.5
2.079375	38.80	56.00	17.20	1000.0	9.000	L1	10.3
2.923125	40.22	56.00	15.78	1000.0	9.000	L1	10.3
12.395625	40.10	60.00	19.90	1000.0	9.000	L1	11.0
12.496875	40.55	60.00	19.45	1000.0	9.000	L1	11.0

Final Average measurement result:

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	46.86	55.12	8.26	1000.0	9.000	L1	10.4
0.538125	28.02	46.00	17.98	1000.0	9.000	L1	10.5
0.594375	32.17	46.00	13.83	1000.0	9.000	L1	10.5
2.090625	29.68	46.00	16.32	1000.0	9.000	L1	10.3
2.855625	31.13	46.00	14.87	1000.0	9.000	L1	10.3
12.553125	32.39	50.00	17.61	1000.0	9.000	L1	11.0



**Figure 6: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 3**


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	56.72	65.12	8.39	1000.0	9.000	N	10.6
0.594375	42.29	56.00	13.71	1000.0	9.000	N	10.5
2.079375	39.06	56.00	16.94	1000.0	9.000	N	10.7
2.495625	40.20	56.00	15.80	1000.0	9.000	N	10.8
12.541875	40.30	60.00	19.70	1000.0	9.000	N	11.3
15.500625	41.30	60.00	18.70	1000.0	9.000	N	11.4

Final Average measurement result:

Frequency (MHz)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.166875	46.95	55.12	8.17	1000.0	9.000	N	10.6
0.594375	29.60	46.00	16.40	1000.0	9.000	N	10.5
2.090625	30.48	46.00	15.52	1000.0	9.000	N	10.7
2.855625	31.84	46.00	14.16	1000.0	9.000	N	10.8
12.395625	31.91	50.00	18.09	1000.0	9.000	N	11.3
12.474375	32.06	50.00	17.94	1000.0	9.000	N	11.3

## 5.2 Emission in the Frequency Range above 30 MHz

### 5.2.1 Radiated emission (30-1000 MHz)

<b>Result:</b>	<b>Passed</b>
----------------	---------------

Date of testing	: 2023-12-27
Test procedure	: FCC 47 CFR Part 15, Subpart B:2021, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-3
Product classification	: Class B
Frequency range	: 30 – 1000 MHz (see Note 1)
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB $\mu$ V/m; 88 – 216 MHz, 43.5 dB $\mu$ V/m; 216 – 1000 MHz, 46 dB $\mu$ V/m (see Note 2)
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Input voltage	: AC 120 V, 60 Hz with LED driver
Operational mode	: Mode 1: lighting on mode Mode 2: flashing mode Mode 3: sensor mode
Ambient condition	: Temperature: 19.7 °C; Relative humidity: 50.2 %
Expanded measurement uncertainty ( $k=2$ )	: 5.49 dB

The minimum margin to the limit is 12.6 dB at 862.623750 MHz. The margin is higher than expanded measurement uncertainty.

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on an 80 cm wooden support above the reference ground plane. The wooden support was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “×” means quasi-peak test results.

Notes on following tables of radiated emission results and conversions:


**Prüfbericht - Nr.:** CN23IU8 001  
Test Report No.:**Seite 19 von 28**  
Page 19 of 28

QuasiPeak (dB $\mu$ V/m): final measurement results by using quasi-peak detector  
Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB $\mu$ V/m) - QuasiPeak (dB $\mu$ V/m)


*Note 1: The highest frequency in the EUT is 24 MHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 1000 MHz.*

*Note 2: The class B limits of ICES-005:2018 is stricter than those FCC 47 CFR Part 15, Subpart B:2021 for 3 m test distance. Therefore, the former limits are used in following figures and tables.*

**Figure 7: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 1**



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
40.548750	22.7	120.000	100.0	H	-180.0	19.5	17.3	40.0
119.118750	22.0	120.000	100.0	H	-180.0	18.9	21.5	43.5
143.732500	22.5	120.000	100.0	H	-180.0	18.0	21.0	43.5
281.836250	23.1	120.000	100.0	H	-180.0	20.0	22.9	46.0
574.412500	30.0	120.000	100.0	H	-180.0	26.4	16.0	46.0
864.321250	33.3	120.000	100.0	H	-180.0	28.8	12.7	46.0

**Figure 8: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 1**



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
47.581250	27.1	120.000	100.0	V	-180.0	16.0	12.9	40.0
98.627500	22.5	120.000	100.0	V	-180.0	17.4	21.0	43.5
113.541250	21.8	120.000	100.0	V	-180.0	18.8	21.7	43.5
363.558750	25.3	120.000	100.0	V	-180.0	22.0	20.7	46.0
462.377500	27.8	120.000	100.0	V	-180.0	24.6	18.2	46.0
862.623750	33.4	120.000	100.0	V	-180.0	28.8	12.6	46.0

**Figure 9: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 2**



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
33.273750	26.6	120.000	100.0	H	-180.0	23.3	13.4	40.0
47.823750	19.1	120.000	100.0	H	-180.0	15.9	20.9	40.0
145.187500	25.3	120.000	100.0	H	-180.0	17.9	18.2	43.5
257.586250	23.6	120.000	100.0	H	-180.0	20.5	22.4	46.0
419.212500	27.2	120.000	100.0	H	-180.0	23.9	18.8	46.0
888.571250	33.3	120.000	100.0	H	-180.0	28.7	12.7	46.0

**Figure 10: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 2**


Final quasi-peak measurement results:


Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
46.975000	26.9	120.000	100.0	V	180.0	16.2	13.1	40.0
97.900000	23.4	120.000	100.0	V	180.0	17.3	20.1	43.5
149.673750	21.8	120.000	100.0	V	180.0	17.6	21.7	43.5
303.176250	23.5	120.000	100.0	V	180.0	20.3	22.5	46.0
732.037500	31.0	120.000	100.0	V	180.0	27.5	15.0	46.0
965.201250	33.0	120.000	100.0	V	180.0	29.5	13.0	46.0

**Figure 11: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 3**


Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
38.851250	23.6	120.000	100.0	H	-180.0	20.4	16.4	40.0
84.926250	17.6	120.000	100.0	H	-180.0	14.6	22.4	40.0
145.430000	25.2	120.000	100.0	H	-180.0	17.8	18.3	43.5
264.133750	23.7	120.000	100.0	H	-180.0	20.8	22.3	46.0
655.165000	29.8	120.000	100.0	H	-180.0	26.3	16.2	46.0
813.881250	31.9	120.000	100.0	H	-180.0	28.0	14.1	46.0



**Figure 12: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 3**


Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
38.608750	24.8	120.000	100.0	V	-180.0	20.5	15.2	40.0
47.460000	25.2	120.000	100.0	V	-180.0	16.0	14.8	40.0
107.963750	21.5	120.000	100.0	V	-180.0	18.5	22.0	43.5
294.931250	23.2	120.000	100.0	V	-180.0	20.2	22.8	46.0
596.722500	30.7	120.000	100.0	V	-180.0	26.9	15.3	46.0
927.856250	33.2	120.000	100.0	V	-180.0	28.9	12.8	46.0

## **6 Photographs of the Test Set-Up**

Refer to the test setup file.

## 7 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date	Due Date
				DD.MM.YYYY	DD.MM.YYYY
9053584	Shielded enclosure	FRSR	Frankonia	02.12.2022	02.12.2027
9023229	EMI test receiver	ESR3	Rohde&Schwarz	23.08.2023	23.08.2024
G1830003	Artificial mains network	ENV432	Rohde&Schwarz	16.10.2023	16.10.2024
G1824248	Dual display multimeter	F45	Fluke	08.10.2022	08.10.2024
G1811378	3m semi-anechoic chamber	SAC3	Frankonia	10.06.2021	10.06.2024
G1811391	EMI test receiver	ESCI	Rohde&Schwarz	29.09.2023	29.09.2024
G1811425	Bilog antenna	CBL 6112D	Teseq	20.04.2023	20.04.2026
G1824845	EMC measurement software	EMC32 (Ver 10.20.01)	Rohde&Schwarz	N/A	N/A

## 8 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 1 .....	12
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 1 .....	13
Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 2 .....	14
Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 2 .....	15
Figure 5: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L on mode 3 .....	16
Figure 6: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N on mode 3 .....	17
Figure 7: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 1 .....	20
Figure 8: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 1 .....	21
Figure 9: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 2 .....	22
Figure 10: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 2 .....	23
Figure 11: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization on mode 3 .....	24
Figure 12: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization on mode 3 .....	25

**End of test report**