

Prüfbericht-Nr.: <i>Test Report No.:</i>	CN22QMCE 001	Auftrags-Nr.: <i>Order No.:</i>	244431322	Seite 1 von 23 <i>Page 1 of 23</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	1288983	Auftragsdatum: <i>Order date.:</i>	2022-06-23	
Auftraggeber: <i>Client:</i>	IKEA of Sweden AB Box 702, SE-343 81 Älmhult, Sweden			
Prüfgegenstand: <i>Test item:</i>	Portable Luminaire			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	K2203 LAGERGÅNG			
Auftrags-Inhalt: <i>Order content:</i>	TÜV Rheinland EMC service			
Prüfgrundlage: <i>Test specification:</i>	FCC 47 CFR Part 15, Subpart B:2020 Class B ICES-005:2018			
Wareneingangsdatum: <i>Date of receipt:</i>	2022-06-22	Refer to the EUT photos file		
Prüfmuster-Nr.: <i>Test sample No.:</i>	A003282875-001			
Prüfzeitraum: <i>Testing period:</i>	Refer to test report			
Ort der Prüfung: <i>Place of testing:</i>	Refer to clause 1.1			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: / tested by: Jessie Xu		genehmigt von: / authorized by: Jiayi Zhou		
Datum: / Date: 2022-08-25 <i>Jessie Xu</i>		Datum: / Date: 2022-08-25 <i>Jiayi Zhou</i>		
Stellung: / Position: Project manager		Stellung: / Position: Senior manager		
Sonstiges / Other:	FCC ID: FHO-K2203 Test Firm Registration Number: 958801			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht - Nr.: CN22QMCE 001

Test Report No.:

Seite 2 von 23

Page 2 of 23

TEST SUMMARY

5.1.1 CONDUCTED EMISSION

*Result:**Passed*

5.2.1 RADIATED EMISSION

*Result:**Passed*

Contents

1	TEST SITES	4
1.1	TEST FACILITIES	4
2	GENERAL PRODUCT INFORMATION	5
2.1	PRODUCT FUNCTION AND INTENDED USE	5
2.2	RATINGS AND SYSTEM DETAILS	5
2.3	INDEPENDENT OPERATION MODES	5
2.4	DESCRIPTION OF INTERCONNECTING CABLES	5
2.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS	5
2.6	HIGHEST FREQUENCY GENERATED OR USED IN THE DEVICE OR ON WHICH THE DEVICE OPERATES OR TUNES	5
2.7	SUBMITTED DOCUMENTS	5
3	TEST SET-UP AND OPERATION MODES	6
3.1	PRINCIPLE OF CONFIGURATION SELECTION	6
3.2	EQUIPMENT AND CABLE ARRANGEMENT	6
3.3	TEST SOFTWARE	7
3.4	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	7
3.5	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	7
4	CONFORMITY DECISION RULE	8
5	TEST RESULTS EMISSION	9
5.1	EMISSION IN THE FREQUENCY RANGE UP TO 30 MHz	9
5.1.1	Conducted emission	9
5.2	EMISSION IN THE FREQUENCY RANGE ABOVE 30 MHz	15
5.2.1	Radiated emission	15
6	PHOTOGRAPHS OF THE TEST SET-UP	21
7	LIST OF TEST AND MEASUREMENT INSTRUMENTS	22
8	LIST OF FIGURES	23

Prüfbericht - Nr.: CN22QMCE 001
Test Report No.:

Seite 4 von 23
Page 4 of 23

1 Test Sites

1.1 Test Facilities

Laboratory: TÜV Rheinland (Shanghai) Co., Ltd.

Address: No.177, 178, Lane 777 West Guangzhong Road, Jing'an District, Shanghai, China

The used test equipment is in accordance with CISPR 16-1 series standards for measurement of radio interference.

Refer to Clause 7 for test and measurement instruments.

2 General Product Information

2.1 Product Function and Intended Use

The EUT (equipment under test) is the ordinary portable luminaire for lighting and similar use. For the further information, refer to the user's manual.

2.2 Ratings and System Details

Rated input	:	DC 5 V, Max 4.4 W
Protection class	:	III

2.3 Independent Operation Modes

The basic operation modes are: "ON" and "OFF" with dimming function.

2.4 Description of interconnecting cables

No.	Interface and name	Shielded or not	Specified length (m)
1	USB power input line	Unshielded	1.5

2.5 Noise Generating and Noise Suppressing Parts

Refer to the circuit diagram for further information.

2.6 Highest frequency generated or used in the device or on which the device operates or tunes

The highest frequency used in the EUT is less than 108 MHz.

2.7 Submitted Documents

Circuit diagram, user's manual and rating label.

3 Test Set-up and Operation Modes

3.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible emission level. The test conditions were adapted accordingly in reference to the instructions for use.


Refer to the related paragraph of this report.

The sequence of testing:


1. Radiated emission tests were performed on 2022-07-06.
2. Conducted emission tests were performed on 2022-07-07.

3.2 Equipment and cable arrangement

Block diagram for both conducted emission and radiated emission tests is as follows:



(Conducted emission)



(Radiated emission)

Also refer to photographs on clause 6 for test setups for both conducted emission test and radiated emission test.

Prüfbericht - Nr.: CN22QMCE 001
Test Report No.:Seite 7 von 23
Page 7 of 23

3.3 Test Software

No special test software was used during the tests.

3.4 Special Accessories and Auxiliary Equipment

During the tests, the power supply and laptop were used.

Product	Model	Brand
Power supply	A2244 Input: AC 100-240 V, 50-60 Hz, 0.5 A Output: DC 5 V, 3 A; DC 9 V, 2.22 A	APPLE
Laptop	T450	Thinkpad

3.5 Countermeasures to achieve EMC Compliance

No other special measure is employed to achieve the requirement.

4 Conformity Decision Rule

For all EMI tests included in this report, as measurement uncertainties are less than the values U_{CISPR} given in CISPR 16-4-2, compliance with the limits is determined by comparing measurement results directly with corresponding limits without taking into consideration of measurement uncertainties.

5 Test Results EMISSION

5.1 Emission in the Frequency Range up to 30 MHz

5.1.1 Conducted emission

Result:	Passed
Date of testing	: 2022-07-07
Test procedure	: FCC 47 CFR Part 15, Subpart B:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-1
Frequency range	: 0.15 – 30 MHz
Limits	: Quasi-peak limit: 0.15 – 0.5 MHz, 66 to 56 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 56 dB μ V; 5 – 30 MHz, 60 dB μ V Average limit: 0.15 – 0.5 MHz, 56 to 46 dB μ V (decrease with the logarithm of frequency); 0.5 – 5 MHz, 46 dB μ V; 5 – 30 MHz, 50 dB μ V
Bandwidth of EMI receiver for final measurement	: 9 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Shielded room
Input voltage	: AC 120 V, 60 Hz for adapter
Operational mode	: Mode 1: lighting on by adapter powered Mode 2: lighting on by laptop powered
Ambient condition	: Temperature: 23.6 °C; Relative humidity: 41.2 %
Expanded measurement uncertainty ($k=2$)	: 3.39 dB

The measurement setup was made according to ANSI C63.4-2014 in a shielded room.

The measurement equipment like test receivers, quasi-peak detector and artificial mains network (AMN) are in compliance with CISPR 16-1 series standards.

The tested object was set-up on a wooden support. The EUT was set 0.8 m away from the AMN. The cord longer than necessary to be connected to the AMN was folded forth and back parallel so as to form a bundle with a length between 0.3 m and 0.4 m.

The disturbance voltage test was performed on the neutral line and phase line of the power supply of the EUT respectively.

The following figures and tables were those measured by an automatic measuring system. Both quasi-peak and average measurements were performed. In the following spectral diagram, “*”

Prüfbericht - Nr.: CN22QMCE 001

Test Report No.:

Seite 10 von 23

Page 10 of 23


means Quasi-Peak Value and “*” means Average Value results.

Notes on following tables of conducted emission results and conversions:

Level (dB μ V): final measurement results by using quasi-peak detector and average detector

Transd (dB): transducer factor including cable loss, insertion loss of artificial mains network and gain of pre-amplifier (if used)

Margin: Limit (dB μ V) - Level (dB μ V)


Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L for mode 1


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.493125	4.53	56.12	51.59	L1	9.6
1.370625	5.10	56.00	50.90	L1	9.6
4.126875	6.55	56.00	49.45	L1	9.7
12.373125	10.09	60.00	49.91	L1	10.0
16.243125	11.65	60.00	48.35	L1	10.2
28.786875	11.82	60.00	48.18	L1	10.1

Final Average measurement result:

Frequency (MHz)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
28.786875	6.60	50.00	43.40	L1	10.1
16.243125	8.26	50.00	41.74	L1	10.2
1.370625	-0.41	46.00	46.41	L1	9.6
0.493125	-1.05	46.12	47.17	L1	9.6
12.361875	5.55	50.00	44.45	L1	10.0
4.126875	1.25	46.00	44.75	L1	9.7


Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N for mode 1


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.493125	4.27	56.12	51.85	N	9.6
0.346875	4.45	59.04	54.59	N	9.6
1.381875	5.13	56.00	50.87	N	9.6
4.138125	6.59	56.00	49.41	N	9.6
9.650625	9.02	60.00	50.98	N	9.8
28.888125	12.05	60.00	47.95	N	10.2

Final Average measurement result:

Frequency (MHz)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
28.888125	6.85	50.00	43.15	N	10.2
9.650625	3.94	50.00	46.06	N	9.8
0.526875	-1.40	46.00	47.40	N	9.6
0.346875	-1.23	49.04	50.26	N	9.6
4.138125	0.91	46.00	45.09	N	9.6
1.381875	-0.45	46.00	46.45	N	9.6


Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L for mode 2


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
4.149375	23.51	56.00	32.49	L1	9.7
0.988125	24.19	56.00	31.81	L1	9.6
4.835625	25.45	56.00	30.55	L1	9.7
5.521875	27.06	60.00	32.94	L1	9.7
0.369375	32.79	58.52	25.72	L1	9.6
0.200625	38.55	63.59	25.04	L1	9.5

Final Average measurement result:

Frequency (MHz)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
22.070625	19.17	50.00	30.84	L1	10.1
12.429375	19.65	50.00	30.35	L1	10.0
11.056875	19.63	50.00	30.37	L1	10.0
0.403125	17.05	47.79	30.74	L1	9.6
4.149375	16.40	46.00	29.60	L1	9.7
4.824375	17.11	46.00	28.89	L1	9.7

Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N for mode 2


Final Quasi-peak measurement result:

Frequency (MHz)	QuasiPeak (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.988125	23.67	56.00	32.33	N	9.6
4.160625	24.73	56.00	31.27	N	9.6
4.835625	26.13	56.00	29.87	N	9.6
27.729375	28.92	60.00	31.08	N	10.2
0.369375	32.47	58.52	26.04	N	9.6
0.346875	33.22	59.04	25.82	N	9.6

Final Average measurement result:

Frequency (MHz)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
22.171875	21.86	50.00	28.14	N	10.2
27.718125	23.46	50.00	26.54	N	10.2
12.485625	22.09	50.00	27.91	N	9.9
4.160625	17.60	46.00	28.40	N	9.6
4.813125	17.22	46.00	28.78	N	9.6
11.101875	22.32	50.00	27.68	N	9.8

5.2 Emission in the Frequency Range above 30 MHz

5.2.1 Radiated emission

Result:
Passed

Date of testing	: 2022-07-06
Test procedure	: FCC 47 CFR Part 15, Subpart B:2020, ICES-005:2018, ANSI C63.4-2014 and CISPR 16-2-2
Product classification	: Class B
Frequency range	: 30 – 1000 MHz (see Note 1)
Limits	: Quasi-peak limits (3 m distance): 30 – 88 MHz, 40 dB μ V/m; 88 – 216 MHz, 43.5 dB μ V/m; 216 – 1000 MHz, 46 dB μ V/m (see Note 2)
Bandwidth of EMI receiver for final measurement	: 120 kHz
Measurement time for final measurement	: 1 s
Kind of test site	: Semi-anechoic chamber
Input voltage	: AC 120 V, 60 Hz for adapter
Operational mode	: Mode 1: lighting on by adapter powered Mode 2: lighting on by laptop powered
Ambient condition	: Temperature: 21.6 °C; Relative humidity: 56.2 %
Expanded measurement uncertainty ($k=2$)	: 5.49 dB

The radiated disturbance test was carried out in a semi-anechoic chamber. The test distance from the receiving antenna to the EUT is 3 m. The normalized site attenuation of the semi-anechoic chamber is regularly calibrated to ensure the radiated disturbance test results are valid. During the test, the EUT was placed on an 80 cm wooden support above the reference ground plane. The wooden support was rotated 360° around and the height of the antenna was varied from 1 m to 4 m to find the maximum disturbance. The test was performed with the antenna both in its horizontal and vertical polarizations.

The following figures and tables were those measured by an automatic measurement system. A preview test was firstly performed with peak detector. The final test was performed with quasi-peak at those critical frequencies during the preview test. In the following spectral diagram, “×” means quasi-peak test results.

Note 1: The highest frequency in the EUT is less than 108 MHz. According to FCC Part 15 subpart B §15.33 (b) (1), the upper frequency for radiated emission measurement is 1000 MHz.

Note 2: The class B limits of ICES-005:2018 is stricter than those FCC 47 CFR Part 15, Subpart B:2020 for 3 m test distance. Therefore, the former limits are used in following figures and tables.

Prüfbericht - Nr.: CN22QMCE 001

Test Report No.:

Seite 16 von 23


Page 16 of 23

Notes on following tables of radiated emission results and conversions:

QuasiPeak (dB μ V/m): final measurement results by using quasi-peak detector


Corr. (dB): correction factor including: antenna factor, cable loss, and gain of pre-amplifier (if used)

Margin: Limit (dB μ V/m) - QuasiPeak (dB μ V/m)

Figure 5: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization for mode 1



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
137.152667	22.5	1000.0	120.000	100.0	H	120.0	18.3	21.0	43.5
201.657667	29.4	1000.0	120.000	100.0	H	-10.0	16.2	14.1	43.5
334.321333	32.7	1000.0	120.000	100.0	H	-120.0	20.6	13.3	46.0

Figure 6: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization for mode 1



Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
50.370000	28.1	1000.0	120.000	100.0	V	-80.0	14.4	11.9	40.0
53.150667	27.1	1000.0	120.000	100.0	V	120.0	13.6	12.9	40.0
128.616667	26.5	1000.0	120.000	100.0	V	10.0	18.7	17.0	43.5

Figure 7: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization for mode 2


Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
54.153000	25.5	1000.0	120.000	150.0	H	120.0	13.3	14.5	40.0
265.677667	24.2	1000.0	120.000	150.0	H	40.0	20.6	21.8	46.0
894.625667	32.2	1000.0	120.000	150.0	H	-20.0	28.4	13.8	46.0

Figure 8: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization for mode 2


Final quasi-peak measurement results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBµV/m)
51.340000	32.8	1000.0	120.000	150.0	V	-40.0	14.1	7.2	40.0
54.088333	31.3	1000.0	120.000	150.0	V	60.0	13.3	8.7	40.0
194.124000	28.5	1000.0	120.000	150.0	V	20.0	16.0	15.1	43.5

Prüfbericht - Nr.: CN22QMCE 001
Test Report No.:

Seite 21 von 23
Page 21 of 23

6 Photographs of the Test Set-Up

Refer to the test setup file.

Prüfbericht - Nr.: CN22QMCE 001

Test Report No.:

Seite 22 von 23

Page 22 of 23

7 List of Test and Measurement Instruments

Equip.	Description	Model	Manufacturer	Last Date	Due Date
				DD.MM.YYYY	DD.MM.YYYY
9023229	EMI test receiver	ESR3	Rohde&Schwarz	22.03.2021	31.08.2022
G1811403	Artificial mains network	ENV216	Rohde&Schwarz	04.11.2021	04.11.2022
G1824248	Dual display multimeter	F45	Fluke	18.09.2020	18.09.2022
G1811378	3m modified semi-anechoic chamber	SAC3	Frankonia	27.06.2019	31.08.2022
9042162	EMI test receiver	ESR7	Rohde&Schwarz	02.03.2022	02.03.2023
G1811425	Bilog antenna	CBL 6112D	Teseq	10.03.2020	10.03.2023
G1814622	CDN for emission measurement	CDNE M210	Teseq	03.07.2021	03.07.2023
G1824845	EMC measurement software	EMC32 (Ver 10.20.01)	Rohde&Schwarz	N/A	N/A

8 List of Figures

Figure 1: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L for mode 1	11
Figure 2: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N for mode 1	12
Figure 3: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, L for mode 2	13
Figure 4: Spectral Diagrams, Conducted Emission, 150 kHz – 30 MHz, N for mode 2	14
Figure 5: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization for mode 1	17
Figure 6: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization for mode 1	18
Figure 7: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Horizontal polarization for mode 2	19
Figure 8: Spectral Diagrams, Radiated Emission, 30 MHz – 1000 MHz, Vertical polarization for mode 2	20

End of test report