

LUNNOM LED sign bulb E12 100lm clear 2-p-NA



刀线 ———
 压线 ———
 齿刀线 - - - -

E12

LED21753

15 W
100 lm

120 V
15 MHz
0.5 mm
1.5 x
x15 000
L
111 mm

LUNNOM LED

IKEA

Design and Quality
WEA of Sweden

CAUTION: THIS DEVICE IS NOT INTENDED FOR USE WITH EMERGENCY EXITS.
 RISK OF ELECTRIC SHOCK-USE IN DRY LOCATION ONLY.
 Ambient operating temperature is 0-35°C.
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation (CAN ICES-1 (B)).

Please note that changes or modifications of this product is not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

ATTENTION - AVOIDER DE CHOC ÉLECTRIQUE:
 RISK OF ELECTRIC SHOCK-USE IN DRY LOCATION ONLY.
 Température ambiante de fonctionnement: 0-35°C.
 Ce dispositif est conforme à la partie 15 des Règles de la FCC. Son utilisation est soumise aux conditions suivantes: (1) ce dispositif ne doit pas causer d'interférence nuisible et (2) ce dispositif doit accepter toute interférence reçue, y compris l'interférence qui peut causer un fonctionnement indésirable.

ATTENTION - RISK OF ELECTRIC SHOCK-USE IN DRY LOCATION ONLY.
 Ambient operating temperature is 0-35°C.
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation (CAN ICES-1 (B)).

IDGM

INTERNATIONAL DIGITAL GRAPHICS MANAGEMENT
 10000 WALKER BLVD. SUITE 100
 FORT WORTH, TEXAS 76116-7000
 TEL: 817.339.1111 FAX: 817.339.1112
 WWW.IDGM.COM

INSTRUCTIONS: RESISTOR DE FUSION PARA EL CABLEADO ELECTRICO.
 Este dispositivo no debe ser instalado en un lugar húmedo o con alta humedad, ni en un lugar con alta temperatura. No debe ser instalado en un lugar con alta humedad y alta temperatura. No debe ser instalado en un lugar con alta temperatura y alta humedad. No debe ser instalado en un lugar con alta temperatura y alta humedad y alta temperatura.

© 2011 IDGM Systems B.V. 2011
 www.idgm.com