

EMC TEST REPORT

No. 1907679STO-001, Ed. 2

Electromagnetic disturbances

EQUIPMENT UNDER TEST

Equipment: Self-ballasted LED-lamp
Tested Type/Model: LED1805E22
Manufacturer: IKEA of Sweden AB
Tested by request of: IKEA of Sweden AB

SUMMARY

Referring to the emission limits, and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards:

FCC 47 CFR Part 15: Radio frequency device, Subpart B: Unintentional radiators. Class B equipment.

ICES-005 Issue 5: Lighting Equipment, Class B. (2018)

Date of issue: February 11, 2020

Tested by:


Ann-Christine Norrström

Approved by:


Per Granberg

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Edition	Date	Description	Changes
1	May 24, 2019	First release	
2	February 11, 2020	Second release	<p>The report was updated according to order number 2010438STO-101</p> <p>Photos of EUT and test setups in annex 1.</p>

CONTENTS

	Page
1. Client Information	4
2. Equipment under test (EUT).....	4
2.1 Identification of the EUT	4
2.2 Test set up and EUT photos	4
2.3 Purpose of the test	5
2.4 Additional information about the EUT	5
2.5 Modifications made to improve EMC-characteristics	5
3. Test Specifications	6
3.1 Standards	6
3.2 Additions, deviations and exclusions from standards and accreditation	6
3.3 Test site	6
3.4 Mode of operation during the test	6
3.5 Compliance	7
4. Test Summary	8
5. Conducted continuous disturbances	9
5.1 Operating environment.....	9
5.2 Test set-up and test procedure	9
5.3 Measurement uncertainty.....	9
5.4 Test results, AC Power input port, Class B, max luminous intensity	10
5.5 Test results, AC Power input port, Class B, min luminous intensity	11
5.6 Test equipment	12
6. Radiated rf Emission in the frequency-range 30 MHz – 13 GHz	13
6.1 Operating environment.....	13
6.2 Test set-up and test procedure	13
6.3 Test conditions	13
6.4 Measurement uncertainty.....	14
6.5 Test results, 30 – 1000 MHz, Class B, max luminous intensity	15
6.6 Test results, 30 – 1000 MHz, Class B, min luminous intensity	16
6.7 Test equipment	17
6.8 Test results, 1 – 13 GHz, Class B, max luminous intensity	18
6.9 Test results, 1 – 13 GHz, Class B, min luminous intensity	19
6.10 Test equipment	19

1. CLIENT INFORMATION

The EUT has been tested by request of

Company **IKEA of Sweden AB**
 Box 702
 343 81 Älmhult
 Sweden

Name of contact **Jörgen Skoog**

2. EQUIPMENT UNDER TEST (EUT)

2.1 Identification of the EUT

Equipment **Self-ballasted LED-lamp**
 Type/Model **LED1805E22**
 Brand name 
 Serial Number -
 Manufacturer **IKEA of Sweden AB**
 Rating **120 V, 60 Hz, max 25 W**
 Class -
 Highest frequency **2405 – 2480 MHz**
 Software version -



PRECAUCIÓN:
 RIESGO DE CHOQUE ELÉCTRICO -
 USAR SOLO EN LUGARES SECOS
 NO USAR CON ATENUADORES DE LUZ
 COMUNES, VÉASE LAS INSTRUCCIONES.
 COMPONENTE INTEGRADO

RECOGNIZED COMPONENT



Intertek
3067563

120VAC/60Hz PF>0.9 Max 25W 260mA
 LED1805E22 2000lm 90lm/W 54VDC 0.39A
 MADE IN CHINA 21633 YYWW-XXX
 CCT TRÅDFRI WS CANICES005(B)/NMB-005(B)
 CONFORMS TO UL STD.8750
 CERTIFIED TO CSA STD. C22.2 NO.250.13
 CONTAINS FCC ID:FHO-ICC-A-1 AND IC:10912A-ICCA1



IKEA of Sweden AB
SE-343 81 Älmhult

ATTENTION: RISQUE DE CHOC ÉLECTRIQUE -
 UTILISER DANS UN EMPLACEMENT SEC UNIQUEMENT.
 NE PAS UTILISER AVEC DES GRADATEURS STANDARD.
 SE REPORTER A UX INSTRUCTIONS. COMPOSANT INTÉGRÉ

• tc 80 °C

CAUTION: RISK OF ELECTRIC SHOCK - USE IN DRY LOCATION ONLY.
 DO NOT USE WITH STANDARD DIMMERS, SEE INSTRUCTIONS.
 BUILT-IN COMPONENT

Rating plate

2.2 Test set up and EUT photos

Test set up and EUT photos are enclosed in Annex 1 to this test report.

2.3 Purpose of the test

The purpose of the tests was to verify that the EUT fulfills the requirements according to FCC 47 CFR Part 15: Radio frequency device, Subpart B: Unintentional radiators Class B and ICES-005 Issue 5: Lighting Equipment, Class B.

2.4 Additional information about the EUT

The EUT is a self-ballasted LED – lamp provided with a radio remote control for on/off, color setting and dimming.

The EUT has the following noted components: radio module, type ICC-A-1

The EUT was tested in a tabletop configuration.

The EUT was tested with the following cables

Port	Type	Length [m]	Specifications
AC Mains	Fixed connection	-	-

2.5 Modifications made to improve EMC-characteristics

In order to comply with the requirements regarding radiated emission 30 – 1000 MHz, the electronic is slightly modified by the manufacturer. The modification of the electronic circuit consists of adjusted component values and adding of an inductor, see table below.

Component/position	Original value	Adjusted value
C26	2.2 nF	3.3nF
R5	10 Ω	47 Ω
R1, R4	100 Ω	20 Ω
C3, C33	100 pF	220 pF
L5 (inductor)	-	10*6*5-5:5 (added component)

These modifications may also affect the EMC-characteristics regarding conducted emission, and a re-test of conducted emission is therefore performed. The previous found test result for radiated emission 1-13 GHz is deemed to be the same irrespective of the modifications.

3. TEST SPECIFICATIONS

3.1 Standards

Requirements:

FCC 47 CFR Part 15: Radio frequency device, Subpart B: Unintentional radiators.

ICES-005 Issue 5: Lighting Equipment (2018).

Test methods:

ANSI C63.4: 2014: American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Additions, deviations and exclusions from standards and accreditation

No additions, deviations or exclusions have been made from standards and accreditation.

3.3 Test site

Measurements were performed at:

Intertek Semko AB.
Torshamnsgatan 43,
P.O. Box 1103
SE-164 22 Kista

Intertek Semko AB is a FCC listed test site with site registration number 90913

Intertek Semko AB is a FCC accredited conformity assessment body with designation number SE0002

Intertek Semko AB is an Industry Canada listed test facility with IC assigned code 2042G

Measurement chambers

Measurement Chamber	Type of chamber	IC Site filing #
STORA HALLEN	Semi-anechoic 10 m and 3 m	2042G-2

3.4 Mode of operation during the test

The EUT was supplied with 120 V, 60 Hz.

Measurements were performed with the dimmer regulation set to max luminous intensity and min luminous intensity.

3.5 Compliance

The EUT shall comply with the emission limits according to the standards as listed below

Conducted emission requirements:

The EUT shall meet the limits for the standards.

Reference: 47 CFR §15.107
ICES-005, section 5.5.2

Limits for conducted emission according to FCC and ICES-005

Class B

Frequency range [MHz]	Limits [dB μ V]	
	Quasi-Peak	Average
0.15 – 0.50	66 – 56	56 – 46
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Radiated Emission requirements:

The EUT shall meet the limits for the standards.

Reference: 47 CFR §15.109
ICES-005, section 5.5.3

Limits for radiated emission according to FCC

Class B

Frequency range [MHz]	Field strength at 3 m (dB μ V/m)	Field strength at 10 m (dB μ V/m)	Detector
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.0	Quasi Peak
216 – 960	46.0	35.5	Quasi Peak
960 – 1000	54.0	43.5	Quasi Peak
Above 1000	54.0 / 74.0	43.5 / 63.5	Average / Peak

The values for 10 m measuring distance are calculated by subtracting 10.5 dB from the 3 m limit. (i.e. an extrapolation factor of 20 dB/decade according to §15.31(f)(1))

Limits for radiated emission according to ICES-005

Class B

Frequency range [MHz]	Field strength at 3 m (dB μ V/m)	Field strength at 10 m (dB μ V/m)	Detector
30 – 88	40.0	29.5	Quasi Peak
88 – 216	43.5	33.1	Quasi Peak
216 – 1000	46.0	35.6	Quasi Peak

4. TEST SUMMARY

The results in this report apply only to sample tested:

Standard	Description	Result
	Emission	
FCC Part 15 subpart B ICES-005	Conducted continuous emission in the frequency range 0.150 – 30 MHz, AC Power input port The EUT complies with the Class B limits. The margin to the limit was at least 15.5 dB at 0.179 MHz See clauses 5.4 – 5.5.	PASS
FCC Part 15 subpart B ICES-005	Radiated emission of electromagnetic fields in the frequency range 30 – 1000 MHz The EUT complies with the Class B limits. The margin to the limit was at least 2.5 dB at 63.900 MHz. The measured value is within the measurement uncertainty interval to the limit. See clauses 6.5 – 6.6.	PASS
FCC Part 15 subpart B	Radiated emission of electromagnetic fields in the frequency range 1.0 – 13 GHz The EUT complies with the Class B limits. The margin to the limit was at least 18 dB for all frequencies. See clause 6.8 – 6.9	PASS

5. CONDUCTED CONTINUOUS DISTURBANCES in the frequency-range 0,009 to 30 MHz

5.1 Operating environment

Date of test:	Temperature:	Relative Humidity:
May 23, 2019	23 [°C]	48 [%]

5.2 Test set-up and test procedure

The test method is in accordance with ANSI C63.4.

The EUT was connected to the power via Artificial Mains Networks AMN.

The EUT was placed on an insulating support 0.8 m above the floor, 0.4 m from the vertical reference ground plane (RGP) and 0.8 m from the AMN/ISN.

Overview sweeps were performed for each lead.

During the tests the EUT was operated according to the mode of operation mentioned in clause 3.4.

5.3 Measurement uncertainty


Continuous conducted disturbances with AMN
in the frequency range 150 kHz to 30 MHz

± 3.3 dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2: 2011.

The measurement uncertainty is given with a confidence of 95 %.

5.4 Test results, AC Power input port, Class B, max luminous intensity



Diagram, Peak and Average overview sweep

Measurement results, Quasi-peak, Class B

Frequency [MHz]	Level [dBµV]	Limit [dBµV]	Line L/N	Margin [dB]
0.177	48.2	64.6	N	16.4
0.179	49.0	64.5	N	15.5
0.285	43.6	60.7	N	17.1
0.321	42.4	59.7	N	17.3
0.359	42.4	58.8	N	16.4
0.465	39.7	56.6	N	16.9
1.997	37.6	56.0	L	18.4


Measurement results, Average, Class B

Frequency [MHz]	Level [dBµV]	Limit [dBµV]	Line L/N	Margin [dB]
0.215	33.8	53.0	N	19.2
0.321	30.4	49.7	N	19.3
0.463	27.9	46.6	N	18.7

All other measured disturbances have a margin of more than 20 dB to the limits.

Result [dBµV] = Analyser reading [dBµV] + cable loss [dB] + LISN insertion loss [dB]

5.5 Test results, AC Power input port, Class B, min luminous intensity



Diagram, Peak and Average overview sweep

Measurement results, Quasi-peak, Class B

All measured disturbances have a margin of more than 20 dB to the limits.

Measurement results, Average, Class B

All measured disturbances have a margin of more than 20 dB to the limits.

$$\text{Result [dB}\mu\text{V]} = \text{Analyser reading [dB}\mu\text{V]} + \text{cable loss [dB]} + \text{LISN insertion loss [dB]}$$

5.6 Test equipment

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - V10.50.00	--	--	--
Measurement Receiver	Rohde & Schwarz	ESU 8	12866	07-2018	1 year
Pulse limiter	Rohde & Schwarz	ESH3-Z2	32455	07-2018	1 year
Artificial mains network	Rohde & Schwarz	ESH3-Z5	2728	07-2018	1 year
Measurement cable	Suhner	RG 58	9815	07-2018	1 year
Measurement cable	Suhner	G03232D-01	9701	07-2018	1 year

6. RADIATED RF EMISSION IN THE FREQUENCY-RANGE 30 MHz – 13 GHz

6.1 Operating environment

Date of test:	Temperature:	Relative Humidity:
May 21, 2019	21 [°C]	52 [%]
March 25, 2019	21 [°C]	13 [%]

6.2 Test set-up and test procedure

The test method is in accordance with ANSI C63.4.

The EUT was set up according to the standard

The EUT was placed on an insulating support 0.8 m above the turntable which is part of the reference ground plane.

Overview sweeps were performed with the measurement receiver in max-hold mode and the peak detector activated in the frequency-range 30 – 1000 MHz

Above 1 GHz additionally the average detector was activated.

During height scan above 1 GHz the EUT was kept in antennas cone of radiation.

6.3 Test conditions

Test set-up:

30 – 1000 MHz

Test receiver set-up:

Preview test:

Peak, RBW 120 kHz VBW 1 MHz

Final test:

Quasi-Peak, RBW 120 kHz

Measuring distance:

3 m

Measuring angle:

0 – 359°

Antenna

Height above ground plane:

1 – 4 m

Polarisation:

Vertical and Horizontal

Type:

Bilog

Test setup:

1 – 13 GHz

Test receiver set-up:

Preview test:

Peak, RBW 1 MHz VBW 3 MHz

Final test:

Average, RBW 1 MHz

Peak, RBW 1 MHz

Measuring distance:

3 m

Measuring angle:

0 – 359°

Antenna

Height above ground plane:

1 – 4 m

Polarisation:

Vertical and Horizontal

Type:

Horn

Antenna tilt:

Activated

6.4 Measurement uncertainty

Measurement uncertainty for radiated disturbance


Uncertainty for the frequency range 30 to 1000 MHz at 3 m ± 5.1 dB

Uncertainty for the frequency range 1.0 to 18 GHz at 3 m ± 4.5 dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2: 2011.

The measurement uncertainty is given with a confidence of 95 %.

6.5 Test results, 30 – 1000 MHz, Class B, max luminous intensity



Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance.

Measurement results, Quasi Peak, Class B


Frequency [MHz]	Level [dBµV/m]	Limit [dBµV/m]	Polarization H/V	Margin [dB]
41.700	35.3	40.0	V	4.7*
43.290	35.5	40.0	V	4.5*
60.030	34.6	40.0	V	5.4*
63.900	37.5	40.0	V	2.5*
64.230	36.8	40.0	V	3.2*
103.050	32.9	43.5	V	10.6
136.800	31.3	43.5	V	12.2

The margin to the limits for the measured values are equal for FCC part 15 B and ICES-005.

*The measured result is below the limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance with the specification limit.

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

6.6 Test results, 30 – 1000 MHz, Class B, min luminous intensity



Diagram, Peak overview sweep, 30 – 1000 MHz at 3 m distance.

Measurement results, Quasi Peak, Class B

Frequency [MHz]	Level [dBµV/m]	Limit* [dBµV/m]	Polarization H/V	Margin [dB]
43.290	25.8	40.0	V	14.2
64.500	25.2	40.0	V	14.8
93.330	26.1	43.5	V	17.4


The margin to the limits for the measured values are equal for FCC part 15 B and ICES-005.

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

6.7 Test equipment

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - V10.50.0	--	--	--
Measurement Receiver	Rohde & Schwarz	ESW44	33890	02-2018	1.5 years
Antenna	Chase	CBL 6111A	971	09-2017	3 years
Pre-amplifier	SEMKO	AM1331	7992	04-2019	1 year
Measurement cable	Huber & Suhner	Sucoflex 106	39122	03-2019	1 year
Measurement cable	Rosenberger	LA5-S003-7000	39162	04-2019	1 year
Measurement cable	Rosenberger	LA5-S003-7000	39163	04-2019	1 year

6.8 Test results, 1 – 13 GHz, Class B, max luminous intensity



Diagram, Peak and average overview sweep, 1 – 13 GHz at 3 m distance.

Measurement results, Peak, Class B


No disturbance above the background noise is found, the closest margin of the background noise to the limit is 18 dB.

Measurement results, Average, Class B

No disturbance above the background noise is found, the closest margin of the background noise to the limit is 18 dB.

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

6.9 Test results, 1 – 13 GHz, Class B, min luminous intensity



Diagram, Peak and average overview sweep, 1 – 13 GHz at 3 m distance.

Measurement results, Peak, Class B

No disturbance above the background noise is found, the closest margin of the background noise to the limit is 18 dB.

Measurement results, Average, Class B

No disturbance above the background noise is found, the closest margin of the background noise to the limit is 18 dB.

Result [dBµV/m] = Analyser reading [dBµV] + Antenna factor [1/m] - Amplifier gain [dB] + Cable loss [dB]

6.10 Test equipment

Equipment type	Manufacturer	Model	Inv. No.	Last Cal. date	Cal. interval
Measurement software	Rohde & Schwarz	EMC32 - V10.50.0	--	--	--
Measurement Receiver	Rohde & Schwarz	ESW44	33890	02-2018	1.5 years
Antenna	Rohde & Schwarz	HF907	31245	12-2016	3 years
Pre-amplifier	Bonn	BLMA 0118M	312456	04-2019	1 year
Measurement cable	Huber & Suhner	Sucoflex 106	39122	03-2019	1 year
Measurement cable	Rosenberger	LA5-S003-7000	39162	04-2019	1 year
Measurement cable	Rosenberger	LA5-S003-7000	39163	04-2019	1 year