

RF Exposure Considerations for FCC ID: F15-DW201

The calculation of the MPE is as following:

Prediction of MPE limit at a prediction distance:

$$S = \frac{P.G}{4.\pi.R^2} = \frac{E.I.R.P}{4.\pi.R^2}$$

S: Power density (mW/cm²)

P: Peak output power at antenna terminal (mW)

G: Numerical Antenna gain

R: Distance of radiation to antenna (cm)

MPE calculation

Frequency (MHz)	Maximum E.I.R.P. (mW)	R (cm)	Power Density S (mW/cm ²)	MPE limit (mW/cm ²)	% of limit	Limit (%)	Verdict
2402 / 2480 (BLE mode)	2.5 (*)	20	0.0005	1.0	0.05	-	<i>Below MPE limit for uncontrolled exposure</i>
<i>Simultaneous transmissions</i>				SUM =	N/A	100%	

(*): Rated output power including tolerance. (Converted to EIRP)

Conclusion: Therefore the device complies with FCC's RF radiation exposure limits for general population for a mobile device.

Prepared By

Laurent CHAPUS (Agent for this device)

SMEE

Rue de Taille

ZI des Blanchisseries

38500 Voiron - France

laurent.chapus@smee.fr

FCC Registration Number: 0020356952 (FRN)

Applicant for this device:

MICHELIN NORTH AMERICA (US) INC.

One Parkway South

Greenville 29615 - South Carolina

Michael Flaker

michael.flaker@michelin.com

FRN: 0004506341

COORDONNEES

SMEE

Rue de Taille – ZI Des Blanchisseries

38500 VOIRON - France

TEL : 04 76 65 76 50

FAX : 04 76 66 18 30

SAS au capital de 50 000 € / RC Grenoble B534 796 453 / SIRET 534 796 453 00015 / code APE 7490B / n° TVA : FR 59 534 796 453