



MA-IS91-T2

915 MHz Subscriber Antenna

MARS 915 MHz Antenna is designed for Point-to-Multipoint systems using the ISM 915 MHz band.

Additional features:

- · High efficiency.
- Superb co-sitting performance due to high crosspol rejection.
- Unobtrusive, blends easily with the environment.
- Optionally available with Pole Mount or MNT-22 (pole/wall, azimuth and elevation adjustable mount).



Specifications

 $\alpha c \tau$	ricol
	rical

Frequency range	902-928 MHz
GAIN, min.	10.5 dBi
VSWR, max.	1.5:1
Polarization	Linear, Vertical (Horizontal with MNT-22 Option)
3 dB Beam-Width, H-Plane, typ.	55°
3 dB Beam-Width, E-Plane, typ.	60°
Side Lobes, min.	-20 dB
Cross Polarization, min.	-17 dB
Front to Back Ratio, min.	-27 dB
Input power, max	10 Watt
Input Impedance	50 Ohm
Lightning Protection	DC Grounded

Mechanical

Dimensions (HxWxD)	305 x 305 x 25 mm (12" x 12" x 1")	
Weight	1.3 kg.	
Connector	N-Type, Female	
Back Plane	Aluminum; protected through chemical passivation	
Radome	UV Protected Polycarbonate	
Mount	See Ordering Options	

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Ordering Options	
MA-IS91-T2 PM	Antenna with integral Pole Mount includes stainless steel brackets
MA-IS91-T2 MNT	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-IS91-T2 MNTB	Antenna with MNT-22 mount
MA-IS91-T2C (*)	Antenna Suited for MNT-22 (optional wall/pole adjustable mount)
MA-IS91-T2CB (*)	Antenna with MNT-22 mount

^(*) Approved by MOTOROLA for CANOPY 915 MHz System

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.