

FCC Part 15C
Measurement and Test Report
For
SIIG Inc
6078 Stewart Avenue, Fremont, CA 94538-3152,USA

FCC ID: FK3SIIGJK-WR0CG

FCC Rule(s):	<u>FCC Part 15.249</u>
Product Description:	<u>2.4GHz Wireless Optical Mouse</u>
Tested Model:	<u>JK-WR0C12-S1/ JK-X00029-1</u>
Report No.:	<u>STR14108145I</u>
Tested Date:	<u>2014-10-23 to 2014-10-29</u>
Issued Date:	<u>2014-10-29</u>
Tested By:	<u>Mark chen / Engineer</u> <i>Mark chen</i>
Reviewed By:	<u>Lahm Peng / EMC Manager</u> <i>Lahm peng</i>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u> <i>Jandyso</i>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3
1.2 TEST STANDARDS.....4
1.3 TEST METHODOLOGY.....4
1.4 TEST FACILITY.....4
1.5 EUT SETUP AND TEST MODE.....5

2. SUMMARY OF TEST RESULTS6

3. ANTENNA REQUIREMENTS.....7
3.1 STANDARD APPLICABLE.....7
3.2 TEST RESULT.....7

4. RADIATED EMISSIONS.....8
4.1 MEASUREMENT UNCERTAINTY8
4.2 STANDARD APPLICABLE.....8
4.3 TEST EQUIPMENT LIST AND DETAILS8
4.4 TEST PROCEDURE.....9
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....9
4.6 ENVIRONMENTAL CONDITIONS10
4.7 SUMMARY OF TEST RESULTS/PLOTS10

5. OUT OF BAND EMISSIONS.....19
5.1 STANDARD APPLICABLE.....19
5.2 TEST EQUIPMENT LIST AND DETAILS19
5.3 TEST PROCEDURE.....19
5.4 ENVIRONMENTAL CONDITIONS19
5.5 SUMMARY OF TEST RESULTS/PLOTS19

6. EMISSION BANDWIDTH.....22
6.1 STANDARD APPLICABLE.....22
6.2 TEST EQUIPMENT LIST AND DETAILS22
6.3 TEST PROCEDURE.....22
6.4 ENVIRONMENTAL CONDITIONS22
6.5 SUMMARY OF TEST RESULTS/PLOTS22

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: SIIG Inc
 Address of applicant: 6078 Stewart Avenue, Fremont, CA 94538-3152,
 USA
 Manufacturer: SIIG Inc
 Address of manufacturer: 6078 Stewart Avenue, Fremont, CA 94538-3152,
 USA

General Description of EUT	
Product Name:	2.4GHz Wireless Optical Mouse
Trade Name:	SIIG
Model No.:	JK-WR0C12-S1/ JK-X00029-1
Adding Model(s):	JK-WR0D12-S1/ JK-X00030-1; JK-WR0E12-S1/ JK-X00031-1; JK-WR0F12-S1/ JK-X00032-1; JK-WR0G12-S1/ JK-X00033-1
Rated Voltage:	Battery:3V
Power Adapter Model:	/
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model JK-WR0C12-S1/ JK-X00029-1, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Frequency Range:	2424-2477MHz
Max. Field Strength:	83.73 dBuV/m (at 3m distance)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	54
Channel Separation:	1MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-1dBi
Lowest Internal Frequency of EUT:	12MHz

1.2 Test Standards

The following report is prepared on behalf of the SIIG Inc in accordance with FCC Part 15, Subpart B, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.107,15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2424MHz
TM2	Middle Channel	2454MHz
TM3	High Channel	2477MHz

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	lenovo	E10	N/A

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215 (c)	Emission Bandwidth	Compliant

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

4.2 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.3 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2014-05-24	2015-05-23

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBµV means the emission is 6dBµV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.6 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar

4.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst margin of:

-13.91 dB at 900.1474 MHz in the Horizontal polarization, Low Channel, 9 kHz to 25 GHz, 3Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: 2.4GHz Wireless Optical Mouse
 Tested Model: JK-WROC12-S1/ JK-X00029-1
 Operating Condition: Transmitting Low Channel (2424MHz)
 Comment: Battery:3V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.9948	23.22	-7.45	15.77	40.00	-24.23	105	100	peak
2	192.4186	26.88	-9.81	17.07	43.50	-26.43	127	100	peak
3	348.0274	28.09	-4.31	23.78	46.00	-22.22	169	100	peak
4*	900.1474	26.71	5.38	32.09	46.00	-13.91	181	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1*	73.3593	32.85	-12.73	20.12	40.00	-19.88	125	100	peak
2	110.1816	29.18	-9.63	19.55	43.50	-23.95	139	100	peak
3	122.4040	32.53	-11.63	20.90	43.50	-22.60	184	100	peak
4	282.9852	28.39	-6.62	21.77	46.00	-24.23	201	100	peak

Operating Condition: Transmitting Middle Channel (2454MHz)


Comment: Battery:3V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.3402	23.23	-7.46	15.77	40.00	-24.23	115	100	peak
2	97.4560	23.13	-9.87	13.26	43.50	-30.24	128	100	peak
3	372.0045	27.15	-3.78	23.37	46.00	-22.63	149	100	peak
4*	909.6667	23.56	5.49	29.05	46.00	-16.95	167	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1*	53.1313	23.91	-7.76	16.15	40.00	-23.85	116	100	peak
2	119.4361	27.52	-11.17	16.35	43.50	-27.15	147	100	peak
3	160.3457	29.09	-12.32	16.77	43.50	-26.73	195	100	peak
4	216.7828	30.95	-8.93	22.02	46.00	-23.98	224	100	peak

Operating Condition: Transmitting High Channel (2477MHz)


Comment: Battery:3V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	46.5030	23.62	-7.46	16.16	40.00	-23.84	125	100	peak
2	101.2885	23.07	-9.56	13.51	43.50	-29.99	149	100	peak
3	225.3080	29.66	-8.61	21.05	46.00	-24.95	167	100	peak
4*	396.2415	26.43	-3.06	23.37	46.00	-22.63	188	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	1*	47.8260	23.95	-7.46	16.49	40.00	-23.51	122	100
2	2	115.7256	29.81	-10.55	19.26	43.50	-24.24	134	100
3*	3	177.5092	28.47	-11.31	17.16	43.50	-26.34	149	100
4	4	234.9909	26.79	-8.06	18.73	46.00	-27.27	167	100

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2424MHz							
2424	80.55	-3.46	77.09	114	-36.91	H	PK
2424	69.15	-3.46	65.69	94	-28.31	H	AV
4848	42.45	0.60	43.05	74	-30.95	H	PK
4848	32.77	0.60	33.37	54	-20.63	H	AV
7272	34.84	3.72	38.56	74	-35.44	H	PK
7272	26.07	3.82	29.89	54	-24.11	H	AV
2424	83.96	-3.46	80.50	114	-33.50	V	PK
2424	72.64	-3.46	69.18	94	-24.82	V	AV
4848	42.66	0.60	43.26	74	-30.74	V	PK
4848	31.54	0.94	32.48	54	-21.52	V	AV
7272	36.58	3.72	40.30	74	-33.70	V	PK
7272	26.14	3.82	29.96	54	-24.04	V	AV
Middle Channel-2454 MHz							
2454	86.69	-3.38	83.31	114	-30.69	H	PK
2454	72.19	-3.38	68.81	94	-25.19	H	AV
4908	44.95	0.70	45.65	74	-28.35	H	PK
4908	32.71	0.70	33.41	54	-20.59	H	AV
7362	37.34	3.79	41.13	74	-32.87	H	PK
7362	26.06	3.82	29.88	54	24.12	H	AV
2454	84.29	-3.38	80.91	114	-33.09	V	PK
2454	69.77	-3.38	66.39	94	-27.61	V	AV
4908	44.90	0.70	45.60	74	-28.40	V	PK
4908	32.65	0.70	33.35	54	-20.65	V	AV
7362	37.57	3.79	41.36	74	-32.64	V	PK
7362	26.09	3.82	29.91	54	-24.09	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2477MHz							
2477	87.06	-3.33	83.73	114	-30.27	H	PK
2477	75.83	-3.33	72.50	94	-21.50	H	AV
4954	42.44	0.70	43.14	74	-30.86	H	PK
4954	32.15	0.77	32.92	54	-21.08	H	AV
7431	37.90	3.84	41.74	74	-32.26	H	PK
7431	26.05	3.82	29.87	54	-24.13	H	AV
2477	84.05	-3.33	80.72	114	-33.28	V	PK
2477	72.81	-3.33	69.48	94	-24.52	V	AV
4954	43.91	0.76	44.67	74	-29.37	V	PK
4954	32.27	0.77	33.04	54	-20.96	V	AV
7431	37.37	3.84	41.21	74	-32.79	V	PK
7431	26.12	3.82	29.94	54	-24.06	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The measurements greater than 20dB below the limit from 9kHz to 30MHz..

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2014-05-28	2015-05-27
EMI Test Receiver	R&S	ESVB	825471/005	2014-05-28	2015-05-27
Pre-amplifier	Agilent	8447F	3113A06717	2014-05-28	2015-05-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2014-05-28	2015-05-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2014-05-24	2015-05-23
Horn Antenna	ETS	3117	00086197	2014-05-24	2015-05-23

5.3 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

5.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	60 %
ATM Pressure:	1012 mbar


5.5 Summary of Test Results/Plots

Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
	2400.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.


Please refer to the test plots as below.

Lowest Bandedge



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	23.37	16.34	39.71	54.00	-14.29	Ave Detector
	2310.000	35.71	16.34	52.05	74.00	-21.95	Peak Detector
2	2390.000	22.92	17.03	39.95	54.00	-14.05	Ave Detector
	2390.000	36.00	17.03	53.03	74.00	-20.97	Peak Detector
3	2400.000	22.99	17.11	40.10	54.00	-13.90	Ave Detector
	2400.000	35.12	17.11	52.23	74.00	-21.77	Peak Detector
4	2424.000	66.34	17.29	83.63	/	/	Ave Detector

Highest Bandedge



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2477.050	65.78	17.69	83.47	/	/	Average Detector
	2477.050	66.06	17.69	83.75	/	/	Peak Detector
2	2483.500	22.80	17.73	40.53	54.00	-13.47	Average Detector
	2483.500	32.71	17.73	50.44	74.00	-23.56	Peak Detector
3	2500.000	22.84	17.86	40.70	54.00	-13.30	Average Detector
	2500.000	31.54	17.86	49.40	74.00	-24.60	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2014-05-28	2015-05-27
Attenuator	ATTEN	ATS100-4-20	/	2014-05-28	2015-05-27

6.3 Test Procedure

According to the ANSI 63.4-2003, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW \geq 1% 20dB Bandwidth, VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.4 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.5 Summary of Test Results/Plots


Channel	Frequency MHz	20dB Bandwidth kHz	99% Bandwidth kHz
Low Channel	2424	126.894	129.4911
Middle Channel	2454	116.845	159.2337
High Channel	2477	145.455	205.5033

Please refer to the following test plots


Low Channel:



Middle Channel:



High Channel:



***** END OF REPORT *****