

KEYPAD

K622

FCC ID : FKD46AK622

FEDERAL COMMUNICATIONS COMMISSION

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

NOTE

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Shielded interface cables must be used in order to comply with emission limits.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

1. Scope:

The MONTEREY Slim Key PAD K622 is 18/19 keys standard numeric layout. It is compatible with IBM PC USB and compatible personal computer.

2. Features:

- ✧ Fashion Styling
- ✧ 18/19 standard numeric layout
- ✧ Microsoft Windows compatible
- ✧ IBM PC USB compatible
- ✧ Laser engraved printing
- ✧ Nice feeling, light touch membrane tactile switches
- ✧ Compact low profile

3. Specification:


3.1 Power Requirement

Input Voltage: DC 4.75V to 5.25V

Input Current: 300 mA max.

3.2 Cable Connector

PIN	SIGNAL
G	Ground
D+	VP
D-	VM
V	VCC
Shield	Frame Ground



3.3 Contact Resistance : 500 ohm Max.

3.4 Insulation Resistance : 100 ohm, 250V DC

3.5 Bounce : • 10 MilliSecond