



FCC ID: FKGR1101



Page: 1 / 42  
Rev.: 00

## FCC TEST REPORT

For

Module

Trade Name: DURABOOK

Model:9260NGW

Issued to

TWINHEAD INTERNATIONAL CORP.

11F, No 550, Rueiguang Rd , Neihu, Taipei, Taiwan 11492, R.O.C.

Issued by

Compliance Certification Services Inc.

No.11, Wugong 6th Rd., Wugu Dist.,

New Taipei City 24891,

Taiwan. (R.O.C.)

<http://www.ccsrf.com>

[service@ccsrf.com](mailto:service@ccsrf.com)

Issued Date: 2018/11/14

**Note:** This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Compliance Certification Services Inc. No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan / 新北市五股區五工六路 11 號

程智科技股份有限公司

t (886-2) 2299-9720 f (886-2) 2298-1882 [www.ccsrf.com](http://www.ccsrf.com)

Member of SGS Group



Report No.: T180918D06-SF

Page 2 / 42  
Rev. 00

### Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2018/11/14	Initial Issue	ALL	Stella Chang

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Compliance Certification Services Inc.

程智科技股份有限公司

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan / 新北市五股區五工六路 11 號

t (886-2) 2299-9720 f (886-2) 2298-1882 www.ccsrf.com

Member of SGS Group



Report No.: T180918D06-SF

Page 3 / 42  
Rev. 00

## Table of Contents

<b>1</b>	<b>Certificate of Compliance (SAR Evaluation)</b>	<b>5</b>
<b>2</b>	<b>Description of Equipment Under Test</b>	<b>6</b>
2.1	Summary of Highest SAR Values	7
<b>3</b>	<b>Requirements for Compliance Testing Defined</b>	<b>8</b>
3.1	Requirements for Compliance Testing Defined by the FCC	8
<b>4</b>	<b>Dosimetric Assessment System</b>	<b>9</b>
4.1	Measurement System Diagram	10
4.2	System Components	12
<b>5</b>	<b>Evaluation Procedures</b>	<b>15</b>
<b>6</b>	<b>SAR Measurement Procedures</b>	<b>17</b>
6.1	Normal SAR Test Procedure	17
<b>7</b>	<b>Device Under Test</b>	<b>19</b>
7.1	Wireless Technologies	19
7.2	Maximum Tune-up Power	20
7.3	Wi-Fi (2.4GHz Band)	21
7.4	Wi-Fi (5GHz Band)	22
7.5	Bluetooth	25
<b>8</b>	<b>Summary of SAR Test Exclusion Configurations</b>	<b>26</b>
8.1	Standalone SAR Test Exclusion Calculations	26
8.1.1	SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User	27
8.1.2	SAR Exclusion Calculations for WWAN & WLAN Antenna > 50mm from the User	28
8.1.3	SAR Required Test Configuration	29
<b>9</b>	<b>Exposure Limit</b>	<b>30</b>
<b>10</b>	<b>Tissue Dielectric Properties</b>	<b>31</b>
10.1	Test Liquid Confirmation	31
10.2	Typical Composition of Ingredients for Liquid Tissue Phantoms	32
10.3	Simulating Liquids Parameter Check Results	33
<b>11</b>	<b>Measurement Uncertainty</b>	<b>34</b>
<b>12</b>	<b>System Performance Check</b>	<b>35</b>
12.1	System Performance Check Results	36
<b>13</b>	<b>SAR Measurements Results</b>	<b>37</b>
<b>14</b>	<b>Equipment List &amp; Calibration Status</b>	<b>40</b>
<b>15</b>	<b>Facilities</b>	<b>41</b>

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。



Report No.: T180918D06-SF

Page 4 / 42  
Rev. 00

16 Reference.....41

17 Attachments.....42

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

**1 Certificate of Compliance (SAR Evaluation)**

**Applicant** TWINHEAD INTERNATIONAL CORP.  
11F, No 550, Rueiguang Rd , Neihsu, Taipei, Taiwan 11492, R.O.C.

**Equipment Under Test:** Module

**Trade Name:** DURABOOK

**Model Number:** 9260NGW

**Date of Test:** November 12,13 , 2018

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	<ul style="list-style-type: none"> <li>● IEEE 1528 2013</li> <li>● KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04</li> <li>● KDB 865664 D02 RF Exposure Reporting v01r02</li> <li>● KDB 447498 D01 General RF Exposure Guidance v06</li> <li>● KDB 616217 D04 SAR for laptop and tablets v01r02</li> <li>● KDB 248227 D01 SAR Meas for 802.11 v02r02</li> </ul>
Limit	
1.6 W/kg	
Test Result	
Pass	

The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Tested by:




Scott Hsu  
Section Manager  
Compliance Certification Services Inc.

Stella Chang  
SAR Engineer  
Compliance Certification Services Inc.

## 2 Description of Equipment Under Test

Product	Module		
Trade Name	DURABOOK		
Model Number	9260NGW		
WLAN Module	Intel 9260NGW		
Test Software	DRTU	Version	18.40.0.2
Modulation Technique	Bluetooth:GFSK for 1Mbps; $\pi$ /4-DQPSK for 2Mbps;8DPSK for 3Mbps		
	802.11a: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11b: Direct Sequence Spread Spectrum(DSSS)		
	802.11g: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11n: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11ac: Orthogonal Frequency Division Multiplexing (OFDM)		
WLAN Antenna Specification	Brand name	Durabook Americas inc	
	Parts Number	Main:TWAH6WIPB01+A	
		Aux:TWAH6WIPB02+A	
	Type	PIFA	
Rechargeable Li-polymer Battery–alternate	Brand:Lithium Polymer Model:R11AH Rating:11.1V / 3.95Ah		

**Remark:**

- 1.The sample selected for test was prototype that representative to production product and was provided by manufacturer

## 2.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode.

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
WiFi 2.4 GHz	Edge 1	802.11b	0.769
Wi-Fi 5.3 GHz(U-NII 2A)	Edge 2	802.11a	0.831
Wi-Fi 5.5 GHz(U-NII 2C)	Edge 2	802.11ac	1.058
Wi-Fi 5.8 GHz(U-NII 3)	Edge 2	802.11a	1.196

### 3 Requirements for Compliance Testing Defined

#### 3.1 Requirements for Compliance Testing Defined by the FCC


The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the FCC 47 CFR §2.1093 and IEEE Std 1528-2013.



## 4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY4/DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3665 & EX3DV4-SN: 3831 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2013.

Report No.: T180918D06-SF

**4.1 Measurement System Diagram**

The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7
- DASY4 software version: 4.7, Build 80.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid
- 
- 

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

**Report No.:** T180918D06-SF

Page 11 / 42  
Rev. 00

- 
- mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

Report No.: T180918D06-SF

**4.2 System Components****DASY4/DASY5 Measurement Server**

The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

**Data Acquisition Electronics (DAE)**

The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

**EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements**


**Construction:** Symmetrical design with triangular core  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

**Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.

**Frequency:** 10 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)

**Directivity:**  $\pm 0.3$  dB in HSL (rotation around probe axis)  
 $\pm 0.5$  dB in HSL (rotation normal to probe axis)

**Dynamic Range:** 10  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB  
(noise: typically < 1  $\mu$ W/g)



**Dimensions:** Overall length: 330 mm (Tip: 20 mm)  
Tip diameter: 2.5 mm (Body: 12 mm)  
Distance from probe tip to dipole centers: 1 mm

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

**SAM Phantom (V4.0)**

**Construction:** The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 2013, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

**Shell Thickness:**  $2 \pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 810mm; Length: 1000mm; Width: 500mm

**SAM Phantom (ELI4)**

**Construction:** Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

**Shell Thickness:**  $2.0 \pm 0.2$  mm (sagging: <1%)


**Filling Volume:** Approx. 25 liters

**Dimensions:** Major ellipse axis: 600 mm  
Minor axis: 400 mm 500mm

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

**Device Holder for SAM Twin Phantom**

**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).

**System Validation Kits for SAM Phantom (V4.0)**

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )

**Dimensions:** D2450V2: dipole length: 52.0 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

**System Validation Kits for ELI4 phantom**

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W ( $f < 1\text{GHz}$ ); > 40 W ( $f > 1\text{GHz}$ )

**Dimensions:** D2450V2: dipole length: 52.0 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

## 5 Evaluation Procedures

### Data Evaluation

The DASY4/DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	$dcp_i$
Device parameters:	- Frequency	$f$
	- Crest factor	$cf$
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$U_i$	= Input signal of channel i	(i = x, y, z)
	$cf$	= Crest factor of exciting field	(DASY parameter)
	$dcp_i$	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:

$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)

$\mu V/(V/m)^2$  for E0field Probes

$ConvF$	= Sensitivity enhancement in solution
$a_{ij}$	= Sensor sensitivity factors for H-field probes
$f$	= Carrier frequency (GHz)
$E_i$	= Electric field strength of channel i in V/m
$H_i$	= Magnetic field strength of channel i in A/m

**Report No.:** T180918D06-SF

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

$SAR$  = local specific absorption rate in W/kg

$E_{tot}$  = total field strength in V/m

$\sigma$  = conductivity in [mho/m] or [Siemens/m]

$\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

$P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m



## 6 SAR Measurement Procedures

### 6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency  $\leq 2\text{GHz}$ ; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04

	$\leq 3\text{ GHz}$	$> 3\text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1\text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5\text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$	$\leq 2\text{ GHz}: \leq 15\text{ mm}$ $2 - 3\text{ GHz}: \leq 12\text{ mm}$	$3 - 4\text{ GHz}: \leq 12\text{ mm}$ $4 - 6\text{ GHz}: \leq 10\text{ mm}$
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Report No.: T180918D06-SF

### • Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency  $\leq 2$ GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04

			$\leq 3$ GHz	$> 3$ GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm	3 – 4 GHz: $\leq 5$ mm 4 – 6 GHz: $\leq 4$ mm
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$ :between 1 <sup>st</sup> two points losest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{\text{Zoom}}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Maximum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	

### • Power Drift Measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

### • Z-Scan

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

## 7 Device Under Test

### 7.1 Wireless Technologies

Wireless technologies	Tx Frequency Bands	Operating mode	Duty Cycle used for testing
WI-FI	2.4GHz Band	802.11b 802.11g 802.11n(HT20) 802.11n(HT40)	100%
	5GHz Band	802.11a 802.11n(HT20) 802.11n(HT40) 802.11ac(VHT80)	100%
Bluetooth	Bluetooth	2.1 4.1 LE 5.0	N/A

## 7.2 Maximum Tune-up Power

Tolerance (dB): $\pm 1$		RF Output Power (dBm)	
Band (GHz)	Mode	Target	Max. tune-up power
2.4	802.11b	19.00	20.00
	802.11g	19.00	20.00
	802.11n HT20	19.00	20.00
	802.11n HT40	14.50	15.50
Tolerance (dB): $\pm 1$		RF Output Power (dBm)	
Band (GHz)	Mode	Target	Max. tune-up power
5.2 (UNII-1)	802.11a	19.00	20.00
	802.11n HT20	19.00	20.00
	802.11n HT40	17.50	18.50
	802.11ac VHT80	16.25	17.25
5.3 (UNII-2A)	802.11a	19.00	20.00
	802.11n HT20	19.00	20.00
	802.11n HT40	17.00	18.00
	802.11ac VHT80	15.00	16.00
5.5 (UNII-2C)	802.11a	19.00	20.00
	802.11n HT20	19.00	20.00
	802.11n HT40	19.00	20.00
	802.11ac VHT80	19.00	20.00
5.8 (UNII-3)	802.11a	19.00	20.00
	802.11n HT20	19.00	20.00
	802.11n HT40	18.50	19.50
	802.11ac VHT80	18.00	19.00
Mode		Max. tune-up power	
Bluetooth		9.0	
Bluetooth LE		6.0	
Bluetooth 5.0		3.0	

### 7.3 Wi-Fi (2.4GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)			SAR Test (Yes/No)	Note
					Main	Aux	MIMO	Main	Aux	MIMO		
2.4	802.11b	1	1	2412	18.50	18.60		18.75	19.00		Yes	
			6	2437	19.58	19.60		20.00	20.00			
			11	2462	19.44	19.50		20.00	20.00			
	802.11g	6	1	2412	No Required			15.50	16.00		No	1
			6	2437				20.00	20.00			
			11	2462				20.00	20.00			
	802.11n HT20	MCS0	1	2412	No Required			15.50	16.00	13.50	No	1
			6	2437				20.00	20.00	17.00		
			11	2462				15.50	15.70	14.00		
	802.11n HT40	MCS0	3	2422	Not Required			13.00	12.50	11.00	No	1
			6	2437				15.50	15.50	13.50		
			9	2452				14.00	13.50	12.00		

#### Note(s):

- Output Power and SAR is not required for 802.11 g/n HT20/n HT40 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

## 7.4 Wi-Fi (5GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)			SAR Test (Yes/No)	Note
					Main	Aux	MIMO	Main	Aux	MIMO		
5.2 (U-NII 1)	802.11a	6	36-48	5180-5240	Not Required			20.00	20.00		No	1
	802.11n (HT20)	MCS0	36-48	5180-5240				20.00	20.00		No	1
	802.11n (HT40)	MCS0	38-46	5190-5230				18.50	18.00		No	1
	802.11ac (VHT80)	VHT0	42	5210				17.25	17.25		No	1
	802.11ac (VHT160)	VHT0	50	5250				12.50	12.50		No	1
	802.11a	6	36-48	5180-5240	Not Required			15.0	15.0	18.0	No	1
	802.11n (HT20)	MCS0	36-48	5180-5240				15.0	15.0	18.0	No	1
	802.11n (HT40)	MCS0	38-46	5190-5230				14.5	14.5	17.5	No	1
	802.11ac (VHT80)	VHT0	42	5210				11.0	11.0	14.0	No	1
	802.11ac (VHT160)	VHT0	50	5250				7.0	7.0	10.0	No	1
5.3 (U-NII 2A)	802.11a	6	52	5745	19.68	19.86		20.00	20.00		Yes	
		6	56	5765	19.60	19.60		20.00	20.00		Yes	
		6	60	5785	19.48	19.79		20.00	20.00		Yes	
		6	64	5805	16.18	16.15		20.00	20.00		Yes	
	802.11n (HT20)	MCS0	52-64	5260-5320	Not Required			20.00	20.00		No	2
	802.11n (HT40)	MCS0	54-62	5270-5310				18.00	18.00		No	2
	802.11ac (VHT80)	VHT0	58	5290				16.00	15.00		No	2
	802.11a	6	52	5745	14.4	14.3	17.4	15.0	15.0	18.0	No	2
		6	56	5765	14.1	14.1	17.1	15.0	15.0	18.0	No	2
		6	60	5785	14.2	14.2	17.2	15.0	15.0	18.0	No	2
		6	64	5805	12.4	12.4	15.4	15.0	15.0	18.0	No	2
	802.11n (HT20)	MCS0	52-64	5260-5320	Not Required			15.0	15.0	18.0	No	2
	802.11n (HT40)	MCS0	54-62	5270-5310				14.0	14.0	17.0	No	2
	802.11ac (VHT80)	VHT0	58	5290				10.5	10.5	13.5	No	2

### Note(s):

- When the specified maximum output power is the same for both UNII band I and UNII band 2A, begin SAR measurement in UNII band 2A; and if the highest reported SAR for UNII band 2A is
  - $1.1 \leq 1.2$  W/kg, SAR is not required for UNII band I.
  - $1.2 > 1.2$  W/kg, both bands should be tested independently for SAR.
- Output Power and SAR measurement is not required for 802.11n HT20/n HT40/802.11ac channels when the specified maximum tune-up powers are less or same with 802.11a.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Report No.: T180918D06-SF

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)			SAR Test (Yes/No)	Note
					Main	Aux	MIMO	Main	Aux	MIMO		
5.5 (U-NII-2C)	802.11a	6	100-140	5500-5700	Not Required			20.00	20.00		No	1
	802.11n (HT20)	MCS0	100-144	5500-5720				20.00	20.00		No	1
	802.11n (HT40)	MCS0	102-142	5510-5710				20.00	20.00		No	1
	802.11ac (VHT80)	VHT0	106	5530	16.72	16.10		17.00	16.50		Yes	
		VHT0	122	5610	19.66	19.68		20.00	20.00		Yes	
		VHT0	138	5690	19.48	19.51		20.00	20.00		No	
	802.11ac (VHT160)	VHT0	114	5570	Not Required			14.50	14.25		No	1
	802.11a	6	100-140	5500-5700	Not Required			15.0	15.0	18.0	No	1
	802.11n (HT20)	MCS0	100-144	5500-5720				15.0	15.0	18.0	No	1
	802.11n (HT40)	MCS0	102-142	5510-5710				15.0	15.0	18.0	No	1
	802.11ac (VHT80)	VHT0	106	5530	11.2	11.2	14.2	11.5	11.5	14.5	No	1
		VHT0	122	5610	14.2	14.2	17.2	15.0	15.0	18.0	No	1
		VHT0	138	5690	14.3	14.2	17.3	15.0	15.0	18.0	No	1
	802.11ac (VHT160)	VHT0	114	5570	Not Required			10.0	10.0	13.0	No	1

## Note(s):

- Output Power and SAR measurement is not required for 802.11 a/ 802.11n HT20/n HT40 channels when the specified maximum tune-up powers are less or same with 802.11ac.

Report No.: T180918D06-SF

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)			SAR Test (Yes/No)	Note
					Main	Aux	MIMO	Main	Aux	MIMO		
5.8 (U-NII-3)	802.11a	6	149	5745	19.88	19.93		20.00	20.00		Yes	
		6	153	5765	19.75	19.81		20.00	20.00		Yes	
		6	157	5785	19.81	19.83		20.00	20.00		Yes	
		6	161	5805	19.80	19.73		20.00	20.00		Yes	
		6	165	5825	19.75	19.76		20.00	20.00		Yes	
	802.11n (HT20)	MCS0	149-165	5745-5825	Not Required			20.00	20.00		No	1
	802.11n (HT40)	MCS0	151-159	5755-5795				19.50	19.50		No	1
	802.11ac (VHT80)	VHT0	155	5775				18.50	19.00		No	1
	802.11a	6	149	5745	14.4	14.3	17.4	15.0	15.0	18.0	No	1
		6	153	5765	14.3	14.3	17.3	15.0	15.0	18.0	No	1
		6	157	5785	14.4	14.4	17.4	15.0	15.0	18.0	No	1
		6	161	5805	14.4	14.3	17.3	15.0	15.0	18.0	No	1
		6	165	5825	14.4	14.2	17.3	15.0	15.0	18.0	No	1
	802.11n (HT20)	MCS0	149-165	5745-5825	Not Required			15.0	15.0	18.0	No	1
	802.11n (HT40)	MCS0	151-159	5755-5795				14.5	14.5	17.5	No	1

## Note(s):

- Output Power and SAR measurement is not required for 802.11n HT20/n HT40/802.11ac channels when the specified maximum tune-up powers are less or same with 802.11a.



## **7.5 Bluetooth**

Per exclusion calculations in Section 11, SAR testing for Bluetooth is not required

## 8 Summary of SAR Test Exclusion Configurations

### 8.1 Standalone SAR Test Exclusion Calculations

Since the Dedicated Host Approach is applied, the standalone SAR test exclusion procedure in KDB 447498 section 4.3.1 is applied in conjunction with KDB 616217 section 4.3 to determine the minimum test separation distance:

1. According to KDB 447498 Section 4.1 5) if the antenna is at close proximity to user then the outer surface of the DUT should be treated as the radiating surface. The test separation distance is then determined by the smallest distance between the outer surface of the device and the user. For the purposes of this report close proximity has been defined as closer than 50 mm. For antennas <50 mm from the rear or edge the separation distance used for the estimated SAR calculations is 0 mm.
2. When the minimum test separation distance is < 5mm, a distance of 5mm is applied to determine SAR test exclusion.
3. When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.
4. If the antenna to DUT adjacent edge or bottom separation distance >50mm the actual antenna to user separation distance is used to determine SAR exclusion and estimated SAR value.

Refer to Appendix for the specific details on the antenna-to-antenna and antenna-to-edge distances used for test exclusion calculations.

**8.1.1 SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User**

According to KDB 447498 v06 r02 in section 4.3.1, if the calculated threshold value is > 3 then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	20.00	100	15.00	19.20	222.86	179.14	50.50	10.41	8.13	>50mm	>50mm	>50mm
	5.3GHz	5280	20.00	100	15.00	19.20	222.86	179.14	50.50	15.32	11.97	>50mm	>50mm	>50mm
	5.5GHz	5580	20.00	100	15.00	19.20	222.86	179.14	50.50	15.75	12.30	>50mm	>50mm	>50mm
	5.8GHz	5745	20.00	100	15.00	19.20	222.86	179.14	50.50	15.98	12.48	>50mm	>50mm	>50mm

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	20.00	100	2.87	33.75	7.95	128.20	298.75	31.22	4.63	19.64	>50mm	>50mm
	5.3GHz	5280	20.00	100	2.87	33.75	7.95	128.20	298.75	45.96	6.81	28.90	>50mm	>50mm
	5.5GHz	5580	20.00	100	2.87	33.75	7.95	128.20	298.75	47.24	7.00	29.71	>50mm	>50mm
	5.8GHz	5745	20.00	100	2.87	33.75	7.95	128.20	298.75	47.94	7.10	30.15	>50mm	>50mm
	Bluetooth	2441	9.00	8	2.87	33.75	7.95	128.20	298.75	2.50	0.37	1.57	>50mm	>50mm

### 8.1.2 SAR Exclusion Calculations for WWAN & WLAN Antenna > 50mm from the User

According to KDB 447498 v06 r02, if the calculated Power threshold is less than the output power then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	20.00	100	15.00	19.20	222.86	179.14	50.50	<50mm	<50mm	1824.69	1387.49	101.09
	5.3GHz	5280	20.00	100	15.00	19.20	222.86	179.14	50.50	<50mm	<50mm	1793.88	1356.68	70.28
	5.5GHz	5580	20.00	100	15.00	19.20	222.86	179.14	50.50	<50mm	<50mm	1792.10	1354.90	68.50
	5.8GHz	5745	20.00	100	15.00	19.20	222.86	179.14	50.50	<50mm	<50mm	1791.18	1353.98	67.58

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	20.00	100	2.87	33.75	7.95	128.20	298.75	<50mm	<50mm	<50mm	878.09	2961.84
	5.3GHz	5280	20.00	100	2.87	33.75	7.95	128.20	298.75	<50mm	<50mm	<50mm	847.28	2961.84
	5.5GHz	5580	20.00	100	2.87	33.75	7.95	128.20	298.75	<50mm	<50mm	<50mm	845.50	2961.84
	5.8GHz	5745	20.00	100	2.87	33.75	7.95	128.20	298.75	<50mm	<50mm	<50mm	844.58	2961.84
	Bluetooth	2441	9.00	8	2.87	33.75	7.95	128.20	298.75	<50mm	<50mm	<50mm	878.01	4164.55

### 8.1.3 SAR Required Test Configuration

Test Configurations	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main 2.4GHz	YES	YES	No	No	No
Wi-Fi Main 5.2GHz	YES	YES	No	No	No
Wi-Fi Main 5.3GHz	YES	YES	No	No	No
Wi-Fi Main 5.5GHz	YES	YES	No	No	No
Wi-Fi Main 5.8GHz	YES	YES	No	No	No
Wi-Fi Aux 2.4GHz	YES	YES	YES	No	No
Wi-Fi Aux 5.2GHz	YES	YES	YES	No	No
Wi-Fi Aux 5.3GHz	YES	YES	YES	No	No
Wi-Fi Aux 5.5GHz	YES	YES	YES	No	No
Wi-Fi Aux 5.8GHz	YES	YES	YES	No	No
Bluetooth	No	No	No	No	No

#### Note(s):

1. Yes = SAR is required.
2. No = SAR is not required.

## 9 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

### Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

### Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

**NOTE**  
**GENERAL POPULATION/UNCONTROLLED EXPOSURE**  
**PARTIAL BODY LIMIT**  
**1.6 W/kg**

## 10 Tissue Dielectric Properties

### 10.1 Test Liquid Confirmation

#### Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below.  $5\%$  may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2013

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Report No.: T180918D06-SF

**10.2 Typical Composition of Ingredients for Liquid Tissue Phantoms**

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ<sup>+</sup> resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

**Simulating Liquids for 5 GHz, Manufactured by SPEAG**

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2



## 10.3 Simulating Liquids Parameter Check Results

Date	Band	Freq(MHz)	Measured			Standard		$\Delta$		Limit (%)
			e' ( $\epsilon_r$ )	e''	$\sigma$	e' ( $\epsilon_r$ )	$\sigma$	e' ( $\epsilon_r$ )	$\sigma$	
2018/11/12	Head 2450	2412	37.46	12.77	1.71	39.27	1.77	-4.60%	-3.13%	$\pm 5$
		2437	37.43	12.85	1.74	39.22	1.79	-4.57%	-2.74%	$\pm 5$
		2442	37.42	12.86	1.74	39.21	1.79	-4.57%	-2.68%	$\pm 5$
		2450	37.41	12.89	1.75	39.20	1.80	-4.57%	-2.51%	$\pm 5$
		2462	37.38	12.94	1.77	39.18	1.81	-4.60%	-2.35%	$\pm 5$
		2472	37.35	12.97	1.78	39.17	1.82	-4.65%	-2.31%	$\pm 5$
2018/11/13	Head 5000	5180	36.56	15.98	4.60	36.02	4.64	1.51%	-0.86%	$\pm 5$
		5200	36.52	15.98	4.62	36.00	4.66	1.45%	-0.92%	$\pm 5$
		5220	36.50	15.97	4.63	35.98	4.68	1.45%	-1.01%	$\pm 5$
		5240	36.47	15.97	4.65	35.96	4.70	1.40%	-1.07%	$\pm 5$
		5260	36.44	16.01	4.68	35.94	4.72	1.38%	-0.90%	$\pm 5$
		5280	36.41	16.03	4.70	35.92	4.74	1.38%	-0.80%	$\pm 5$
		5300	36.39	16.02	4.72	35.87	4.76	1.44%	-0.87%	$\pm 5$
		5320	36.35	16.03	4.74	35.88	4.78	1.32%	-0.91%	$\pm 5$
		5500	36.09	16.13	4.93	35.60	4.96	1.36%	-0.66%	$\pm 5$
		5520	36.07	16.12	4.94	35.58	4.98	1.38%	-0.79%	$\pm 5$
		5540	36.05	16.12	4.96	35.56	5.00	1.37%	-0.86%	$\pm 5$
		5560	36.01	16.09	4.97	35.54	5.03	1.31%	-1.13%	$\pm 5$
		5580	35.95	16.11	4.99	35.52	5.05	1.21%	-1.08%	$\pm 5$
		5600	35.92	16.15	5.02	35.50	5.07	1.17%	-0.92%	$\pm 5$
		5620	35.91	16.16	5.04	35.48	5.09	1.22%	-0.89%	$\pm 5$
		5640	35.89	16.17	5.07	35.46	5.11	1.22%	-0.85%	$\pm 5$
		5660	35.88	16.15	5.08	35.44	5.13	1.23%	-1.02%	$\pm 5$
		5680	35.82	16.13	5.09	35.42	5.15	1.12%	-1.14%	$\pm 5$
		5700	35.77	16.17	5.12	35.40	5.17	1.04%	-0.97%	$\pm 5$
		5745	35.73	16.21	5.17	35.36	5.22	1.06%	-0.80%	$\pm 5$
		5765	35.73	16.20	5.19	35.34	5.24	1.11%	-0.89%	$\pm 5$
		5785	35.68	16.18	5.20	35.32	5.26	1.03%	-1.07%	$\pm 5$
		5805	35.62	16.20	5.23	35.30	5.28	0.92%	-0.96%	$\pm 5$
		5825	35.59	16.23	5.25	35.28	5.30	0.91%	-0.84%	$\pm 5$

## 11 Measurement Uncertainty

According to KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz section 2.8.2, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

## 12 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be  $\geq 15.0$  cm
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN: 3665 & an E-field probe EX3DV4 SN: 3831 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ( $dx=dy=5$  mm,  $dz=5$  mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was  $100\text{ mW} \pm 3\%$ .
- The results are normalized to 1 W input power.

### Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	735	2017/12/15	2450	1g	51.40	50.60
				10g	23.90	23.90
D5GHzV2	1004	2017/11/17	5300	1g	80.30	79.70
				10g	23.20	22.30
D5GHzV2	1004	2017/11/17	5600	1g	82.20	81.90
				10g	23.60	22.70
D5GHzV2	1004	2017/11/17	5800	1g	77.10	77.90
				10g	22.00	21.40



Report No.: T180918D06-SF

Page 36 / 42  
Rev. 00

### 12.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2018/11/12	D2450V2	735	Body	1g SAR:	50.60	51.70	2.17	± 5
				10g SAR:	23.90	24.00	0.42	± 5
2018/11/13	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	79.70	79.10	-0.75	± 5
				10g SAR:	22.30	21.80	-2.24	± 5
2018/11/13	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	81.90	84.30	2.93	± 5
				10g SAR:	22.70	22.30	-1.76	± 5
2018/11/13	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	77.90	76.00	-2.44	± 5
				10g SAR:	21.40	21.10	-1.40	± 5

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

### 13 SAR Measurements Results

#### Wi-Fi (2.4GHz Band):

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Peak SAR of Area Scan (W/kg)
							Tune up limit	Meas.	
2.4GHz	802.11b	0	Edge 1	6	2437	Main	20.0	19.58	1.110
		0	Rear	6	2437	Main	20.0	19.58	0.526
		0	Edge 1	6	2437	Aux	20.0	19.60	0.042
		0	Edge 2	6	2437	Aux	20.0	19.60	0.331
		0	Rear	6	2437	Aux	20.0	19.60	0.116

#### Note(s):

The maximum Peak SAR location of the Area Scan was chosen to perform the Zoom Scan in accordance with KDB 248227 D01. The Reported SAR value was used to determine whether other channels needed testing.

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Ant.	Power (dBm)		Zoom Scan 1g SAR (W/kg)	Reported SAR (W/kg)	Note	Plot No.
							Tune up limit	Meas.				
2.4GHz	802.11b	0	Edge 1	6	2437	Main	20.0	19.58	0.698	0.769		1
		0	Rear	6	2437	Main	20.0	19.58	0.334	0.368	1	
		0	Edge 2	6	2437	Aux	20.0	19.60	0.175	0.192		

#### Note(s):

- Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.

Report No.: T180918D06-SF  
Wi-Fi (5 GHz Band):

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Peak SAR of Area Scan (W/Kg)
							Tune up limit	Meas.	
5.3 (U-NII-2A)	802.11a	0	Edge 1	52	5260	Main	20.00	19.68	1.350
		0	Rear	52	5260	Main	20.00	19.68	0.892
		0	Edge 1	52	5260	Aux	20.00	19.86	0.175
		0	Edge 2	52	5260	Aux	20.00	19.86	1.840
		0	Edge 2	60	5300	Aux	20.00	19.79	1.580
		0	Rear	52	5260	Aux	20.00	19.86	1.350
5.5 (U-NII-2C)	802.11ac VHT80	0	Edge 1	122	5610	Main	20.00	19.66	0.920
		0	Rear	122	5610	Main	20.00	19.66	1.750
		0	Rear	138	5690	Main	20.00	19.48	1.240
		0	Edge 1	122	5610	Aux	20.00	19.68	0.220
		0	Edge 2	122	5610	Aux	20.00	19.68	2.030
		0	Edge 2	138	5690	Aux	20.00	19.51	1.860
		0	Rear	122	5610	Aux	20.00	19.68	1.350
5.8 (U-NII-3)	802.11a	0	Edge 1	149	5775	Main	20.00	19.88	3.770
		0	Rear	149	5775	Main	20.00	19.88	2.350
		0	Rear	157	5775	Main	20.00	19.81	2.390
		0	Edge 1	149	5775	Aux	20.00	19.93	0.256
		0	Edge 2	149	5775	Aux	20.00	19.93	1.990
		0	Edge 2	149	5745	Aux	20.00	19.93	1.970
		0	Edge 2	157	5785	Aux	20.00	19.83	1.780
		0	Rear	149	5775	Aux	20.00	19.93	1.430

## Note(s):

The maximum Peak SAR location of the Area Scan was chosen to perform the Zoom Scan in accordance with KDB 248227 D01. The Reported SAR value was used to determine whether other channels needed testing.

Report No.: T180918D06-SF

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Ant.	Power (dBm)		Zoom Scan 1g SAR (W/kg)	Reported SAR (W/kg)	Note	Plot No.
							Tune up limit	Meas.				
5.3 (U-NII-2A)	802.11a	0	Edge 1	52	5260	Main	20.00	19.68	0.578	0.622		
		0	Rear	52	5260	Main	20.00	19.68	0.394	0.424	1	
		0	Edge 1	52	5260	Aux	20.00	19.86	0.110	0.114		
		0	Edge 2	52	5260	Aux	20.00	19.86	0.776	0.801		
		0	Edge 2	60	5300	Aux	20.00	19.79	0.792	0.831	2	2
		0	Rear	52	5260	Aux	20.00	19.86	0.576	0.595	1	
5.5 (U-NII-2C)	802.11ac VHT80	0	Edge 1	122	5610	Main	20.00	19.66	0.444	0.480		
		0	Rear	122	5610	Main	20.00	19.66	0.898	0.971	2	
		0	Rear	138	5690	Main	20.00	19.48	0.700	0.789		
		0	Edge 1	122	5610	Aux	20.00	19.68	0.165	0.178	1	
		0	Edge 2	122	5610	Aux	20.00	19.68	0.983	1.058		3
		0	Edge 2	138	5690	Aux	20.00	19.51	0.933	1.044		
5.8 (U-NII-3)	802.11a	0	Rear	122	5610	Aux	20.00	19.68	0.683	0.735		
		0	Edge 1	149	5775	Main	20.00	19.88	0.337	0.346		
		0	Rear	149	5775	Main	20.00	19.88	1.030	1.059		
		0	Rear	157	5775	Main	20.00	19.81	0.948	0.990	2	
		0	Edge 1	149	5775	Aux	20.00	19.93	0.135	0.137	1	
		0	Edge 2	149	5775	Aux	20.00	19.93	1.080	1.098		
		0	Edge 2	157	5785	Aux	20.00	19.93	0.983	0.999		
		0	Edge 2	149	5775	Aux	20.00	19.83	1.150	1.196	3	4
		0	Rear	149	5775	Aux	20.00	19.93	0.711	0.723		

## Note(s):

- Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position
- Repeated measurements are required only when the measured SAR is  $\geq 0.80$  W/kg. If the measured SAR values are < 1.45 W/kg with  $\leq 20\%$  variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04)
  - Original SAR = 1.020 W/kg, therefore second times repeat SAR is required.
  - Repeat SAR = 1.150 W/kg < 1.45W/kg
  - SAR variation= -12.74% < 20%

## 14 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E5071C	MY46316981	1	2019/01/09
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	E4416A	GB41291611	1	2019/08/19
Power Sensor	Agilent	8481H	MY41091956	1	2019/08/19
Data Acquisition Electronics (DAE)	SPEAG	DAE4	877	1	2019/03/19
Dosimetric E-Field Probe	SPEAG	EX3DV4	3665	1	2019/08/05
Dosimetric E-Field Probe	SPEAG	EX3DV4	3831	1	2019/01/22
2450MHz System Validation Dipole	SPEAG	D2450V2	735	1	2018/12/14
5G MHz System Validation Dipole	SPEAG	D5GHZV2	1004	1	2018/11/16
Robot	Staubli	RX90L	F02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	D072602#2	N/A	N/A
Thermometer	Comet	S3120	12932714	1	2019/03/01
Signal Grenerator	Aglient	83630B	3844A01022	1	2020/05/27
Directional Couplers	Aglient	87301D	MY44350252	1	2019/07/23



## 15 Facilities

All measurement facilities used to collect the measurement data are located at

- ☐ No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- ☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- ☐ No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

## 16 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-2005: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 2006.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。



Report No.: T180918D06-SF

Page 42 / 42  
Rev. 00

## 17 Attachments

Exhibit	Content
1	System Performance Check Plots
2	SAR Test Data Plots
3	SAR Equipment calibration report
4	T180918D06-SF PHOTOS

END OF REPORT

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。