



# M. Flom Associates, Inc.

## International Compliance Testing Laboratory

3356 N. San Marcos Place, Suite 107  
Chandler, AZ 85225

toll-free: (866) 311-3268  
fax: (480) 926-3598

<http://www.mflom.com>  
[info@mflom.com](mailto:info@mflom.com)

Date: June 13, 2005

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Wulfsberg Electronics Division  
Equipment: P2000-UHF2A UHF/FM (Hi Split) Radio  
FCC ID: FRW2000-UHF2A  
FCC Rules: Radiofrequency Radiation Exposure Limits  
47 CFR 1.1310  
MPE - Mobiles X Fixed Based Station           

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

David E. Lee, Quality Assurance Manager

enclosure(s)  
cc: Applicant  
DEL/del



# M. Flom Associates, Inc.

## International Compliance Testing Laboratory

3356 N. San Marcos Place, Suite 107  
Chandler, AZ 85225

toll-free: (866) 311-3268  
fax: (480) 926-3598

<http://www.mflom.com>  
[info@mflom.com](mailto:info@mflom.com)

### Environmental Assessment

for

#### Mobiles/Fixed Base Station

**FCC ID: FRW2000-UHF2A**

Model: P2000-UHF2A UHF/FM (Hi Split) Radio

to

#### Federal Communications Commission

**47 CFR 1.1310 (MPE)**

Radiofrequency Radiation Exposure Limits

**Date Of Report:** June 16, 2005

#### On the Behalf of the Applicant:

Wulfsberg Electronics Division

#### At the Request of:

P.O. 19404

Wulfsberg Electronics Division  
6400 Wilkinson Drive  
Prescott, AZ 86301-6164

#### Attention of:

Main: (928) 708-1550; Fax: (928) 541-7627  
Mary Beaumont, Principal RF Engineer  
Direct (928) 708-1543  
Email: [mary.beaumont@wulfsberg.com](mailto:mary.beaumont@wulfsberg.com)

#### Supervised By:

Michael Findley, Laboratory Manager

## Table of Contents

Rule	Description	Page
	Test Report	1
	Identification of the Equipment Under Test	2
	Standard Test Conditions and Engineering Practices	4
1.1310	Environmental Assessment	5

*Required information per ISO/IEC Guide 25-1990, paragraph 13.2:*

a) **Test Report (Supplemental)**

b) Laboratory: M. Flom Associates, Inc.  
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d0560022

d) Client: Wulfsberg Electronics Division  
6400 Wilkinson Drive  
Prescott, AZ 86301-6164

e) Identification: P2000-UHF2A UHF/FM (Hi Split) Radio  
Description: FCC ID: FRW2000-UHF2A  
Mobile FM

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: June 13, 2005  
EUT Received: June 6, 2005

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



Michael Findley, Laboratory Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

### Identification of the Equipment Under Test (EUT)

**Name and Address of Applicant:**

Wulfsberg Electronics Division  
6400 Wilkinson Drive  
Prescott, AZ 86301-6164

**Manufacturer:**

Wulfsberg Electronics Division  
6400 Wilkinson Drive  
Prescott, AZ 86301-6164

**FCC ID:**

FRW2000-UHF2A

**Model Number:**

P2000-UHF2A UHF/FM (Hi Split) Radio

**Description:**

Mobile FM Transceiver

**Type of Emission:**

16K0F3E, 11K0F3E, 20K0F1E, 8K10F1E,  
8K10F1D

**Frequency Range, MHz:**

450.00 to 520.00

**Power Rating, Watts:**

☒ Switchable

☐ Variable

1 and 10

☐ N/A

**Modulation:**

☐ AMPS

☐ TDMA

☐ CDMA

☒ OTHER

**Antenna:**

☐ Helical

☐ Monopole

☐ Whip

☒ Other

**Note:** For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.



## A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 - 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**



## NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at <http://ts.nist.gov/mra> under the 'Asia' category."

BSMI Number: **SL2-IN-E-041R**

## **Standard Test Conditions and Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

**Name of Test:** Environmental Assessment

**Specification:** FCC: 47 CFR 1.1310

**Measurement Guide:** ANSI/IEEE C95.1 1992

**Test Equipment:** Maximum Permissible Exposure (MPE) measurement system, consisting of:  
AR FP6001 Field Monitor Kit  
AR FP4000 Software Suite  
Laptop Computer

**Measurement Procedure:**

1. The following measurements were performed with a FP6001 probe using ANSI/IEEE C95.1 as a guide.
2. Prior to making any measurements, the measurements system was calibrated in accordance with the manufacturer's procedures.
3. The EUT's radiating element (antenna) was placed on a 1 m tall table for ease of testing. For equipment normally operated on a metal surface, a ground plane was used.
4. The remaining equipment necessary to operate the EUT was maintained at a distance from the measurement arrangement suitable to minimize interference with the measurements.
5. The minimum safe distance was calculated from the formula Power Density =  $EIRP / 4\pi R^2$  (Peak Watts/m<sup>2</sup>). The calculation is shown with the measurement data.
6. With the EUT operating at maximum power, a search was initiated for worst case emissions with the probe raised and lowered over a range of 0.2 to 2 meters in height and over a horizontal plane of 0° to 360°.
7. Average values were calculated for the whole body (0.2-2.0m), lower body (0.2-0.8m) and upper body (1.0-2.0m).

**Results:** Attached.



**Test Setup:** Maximum Permissible Exposure (MPE)



**Name of Test:** R.F. Radiation Exposure

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091  
Description, EUT: See page 2 of Test Report

Limits: Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)	0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
	1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
	30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
	300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
	1500-100,000 MHz:	Limit [mW/cm <sup>2</sup> ] = 1.0

Test Frequencies, MHz	450.025	494.025	519.975
Power, Conducted, W	= 10		
Antenna Gain	= 3 dBi (0.85dBd)		
Antenna Model	AT-462 (Manufactured by Comant)		

Pre-test Calculations	Power <sub>[W EIRP]</sub> = P <sub>[conducted]</sub> x G <sub>[antenna]</sub>	=	10.0 x 2 (x 50% Duty Cycle)
	Limit <sub>[mW/cm<sup>2</sup>]</sub>	=	0.300, 0.330, 0.347
	Limit <sub>[W/m<sup>2</sup>]</sub> = 10 x Limit <sub>[mW/cm<sup>2</sup>]</sub>	=	3.00, 3.30, 3.47
	R <sub>[m]</sub> = [P <sub>[W EIRP]</sub> / (4π x Limit <sub>[W/m<sup>2</sup>]</sub> )] <sup>1/2</sup>	=	0.51, 0.49, 0.48

Results at tested distances	Probe Height, m	Power Density, mW/cm <sup>2</sup>		
		Freq. 450 MHz Distance 50 cm	Freq. 494 MHz Distance 50 cm	Freq. 520 MHz Distance 50 cm
	2.0	0.057	0.053	0.054
	1.8	0.143	0.142	0.135
	1.6	0.148	0.145	0.143
	1.4	0.212	0.214	0.206
	1.2	0.213	0.213	0.217
	1.0	0.185	0.177	0.190
	0.8	0.116	0.114	0.111
	0.6	0.081	0.080	0.082
	0.4	0.065	0.060	0.063
	0.2	0.057	0.058	0.059

Power Density Calculations: The measured power density readings were summed and the results divided by the number of readings to calculate the average.

	450 MHz	494 MHz	520 MHz
Whole body average (0.2 - 0.8 m, mW/cm <sup>2</sup> ) =	0.128	0.126	0.126
Lower body average (0.2 - 0.8 m, mW/cm <sup>2</sup> ) =	0.080	0.078	0.079
Upper body average (1.0 - 2.0 m, mW/cm <sup>2</sup> ) =	0.160	0.157	0.158

(The following will be placed in the Instruction Manual)

### **Mandatory Safety Instructions to Installers & Users**

Use only manufacturer or dealer supplied antenna.

**Antenna Minimum Safe Distance: 50cm.**

Antenna Gain: zero dBd referenced to a dipole.

The Federal Communications Commission has adopted a safety standard for human exposure to RF (Radio Frequency) energy which is below the OSHA (Occupational Safety and Health Act) limits.

**Antenna Mounting:** The antenna supplied by the manufacturer or radio dealer must not be mounted at a location such that during radio transmission, any person or persons can come closer than the above indicated minimum safe distance to the antenna i.e. **50cm**.

To comply with current FCC RF Exposure limits, the antenna must be installed at or exceeding the minimum safe distance shown above, and in accordance with the requirements of the antenna manufacturer or supplier.

**Warning:** Maintain a separation distance from the antenna to a person(s) of at least **50cm**.

You, as the qualified end-user of this radio device must control the exposure conditions of bystanders to ensure the minimum separation distance (above) is maintained between the antenna and nearby persons for satisfying RF Exposure compliance. The operation of this transmitter must satisfy the requirements of Occupational/Controlled Exposure Environment, for work-related use. Transmit only when person(s) are at least the minimum distance from the properly installed, externally mounted antenna.

**Testimonial  
and  
Statement of Certification**

**This is to certify that:**

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.



Certifying Engineer:

David E. Lee, Quality Assurance Manager