

ADDRESS: No. 67-9, Shir Men Road, Tu Cheng City,
Taipei Hsien, Taiwan

PHONE : 886-2-22608375 FAX : 886-2-22748013

E - mail : hometek@ms15.hinet.net

FCC TEST REPORT FOR

APPLICANT	:	<u>KYE SYSTEMS CORP.</u>
ADDRESS	:	<u>No. 492, Sec. 5, Chung Hsin Rd., San Chung,</u> <u>Taipei Hsien, 241, Taiwan, R.O.C.</u>
EUT	:	<u>LuxeMate 600 Laser</u>
MODEL NO.	:	<u>GK-060013/K, GK-060013/R</u>
FCC ID	:	<u>FSUGKZGZ</u>

Under Part 15, SUBPART B AND SUBPART C

CLASS B

Certification

MEASUREMENT PROCEDURE USED

FCC RULES AND FCC / ANSI C63.4-2003


PREPARED BY :

HomeTek Technology Inc.

No. 67-9, Shir Men Road, Tu Cheng City,

Taipei Hsien. Taiwan

Report # : FB5K035



HomeTek Technology Inc.

ADDRESS: No. 67-9, Shir Men Road, Tu Cheng City,
Taipei Hsien, Taiwan

PHONE : 886-2-22608375 FAX : 886-2-22748013

E - mail : hometek@ms15.hinet.net

CERTIFICATION

EUT : LuxeMate 600 Laser

MODEL NO. : GK-060013/K, GK-060013/R

FCC ID : FSUGKZGZ

Receipt Date : 11/27/2006 Final Test Date: 11/30/2006

REPORT # : FB5K035

APPLICANT : KYE SYSTEMS CORP.

ADDRESS : No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.

MEASUREMENT PROCEDURE USED :

FCC RULES AND REGULATION PART 15, SUBPART B AND SUBPART C
AND FCC / ANSI C63.4-2003

We hereby show that:

The measurement shown in this test report were made in accordance with and no deviation with the procedures indicated, and the maximum energy emitted by the equipment was found to be within the FCC limits applicable.

This test result of this report applies to above tested sample only.

This test report shall not be reproduce in part without written approval of HomeTek Technology Inc.

APPROVED BY :  12/15/2006

ALAIN LIN / Supervisor



TABLE OF CONTENTS..... 1

GENERAL INFORMATION..... 2

MODIFICATION LIST..... 4

CONDUCTED POWER LINE TEST 5

 1 TEST PROCEDURE..... 5

 2 RESULT OF CONDUCTED EMISSION TEST..... 5

RADIATED EMISSION TEST (3M) 6

 1 TEST INSTRUMENTS & FACILITIES..... 6

 2 EUT OPERATING CONDITION..... 7

 3 TEST SETUP 8

 4 CONFIGURATION OF THE EUT 10

 5 TEST PROCEDURE..... 11

 6 LIMIT OF RADIATED EMISSION CLASS B 12

 7 RESULT OF RADIATED EMISSION TEST..... 13

 8 EMISSION BAND MEASUREMENT 15

PHOTO OF FCC ID LABEL 16

APPENDIX A

 PHOTOS OF TEST CONFIGURATION

APPENDIX B

 PHOTOS OF EUT

APPENDIX C

 PLOT OF OCCUPIED BANDWIDTH



GENERAL INFORMATION

- 1 APPLICANT : KYE SYSTEMS CORP.
- 2 ADDRESS : No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.
- 3 MANUFACTURER : KYE SYSTEMS CORP.
- 4 ADDRESS : No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.
- 5 DESCRIPTION OF EUT :
 - EUT : LuxeMate 600 Laser
 - FCC ID : FSUGKZGZ
 - Model Number : GK-060013/K, GK-060013/R
 - Serial # : N/A



6 FEATURES OF EUT :

- 6.1 Frequency Band: 27MHz.
- 6.2 Carrier Frequency: 27.145MHz.
- 6.3 Modulation Type: FSK.



MODIFICATION LIST

THE FOLLOWING ACCESSORIES WERE ADDED TO THE EUT DURING TESTING :

NO MODIFICATION BY HOMETEK TECHNOLOGY INC.



CONDUCTED POWER LINE TEST

1 TEST PROCEDURE

According to **ANSI C63.4 – 2003**.

2 RESULT OF CONDUCTED EMISSION TEST

N/A(Conducted Power Line Test is not applicable to this EUT
(Model : GK-060013/K, GK-060013/R).

RADIATED EMISSION TEST (3M)

1 TEST INSTRUMENTS & FACILITIES

The following test Instruments was used during the radiated emission test :

Item	Instruments /facilities	Specification	Manufacturer	Model # / S/N#	Date of Cal.
1	OPEN AREA TEST SITE	<input checked="" type="checkbox"/> OATS 3			JUL/2006
2	EMI TEST RECEIVER	20Hz ~ 26.5GHz	ROHDE & SCHWARZ	ESMI 845442/006	FEB/2006
3	PRE-AMPLIFIER	9KHz ~ 3000MHz	ADVANTEST	BB525C 90081001	OCT/2006
4	ANTENNA (LOOP)	10KHz ~ 30MHz	ZHINAN	ZN30900A	NOV/2005
5	Horn Antenna	1G ~ 18GHz	BJXIBAO	040506	OCT/2006
6	Attenuation	50Ω/6dB	JYE BAO	FAT-N (M-F) 001	JUL/2006
7	Cable	10m	SUHNER	RG214/U OS3-003	DEC/2005
8	Cable	14m	BELDEN	9913 OS3-001	DEC/2005
9	EMI 32 (software)	N/A	AUDIX	19991013-0923	N/A


Note : Items 1 ~ 8 were calibrated within period of 1 year.

2 EUT OPERATING CONDITION

- 2.1 Configure the EUT according to the **ANSI C63.4 - 2003**.
- 2.2 The frequency of the EUT is 27.145 MHz.
- 2.3 The radiated emission in the frequency range from 30 MHz - 1000 MHz was test in a horizontal and vertical polarization at HomeTek Lab's open site III.
- 2.4 The crystal frequency of the EUT is 12 MHz (For Model No.: GK-060013/R); the crystal frequency of the EUT is 27.145 MHz (For Model No.: GK-060013/K).
- 2.5 Provided by 2AA battery to Mouse. Connect receiver to USB port of Person computer.
- 2.6 Turn on all the power of EUT and peripheral.
- 2.7 The EUT was operated in its normal operating mode for the purpose of the measurements.
- 2.8 The receiving antenna polarized horizontally was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the ESMI test receiver or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the EUT.
- 2.9 **The photos of radiated test configuration, please refer to appendix A.**


3 TEST SETUP

3.1 TEST SETUP OF OPEN SITE.



3.2 TEST SETUP OF EUT

ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE RANGE OF 9kHz TO 40 GHz

ANSI
C63.4-2003

(Details for setup configuration, please refer to appendix A.)

LEGEND:

1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 to 40 cm long, hanging approximately in the middle between ground plane and table.
2. I/O cables that are connected to a peripheral shall be bundled in center. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1m.
3. If LISNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
4. Cables of hand-operated devices, such as keyboards, mice, etc., have to be placed as close as possible to the controller.
5. Non-EUT components of EUT system being tested.
6. The rear of all components of the system under test shall be located flush with the rear of the table.
7. No vertical conducting wall used.
8. Power cords drape to the floor and are routed over to receptacle.

Test Configuration Tabletop Equipment Radiated Emission



4 CONFIGURATION OF THE EUT

The EUT was configured according to **ANSI C63.4 - 2003**. All I/O ports were connected to the appropriate peripherals. All peripherals and cables are listed below (including internal device) :

4.1 EUT

EUT Type : Proto Type Engineer Type Mass Production
Condition when received : Good Damage : _____
Device : LuxeMate 600 Laser
Applicant : KYE SYSTEMS CORP.
Manufacturer : KYE SYSTEMS CORP.
Model Number : GK-060013/K, GK-060013/R
Serial Number : N/A
FCC ID : FSUGKZGZ
I/O Port : N/A
Power Cord : N/A
Power Supply Type : Battery

4.2 REMARK : N/A

5 TEST PROCEDURE

- 5.1 The EUT was test according to **ANSI C63.4 – 2003 & FCC Part 15.227**.
- 5.2 The radiated test was performed at HomeTek Lab's Open Site III.
- 5.3 This site is on file with the FCC laboratory division, test firm registration number: 713630, expiration Date : 2005/10/20.
- 5.4 For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies. The signal of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 5.5 For emission frequencies measured below and above 1 GHz, set the spectrum analyzer or a 100KHz and 1MHz resolution bandwidth respectively for each frequency measured in item 5.4.
- 5.6 The receiving antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Move the antenna to a position where the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
- 5.7 Repeat item 5.6 until all frequencies need to be measured were completed.
- 5.8 Repeat item 5.7 with search antenna in vertical polarized orientations.
- 5.9 Check seven frequencies of highest emission with varying the placement of cables (if any) associated with EUT to obtain the worst case and record the result.
- 5.10 The frequency range from 30 MHz to 1 GHz were investigated, the measurement were made at 3 meters, with a BI-log antenna.

6 LIMIT OF RADIATED EMISSION CLASS B

Frequency (MHz)	Measurement Distance	dBuV/m	uV/m
Fundamental frequency	3 (M)	48	250
30 - 88	3 (M)	40	100
88 - 216	3 (M)	43.5	150
216 - 960	3 (M)	46	200
Above 960	3 (M)	54	500

- 6.1 The tighter limit shall apply at the edge between two frequency bands.
- 6.1 Measurement distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or peripherals.

7 RESULT OF RADIATED EMISSION TEST

- 7.1 The frequency range from 30 MHz to 1 GHz was investigated.
- 7.2 All readings below or equal 1 GHz are quasi-peak or peak values with resolution bandwidth of 120 KHz. The reading of fundamental frequency is peak or average values. With resolution bandwidth of 120KHz.
- 7.3 The measurements were made at 3 meters of HomeTek Lab's open site III.
- 7.4 Temperature : 25 °C, Humidity : 60 % RH.
- 7.5 Deviation form the test standards and rules : None.
- 7.6 Radiated Emission data : **Horizontal**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	ANT Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Detector
* 27.14	48.38	80.00	-31.62	52.47	15.20	0.74	20.03	Peak
54.29	30.15	40.00	-9.85	47.27	7.85	0.99	25.96	Peak
108.58	31.67	43.50	-11.83	44.25	11.88	1.42	25.88	Peak
135.72	24.16	43.50	-19.34	36.96	11.44	1.59	25.83	Peak
162.87	26.60	43.50	-16.90	40.82	9.80	1.76	25.78	Peak
217.16	25.33	46.00	-20.67	39.86	9.10	2.05	25.68	Peak
352.88	24.02	46.00	-21.98	32.24	14.49	2.64	25.35	Peak
407.17	25.47	46.00	-20.53	31.96	15.76	2.93	25.18	Peak

- Emission Level = Read Level – Preamp Factor + ANT Factor + Cable Loss.
- Sample Calculation for 407.17 MHz .
- Corrected Reading : (31.96) - (25.18) + (15.76) + (2.93) = 25.47 .

7.6 Radiated Emission data : **Vertical**

Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Read Level (dBuV)	ANT Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Detector
* 27.14	49.83	80.00	-30.17	53.92	15.20	0.74	20.03	Peak
54.29	31.04	40.00	-8.96	48.16	7.85	0.99	25.96	Peak
108.58	28.88	43.50	-14.62	41.46	11.88	1.42	25.88	Peak
135.72	24.06	43.50	-19.44	36.86	11.44	1.59	25.83	Peak
217.15	25.48	46.00	-20.52	40.01	9.10	2.05	25.68	Peak
271.45	29.24	46.00	-16.76	39.91	12.64	2.25	25.56	Peak
380.03	25.69	46.00	-20.31	33.03	15.14	2.79	25.27	Peak
407.17	24.33	46.00	-21.67	30.82	15.76	2.93	25.18	Peak

- Emission Level = Read Level – Preamp Factor + ANT Factor + Cable Loss.
- Sample Calculation for 407.17 MHz .
- Corrected Reading : (30.82) - (25.18) + (15.76) + (2.93) = 24.33 .

REMARK :


1. Model : GK-060013/K.
2. Measuring mode : RF Mode.
3. “*”, means this frequency is fundamental.
4. Result : **PASSED**

8 Emission Band Measurement

- 8.1 According to **FCC Part 15.227** emissions from the intentional radiator shall be confined within a band 200KHz wide centered on the operating frequency. The 200KHz band shall lie wholly within the frequency range of 27.145 MHz.
- 8.2 All reading are peak values with resolution bandwidth of 50 KHz.
- 8.3 Temperature : 24 °C, Humidity : 57 % RH.
- 8.4 Deviation form the test standards and rules : None.
- 8.5 The test data of Emission Band, please refer to appendix C.**

PHOTO OF FCC ID LABEL

SAMPLE OF FCC ID LABEL :



Please refer to appendix B photo of ID location.