



BUREAU VERITAS

Test Report No.: RF121119N011-1



TEST REPORT



Applicant:	KYE SYSTEMS CORP.
Address:	No. 492, Sec 5, Chongxin Rd., Sanchong Dist., New Taipei City 24160, Taiwan (R.O.C.)

Manufacturer or Supplier	KYE SYSTEMS CORP.
Address	No. 492, Sec 5, Chongxin Rd., Sanchong Dist., New Taipei City 24160, Taiwan (R.O.C.)
Product	Dongle
Brand Name	Genius
Model:	GM-120015/R
Additional Model & Model Difference:	N/A
Date of tests:	Nov. 20 ~ Nov. 26, 2012

the tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C (Section 15.249)

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Kent Liu Project Engineer / EMC Department	Approved by Sam Tung Manager / EMC Department
	 Date: Nov. 26, 2012

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD.....	3
1 SUMMARY OF TEST RESULTS	4
2 MEASUREMENT UNCERTAINTY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF EUT	5
3.2 DESCRIPTION OF TEST MODES	5
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	6
3.4 DESCRIPTION OF SUPPORT UNITS	6
4. TEST TYPES AND RESULTS	7
4.1 CONDUCTED EMISSION MEASUREMENT	7
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	7
4.1.2 TEST INSTRUMENTS	7
4.1.3 TEST PROCEDURES	8
4.1.4 DEVIATION FROM TEST STANDARD	8
4.1.5 TEST SETUP	9
4.1.6 EUT OPERATING CONDITIONS	9
4.1.7 TEST RESULTS	10
4.2 RADIATED EMISSION MEASUREMENT	12
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	12
4.2.2 TEST INSTRUMENTS	13
4.2.3 TEST PROCEDURES	14
4.2.4 DEVIATION FROM TEST STANDARD	14
4.2.5 TEST SETUP	15
4.2.6 EUT OPERATING CONDITIONS	15
4.2.7 TEST RESULTS	16
4.3 20dB BANDWIDTH MEASUREMENT	22
4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT	22
4.3.2 TEST INSTRUMENTS	22
4.3.3 TEST PROCEDURE	23
4.3.4 DEVIATION FROM TEST STANDARD	23
4.3.5 TEST SETUP	24
4.3.6 EUT OPERATING CONDITIONS	24
4.3.7 TEST RESULTS	24
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	27
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	28



Test Report No.: RF121119N011-1



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121119N011-1	Original release	Nov. 26, 2012

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.249)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
§15.203	Antenna Requirement	PASS	Compliant
§15.207 (a)	Conducted Emission	PASS	Compliant
§15.205	Restricted Band of Operation	PASS	Compliant
§15.209 §15.249(a)	Radiated Emission	PASS	Compliant
§15.215(c)	20dB Bandwidth Test	PASS	Compliant

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44dB
Radiated emissions	30MHz ~ 1GHz	3.64dB
	1GHz ~ 18GHz	2.26dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Dongle
MODEL NO.	GM-120015/R
FCC ID	FSUGMZKE
NOMINAL VOLTAGE	DC 5V from USB
MODULATION TECHNOLOGY	GFSK
OPERATING FREQUENCY	2402-2480MHz
ANTENNA TYPE	Integral PCB Antenna with gain 2.0dBi
I/O PORTS	USB Port
CABLE SUPPLIED	N/A

NOTE: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Following channel(s) was (were) selected for the test as listed below.

TESTED CHANNEL	TESTED FREQUENCY
Low	2402 MHz
Middle	2448 MHz
High	2480 MHz

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.249)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DOC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	5P2PM2X	12400120329	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line :Unshielded, Detachable 1.5m;DC Line: Unshielded, Undetachable 1.8m

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:** 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
EMI Test Receiver Rohde&Schwarz	ESU 26	100005	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ENV216	101173	May 15,12	May 14,13
Artificial Mains Network Rohde&Schwarz	ESH2-Z5	100071	May 15,12	May 14,13
Test software	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA
 2. The test was performed in Dongguan Shielding Room 553.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

Set the EUT under transmission condition continuously at specific channel frequency.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA

PHASE	Line 1	6dB BANDWIDTH	9kHz
-------	--------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17698	10.55	40.03	22.82	50.58	33.37	64.63	54.63	-14.04	-21.25
2	0.23586	10.44	33.53	16.57	43.97	27.01	62.24	52.24	-18.27	-25.23
3	0.29467	10.4	27.42	11.58	37.82	21.98	60.39	50.39	-22.57	-28.41
4	3.45395	9.95	22.1	17.5	32.05	27.45	56	46	-23.95	-18.55
5	19.98152	10.29	31.19	23.36	41.48	33.65	60	50	-18.52	-16.35
6	23.55526	10.46	31.66	24.64	42.12	35.1	60	50	-17.88	-14.9


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16955	10.6	27.32	12.06	37.92	22.66	64.98	54.98	-27.06	-32.32
2	0.18519	10.48	38.12	21.25	48.6	31.73	64.25	54.25	-15.65	-22.52
3	0.23648	10.37	33.01	16.88	43.38	27.25	62.22	52.22	-18.84	-24.97
4	3.34838	9.64	24.69	18.31	34.33	27.95	56	46	-21.67	-18.05
5	20.07145	10.19	30.23	24.49	40.42	34.68	60	50	-19.58	-15.32
6	23.75858	10.45	30.04	23.03	40.49	33.48	60	50	-19.51	-16.52

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply.

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Test Receiver ROHDE & SCHWARZ	ESVD	847398/003	May 15,12	May 14,13
Bilog Antenna TESEQ	CBL 6111D	25758	Jul. 16,12	Jul. 15,13
Horn Antenna EMCO	3117	00062558	Oct.18,12	Oct.17,13
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar. 24,12	Mar. 23,13
RF Cable IMRO	IMRO-400	10m Cable 1#10m	May 16,12	May 15,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Signal Amplifier EMCI	EMC330	980095	Nov. 2,12	Nov. 1,13
Pre-Amplifier HP	8449B	3008A00409	May 31,12	May 30,13
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7.6.15	N/A	N/A	N/A

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
 2. The test was performed in Dongguan 10m Chamber.
 3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6

4.2.7 TEST RESULTS


BELOW 1GHz WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Middle Channel	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	DC5V from PC	DETECTOR FUNCTION	Quasi-Peak

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	215.85	34.9 QP	43.5	-8.6	1.00 H	251	24.04	10.89
2	288.62	37.8 QP	46.0	-8.2	1.00 H	214	22.99	14.85
3	430.92	29.7 QP	46.0	-16.3	1.00 H	327	10.96	18.73
4	720.36	33.8 QP	46.0	-12.2	1.00 H	308	9.53	24.31
5	793.12	35.8 QP	46.0	-10.2	1.00 H	273	10.50	25.32
6	899.85	32.3 QP	46.0	-13.7	1.00 H	358	5.99	26.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.




EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Middle Channel	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	DC5V from PC	DETECTOR FUNCTION	Quasi-Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	215.85	30.4 QP	43.5	-13.1	1.00 V	205	19.47	10.89
2	395.34	31.8 QP	46.0	-14.2	1.00 V	164	14.09	17.67
3	432.53	33.2 QP	46.0	-12.8	1.00 V	311	14.41	18.75
4	600.70	31.4 QP	46.0	-14.6	1.00 V	145	8.76	22.63
5	720.36	34.8 QP	46.0	-11.2	1.00 V	294	10.52	24.31
6	793.12	32.9 QP	46.0	-13.1	1.00 V	72	7.57	25.32

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Low Channel	FREQUENCY RANGE	1 ~ 25GHz
TEST VOLTAGE (SYSTEM)	DC5V from PC	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400	55.2 PK	74	-18.8	1.24 H	158	18.7	36.5
2	2400	4.7 AV	54	-49.3	1.24 H	158	-31.8	36.5
3	*2402.00	89.1 PK	114	-24.9	1.24 H	158	52.58	36.52
4	*2402.00	38.6 AV	94	-55.4	1.24 H	158	2.08	36.52
5	4804	61.5 PK	74	-12.5	1.03 H	71	12.25	49.25
6	4804	11.0 AV	54	-43	1.03 H	71	-38.25	49.25
7	7206	58.8 PK	74	-15.2	1.03 H	62	12.28	46.52
8	7206	8.3 AV	54	-45.7	1.03 H	62	-38.22	46.52
9	9608	57.8 PK	74	-16.2	1.00 H	298	12.9	44.9
10	9608	7.3 AV	54	-46.7	1.00 H	298	-37.6	44.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2400.00	51.8 PK	74.0	-22.2	1.71 V	325	15.30	36.50
2	2400.00	1.3 AV	54.0	-52.7	1.71 V	325	-35.20	36.50
3	*2402.00	84.3 PK	114.0	-29.7	1.71 V	325	47.78	36.52
4	*2402.00	33.8 AV	94.0	-60.2	1.71 V	325	-2.72	36.52
5	4804.00	61.2 PK	74.0	-12.8	1.00 V	320	11.95	49.25
6	4804.00	10.7 AV	54.0	-43.3	1.00 V	320	-38.55	49.25
7	7206.00	58.6 PK	74.0	-15.4	1.03 V	223	12.08	46.52
8	7206.00	8.1 AV	54.0	-45.9	1.03 V	223	-38.42	46.52
9	9608.00	57.7 PK	74.0	-16.3	1.00 V	175	12.80	44.90
10	9608.00	7.2 AV	54.0	-46.8	1.00 V	175	-37.70	44.90

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- " * " : Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (217.39 / 81159) = 20 log (0.3%) = -50.5
Please see page 21 for plotted duty.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Middle Channel	FREQUENCY RANGE	1 ~ 25GHz
TEST VOLTAGE (SYSTEM)	DC5V from PC	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2448.00	87.9 PK	114.0	-26.1	1.00 H	159	50.97	36.93
2	*2448.00	37.4 AV	94.0	-56.6	1.00 H	159	0.47	36.93
3	4896.00	61.0 PK	74.0	-13.0	1.12 H	172	11.77	49.23
4	4896.00	10.5 AV	54.0	-43.5	1.12 H	172	-38.73	49.23
5	7344.00	58.7 PK	74.0	-15.3	1.00 H	345	12.08	46.62
6	7344.00	8.2 AV	54.0	-45.8	1.00 H	345	-38.42	46.62
7	9792.00	57.2 PK	74.0	-16.8	1.00 H	58	12.41	44.79
8	9792.00	6.7 AV	54.0	-47.3	1.00 H	58	-38.09	44.79

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2448	84.6 PK	114	-29.4	1.07 V	186	47.67	36.93
2	*2448	34.1 AV	94	-59.9	1.07 V	186	-2.83	36.93
3	4896	61.0 PK	74	-13	1.00 V	351	11.77	49.23
4	4896	10.5 AV	54	-43.5	1.00 V	351	-38.73	49.23
5	7344	58.2 PK	74	-15.8	1.00 V	70	11.58	46.62
6	7344	7.7 AV	54	-46.3	1.00 V	70	-38.92	46.62
7	9792	57.9 PK	74	-16.1	1.03 V	56	13.11	44.79
8	9792	7.4 AV	54	-46.6	1.03 V	56	-37.39	44.79

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- " * ": Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (217.39 / 81159) = 20 log (0.3%) = -50.5
Please see page 21 for plotted duty.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX High Channel	FREQUENCY RANGE	1 ~ 25GHz
TEST VOLTAGE (SYSTEM)	DC5V from PC	DETECTOR FUNCTION	Peak (PK) Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	89.8 PK	114	-24.2	1.17 H	180	52.59	37.21
2	*2480.00	39.3 AV	94	-54.7	1.17 H	180	2.09	37.21
3	2483.5	50.8 PK	74	-23.2	1.16 H	180	13.56	37.24
4	2483.5	0.3 AV	54	-53.7	1.16 H	180	-36.94	37.24
5	4960	60.9 PK	74	-13.1	1.13 H	171	11.69	49.21
6	4960	10.4 AV	54	-43.6	1.13 H	171	-38.81	49.21
7	7440	58.2 PK	74	-15.8	1.10 H	175	11.5	46.7
8	7440	7.7 AV	54	-46.3	1.10 H	175	-39	46.7
9	9920	57.1 PK	74	-16.9	1.05 H	115	12.39	44.71
10	9920	6.6 AV	54	-47.4	1.05 H	115	-38.11	44.71



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	86.4 PK	114.0	-27.6	1.02 V	206	49.19	37.21
2	*2480.00	35.9 AV	94.0	-58.1	1.02 V	206	-1.31	37.21
3	2483.50	48.6 PK	74.0	-25.4	1.02 V	206	11.36	37.24
4	2483.50	-1.9 AV	54.0	-55.9	1.02 V	206	-39.14	37.24
5	4960.00	61.3 PK	74.0	-12.7	1.03 V	245	12.09	49.21
6	4960.00	10.8 AV	54.0	-43.2	1.03 V	245	-38.41	49.21
7	7440.00	58.2 PK	74.0	-15.8	1.05 V	260	11.50	46.70
8	7440.00	7.7 AV	54.0	-46.3	1.05 V	260	-39.00	46.70
9	9920.00	57.4 PK	74.0	-16.6	1.00 V	168	12.69	44.71
10	9920.00	6.9 AV	54.0	-47.1	1.00 V	168	-37.81	44.71

REMARKS:

- Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
- Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
- The other emission levels were very low against the limit.
- Margin value = Emission level – Limit value.
- " * " : Fundamental frequency.
- The average value of fundamental frequency is: Average = Peak value + 20 log(Duty cycle)
Where the duty factor is calculated from following formula:
20 log (Duty cycle) = 20 log (217.39 / 81159) = 20 log (0.3%) = -50.5
Please see page 21 for plotted duty.

Duty Cycle: $20 \log(\text{Duty cycle}) = 20 \log(217.39\mu\text{s} / 81.159\text{ms}) = 20 \log(0.3\%) = -50.5$



4.3 20dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 20dB BANDWIDTH MEASUREMENT

According to FCC 15.215(c), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer ROHDE & SCHWARZ	E4446A	MY46180622	May 02, 12	May 01, 13
Horn Antenna EMCO	3117	00062558	Oct.18,12	Oct.17,13
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar. 24,12	Mar. 23,13
RF Cable IMRO	IMRO-400	10m Cable 2#3m	May 16,12	May 15,13
Pre-Amplifier HP	8449B	3008A00409	May 31,12	May 30,13
RF Cable DRAKA	M06/25-RG102	10m Cable 2#	May 16,12	May 15,13
Test software ADT	ADT_Radiated_V7.6.15	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Dongguan Chamber 10m.

4.3.3 TEST PROCEDURE


The EUT was placed on a turn table which was 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on a antenna tower. At the frequency band of 30MHz to 1GHz, The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 to 4 m for horizontal and vertical polarizations.

The spectrum analyzer was receiving the maximum emission level. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP




4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 TEST RESULTS

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
Low	2402	1.23
Middle	2448	1.23
High	2480	1.23


Test Data: Low channel



Test Data: Middle channel



Test Data: High channel





Test Report No.: RF121119N011-1



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF121119N011-1



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---