

Exhibit C

Measurement Report  
SAMPO CORPORATION  
FCC ID.: FYLSM34D  
Multimedia Monitor

# FCC CLASS B EMI TEST REPORT

of

EUT : Monitor  
MODEL NO. : SME-23DV3  
FCC ID. : FYLSM34D

for

APPLICANT : SAMPO CORPORATION  
ADDRESS : 216, Sec. 1, Chung Shan Rd., Pan Chiao,  
Taipei Hsien, Taiwan, R.O.C.

Test Performed by

## **ELECTRONICS TESTING CENTER, TAIWAN**

NO. 8 LANE 29, WENMIMG ROAD,  
LOSHAN TSUN, KUI-SHAN HSIANG,  
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026-32,  
Fax:(03)3280034

Report Number : ET87R-08-035-01  
Issued Date : SEP. 09, 1998

# TEST REPORT CERTIFICATION

Applicant : SAMPO CORPORATION  
 216, Sec. 1, Chung Shan Rd., Pan Chiao, Taipei Hsien,  
 Taiwan, R.O.C.

Manufacturer : SAMPO CORPORATION  
 216, Sec. 1, Chung Shan Rd., Pan Chiao, Taipei Hsien,  
 Taiwan, R.O.C.

Description of EUT : Monitor

a) Brand Name : SAMPO

b) Model No. : SME-23DV3

c) FCC ID. : FYLSM34D

d) Power Supply : 100-240VAC, 50/60Hz

e) Data Also Apply to Model: SME-23DXXX, SMA-34DXXX, SMB-34DXXX  
 VC-34XXX, C34XXX, AR34XXX, XV-34XXX  
 SM-34DXXX, DL-34XXX (X: 0-9, A-Z, or blank)

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B (1996)


I HEREBY CERTIFY THAT: The data shown in this report was in accordance with the procedures given in ANSI-63.4 and the energy emitted by the device was found to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note : 1. The results of the testing report relate only to the items tested.  
 2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Test Dated : AUG. 24, 1998

Test Engineer : Tai Cheng Huang  
 ( T. C. Huang )

Approve & Authorized : Will Yauo  
 Will Yauo, Supervisor  
 EMI Test Site of ELECTRONICS  
 TESTING CENTER, TAIWAN



<b>Table of Contents</b>	<b>Page</b>
<b>1. GENERAL INFORMATION .....</b>	<b>1</b>
1.1 Product Description.....	1
1.2 Tested System Details .....	2
1.3 Test Methodology.....	2
1.4 Test Facility .....	2
<b>2. PRODUCT LABELING AND USER INFORMATION .....</b>	<b>3</b>
2.1 Class Definition.....	3
2.2 Class Limitations.....	4
2.3 Labeling Requirement .....	5
2.4 User Information .....	6
<b>3. SYSTEM TEST CONFIGURATION .....</b>	<b>7</b>
3.1 Justification .....	7
3.2 Configuration of Tested System.....	7
3.3 Modification .....	7
<b>4. MEASUREMENT PHOTOS .....</b>	<b>8</b>
4.1 Conducted Measurement Photos.....	8
4.2 Radiated Measurement Photos .....	9
<b>5. CONDUCTED EMISSION DATA.....</b>	<b>10</b>
5.1 Conducted Test Results.....	10
<b>6. RADIATED EMISSION DATA .....</b>	<b>14</b>
6.1 Open Site Radiated Test Results .....	14
6.2 Field Strength Calculation.....	16
<b>7. TEST EQUIPMENT .....</b>	<b>17</b>
7.1 Test Setup .....	17
7.2 Conducted Test Equipments.....	18
7.3 Radiated Test Equipments.....	18

## 1. GENERAL INFORMATION

### 1.1 Product Description

- a) Description of EUT : Monitor
- b) Brand Name : SAMPO
- c) Model No. : SME-23DV3
- d) FCC ID : FYLSM34D
- e) Power Supply : 110-240VAC, 50/60Hz
- f) Data Also Apply to Model: SME-23DXXX, SMA-34DXXX, SMB-34DXXX  
VC-34XXX, C34XXX, AR34XXX, XV-34XXX  
SM-34DXXX, DL-34XXX (X: 0-9, A-Z, or blank)

## 1.2 Tested System Details

The Tested System Detail equipment, plus description of all cables used in the tested system are :

Description	Model No.	FCC ID.	Manufacturer	Cable
Monitor *1	SME-23DV3	FYLSM34D	SAMPO CORPORATION	1.6m Unshielded Power Cord 1.8m Shielded Cable 1.6m S-Video Cable 1.8m Unshielded AV Cable × 4
Modem	1200AT	EF56A51200AT	Smar TEAM Co.	1.0m Shielded Cable
P.C.	LTV466D2	A09-80XWW	Digital	1.5m Unshielded Power Cord
Keyboard	E03786USRETI	CIGE03786	Microsoft	1.5m Unshielded Cable
Printer	2225C+	DSI6XU2225	Hewlett-Packard	1.2m Shielded Cable
Mouse	M-S34	DZL211029	Hewlett-Packard	1.5m Unshielded Cable

\*1 EUT submitted for test.

## 1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in FCC/ANSI C63.4, Radiated testing was performed at an antenna to EUT distance of 3 meters.

## 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No.34, 5 Lirn, Din Fu Tsun, Lin Kou, Taipei, Taiwan, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Feb., 10,1997.

## **2. PRODUCT LABELING AND USER INFORMATION**

### **2.1 Class Definition**

**Class A Digital Device:** A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

**Class B Digital Device :** A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

**Note :** A manufacturer may also qualify a device intended to be marketed in a commercial ,business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

**2.2 Class Limitations**

Class A Line Conducted Emission Limits :

Frequency MHZ	Emissions uV	Emissions dBuV
0.45 - 1.705	1000	60.0
1.705 - 30.0	3000	69.5

Class A Radiated Emission Limits :

Frequency MHZ	Distance Meters	Radiated dBuV/m	Radiated uV/m
30 - 88	10	39.0	90
88 - 216	10	43.5	150
216 - 960	10	46.4	210
above 960	10	49.5	300

Class B Line Conducted Emission Limits :

Frequency MHZ	Emissions uV	Emissions dBuV
0.45 - 30.0	250	48.0

Class B Radiated Emission Limits :

Frequency MHZ	Distance Meters	Radiated dBuV/m	Radiated uV/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500



## **2.3 Labeling Requirement**

The device shall bear the following statement in a conspicuous location on the device.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference
- (2) this device must accept any interference received, including interference that may cause undesired operation.

## 2.4 User Information

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

### **3. SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

The system was configured for testing in EUT is working.

The EUT was rotated to obtain the maximum level of radiated emissions .The antenna was varied in height above ground to obtain the maximum signal strength. The antenna height was varied from 1 to 4 meters.

All test results are listing on chapter 5 and 6.

#### **3.2 Configuration of Tested System**

Please Refer to Page 8 & Page 9

#### **3.3 Modification**

- 1) 4700p CAP, parallel, C702, C703
- 2) 680p CAP, parallel, C724
- 3) KH line in CRT Board add one ferrite core two truns
- 4) The three GND lines contacted in the Shielding Box of CRT Board, each GND line add one ferrite core two turns.
- 5) Bead Core, serial, J265, J264, J263
- 6) Bead Core, serial, Q109, Q111, Q113

## **5. CONDUCTED EMISSION DATA**

### **5.1 Conducted Test Results**

The initial setup in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on following data pages, and these signals are the quasi-peaked.

CONDUCTED EMISSION DATAModel No. : SME-23DV3Operation Mode : 1024×768 48KHzJudgment : Passed by 9.2 dBTest Date : AUG. 24, 1998Temperature : 25 °CHumidity : 50 %

Emission Frequency ( MHz )	Meter Reading ( dB $\mu$ V )		LISN Factor ( dB )	Results ( dB $\mu$ V )		Limit ( dB $\mu$ V )	Margins ( dB )
	VA	VB		VA	VB		
0.4556	26.8	26.5	0.2	27.0	26.7	48.0	-21.0
1.6152	30.6	31.3	0.3	30.9	31.6	48.0	-16.4
1.9469	26.2	26.4	0.3	26.5	26.7	48.0	-21.3
8.6985	27.2	28.2	0.5	27.7	28.7	48.0	-19.3
9.4003	38.1	38.3	0.5	38.6	38.8	48.0	-9.2
16.7485	28.3	30.2	0.8	29.1	31.0	48.0	-17.0

## **6. RADIATED EMISSION DATA**

### **6.1 Open Site Radiated Test Results**

The following data lists the significant emission frequencies, measured levels, correction factor (includes cable and antenna corrections), the corrected reading, and the limit. The result value is quasi-peaked by R & S Test Receiver. Explanation of the Correction Factor is given in paragraph 6.2.

RADIATED EMISSION DATAModel No. : SME-23DV3Operation Mode : 1024×768 48KHzJudgment : Passed by 2.1 dBTest Date : AUG. 13, 1998Temperature : 29 °CHumidity : 52 %

Emission Frequency ( MHz )	Meter Reading ( dB $\mu$ V )		CORR'd Factor ( dB )	Results ( dB $\mu$ V/m )		Limit (dB $\mu$ V/m)	Margins ( dB )
	HOR.	VERT.		HOR.	VERT.		
61.10	52.4	53.7	-16.2	36.2	37.5	40.0	-2.5
65.80	53.1	54.3	-16.4	36.7	37.9	40.0	-2.1
98.70	51.4	50.2	-13.9	37.5	36.3	43.5	-6.0
117.50	42.2	47.0	-11.0	31.2	36.0	43.5	-7.5
122.20	52.3	51.2	-11.0	41.3	40.2	43.5	-2.2
126.90	51.3	48.2	-11.3	40.0	36.9	43.5	-3.5

## 6.2 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor. The basic equation with a sample calculation is as follows:

$$\text{Results} = \text{Meter Reading} + \text{CORR'd Factor}$$

$$\text{CORR'd Factor} = \text{AF} + \text{CF} - \text{AG}$$

$$\text{AF} = \text{Antenna Factor}$$

$$\text{CF} = \text{Cable Attenuation Factor}$$


$$\text{AG} = \text{Amplifier Gain}$$




## 7. TEST EQUIPMENT

### 7.1 Test Setup

#### I. Conducted Test Setup Diagram



#### II. Open Field Test Site Setup Diagram



## 7.2 Conducted Test Equipments

The following test equipments are used during the conducted test .

Equipments	Manufacturer	Model No.	Next Cal. Date
Test Receiver	Rohde and Schwarz	ESH3	JAN. 04, 1999
Spectrum Monitor	Rohde and Schwarz	EZM	N.C.R.
Line Impedance Stabilization Network	Kyoritsu	KNW-407	DEC. 01, 1998
Line Impedance Stabilization Network	EMCO	3825/2	DEC. 01, 1998
Printer	Rohde and Schwarz	PUD-3	N/A
Plotter	Hewlett-Packard	7440A	N/A
Shielded Room	Riken	----	N.C.R.

## 7.3 Radiated Test Equipments

The following test equipments are used during the radiated test .

Equipments	Manufacturer	Model No.	Next Cal. Date
EMI Receiver	Hewlett-Packard	8546A	FEB. 11, 1999
Test Receiver	Rohde and Schwarz	ESVS 30	DEC. 19, 1998
Biconical Antenna	EMCO	3110B	JAN. 13, 1999
Log Periodic Antenna	EMCO	3146	DEC. 10, 1999
Spectrum Analyzer	Hewlett-Packard	8568B	OCT. 16, 1998
Quasi-Peak Adaptor	Hewlett-Packard	85650A	OCT. 07, 1998
RF Preselector	Hewlett-Packard	85685A	OCT. 16, 1998
Amplifier	Hewlett-Packard	8447D	DEC. 23, 1998

## Exhibit D


Equipment ID. Label  
SAMPO CORPORATION  
FCC ID.: FYLSM34D  
Multimedia Monitor

1. A label in the next page will be affixed to rear of the device.  
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Exhibit E


User's Manual  
SAMPO CORPORATION  
FCC ID.: FYLSM34D  
Multimedia Monitor

dBuV



FCC CONDUCTED TEST EUT: MONITOR  
 MODEL: SME-23DV3+MCE-TN3 (MCE-TPA3) POWER: 120V/60HZ  
 MODE: 1024\*768 48KHZ 2:QP  
 LISN: Vb CLASS B LIMIT  
 ETC EMI LAB.

dBuV



FCC CONDUCTED TEST  
 MODEL: SME-23DV3+MCE-TN3 (MCE-TPA3)

EUT: MONITOR  
 POWER: 120V/60HZ  
 MODE: 1024\*768 48KHZ

2: QP  
 LISN: Va

CLASS B LIMIT  
 ETC EMI LAB.