



## FCC 47 CFR MPE REPORT

VTECH ELECTRONICS LTD

SANDY SNACKS-A-LOT

Model Number: 5601

Additional Model: 80-560100,80-560103,80-560104,80-560105,80-560122,  
80-560123, 80-5601XX (XX=00~99)

FCC ID: G2R-5601

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| Applicant:               | VTECH ELECTRONICS LTD                                                          |
| Address:                 | 23/F,TAI PING INDUSTRIAL CENTRE, BLOCK 1,<br>57 TING KOK ROAD,TAI PO,HONG KONG |
|                          |                                                                                |
| Prepared By:             | EST Technology Co., Ltd.                                                       |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong,<br>China         |
| Tel: 86-769-83081888-808 |                                                                                |

|                 |                              |
|-----------------|------------------------------|
| Report Number:  | ESTE-R2403088                |
| Date of Test:   | Mar. 09, 2024~ Mar. 18, 2024 |
| Date of Report: | Mar. 19, 2024                |

## Maximum Permissible Exposure

### Applicable Standards

According to 447498 D04 Interim General RF Exposure Guidance v01  
Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

| Frequency<br>(MHz) | Field Strength<br>(dBuV/m) | Calc Pt(mW) | Limit (mW) |
|--------------------|----------------------------|-------------|------------|
| 13.56              | 50.32                      | 0.0000323   | 1          |

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10((\text{dBuV/m})/20)/10^6$

d = measurement distance in meters (m) ---3m

Field strength =50.32dBuV/m @3m

Ant gain =0dBi, so gt =1

So pt =  $(E \times d)^2 / 30 \times gt = \{ [50.32/20] / 10^6 \times 3 \}^2 / 30 \times 1 \} \times 1000 \text{ mW}$

=0.0000323mW

So a SAR test is not required

**End of Test Report**