

Prüfbericht - Nr.: Test Report No.	CN22OS0E 001	Seite 19 von 20 Page 19 of 20
6 Safety Hum	an Exposure	
6.1 Radio Frequency Exposure Compliance		
6.1.1 Electromagnetic Fields		
RESULT:		Pass
Test Specification		
Test standard	: FCC KDB Publication 447498 v06	
	CFR47 FCC Part 2: Section 2.1093	3
	CFR47 FCC Part 1: Section 1.1310)
	RSS-102 Issue 5 February 2021	
FCC requirement:		
The measured maximum of	conducted output power of the EUT is -2.11 dBm ≈ 0.62 m	<i>N</i> , which is far below

The measured maximum conducted output power of the EUT is -2.11dBm \approx 0.62mW, which is far below the SAR exclusion threshold level 10mW (SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and \leq 50 mm), hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01: Mobile and Portable RF Exposure. Guidance v06.

IC requirements:

The measured maximum specified e.i.r.p of the EUT is -2.11dBm \approx 0.62mW, which is far below the SAR exclusion threshold level 4mW, hence the EUT is excluded from SAR evaluation according to RSS-102 Issue 5 section 2.5.1.