






**CONFORMANCE TEST REPORT
 FOR
 FCC 47 CFR, Part 15 Subpart C**

Report No.: 12-04-MAS-144-02

Client: TAIWAN CAROL ELECTRONICS CO., LTD.
 Product: Bluetooth XLR Transmitter
 Model: BTM-210D
 FCC ID: G4RBTM-210D
 Manufacturer: TAIWAN CAROL ELECTRONICS CO., LTD.

Date test item received: 2012/03/30
 Date test campaign completed: 2012/05/15
 Date of issue: 2012/06/11

The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.
Total number of pages of this test report: 74 pages
Total number of pages of photos: External photos 1 pages
Internal photos 4 pages
Setup photos 2 pages

Test Engineer  Phillip Luo	Checked By  Perry Lin	Approved By  James Cheng
---	--	---

ELECTRONICS TESTING CENTER, TAIWAN
 NO.8, LANE 29, WENMING RD.,
 LESHAN TSUEN, GUISHAN SHIANG,
 TAOYUAN COUNTY, TAIWAN 33383,
 R.O.C.TAIWAN, R.O.C.

TEL: (03) 3276170~4
 INT: +886-3-3276170~4
 FAX: (03) 3276188
 INT: +886-3-3276188



Client : TAIWAN CAROL ELECTRONICS CO., LTD.
 Address : No. 202 Tung Kuang Road, East District, Taichung, Taiwan 401
 Manufacturer : TAIWAN CAROL ELECTRONICS CO., LTD.
 Address : CAROL TECHNOLOGY INDUSTRIAL PARK, (BAO'AN ROAD WEST)
 GONGMING STREET, GUANGMING NEW DISTRICT, SHENZHEN,
 GUANGDOING, CHINA
 EUT : Bluetooth XLR Transmitter
 Brand/Trade name : CAROL
 Model No. : BTM-210D
 Power Source : 3Vdc

Regulations applied : FCC 47 CFR, Part 15 Subpart C

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to relieve the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, TAF, NCC, NVLAP, ILAC MRA, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through TAF
- ⑤ FCC Registration Number: 91095, 392735, 278818
- ⑥ Industry Canada Site Registration number: IC 2949A-2



NVLAP Lab Code 200133-0

Table of Contents	Page
1 GENERAL INFORMATION	5
1.1 Product Description.....	5
1.2 Characteristics of Device	5
1.3 Test Methodology	5
1.4 Modification List of EUT	5
1.5 Test Facility.....	5
1.6 Test Summary	5
2 PROVISIONS APPLICABLE	6
2.1 Definition	6
2.2 Requirement for Compliance	7
2.3 Restricted Bands of Operation	9
2.4 Labeling Requirement.....	9
2.5 User Information	10
3. SYSTEM TEST CONFIGURATION	11
3.1 Justification	11
3.2 Devices for Tested System.....	11
4 RADIATED EMISSION MEASUREMENT	13
4.1 Applicable Standard.....	13
4.2 Measurement Procedure.....	13
4.3 Measuring Instrument	15
4.4 Radiated Emission Data	16
4.5 Field Strength Calculation	21
5 CONDUCTED EMISSION MEASUREMENT	22
6 ANTENNA REQUIREMENT	23
6.1 Standard Applicable.....	23
6.2 Antenna Construction and Directional Gain	23
7 20dB EMISSION BANDWIDTH MEASUREMENT	24
7.1 Standard Applicable.....	24
7.2 Measurement Procedure.....	24
7.3 Measurement EquipMent.....	24
7.4 Measurement Data	25
8 OUTPUT POWER MEASUREMENT	33
8.1 Standard Applicable.....	33
8.2 Measurement Procedure.....	33

8.3 Measurement EquipMent..... 33

8.4 Measurement Data 34

9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT..... 42

9.1 Standard Applicable 42

9.2 Measurement Procedure..... 42

9.3 Measurement EquipMent..... 42

9.4 Measurement Data 43

10 NUMBER OF HOPPING CHANNELS..... 59

10.1 Standard Applicable 59

10.2 Measurement Procedure..... 59

10.3 Measurement EquipMent..... 59

10.4 Measurement Data 59

11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED 63

11.1 Standard Applicable 63

11.2 Measurement Procedure..... 63

11.3 Measurement EquipMent..... 63

11.4 Measurement Data 64

12 DWELL TIME 66

12.1 Standard Applicable 66

12.2 Measurement Procedure..... 66

12.3 Measurement EquipMent..... 66

12.4 Measurement Data 66

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Bluetooth XLR Transmitter
 b) Trade Name : CAROL
 c) Model No. : BTM-210D
 d) FCC ID : G4RBTM-210D

1.2 Characteristics of Device

The EUT is a Bluetooth XLR Transmitter based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4GHz. In this band, 79 RF channels spaced 1MHz apart are defined. The rated output power is 11.54 dBm (14.26 mW).

1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.4 (2003) an FCC CFR 47 Part 2 and Part 15.

1.4 Modification List of EUT

N/A

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

1.6 Test Summary

Requirement	FCC Paragraph #	Test Pass
Radiated Emission	15.209	<input checked="" type="checkbox"/>
Conducted Emission	15.207	N/A
Antenna Requirement	15.203	<input checked="" type="checkbox"/>
20dB Emission Bandwidth	15.247 (a)(1)	<input checked="" type="checkbox"/>
Output Power	15.247 (b)(1)	<input checked="" type="checkbox"/>
OUT-OF-BAND RF Conducted Spurious Emission	15.247 (c)	<input checked="" type="checkbox"/>
Number of Hopping Channels	15.247 (b)(1)	<input checked="" type="checkbox"/>
Hopping Channel Carrier Frequency Separated	15.247 (a)(1)	<input checked="" type="checkbox"/>
Dwell Time	15.247 (a)(1)(iii)	<input checked="" type="checkbox"/>

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to §15.247 (c),(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. (ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

(4) 20dB Bandwidth Requirement

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(b)(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) Power Spectral Density

According to 15.247(d), for bluetooth device, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio / TV technician for help.

To comply with the FCC RF exposure compliance requirement, this device and its antenna must not be co-located or operating to conjunction with any other antenna or transmitter.

3. SYSTEM TEST CONFIGURATION

3.1 Justification


For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But never the less ancillary equipment can influence the test results..

3.2 Devices for Tested System

3.2.1

Device	Manufacture	Model	Cable Description
* Bluetooth XLR Transmitter	TAIWAN CAROL ELECTRONICS CO., LTD.	BTM-210D	----
Notebook	DELL	E5510	2.8m*1, Unshielded Power Line/Adapter 1.2m*1 Unshielded Signal Line

Remark : “*” means equipment under test.



Note: A notebook performs the control test mode. The notebook removes away after the control command is ready.

3.2.2 Test Mode Description

3.2.2.1 Modulation Type

Test Mode	Type	Note
A	NON-EDR	GFSK
B	EDR	$\pi/4$ -DQPSK, 8-DPSK (note 1)

Test Channel	Frequency (MHz)
Channel Low(L)	2402
Channel Mid(M)	2441
Channel Low(H)	2480

3.2.2.2 Test Mode and Worse Case Determination

Item	Test Item	Test Mode	Test Frequency (MHz)
1	Output Power	A	L, M, H
		B	L, M, H
	Worse Case	Mode B (note 1)	
2.	20dB Emission Bandwidth	B	M (Worse Case)
3	Conducted Emission	-	-
4	Out of Band Conducted Emission	B	L, M, H
5.1	Number of Channel	B	L~H
5.2	Channel Separation	B	M (note 2)
5.3	Dwell Time	B	M (note 2)
6.1	Radiated Emission (below 1GHz)	B	M (Worse Case)
6.2	Radiated Emission (above 1GHz)	B	L, M, H
6.3	Radiated Emission (BandEdge)	A, B	L, H

note:

1. The worse case is determined as the modulation with highest output power.
2. Pretest result is no difference in three test modes by channel low, middle and high. Choose one for final testing and record the result.

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and digitally modulated, and the out band emission shall be comply with § 15.247 (c)

4.2 Measurement Procedure

A.Preliminary Measurement For Portable Devices.

For movable devices, the following procedure was performed to determine the maximum emission axis of EUT (X,Y and Z axis):

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. The axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.
4. The position in which the maximum noise occurred was “Y axis”. (Please see the test setup photos.)

B. Final Measurement

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	R&S	ESIB7	06/25/2012
Spectrum Analyzer	Rohde & Schwarz	FSU46	01/08/2013
Horn Antenna	EMCO	3115	07/21/2012
BiLog Antenna	ETC	MCTD2986	11/24/2012
Horn Antenna	EMCO	3116	07/21/2012
Preamplifier	Hewlett-Packard	8449B	10/25/2012

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	300 kHz
	RF Test Receiver	Peak	120 kHz	300 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Apr. 03, 2012 Temperature : 20°C

Humidity : 55%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4804.000	58.0	39.5	63.7	41.6	-2.53	61.2	39.1	74.0	54.0
7206.000	---	---	---	---	0.35	---	---	74.0	54.0
12010.000	---	---	---	---	4.40	---	---	74.0	54.0
14412.000	---	---	---	---	9.08	---	---	74.0	54.0

b) Channel 39

Fundamental Frequency : 2441 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4882.000	56.3	---	59.9	42.0	-2.36	57.5	39.6	74.0	54.0
7323.000	---	---	---	---	0.61	---	---	74.0	54.0
9764.000	51.4	---	---	---	2.36	53.8	---	74.0	54.0
14646.000	---	---	---	---	8.23	---	---	74.0	54.0

c) Channel 78

Fundamental Frequency : 2480 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H Peak	H Ave	V Peak	V Ave		Peak	Ave	Peak	Ave
4960.000	57.5	40.0	61.5	42.1	-2.19	59.3	39.9	74.0	54.0
7440.000	---	---	---	---	0.87	---	---	74.0	54.0
9920.000	---	---	---	---	2.45	---	---	74.0	54.0
12400.000	---	---	---	---	4.56	---	---	74.0	54.0
17360.000	---	---	---	---	9.45	---	---	74.0	54.0


Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

4.4.2 Other Emission

4.4.2.1 below 1GHz


File: MIC-MIC Data: #85 Date: 2012/4/3 Temperature: 20 °C
Time: pm 04:47:00 Humidity: 55 %



Condition: FCC_30-1000MHz Polarization: Horizontal
EUT: Distance: 3m
Model:
Test Mode:

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	51.3828	20.80	peak	10.16	30.96	40.00	-9.04
2	191.3427	15.12	peak	12.23	27.35	43.50	-16.15
3	288.5371	16.75	peak	17.71	34.46	46.00	-11.54
4	309.9198	19.01	peak	18.19	37.20	46.00	-8.80
5	379.8998	15.37	peak	19.97	35.34	46.00	-10.66
6	572.3447	7.36	peak	23.36	30.72	46.00	-15.28

File: MIC-MIC Data: #86 Date: 2012/4/3 Temperature: 20 °C
Time: pm 04:57:59 Humidity: 55 %



Condition: FCC_30-1000MHz Polarization: Vertical
EUT: Distance: 3m
Model:
Test Mode:

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	7.75	peak	20.47	28.22	40.00	-11.78
2	63.0461	20.87	peak	7.26	28.13	40.00	-11.87
3	88.3166	18.68	peak	10.28	28.96	43.50	-14.54
4	175.7916	15.69	peak	13.07	28.76	43.50	-14.74
5	288.5371	13.64	peak	17.71	31.35	46.00	-14.65
6	309.9198	13.05	peak	18.19	31.24	46.00	-14.76
7	379.8998	12.40	peak	19.97	32.37	46.00	-13.63

4.4.2.2 above 1GHz

4.4.2.2.1 Fundamental Frequency : 2402 MHz

Frequency (MHz)	Ant Pol	Reading (dBuV) @3m		Factor (dB/m)	Result (dBuV) @3m		Limit (dBuV/m) @3m	
		Peak	AVG		Peak	AVG	Peak	AVG
1603.5255	H	60.1	---	-11.59	48.5	---	74.0	54.0
1603.5255	V	54.0	---	-11.59	42.4	---	74.0	54.0

4.4.2.2.2 Fundamental Frequency : 2441 MHz

Frequency (MHz)	Ant Pol	Reading (dBuV) @3m		Factor (dB/m)	Result (dBuV) @3m		Limit (dBuV/m) @3m	
		Peak	AVG		Peak	AVG	Peak	AVG
1628.2050	H	58.9	---	-11.46	47.4	---	74.0	54.0
1628.2050	V	53.2	---	-11.46	41.7	---	74.0	54.0

4.4.2.2.3 Fundamental Frequency : 2480 MHz

Frequency (MHz)	Ant Pol	Reading (dBuV) @3m		Factor (dB/m)	Result (dBuV) @3m		Limit (dBuV/m) @3m	
		Peak	AVG		Peak	AVG	Peak	AVG
1652.8846	H	59.2	---	-11.34	47.9	---	74.0	54.0
1652.8846	V	50.3	---	-11.34	39.0	---	74.0	54.0

Note:

1. Place of Measurement: Measuring site of the ETC.
2. If the data table appeared symbol of "****" means the value was too low to be measured.
3. The estimated measurement uncertainty of the result measurement is
 - ±4.6dB (30MHz ≤ f < 300MHz).
 - ±4.4dB (300MHz ≤ f < 1000MHz).
 - ±4.1dB (1GHz ≤ f ≤ 18GHz).
 - ±4.4dB (18GHz < f ≤ 40GHz).
- 4 Remark “----” means that the emissions level is too low to be measured.

4.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies

4.4.3.1 Operation Mode : NON-EDR

(A) Channel 0

Fundamental Frequency : 2402 MHz

Test Date: Apr. 03, 2012 Temperature : 20°C

Humidity : 55%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H		V			Peak	Ave	Peak	Ave
2390.000	28.1	15.6	27.5	14.6	29.8	57.9	45.4	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2310 ~2390 MHz.

(B) Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H		V			Peak	Ave	Peak	Ave
2483.500	39.4	20.8	31.4	17.7	29.8	69.2	50.6	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2483.5 ~2500 MHz.

4.4.3.2 Operation Mode : EDR

(A) Channel 0

Fundamental Frequency : 2402 MHz

Test Date: Apr. 03, 2012

Temperature : 20°C

Humidity : 55%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H		V			Peak	Ave	Peak	Ave
2390.000	27.5	14.8	28.1	14.3	29.8	57.9	44.6	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2310 ~2390 MHz.

(B) Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m) Peak Ave (H/V Max.)		Limit @3m (dBuV/m) Peak Ave.	
	H		V			Peak	Ave	Peak	Ave
2483.500	41.6	20.5	32.7	17.5	29.8	71.4	50.3	74.0	54.0

Note:

The result is the highest value of radiated emission from restrict band of 2483.5 ~2500 MHz.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$Result = Reading + Corrected Factor$$

where

$$Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss - Amplifier Gain$$

5 CONDUCTED EMISSION MEASUREMENT

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (c),(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. (ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

6.2 Antenna Construction and Directional Gain

The peak gain of antenna used is 2 dBi.

Antenna Type	chip
Model Number	N/A
Brand Name	N/A
Peak Antenna Gain	2 dBi

The directional gain of antenna doesn't greater than 6 dBi, the power won't be reduced.

7 20dB EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(1), for frequency hopping systems, hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect it to measurement instrument. Then set it to any convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Figure 3: Emission bandwidth measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012

7.4 Measurement Data

7.4.1 Operation Mode: NON-EDR

Test Date : Mar. 30, 2012


Temperature : 20°C

Humidity: 54%

Channel	20 dB Bandwidth (MHz)	Chart
L	0.840	Page 26
M	0.845	Page 27
H	0.840	Page 28

Note: Please refer to page 26 to page 28 for chart.

File: 0324 MIC Data: #42 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:19:56 Humidity: 54 %



Condition: -8.69dBm Horizontal
EUT: Sweep Time: 3.2ms Att.: 20dB
Model: RBW: 30 KHz VBW: 100 KHz
Test Mode:
Note: FCC-Bluetooth Channel 00-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2401.56000	-8.90
2	2401.99500	11.31
3	2402.40000	-8.70

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	0.84	0.2

File: 0324 MIC


Data: #50

Date: 2012/3/30

Temperature: 20 °C

Time: PM 01:27:03

Humidity: 54 %



Condition: -7.34dBm

Horizontal

EUT:

Sweep Time: 3.2ms Att.: 30dB

Model:

RBW: 30 KHz VBW: 100 KHz


Test Mode:

Note: FCC-Bluetooth Channel 39-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2440.55000	-7.83
2	2440.99500	12.66
3	2441.39500	-7.42

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	0.845	0.41

File: 0324 MIC Data: #46 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:23:18 Humidity: 54 %



Condition: -7.58dBm Horizontal
EUT: Sweep Time: 3.2ms Att.: 30dB
Model: RBW: 30 KHz VBW: 100 KHz
Test Mode:
Note: FCC-Bluetooth Channel 78-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2479.55500	-7.72
2	2479.99500	12.42
3	2480.39500	-7.72

No.		ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	0.84	0

7.4.2 Operation Mode: EDR

Test Date : Mar. 30, 2012


Temperature : 20°C

Humidity: 54%

Channel	20 dB Bandwidth (MHz)	Chart
L	1.215	Page 30
M	1.215	Page 31
H	1.215	Page 32

Note: Please refer to page 30 to page 32 for chart.

File: 0324 MIC Data: #65 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:44:58 Humidity: 54 %




Condition: -9.29dBm Horizontal
EUT: Sweep Time: 3.2ms Att.: 20dB
Model: RBW: 30 KHz VBW: 100 KHz
Test Mode:
Note: FCC-Bluetooth Channel 00-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2401.40000	-9.66
2	2401.99500	10.71
3	2402.61500	-9.36

No.		ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	1.215	0.3

File: 0324 MIC Data: #73 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:57:24 Humidity: 54 %




Condition: -8.09dBm Horizontal
EUT: Sweep Time: 3.2ms Att.: 20dB
Model: RBW: 30 KHz VBW: 100 KHz
Test Mode:
Note: FCC-Bluetooth Channel 39-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2440.40500	-8.10
2	2440.99500	11.91
3	2441.62000	-8.39

No.		ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	1.215	-0.29

File: 0324 MIC Data: #69 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:51:33 Humidity: 54 %



Condition: -8.46dBm Horizontal
EUT: Sweep Time: 3.2ms Att.: 20dB
Model: RBW: 30 KHz VBW: 100 KHz
Test Mode:
Note: FCC-Bluetooth Channel 78-20dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2479.40500	-8.57
2	2479.99500	11.54
3	2480.62000	-9.76

No.		ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	1.215	-1.19

8 OUTPUT POWER MEASUREMENT

8.1 Standard Applicable

For frequency hopping system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
4. Measure the highest amplitude appearing on spectral display and record the level to calculate result data.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012
Power Meter	Agilent	N1922A	11/09/2012
Peak Power Sensor	Agilent	N1912A	11/09/2012

8.4 Measurement Data

8.4.1 Operation Mode: NON-EDR

Test Date : Apr. 05, 2012

Temperature : 20°C

Humidity: 54%

Channel	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
L	9.80	9.55	125	Page 35
M	11.01	12.62	125	Page 36
H	10.77	11.94	125	Page 37

Channel	Maximum Avg Output Power (dBm)	Maximum Avg Output Power (mW)
L	8.21	6.62
M	9.25	8.41
H	9.07	8.07

Note: Please refer to page 35 to page 37 for chart.

File: 0324 MIC


Data: #77

Date: 2012/4/5

Temperature: 20 °C

Time: AM 10:23:22

Humidity: 54 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:


RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH00 Output Power (NON-EDR)

No.	Frequency(MHz)	Level(dBm)
1	2401.95000	9.80


File: 0324 MIC Data: #91 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:48:19 Humidity: 54 %



Condition: Horizontal
 EUT: Sweep Time: 1ms Att.: 20dB
 Model: RBW: 2000 KHz VBW: 2000 KHz
 Test Mode:
 Note: FCC Bluetooth CH39 Output Power (NON-EDR)

No.	Frequency(MHz)	Level(dBm)
1	2441.03330	11.01

File: 0324 MIC Data: #79 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:24:43 Humidity: 54 %



Condition: Horizontal
 EUT: Sweep Time: 1ms Att.: 20dB
 Model: RBW: 2000 KHz VBW: 2000 KHz
 Test Mode:
 Note: FCC Bluetooth CH78 Output Power (NON-EDR)

No.	Frequency(MHz)	Level(dBm)
1	2479.96670	10.77

8.4.2 Operation Mode: EDR

Test Date : Apr. 05, 2012

Temperature : 20°C

Humidity: 54%

Channel	Maximum Peak Output Power (dBm)	Maximum Peak Output Power (mW)	FCC Limit (mW)	Chart
L	10.23	10.54	125	Page 39
M	11.54	14.26	125	Page 40
H	11.07	12.79	125	Page 41

Channel	Maximum Avg Output Power (dBm)	Maximum Avg Output Power (mW)
L	6.83	4.82
M	7.88	6.14
H	7.52	5.65

Note: Please refer to page 39 to page 41 for chart.

File: 0324 MIC


Data: #84

Date: 2012/4/5

Temperature: 20 °C

Time: AM 10:34:25

Humidity: 54 %



Condition:

Horizontal

EUT:

Sweep Time: 1ms Att.: 20dB

Model:


RBW: 2000 KHz VBW: 2000 KHz

Test Mode:

Note: FCC Bluetooth CH00 Output Power (EDR)

No.	Frequency(MHz)	Level(dBm)
1	2401.88330	10.23


File: 0324 MIC Data: #88 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:38:44 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 1ms Att.: 20dB
Model: RBW: 2000 KHz VBW: 2000 KHz
Test Mode:
Note: FCC Bluetooth CH39 Output Power (EDR)

No.	Frequency(MHz)	Level(dBm)
1	2440.92500	11.54

File: 0324 MIC Data: #86 Date: 2012/4/5 Temperature: 20 °C
 Time: AM 10:36:59 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 1ms Att.: 20dB
Model: RBW: 2000 KHz VBW: 2000 KHz
Test Mode:
Note: FCC Bluetooth CH78 Output Power (EDR)

No.	Frequency(MHz)	Level(dBm)
1	2479.91670	11.07

9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012

9.4 Measurement Data

9.4.1 Operation Mode: NON-EDR

Test Date : Mar. 30, 2012

Temperature : 20°C

Humidity: 54%

Test Date : Apr. 05, 2012


Temperature : 20°C

Humidity: 54%

Channel	Test Frequency Range	Note	Chart
L	2350 MHz - 2450 MHz	Lower Band Edge	Page 44-45
H	2433.5 MHz - 2533.5 MHz	Upper Band Edge	Page 46-47
L	30 MHz - 25 GHz		Page 48
M	30 MHz - 25 GHz		Page 49
H	30 MHz - 25 GHz		Page 50

Note: Please refer to page 44 to page 50 for chart.


File: 0324 MIC Data: #78 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:23:49 Humidity: 54 %



Condition: -10.34dBm Horizontal
EUT: Sweep Time: 2.32ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Channel 00-Bandedge (Fixed)

No.	Frequency(MHz)	Level(dBm)
1	2398.00000	-37.50
2	2402.00000	9.66


File: 0324 MIC Data: #82 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:30:39 Humidity: 54 %



Condition: -10.21dBm Horizontal
 EUT: Sweep Time: 2.32ms Att.: 20dB
 Model: RBW: 100 KHz VBW: 300 KHz
 Test Mode:
 Note: FCC-Bluetooth Channel 00-Bandedge (Hopping)

No.	Frequency(MHz)	Level(dBm)
1	2400.00000	-37.08
2	2404.00000	9.79


File: 0324 MIC Data: #80 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:25:07 Humidity: 54 %



Condition: -9.39dBm Horizontal
EUT: Sweep Time: 2.12ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Channel 78-Bandedge (Fixed)

No.	Frequency(MHz)	Level(dBm)
1	2479.98000	10.61
2	2484.52670	-49.83

File: 0324 MIC Data: #83 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:32:25 Humidity: 54 %



Condition: -9.34dBm **Horizontal**
EUT: **Sweep Time: 2.12ms Att.: 20dB**
Model: **RBW: 100 KHz VBW: 300 KHz**
Test Mode:
Note: **FCC-Bluetooth Channel 78-Bandedge (Hopping)**

No.	Frequency(MHz)	Level(dBm)
1	2479.98000	10.66
2	2483.50000	-41.44

File: 0324 MIC


Data: #43

Date: 2012/3/30

Temperature: 20 °C

Time: PM 01:21:29

Humidity: 54 %



Condition: -9.57dBm

Horizontal

EUT:

Sweep Time: 2386.4ms Att.: 20dB

Model:


RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-BT Channel 00-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1611.43330	-53.19
2	2402.15000	10.43
3	24292.51670	-50.45


File: 0324 MIC Data: #51 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:28:35 Humidity: 54 %



Condition: -8.23dBm Horizontal
EUT: Sweep Time: 2386.4ms Att.: 30dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-BT Channel 39-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1028.80000	-50.94
2	2443.76670	11.77
3	23543.41670	-40.89

File: 0324 MIC Data: #47 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:24:49 Humidity: 54 %



Condition: -8.33dBm Horizontal
EUT: Sweep Time: 2386.4ms Att.: 30dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-BT Channel 78-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1653.05000	-50.63
2	2485.38330	11.67
3	23460.18330	-41.57

9.4.2 Operation Mode: EDR


Test Date : Mar. 30, 2012 Temperature : 20°C Humidity: 54%

Test Date : Apr. 05, 2012 Temperature : 20°C Humidity: 54%

Channel	Test Frequency Range	Note	Chart
L	2350 MHz - 2450 MHz	Lower Band Edge	Page 52-53
H	2433.5 MHz - 2533.5 MHz	Upper Band Edge	Page 54-55
L	30 MHz - 25 GHz		Page 56
M	30 MHz - 25 GHz		Page 57
H	30 MHz - 25 GHz		Page 58

Note: Please refer to page 52 to page 58 for chart.


File: 0324 MIC Data: #85 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:34:51 Humidity: 54 %



Condition: -11.31dBm Horizontal
EUT: Sweep Time: 2.32ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Channel 00-Bandedge (Fixed)

No.	Frequency(MHz)	Level(dBm)
1	2399.60000	-32.10
2	2402.00000	8.69

File: 0324 MIC Data: #89 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:42:51 Humidity: 54 %



Condition: -10.98dBm Horizontal
EUT: Sweep Time: 2.32ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Channel 00-Bandedge (Hopping)

No.	Frequency(MHz)	Level(dBm)
1	2399.68000	-32.58
2	2404.00000	9.02

File: 0324 MIC


Data: #87

Date: 2012/4/5

Temperature: 20 °C

Time: AM 10:37:25

Humidity: 54 %



Condition: -10.15dBm

Horizontal

EUT:

Sweep Time: 2.12ms Att.: 20dB

Model:


RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-Bluetooth Channel 78-Bandedge (Fixed)

No.	Frequency(MHz)	Level(dBm)
1	2479.98000	9.85
2	2483.50000	-48.25


File: 0324 MIC Data: #90 Date: 2012/4/5 Temperature: 20 °C
Time: AM 10:44:36 Humidity: 54 %



Condition: -10.07dBm Horizontal
EUT: Sweep Time: 2.12ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Channel 78-Bandedge (Hopping)

No.	Frequency(MHz)	Level(dBm)
1	2478.99000	9.93
2	2483.57330	-45.59


File: 0324 MIC Data: #66 Date: 2012/3/30 Temperature: 20 °C
 Time: PM 01:46:28 Humidity: 54 %



Condition: -10.14dBm Horizontal
 EUT: Sweep Time: 2386.4ms Att.: 20dB
 Model: RBW: 100 KHz VBW: 300 KHz
 Test Mode:
 Note: FCC-BT Channel 00-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1611.43330	-51.55
2	2402.15000	9.86
3	24334.13330	-50.41


File: 0324 MIC Data: #74 Date: 2012/3/30 Temperature: 20 °C
 Time: PM 01:58:55 Humidity: 54 %



Condition: -7.46dBm Horizontal
 EUT: Sweep Time: 2386.4ms Att.: 30dB
 Model: RBW: 100 KHz VBW: 300 KHz
 Test Mode:
 Note: FCC-BT Channel 39-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	862.3333	-50.56
2	2443.76670	12.54
3	24250.90000	-41.08

File: 0324 MIC Data: #70 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:53:04 Humidity: 54 %



Condition: -9.46dBm Horizontal
EUT: Sweep Time: 2386.4ms Att.: 30dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-BT Channel 78-Conducted Spurious

No.	Frequency(MHz)	Level(dBm)
1	1653.05000	-50.29
2	2485.38330	10.54
3	24334.13330	-41.14

10 NUMBER of HOPPING CHANNELS

10.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to hopping operating mode and set spectrum analyzer maximum to measure the number of hopping channels.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012

10.4 Measurement Data

Test Date : Mar. 30, 2012


Temperature : 20°C

Humidity: 54%

Number of hopping channels = 79 channels


Note: Please refer to page 60 to page 62 for chart.

File: 0324 MIC Data: #61 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:39:26 Humidity: 54 %




Condition: Horizontal
EUT: Sweep Time: 1ms Att.: 30dB
Model: RBW: 300 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Number of Hopping Channels -Part1

File: 0324 MIC Data: #62 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:41:14 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 1ms Att.: 30dB
Model: RBW: 300 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Number of Hopping Channels -Part2

File: 0324 MIC Data: #63 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:43:01 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 1ms Att.: 30dB
Model: RBW: 300 KHz VBW: 300 KHz
Test Mode:
Note: FCC-Bluetooth Number of Hopping Channels -Part3

11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED

11.1 Standard Applicable

According to 15.247(a)(1), the frequency hopping system shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any measurement frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set spectrum analyzer maximum hold to measure channel carrier frequency , then adjust channel carrier frequency to adjacent channel.
4. Repeat above procedure until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012

11.4 Measurement Data

Test Date : Mar. 30, 2012

Temperature : 20°C


Humidity: 54%

Channel	Hopping Channel Carrier Frequency Separated (MHz)	Chart
M	1.050	Page 65

Note: 1. Please refer to page 65 for chart.

2. CH Low, CH Mid and CH High have the same test result. Only Mid test result showed in the test report.

File: 0324 MIC Data: #60 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:37:35 Humidity: 54 %



Condition: Horizontal
 EUT: Sweep Time: 3.2ms Att.: 30dB
 Model: RBW: 30 KHz VBW: 100 KHz
 Test Mode:
 Note: FCC-Bluetooth Carrier Frequency Separation

No.	Frequency(MHz)	Level(dBm)
1	2440.96000	10.00
2	2442.01000	8.32

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk2-mk1	1.05	-1.68

12 Dwell Time

12.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The setup of the EUT as shown in figure 3.

12.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	09/18/2012

12.4 Measurement Data

Test Date : Mar. 30, 2012

Temperature : 20°C

Humidity: 54%

12.4.1 DH1


Test period = 0.4(second/channel) × 79 channel = 31.6sec

2402MHz dwell time = 513.4 us × 340 = 174.56 ms

Note: 1. Please refer to page 67 to page 68 for chart.

2. This device complies with the Bluetooth specifications and can operate in hopping mode on N channels, where $20 \leq N \leq 79$. As the same pseudo random hopping channel selection mechanism is used for all cases of N, by complying with the dwell time requirements of channel occupancy $< 0.4s$ in $N \times 0.4s$ for $N = 79$, compliance with any value for N is demonstrated.

File: 0324 MIC Data: #54 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:33:22 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 3300ms Att.: 30dB
Model: RBW: 1000 KHz VBW: 1000 KHz
Test Mode:
Note: DH1 Hops per 3.16 seconds

12.4.2 DH3


Test period = $0.4(\text{second/channel}) \times 79 \text{ channel} = 31.6\text{sec}$

2441MHz dwell time = $1.775 \text{ ms} \times 170 = 301.75 \text{ ms}$

Note: 1. Please refer to page 70 to page 71 for chart.

2. This device complies with the Bluetooth specifications and can operate in hopping mode on N channels, where $20 \leq N \leq 79$. As the same pseudo random hopping channel selection mechanism is used for all cases of N, by complying with the dwell time requirements of channel occupancy $< 0.4s$ in $N \times 0.4s$ for $N = 79$, compliance with any value for N is demonstrated.

File: 0324 MIC Data: #57 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:34:59 Humidity: 54 %




Condition: -30.92dBm Horizontal
EUT: Sweep Time: 3ms Att.: 30dB
Model: RBW: 1000 KHz VBW: 1000 KHz
Test Mode:
Note: DH3 pusle width

No.	Sweep time(ms)	Level(dBm)
1	0.6850	-48.62
2	2.0400	4.08
3	2.4600	-47.62

No.		Δ Time(ms)	Δ Level(dB)
1	mk3-mk1	1.775	1

File: 0324 MIC Data: #56 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:34:45 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 3300ms Att.: 30dB
Model: RBW: 1000 KHz VBW: 1000 KHz
Test Mode:
Note: DH3 Hops per 3.16 seconds

12.4.3 DH5


Test period = $0.4(\text{second/channel}) \times 79 \text{ channel} = 31.6\text{sec}$

2480MHz dwell time= $3.0333 \text{ ms} \times 110 = 333.66 \text{ ms}$

Note: 1. Please refer to page 73 to page 74 for chart.

2. This device complies with the Bluetooth specifications and can operate in hopping mode on N channels, where $20 \leq N \leq 79$. As the same pseudo random hopping channel selection mechanism is used for all cases of N, by complying with the dwell time requirements of channel occupancy $< 0.4s$ in $N \times 0.4s$ for $N = 79$, compliance with any value for N is demonstrated.

File: 0324 MIC Data: #59 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:36:38 Humidity: 54 %




Condition: -31.03dBm Horizontal
EUT: Sweep Time: 5ms Att.: 30dB
Model: RBW: 1000 KHz VBW: 1000 KHz
Test Mode:
Note: DH5 pulse width

No.	Sweep time(ms)	Level(dBm)
1	0.6750	-48.46
2	3.0250	3.97
3	3.7083	-45.88

No.		Δ Time(ms)	Δ Level(dB)
1	mk3-mk1	3.0333	2.58

File: 0324 MIC Data: #58 Date: 2012/3/30 Temperature: 20 °C
Time: PM 01:36:23 Humidity: 54 %



Condition: Horizontal
EUT: Sweep Time: 3300ms Att.: 30dB
Model: RBW: 1000 KHz VBW: 1000 KHz
Test Mode:
Note: DH5 Hops per 3.16 seconds