

No. : HM162445 New Bright Industrial Co. Ltd. **Applicant (NEB001):** 9/F, New Bright Building, 11 Sheung Yuet Road Kowloon Bay Hong Kong China **Manufacturer:** New Bright Industrial Co. Ltd.

9/F, New Bright Building, 11 Sheung Yuet Road Kowloon Bay Hong Kong China Radio Control Toy Transmitter New Bright

G6D10855HK

G6D10855HK

Brand Name: Model Number: FCC ID:

2008-08-28

2008-09-03

Product:

**Date Samples Received:** 

**Description of Samples:** 

**Date Tested:** 

Date : 2008-09-16

**Investigation Requested:** 

**Conclusions:** 

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2006 and ANSI C63.4:2003 for FCC Certification.

The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

**Remarks:** 


Dr. LEE Kam Chuen, ElectroMagnetic Compatibility Department For and on behalf of The Hong Kong Standards and Testing Centre Ltd



This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre Ltd. For full text of "Conditions of Issuance of Test Report", please refer to overleaf or refer to the website of Homepage.

Page 1 of 18





The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 3 of 18

# Appendix A

List of Measurement Equipment

# Appendix B

Duty Cycle Correction During 100 msec

# Appendix C

Photographs

Page 17-18 of 18

Page 14-16 of 18

Page 13 of 18





The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



No. : HM162445

# 1.0 General Details

# 1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

# 1.2 Applicant Details Applicant

New Bright Industrial Co. Ltd. 9/F, New Bright Building, 11 Sheung Yuet Road Kowloon Bay Hong Kong China

# Manufacturer

New Bright Industrial Co. Ltd. 9/F, New Bright Building, 11 Sheung Yuet Road Kowloon Bay Hong Kong China



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd . For Conditions of Issuance of this test report, please refer to the overleaf or Hom epage

Page 4 of 18



No. : HM162445

Page 5 of 18

# 1.3 Equipment Under Test [EUT] Description of Sample

Model Name: Manufacturer: Brand Name: Model Number: Input Voltage: Radio Control Toy Transmitter New Bright Industrial Co. Ltd. New Bright G6D10855HK 3Vd.c ("AA" size battery x 2)

# **1.3.1** Description of EUT Operation

The Equipment Under Test (EUT) is a New Bright Industrial Co. Ltd., Radio Control Toy Transmitter. The transmitter is a 2 joystick transmitter. The EUT continues to transmit while joystick is being pressed, It is pulse transmitter, Modulation by IC, and type is pulse modulation.

# 1.4 Date of Order

2008-08-28

# 1.5 Submitted Sample(s):

1 Sample

## **1.6** Test Duration

2008-09-03

# **1.7** Country of Origin

China



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



No. : HM162445

2.2

Page 6 of 18

#### 2.0 **Technical Details**

#### 2.1 **Investigations Requested**

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2007 and ANSI C63.4:2003 for FCC Certification.

# **Test Standards and Results Summary Tables** Г

EMISSION Results Summary							
Test Condition	Test Requirement	Test Method	Class /	Test	Result		
			Severity	Pass	Failed		
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.235	ANSI C63.4:2003	N/A	$\boxtimes$			
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2003	N/A	$\boxtimes$			

Note: N/A - Not Applicable



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org




Date	: 2008-09-16		Page 7 of 18
No.	: HM162445		
3.0			
<u>3.0</u>	<u>Test Results</u>		
3.1	Emission		
3.1.1	Radiated Emissions (30	) – 1000MHz)	
	Test Requirement:	FCC 47CFR 15.235	
	Test Method:	ANSI C63.4:2003	
	Test Date:	2008-09-03	
	Mode of Operation:	Tx mode	

### **Test Method:**

The sample was placed 0.8m above the ground plane of Semi-Anechoic Chamber\*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\* Semi-Anechoic Chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd. with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 8 of 18

# Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Fundamental Emission
	[Peak]	[Average]
[MHz]	[µV/m]	[µV/m]
49.82-49.90	100,000	10,000

**Results:** 

Field Strength of Fundamental Emissions								
	Peak Value							
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBμV	dB/m	dBuV/m	μV/m	μV/m	-		
49.86	63.4	9.7	73.1	4,518.6	100,000	Horizontal		

Field Strength of Fundamental Emissions							
Average							
Frequency	Measured	Adjusted by	Correction	Field	Field	Limit @3m	E-Field
	Level @3m	Duty Cycle	Factor	Strength	Strength		Polarity
	dBµV		dB/m	dBuV/m	μV/m	μV/m	
49.86	58.9	-4.50	9.7	68.6	2,691.5	10,000	Horizonta
		5					

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

### Remarks:

Correction Factor inclu	des Antenna Facto	or and Cable A	Attenuation.		
Calculated measuremen	t uncertainty	: 301	MHz to 1GHz	5.2dB	

The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



No. : HM162445

Page 9 of 18

# Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range	Quasi-Peak Limits
[MHz]	[µV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

# **Results:**

	Radiated Emissions								
Quasi-Peak									
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	dBµV	dB/m	dBµV/m	μV/m	μV/m				
99.72	17.5	10.1	27.6	24.0	150	Horizontal			
149.58	< 1.0	10.3	< 11.3	< 3.7	150	Vertical			
199.44	8.2	11.6	19.8	9.8	150	Horizontal			
243.30	17.2	13.6	30.8	34.7	200	Horizontal			
249.30	< 1.0	15.9	< 16.9	< 7.0	200	Vertical			
299.16	< 1.0	15.3	< 16.3	< 6.5	200	Vertical			
349.02	< 1.0	17.2	< 18.2	< 8.1	200	Vertical			
398.88	< 1.0	17.3	< 18.3	< 8.2	200	Vertical			
448.74	< 1.0	20.5	< 21.5	< 11.9	200	Vertical			
498.60	< 1.0	20.6	< 21.6	< 12.0	200	Vertical			

Remarks:

No further spurious emissions found between lowest internal frequency and 30MHz.

Correction Factor includes Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz 5.2dB



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 10 of 18

# 3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: Test Method: Test Date: Mode of Operation: FCC 47 CFR 15.235 ANSI C63.4:2003 (Section 13.1.7) 2008-09-03 On mode

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.




The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



No. : HM162445

Page 11 of 18


Limits for 20dB Bandwidth of Fundamental Emission:



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 12 of 18





The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



No. : HM162445

# Appendix A

## List of Measurement Equipment

		Radiated Emis	sion			
EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLER	EMCO	2090	00024676	N/A	N/A
EM216	MINI MAST SYSTEM	ЕМСО	2075	00026842	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	ЕМСО	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-Linggren	FACT-3		2006/05/02	2009/05/02
EM174	BICONILOG ANTENNA	EMCO	3142C	00029071	2008/01/24	2009/01/24
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072	2008/06/16	2009/06/16
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	2006/07/26	2009/07/26

# **Remarks:-**

- CM Corrective Maintenance
- N/A Not Applicable or Not Available
- TBD To Be Determined





### The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd . For Conditions of Issuance of this test report, please refer to the overleaf or Hom epage

Page 13 of 18



**Appendix B** 


### **Duty Cycle Correction During 100msec**

Each function key sends a different series of characters, but each packet period (16.53msec) never exceeds a series of 4 long (1.36msec) and 10 short (0.441msec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered (4x1.36)+(10x0.441)msec per 16.53msec=59.6% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = 20Log(0.596) =-4.5dB

The following figures [Figure A to Figure B] show the characteristics of the pulse train for one of these functions.




The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Ltd . For Conditions of Issuance of this test report, please refer to the overleaf or Hom epage

Page 14 of 18



Page 15 of 18






The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 16 of 18





The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 17 of 18

Appendix C

**Photographs of EUT** 




**Inner Circuit Top View** 

**Rear View of the product** 



**Inner Circuit Bottom View** 







The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Page 18 of 18



\*\*\*\*\* End of Test Report \*\*\*\*\*



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org