

Hong Kong Standards and Testing Centre

Date : 2005-10-06 No. : HM155217

**Applicant:** 

# TEST REPORT

Page 1 of 17

NEW BRIGHT INDUSTRIAL CO., LTD. 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, H.K.

**Description of Samples:** 

Model no.: Brand name: FCC ID:

2005-09-28

Model name:

Radio Control Toy Vehicles Transmitters and Receiver 656HS NEW BRIGHT G6D656HS

Date Samples Received:

Date Tested:

2005-10-03 to 2005-10-04

**Investigation Requested:** 

FCC Part 15 Subpart C

Conclusions:


The submitted product <u>COMPLIED</u> with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks:


K C Lee, EMD for Chief Executive

This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.

香港新界大埔工業村大宏街 10號



#### 香港新界大埔工業村大宏街 10號



#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

## **TEST REPORT**

Page 4 of 17

#### 1.0 General Details

#### 1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone:852 2666 1888Fax:852 2664 4353

#### 1.2 Applicant Details Applicant

NEW BRIGHT INDUSTRIAL CO., LTD. 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, H.K.

#### **HKSTC Code Number for Applicant**

<u>NEB001</u>

#### Manufacturer

NEW BRIGHT INDUSTRIAL CO., LTD. 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, H.K.



#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

## TEST REPORT

Page 5 of 17

- 1.3 Equipment Under Test [EUT] Description of Sample
  - Model Name: Manufacturer: Brand Name: Model Number: Rating:

Radio Control Toy Vehicles Transmitters and Receiver NEW BRIGHT INDUSTRIAL CO., LTD. NEW BRIGHT 656HS 9Vd.c ("AA" size battery x 6)

#### 1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a NEW BRIGHT INDUSTRIAL CO., LTD., Radio Control Toy Vehicles Transmitters and Receiver. The transmitter is a 2 joystick transmitter. The EUT continues to transmit while joystick is being pressed, It is pulse transmitter, Modulation by IC, and type is pulse modulation.

#### 1.4 Date of Order

2005-09-28

#### 1.5 Submitted Sample(s):

1 Sample per model

#### 1.6 Test Duration

2005-10-03 to 2005-10-04

#### 1.7 Country of Origin

CHINA



#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

### TEST REPORT

Page 6 of 17

### 2.0 Technical Details

#### 2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

#### 2.2 Test Standards and Results Summary Tables

EMISSION Results Summary									
Test Condition Test Requirement Test Method Class / Test Result									
			Severity	Pass	Failed	N/A			
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.227	ANSI C63.4:2003	N/A	$\boxtimes$					
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.4:2003	Class B	$\boxtimes$		Ы			
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B			$\boxtimes$			

Note: N/A - Not Applicable



#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

TEST REPORT

Page 7 of 17

### 3.0 Test Results

### 3.1 Emission


3.1.1 Radiated Emissions (30 - 1000MHz)

Test Requirement: Test Method: Test Date: Mode of Operation: FCC 47CFR 15.227 ANSI C63.4:2003 2005-10-03 Tx mode

#### **Test Method:**

The sample was placed 0.8m above the ground plane on the OATS \*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

OATS [Open Area Test Site] located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.



#### 香港新界大埔工業村大宏街 10號



Date : 2005-10-06

No. : HM155217

TEST REPORT

Page 8 of 17

#### Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of	Field Strength of	Field Strength of
Fundamental	Fundamental Emission	Fundamental Emission
	[Peak]	[Average]
[MHz]	[µV/m]	[µV/m]
26.96-27.28	100,000	10,000

#### **Results:**

Field Strength of Fundamental Emissions Peak Value								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBµV	dB/m	dBµV/m	μV/m	μV/m			
27.15	53.20	19.2	72.4	4,168.7	100,000	Vertical		

Field Strength of Fundamental Emissions Average								
Frequency	Measured	Adjusted by	Correction	Field	Field	Limit @3m	E-Field	
	Level @3m	Duty Cycle	Factor	Strength	Strength		Polarity	
MHz	dBµV	dB	dB/m	dBµV/m	μV/m	μV/m		
27.15	28.5	-24.7	19.2	47.7	242.7	10,000	Vertical	

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Remarks:

Correction Factor includes Antenna Factor and Cable Attenuation. Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB

香港新界大埔工業村大宏街 10號



Date : 2005-10-06

No. : HM155217

TEST REPORT

Page 9 of 17

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [µV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

#### **Results :**

	Radiated Emissions Quasi-Peak								
Frequency	Lev	easured el @3m	Correction Factor	S	Field trength	S	Field trength	Limit @3m	E-Field Polarity
MHz	C	lBμV	dB/m	di	BµV/m		µV/m	μV/m	
54.29	<	1.0	10.1	<	11.1	<	3.6	100	Vertical
81.44	<	1.0	9.5	<	10.5	<	3.3	100	Vertical
108.58	<	1.0	10.7	<	11.7	<	3.8	150	Vertical
135.73	<	1.0	10.2	<	11.2	<	3.6	200	Vertical
162.87	<	1.0	11.9	<	12.9	<	4.4	200	Vertical
190.02	<	1.0	12.4	<	13.4	<	4.7	200	Vertical
217.16	<	1.0	13.2	<	14.2	<	5.1	200	Vertical
244.31	<	1.0	15.0	<	16.0	<	6.3	200	Vertical
271.45	<	1.0	16.1	<	17.1	<	7.2	200	Vertical

#### Remarks:

Correction Factor includes Antenna Factor and Cable Attenuation. Calculated measurement uncertainty : 30MHz to 1GHz









Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

<u>TEST REPORT</u>

Page 10 of 17

3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: Test Method: Test Date: Mode of Operation: FCC 47CFR 15.207 ANSI C63.4:2003 N/A N/A

#### Results: N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.





#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06

No. : HM155217

TEST REPORT

Page 11 of 17

#### 3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: Test Method: Test Date: Mode of Operation:

FCC 47 CFR 15.227 ANSI C63.4:2003 (Section 13.1.7) 2005-10-04 On mode

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

#### **Test Setup:**


As Test Setup of clause 3.1.1 in this test report.




#### 香港新界大埔工業村大宏街 10號



Limits for 20dB Bandwidth of Fundamental Emission:





Colled Colled Colled

#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

## **TEST REPORT**

Page 13 of 17

Date : 2005-10-06 No. : HM155217

Appendix A

List of Measurement Equipment

		Radiated Emissi			
EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	15/06/04
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	15/06/04
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	15/06/04
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	15/06/04
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	15/06/04
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	15/06/04
EM020	HORN ANTENNA	ETS-Linggren	3115	4032	30/07/03
EM022	LOOP ANTENNA	ETS-Linggren	6502	1189-2424	19/09/03
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/02/03
EM131	EMC ANALYZER	HEWLETT PACKARD	8595EM	3710A00155	13/01/04
EM145	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESCS 30	830245/021	04/10/04
EM195	ANTENNA POSITIONING MAST	ETS-Linggren	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	ETS-Linggren	2090	1662	N/A
EM215	MULTIDEVICE CONTROLER	ETS-Linggren	2090	00024676	N/A
EM216	MINI MAST SYSTEM	ETS-Linggren	2075	00026842	N/A
EM217	ELECTRIC POWERED TURNTABLE	ETS-Linggren	2088	00029144	N/A
EM218	ANECHOIC CHAMBER	ETS-Linggren	FACT-3		19/03/04
EM219	BICONILOG ANTENNA	ETS-Linggren	3142C	00029071	28/10/03
EM218	ETS ANECHOIC CHAMBER	EMCO	Fact-3	N/A	15/03/04
EM215	MULTI-DEVICE CONTROLLER	EMCO	2090	00024676	N/A
EM216	ANTENNA POSITIONING MAST	EMCO	2070	00024727	N/A

#### Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	27/01/05
EM119	LISN	ROHDE & SCHWARZ	ESH3-Z5	0831.5518.52	14/10/04
EM127	ISOLATION TRANSFORMER 220 TO 300V	WING SUN	N/A	N/A	СМ
EM142	PULSE LIMITER	ROHDE & SCHWARZ	ESH3Z2	357.8810.52	04/08/04
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072	06/01/04
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	27/01/05
EM197	LISN	ETS-Linggren	4825/2	1193	05/06/04
EM213	DIGITAL POWER METER	VICNOBL	VIP120	00277	14/09/04

#### Remarks:-

- CM Corrective Maintenance
- N/A Not Applicable or Not Available
- TBD To Be Determined

#### 香港新界大埔工業村大宏街 10號



Hong Kong Standards and Testing Centre

Date : 2005-10-06 No. : HM155217 TEST REPORT

Page 14 of 17


Appendix B

**Duty Cycle Correction During 100msec** 

Each function key sends a different series of characters, but each packet period (59.5msec) never exceeds a series of short (3.5msec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered 3.5msec per 59.5msec=5.8% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = 20Log(0.058) =-24.7dB



The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.

#### 香港新界大埔工業村大宏街 10號



Figure B [Long or Short Pulse] MARKER 3.5000 ACTV DE .31 dB LOG REF 67.0 dBpV 10 dB/ MATH 0 dB M VA SB SC FC CORR CENTER 27.14560 F BW 3.9 MHZ SPAN 0 Hz 100 ssec AVG BW 3 kHz #SWP



#### 香港新界大埔工業村大宏街 10 號



#### 香港新界大埔工業村大宏街 10號




Date : 2005-10-06 No. : HM155217

## TEST REPORT

Page 17 of 17

Photographs of EUT



\*\*\*\*\* End of Test Report \*\*\*\*\*



#### 香港新界大埔工業村大宏街 10號