






**BUREAU
VERITAS**

TEST REPORT No.: (5216)155-0874

TEST REPORT

To:	NEW BRIGHT INDUSTRIAL CO., LTD	To:	-
Attn:	Eric Kwok	Attn:	-
Address:	9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, HONG KONG	Address:	-
Fax:	852 27953665	Fax:	-
E-mail:	ypeng01@newbright.com chkwok01@newbright.com	E-mail:	-
Folder No.:	NBT-16JU018MTHS-B-A		
Factory Name:	NEW BRIGHT INDUSTRIAL CO., LTD		
Location:	9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, HONG KONG		
Product:	TOY Transmitter MODEL: G21HB		
	Sample No:	HK160526/029	
	Date of Receipt:	May 26, 2016	
	Test date:	June 11, 2016	
	Test Requested:	FCC Part 15 – 2012	
	Test Method:	ANSI C63.4 – 2009	
	FCC ID:	G6DG21HB	
The results given in this report are related to the tested specimen of the described electrical apparatus.			
CONCLUSION: The submitted sample was found to <u>COMPLY</u> with requirement of FCC Part 15 Subpart C.			
Authorized Signature:			
			
Reviewed by: Keith Yeung		Approved by: Law Man Kit	
Date: June 13, 2016		Date: June 13, 2016	

**BUREAU VERITAS HONG KONG LIMITED –
Kowloon Bay Office**
1/F Pacific Trade Centre,
2 Kai Hing Road, Kowloon Bay,
Kowloon, HONG KONG
Tel: +852 2331 0888
Fax: +852 2331 0889
www.cps.bureauveritas.com

This report is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Our report is limited to the test samples identified herein. The results set forth in this report are not necessarily indicative or representative of the statistical quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof. You shall have thirty days from receipt of this report to request additional testing of the samples or to notify us of any errors or omissions relating to our report, provided, however, such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TEST REPORT No.: (5216)155-0874

Test Result Summary

EMISSION TEST			
Test requirement: FCC Part 15 - 2012			
Test Condition	Test Method	Test Result	
		Pass	Failed
Radiated Emission Test, 9kHz to 1GHz	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Frequency range of Fundamental Emission	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>
26dB Bandwidth of Fundamental Emission	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Duty Cycle Correction During 100mesc	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Report Revision & Sample Re-submit History:

--



TEST REPORT No.: (5216)155-0874

Test Laboratory & Test Instruments List

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009. An Open Area Test Site and Full Anechoic Chamber (FCC Listed Site, Registration No. 642151) are set up for investigation and located at:

BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre,
26 Hung To Road,
Kwun Tong, Kowloon,
Hong Kong

Test Instrument List

Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATION DUE
EMI TEST RECEIVER	R&S	ESCI	100379	22-Feb-2017
SIGNAL ANALYZER 40GHZ	R&S	FSV 40	100977	29-Jun-2016
LOOP ANTENNA	ETS-LINDGREN	6502	00102266	05-Nov-2016
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	26-Feb-2017
OPEN AREA TEST SITE	BVCPS	N/A	N/A	18-Jun-2016
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	11-Feb-2017
COAXIAL CABLE	SUHNER	RG214	N/A	04-Oct-2016
Biconical Antenna	Rohde & Schwarz	HK116	100179	13-Apr-2018
Log-Periodic Dipole Array Antenna	Rohde & Schwarz	HL223	832369/001	06-Apr-2018

Measurement Uncertainty

Measurement	Frequency	Uncertainty
Radiated emissions	9kHz to 30MHz	4.2dB
	30MHz to 200MHz	4.5dB
	200MHz to 1GHz	5.6dB
	1GHz to 18GHz	4.9dB
	18GHz to 40GHz	4.8dB

Remarks: -

N/A: Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result

TEST REPORT No.: (5216)155-0874

Equipment Under Test [EUT]

Description of Sample:

Product: TOY Transmitter
Model No.: G21HB
Additional Model name: --
Additional Model number: --
Additional Model Information: --
Power Supply: 3Vd.c. ("AA" size battery x 2)

Description of EUT Operation:

The Equipment Under Test (EUT) is a **NEW BRIGHT INDUSTRIAL CO., LTD** of Radio Control toy. The transmitter is 2 sticks and operating at 27.146MHz. The EUT continues to transmit while stick are being pushed or pulled, Modulation by IC, and type is pulse modulation.

The transmitter has different control:

1. Left Stick – control forward and backward
2. Right Stick – control left and right

Antenna Requirement (Section 15.203)

The EUT is use of a permanently antenna. The antenna consists of 36cm long wire. It is soldered on the PCB. The antenna is not replaceable or user serviceable. The requirements of S15.203 are met. There are no deviations or exceptions to the specifications.

Photo of Antenna



TEST REPORT No.: (5216)155-0874

Test Results

Radiated Emissions (Fundamental)

Test Requirement: FCC Part 15 Section 15.227
 Test Method: ANSI C63.4
 Test Date(s): 2016-06-11
 Temperature: 27.0 °C
 Humidity: 85.0 %
 Atmospheric Pressure: 100.2 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: 3Vd.c. ("AA" size battery x 2)

Test Method:


Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Test Setup: Open Area Test Site





TEST REPORT No.: (5216)155-0874

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [μV/m]	Field Strength of Fundamental Emission [Average] [μV/m]
26.96 – 27.28	100,000 (100 dBμV/m)	10,000 (80 dBμV/m)

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Peak

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.146	V/0°	9.7	47.9	100.0	-52.1

Detection mode: # Average

Frequency (MHz)	Polarity (H/V) and degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.146	V/0°	9.7	**43.7	80.0	-36.3

For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

**Duty Cycle Correction = $20\log(0.62) = -4.2\text{dB}$

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 100KHz
VBW = 300KHz



TEST REPORT No.: (5216)155-0874

Radiated Emissions (9kHz – 1GHz)

Test Requirement: FCC Part 15 Section 15.209
 Test Method: ANSI C63.4
 Test Date(s): 2016-06-11
 Temperature: 27.0 °C
 Humidity: 85.0 %
 Atmospheric Pressure: 100.2 kPa
 Mode of Operation: Transmission mode
 Tested Voltage: 3Vd.c. ("AA" size battery x 2)

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [$\mu\text{V}/\text{m}$]	Measurement Distance m
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above960	500	3

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB $\mu\text{V}/\text{m}$)	Limit at 3m (dB $\mu\text{V}/\text{m}$)	Margin (dB)
Emissions detected are more than 20 dB below the limit line(s) in 9kHz to 30MHz				

Note: Field Strength includes Antenna Factor and Cable Loss.



TEST REPORT No.: (5216)155-0874

Measurement Data

Test Result of (Transmission mode): PASS

Detection mode: Quasi-Peak

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
54.292	H	9.3	37.3	40.0	-2.7
81.438	H	9.1	28.6	40.0	-11.4
108.584	H	10.6	27.3	43.5	-16.2
135.730	H	12.2	25.6	43.5	-17.9
162.876	H	13.5	31.8	43.5	-11.7
190.022	H	14.7	25.3	43.5	-18.2
217.168	H	11.2	25.7	46.0	-20.3
244.314	H	11.8	29.8	46.0	-16.2
271.460	H	13.4	42.5	46.0	-3.5
298.606	H	13.6	42.3	46.0	-3.7
325.752	H	14.6	40.9	46.0	-5.1
352.898	H	15.3	33.8	46.0	-12.2

Frequency (MHz)	Polarity (H/V)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
54.292	V	9.3	32.6	40.0	-7.4
81.438	V	9.1	27.6	40.0	-12.4
108.584	V	10.6	27.0	43.5	-16.5
135.730	V	12.2	27.4	43.5	-16.1
162.876	V	13.5	33.3	43.5	-10.2
190.022	V	14.7	26.2	43.5	-17.3
217.168	V	11.2	26.3	46.0	-19.7
244.314	V	11.8	30.1	46.0	-15.9
271.460	V	13.4	39.8	46.0	-6.2
298.606	V	13.6	40.1	46.0	-5.9
325.752	V	14.6	40.3	46.0	-5.7
352.898	V	15.3	31.7	46.0	-14.3

Note: Field Strength includes Antenna Factor and Cable Loss.

Receiver setting: RBW = 120KHz
 VBW = 120KHz



TEST REPORT No.: (5216)155-0874

26dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.227
Test Method: ANSI C63.4
Test Date(s): 2016-06-11
Temperature: 27.0 °C
Humidity: 85.0 %
Atmospheric Pressure: 100.2 kPa
Mode of Operation: Transmission mode
Tested Voltage: 3Vd.c. ("AA" size battery x 2)

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Limits for 26dB Bandwidth of Fundamental Emission:

Frequency [MHz]	26dB Bandwidth [KHz]	Limits [MHz]
27.14688	30.08	within 26.96 – 27.28



BUREAU VERITAS

TEST REPORT No.: (5216)155-0874


Measurement Data

Test Result of 26dB Bandwidth of Fundamental Emission: PASS



*RBW 3 kHz Marker 1 [T1]
VBW 10 kHz 50.64 dBµV/m
SWT 40 ms 27.146880000 MHz

Ref 82 dBµV/m *Att 10 dB



Date: 11.JUN.2016 10:02:04



TEST REPORT No.: (5216)155-0874

Duty Cycle Correction During 100msec:

Each function key sends a different series of characters, but each packet period (100msec) never exceeds a series of 8 long (1.6msec) and 82 short (0.6msec) pulses. Assuming any combination of pulses maybe obtained due to encoding the worst case transmit duty cycle would be considered $(8 \times 1.6\text{msec}) + (82 \times 0.6\text{msec})$ per 100msec = 62.0% duty cycle.

Remarks: -

Duty Cycle Correction = $20\text{Log}(0.62) = -4.2\text{dB}$


The following figures [Figure A to Figure B] show the characteristics of the pulse train for one of these functions.



BUREAU VERITAS


TEST REPORT No.: (5216)155-0874

Figure A (Long Pulse)



Date: 11.JUN.2016 10:04:29

Figure B (Short Pulse)



Date: 11.JUN.2016 10:04:52

TEST REPORT No.: (5213)331-1368
Photographs of EUT

Front View of the product



Rear View of the product



Top View of the product



Bottom View of the product



Side View of the product



Side View of the product



Battery compartment



Battery Cover



TEST REPORT No.: (5213)331-1368
Photographs of EUT


Internal View of the product




Internal View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Antenna



TEST REPORT No.: (5213)331-1368

Measurement of Radiated Emission Test Set Up



******* End of Report *******