



TEST REPORT No.: (5217)137-0074(E)

## TEST REPORT

To:	<b>NEW BRIGHT INDUSTRIAL CO., LTD</b>	To:	-
Attn:	Erick Kwok	Attn:	-
Address:	9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, HONG KONG.	Address:	-
Fax:	852 27953665	Fax:	-
E-mail:	<a href="mailto:ypeng01@newbright.com">ypeng01@newbright.com</a> / <a href="mailto:chkwok01@newbright.com">chkwok01@newbright.com</a>	E-mail:	-
Folder No.:	NBT-17AP158MTHS-B-C		
Factory Name:	<b>NEW BRIGHT INDUSTRIAL CO., LTD</b>		
Location:	9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY, KOWLOON, HONG KONG.		
Product:	TOY Receiver		
Model No.:	GF3718RR		
Additional Model No.:	--		
		Sample No:	HK170418/049
		Date of Receipt	April 18, 2017
		Test Date(s):	May 08, 2017 to May 12, 2017
		Test Requested:	FCC Part 15 – 2015
		Test Method:	ANSI C63.4 – 2014
<p><b>The results given in this report are related to the tested specimen of the described electrical apparatus.</b></p> <p><b>CONCLUSION: The submitted sample was found to <u>COMPLY</u> with requirement of FCC Part 15 Subpart B.</b></p>			

Assistant Manager,  
EMC Department

Name: Law Man Kit  
Date: June 06, 2017



## TEST REPORT No.: (5217)137-0074(E)

### Equipment Under Test:

Product : TOY Receiver  
Model No. : GF3718RR  
Power Supply : USB: 5Vd.c.  
Data Cable : --  
Power Line Cable : 0.46m non-shielded USB cable  
Accessory Device : --

### Description of Adaptor

Adaptor : SUPER  
Model : S-1200R  
Input : 120Va.c., 60Hz, 31.8W  
Input power line cable : 1.83m non-shielded cable  
Output : 3.0-15Vd.c., 1200mA  
Output power line cable : 1.01m non-shielded cable

### Additional Product Name:

--

### Additional Model No.:

--

### Additional Model Information:

--

### Description of Test modes:

Charge mode: with indicator light

### Report Revision & Sample Re-submit History:

--

### Remark: -

For the test results, the EUT had been tested with all conditions. The worst case was showed in test report.



**TEST REPORT No.: (5217)137-0074(E)**

## Test Result Summary

<b>EMISSION TEST</b>			
<b>Test requirement: FCC Part 15 - 2015</b>			
Test Condition	Test Method	Test Result	
		Pass	Failed
Conducted Emission Test, 0.15MHz to 30MHz	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission Test, 30MHz to 1GHz	ANSI C63.4	<input checked="" type="checkbox"/>	<input type="checkbox"/>



**TEST REPORT No.: (5217)137-0074(E)**

## Test Laboratory & Test Instruments List

Radiated and Conducted emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014. An Open Area Test Site and Full Anechoic Chamber are set up for investigation and located at:

### BUREAU VERITAS HONG KONG LIMITED, EMC CENTRE

No. 2106-2107, 21/F., Westin Centre,  
26 Hung To Road,  
Kwun Tong, Kowloon,  
Hong Kong

### Test Instrument List

#### Radiated Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
EMI TEST RECEIVER	R&S	ESCI	100379	22-FEB-2017	21-FEB-2018
SIGNAL ANALYZER 40GHZ	R&S	FSV 40	100977	16-AUG-2016	15-AUG-2017
BILOG ANTENNA	SCHAFFNER	CBL6112D	25229	27-FEB-2016	26-FEB-2018
OPEN AREA TEST SITE	BVCPS	N/A	N/A	18-JUN-2016	17-JUN-2017
ANECHOIC CHAMBER	ALBATROSS	M-CDC	80374004499B	10-MAY-2017	09-MAY-2018
BICONICAL ANTENNA	R&S	HK116	100179	14-APR-2016	13-APR-2018
LOG-PERIODIC DIPOLE ARRAY ANTENNA	R&S	HL223	832369/001	07-APR-2016	06-APR-2018

#### Conducted Emission

EQUIPMENT	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
EMI TEST RECEIVER	R&S	ESCI	100379	22-FEB-2017	21-FEB-2018
LISN	R&S	ENV216	100024	19-OCT-2016	18-OCT-2017
SOFTWARE	MANUFACTURER	VERSION	SERIAL NO.		
EMC32-E	R&S	8.4	N/A		

### Measurement Uncertainty

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz to 30MHz	2.9dB
Radiated emissions	9kHz to 30MHz	4.2dB
	30MHz to 200MHz	4.5dB
	200MHz to 1GHz	5.6dB
	1GHz to 18GHz	4.7dB

#### Remarks: -

N/A: Not Applicable or Not Available

The measurement instrumentation uncertainty would be taking into consideration on each of the test result



## TEST REPORT No.: (5217)137-0074(E)

### Test Results

#### Conducted Emissions (150kHz to 30MHz)

Test Requirement:	FCC Part 15 Section 15.107
Test Method:	ANSI C63.4
Test Limits:	Class B
Test Date(s):	2017-05-08
Temperature:	25.0 °C
Humidity:	70.0 %
Atmospheric Pressure:	99.9 kPa
Mode of Operation:	Charge mode
Tested Voltage:	120Va.c., 60Hz


#### Test Method:

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2014. The EUT was setup as described in the procedures, and both lines were measured.

Initial measurements were performed in peak and average detection modes on the live and neutral line, any emissions recorded within 30dB of the relevant limit lines were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Location: No. 603, 6/F., Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

#### Test Setup: Shielding Room





**TEST REPORT No.: (5217)137-0074(E)**


**Measurement Data**

**Test Result of (Charge mode): PASS**

**Results and limit lines for Conducted Emission:**

Limits for Conducted Emission Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

FCC Part 15 Class B Voltage



Receiver setting: RBW = 120 kHz  
VBW = 120 kHz

## TEST REPORT No.: (5217)137-0074(E)

### Radiated Emissions (30MHz to 1GHz)

Test Requirement: FCC Part 15 Section 15.109  
 Test Method: ANSI C63.4  
 Test Limits: Class B  
 Test Date(s): 2017-05-12  
 Temperature: 27.0 °C  
 Humidity: 63.0 %  
 Atmospheric Pressure: 99.5 kPa  
 Mode of Operation: Charge mode  
 Tested Voltage: 120Va.c., 60Hz


### Test Method:

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

Location: The Roof, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

### Test Setup: Open Area Test Site





**TEST REPORT No.: (5217)137-0074(E)**

**Limits for Radiated Emission: FCC Part 15.109**

Frequency Range [MHz]	Limits [dB $\mu$ V/m @ 3m]
30-88	40.0
88-216	43.5
216-960	46.0
Above 960	54.0

**Measurement Data**

**Test Result of (Charge mode): PASS**

**Detection mode: Quasi-Peak**

Frequency (MHz)	Polarity (H/V)	Field Strength at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Emissions detected are more than 20 dB below the limit line(s)				

Note: Field Strength includes Antenna Factor and Cable Loss.





**TEST REPORT No.: (5217)137-0074(E)**

**Appendix I  
Regulatory Statement and Label Marking Advice for the FCC Verification (Class B)**

**1. Marking suggested for the Label:**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
(1) this device may not cause harmful interference, and  
(2) this device must accept any interference received, including interference that may cause undesired operation.

**2. Regulatory Statement suggested for the User Manual:**

Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

\*\*\*\*\*

Notes: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

\*\*\*\*\*

If shielded cables or special accessories are required for compliance, a statement must be included which instructs the user to employ them, for example, Shielded cables must be used with this unit to ensure compliance with the Class B FCC limits.

**\*\*\*\* End of Test Report \*\*\*\***