



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-210 ISSUE 9**

**TEST REPORT**

*For*

**TOY Transmitter**

**MODEL NUMBER: GGH2B**

**FCC ID: G6DGGH2B**

**IC:9650A-GGH2B**

**REPORT NUMBER: 4788921510.1-2**

**ISSUE DATE: March 27, 2019**

*Prepared for*

**NEW BRIGHT INDUSTRIAL CO., LTD  
9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY,  
KOWLOON, HONG KONG.**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake  
Hi-Tech Development Zone Dongguan, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V0	03/27/2019	Initial Issue	



Summary of Test Results			
Clause	Test Items	IC Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	CFR 47 FCC 15.249(d) ISED RSS-Gen Clause 6.7	Pass
2	Radiated emission	CFR 47 FCC §15.249 (a)(d)(e) ISED RSS-210 Clause Annex B B.10 CFR 47 FCC §15.205 and §15.209 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	Pass
3	Antenna Requirement	FCC Part 15.203 ISED RSS-Gen Clause 8.3	Pass



## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>5</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>8</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>8</i>
5.3. <i>CHANNEL LIST.....</i>	<i>8</i>
5.4. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>8</i>
5.5. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.6. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>9</i>
5.7. <i>TEST ENVIRONMENT .....</i>	<i>9</i>
5.8. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>10</i>
5.9. <i>MEASURING INSTRUMENT AND SOFTWARE USED.....</i>	<i>11</i>
<b>6. ANTENNA PORT TEST RESULTS .....</b>	<b>12</b>
6.1. <i>ON TIME AND DUTY CYCLE.....</i>	<i>12</i>
6.2. <i>20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH .....</i>	<i>14</i>
<b>7. RADIATED TEST RESULTS.....</b>	<b>18</b>
7.1. <i>LIMITS AND PROCEDURE.....</i>	<i>18</i>
7.2. <i>RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS</i> <i>25</i>	
7.3. <i>SPURIOUS EMISSIONS (1~3GHz).....</i>	<i>31</i>
7.4. <i>SPURIOUS EMISSIONS (3~18GHz).....</i>	<i>37</i>
7.5. <i>SPURIOUS EMISSIONS (18~26GHz).....</i>	<i>43</i>
7.6. <i>SPURIOUS EMISSIONS BELOW 30M.....</i>	<i>45</i>
7.7. <i>SPURIOUS EMISSIONS BELOW 1 GHz.....</i>	<i>51</i>
<b>8. ANTENNA REQUIREMENTS.....</b>	<b>53</b>



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: NEW BRIGHT INDUSTRIAL CO., LTD  
Address: 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD,  
KOWLOON BAY, KOWLOON, HONG KONG.

## Manufacturer Information

Company Name: NEW BRIGHT INDUSTRIAL CO., LTD  
Address: 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD,  
KOWLOON BAY, KOWLOON, HONG KONG.

## EUT Description

EUT Name: TOY Transmitter  
Model: GGH2B  
Brand Name: /  
Sample Status: Normal  
Date of Tested: March 11, 2019 ~ March 26, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-210 Issue 9	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Denny Huang  
Engineer Project Associate  
Approved By:

Stephen Guo  
Laboratory Manager

Checked By:

Shawn Wen  
Laboratory Leader



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2014, ISED RSS-210 Issue 9 and RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>IC(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	5.78dB (1GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	TOY Transmitter		
EUT Description	The EUT is a wireless remote controller.		
Model	GGH2B		
Product Description	Operation Frequency	2410 MHz ~ 2473 MHz	
	Modulation Type	GFSK	
Battery	DC 3.0V		

### 5.2. MAXIMUM OUTPUT POWER

Frequency Range (MHz)	Number of Transmit Chains (NTX)	Frequency (MHz)	Channel Number	Max Power (dB $\mu$ V/m)
2410 ~ 2473	1	2410	1[32]	89.52

### 5.3. CHANNEL LIST

Channel	Frequency (MHz)						
1	2410	11	2429	21	2450	31	2469
2	2414	12	2430	22	2452	32	2473
3	2415	13	2431	23	2454	/	/
4	2416	14	2433	24	2456	/	/
5	2417	15	2434	25	2458	/	/
6	2418	16	2439	26	2462	/	/
7	2419	17	2441	27	2464	/	/
8	2421	18	2442	28	2465	/	/
9	2426	19	2444	29	2466	/	/
10	2428	20	2446	30	2467	/	/

### 5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2410~ 2473	PCB Antenna	1.9

Test Mode	Transmit and Receive Mode	Description
GFSK	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.



### 5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 1, CH 18, CH 32	2410MHz, 2442MHz, 2473MHz

### 5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2410 ~ 2473MHz Band				
Test Software		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH 1	CH 18	CH 32
GFSK	1	Default	Default	Default

### 5.7. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28°C
	VL	N/A
Voltage :	VN	DC 3.0V
	VH	N/A

Note: VL= Lower Extreme Test Voltage  
 VN= Nominal Voltage  
 VH= Upper Extreme Test Voltage  
 TN= Normal Temperature



## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	/	/	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	/	/	/	/	/

### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

### TEST SETUP

The EUT have the engineer mode inside.

### SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.



### 5.9. MEASURING INSTRUMENT AND SOFTWARE USED

Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17,2018	Sep.17,2021
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A09099	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17,2018	Sep.17,2021
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.18,2018	Aug.18,2021
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Software						
Used	Description	Manufacturer	Name	Version		
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance	Farad	EZ-EMC	Ver. UL-3A1		
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.10,2018	Dec.10,2019
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.10,2018	Dec.10,2019



## 6. ANTENNA PORT TEST RESULTS

### 6.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### RESULTS

	On Time (ms)	Times	Total Ton times (ms)
Ton	0.272	6	1.632


Note: Total Ton times= Ton\*3

Total Ton times (ms)	Period (ms)	Duty Cycle (Linear)	Duty Cycle Correction Factor
1.632	9.962	0.1638	-15.71

Note: Duty Cycle Correction Factor=20log(x).  
Where: x is Duty Cycle



### Duty Cycle Test - 1



Date: 21.MAR.2019 07:53:47

Note 1: All test mode has been tested, only the worst duty cycle record in the report.

Note 2: Lab had already confirmed that the period is the same at any time.

## 6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.249) , Subpart C RSS-Gen Issue 5			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.249(d)	20dB Bandwidth	for reporting purposes only	2400-2483.5
ISED RSS-Gen Clause 6.7 Issue 5	99% Occupied Bandwidth	For reporting purposes only.	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.


### TEST SETUP






**RESULTS**

Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2410	1.279	1.4676	PASS






Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2442	1.252	1.5571	PASS





Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2473	1.389	1.7945	PASS





## 7. RADIATED TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMITS

CFR 47 FCC §15.205 and §15.209

CFR 47 FCC §15.249 (a)(d)(e)

ISED RSS-210 Issue 9 Clause Annex B B.10

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



IC Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands <sup>Note 1</sup>		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.



FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

**TEST SETUP AND PROCEDURE**

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. Average Value=Peak Value + Duty Correction Factor

For the Duty Cycle and Correction Factor please refer to clause 6.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:




Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (Y axis) data recorded in the report.



## 7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS

### RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2399.010	20.40	32.98	53.38	74.00	-20.62	peak
2	2400.000	19.58	32.98	52.56	74.00	-21.44	peak
3	2410.280	56.46	33.06	89.52	114.00	-24.48	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2386.705	15.89	32.94	48.83	74.00	-25.17	peak
2	2400.000	14.38	32.98	47.36	74.00	-26.64	peak
3	2410.280	45.94	33.06	79.00	114.00	-35.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2441.760	55.93	33.29	89.22	114.00	-24.78	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2441.840	46.46	33.29	79.75	114.00	-34.25	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2473.240	55.42	33.51	88.93	114.00	-25.07	peak
2	2483.500	16.28	33.58	49.86	74.00	-24.14	peak
3	2486.410	19.49	33.61	53.10	74.00	-20.90	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2473.540	48.49	33.51	82.00	114.00	-32.00	peak
2	2483.500	14.38	33.58	47.96	74.00	-26.04	peak
3	2494.600	16.36	33.66	50.02	74.00	-23.98	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



### 7.3. SPURIOUS EMISSIONS (1~3GHz)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1265.039	44.06	-11.64	32.42	74.00	-41.58	peak
2	1410.389	44.69	-11.88	32.81	74.00	-41.19	peak
3	1558.680	44.75	-11.03	33.72	74.00	-40.28	peak
4	2013.382	44.78	-9.59	35.19	74.00	-38.81	peak
5	2410.872	49.92	-7.02	42.90	74.00	-31.10	peak
6	2750.608	45.44	-6.29	39.15	74.00	-34.85	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1071.664	45.49	-12.75	32.74	74.00	-41.26	peak
2	1370.673	45.51	-11.71	33.80	74.00	-40.20	peak
3	1518.120	44.97	-11.42	33.55	74.00	-40.45	peak
4	2002.353	44.41	-9.75	34.66	74.00	-39.34	peak
5	2437.504	44.51	-6.82	37.69	74.00	-36.31	peak
6	2566.670	45.78	-6.65	39.13	74.00	-34.87	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1015.500	46.44	-13.03	33.41	74.00	-40.59	peak
2	1404.205	46.46	-11.90	34.56	74.00	-39.44	peak
3	1614.451	45.72	-10.63	35.09	74.00	-38.91	peak
4	1935.307	45.35	-9.47	35.88	74.00	-38.12	peak
5	2442.866	53.62	-6.78	46.84	74.00	-27.16	peak
6	2925.146	45.00	-5.00	40.00	74.00	-34.00	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1214.648	45.89	-12.25	33.64	74.00	-40.36	peak
2	1407.294	46.28	-11.90	34.38	74.00	-39.62	peak
3	1803.907	44.73	-9.42	35.31	74.00	-38.69	peak
4	2232.419	45.16	-8.13	37.03	74.00	-36.97	peak
5	2442.866	46.19	-6.78	39.41	74.00	-34.59	peak
6	2744.571	46.13	-6.43	39.70	74.00	-34.30	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1323.323	45.58	-11.38	34.20	74.00	-39.80	peak
2	1753.109	44.98	-10.03	34.95	74.00	-39.05	peak
3	2115.420	45.09	-8.34	36.75	74.00	-37.25	peak
4	2472.566	51.24	-6.54	44.70	74.00	-29.30	peak
5	2575.143	47.34	-6.69	40.65	74.00	-33.35	peak
6	2849.027	45.50	-5.17	40.33	74.00	-33.67	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1399.584	46.47	-11.92	34.55	74.00	-39.45	peak
2	1737.769	45.50	-10.22	35.28	74.00	-38.72	peak
3	1811.851	45.86	-9.40	36.46	74.00	-37.54	peak
4	2472.566	46.20	-6.54	39.66	74.00	-34.34	peak
5	2589.328	46.90	-6.75	40.15	74.00	-33.85	peak
6	2784.050	45.29	-5.56	39.73	74.00	-34.27	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



## 7.4. SPURIOUS EMISSIONS (3~18GHz)

### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4820.000	57.92	-0.21	57.71	74.00	-16.29	peak
2	4820.000	57.92	-0.21	42.00	54.00	-12.00	AVG
3	7153.599	40.20	6.88	47.08	74.00	-26.92	peak
4	8211.874	38.80	9.50	48.30	74.00	-25.70	peak
5	10534.290	37.25	12.10	49.35	74.00	-24.65	peak
6	14006.555	34.64	16.36	51.00	74.00	-23.00	peak
7	18000.000	30.17	23.27	53.44	74.00	-20.56	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4820.000	60.24	-0.21	60.03	74.00	-13.97	peak
2	4820.000	60.24	-0.21	44.32	54.00	-9.68	AVG
3	7414.599	39.53	7.46	46.99	74.00	-27.01	peak
4	8138.634	39.95	9.25	49.20	74.00	-24.80	peak
5	12223.395	36.65	14.26	50.91	74.00	-23.09	peak
6	13562.027	34.88	15.92	50.80	74.00	-23.20	peak
7	17807.526	28.18	23.21	51.39	74.00	-22.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4884.031	57.24	-0.12	57.12	74.00	-16.88	peak
2	4884.031	57.24	-0.12	41.41	54.00	-12.59	AVG
3	7051.791	40.57	6.81	47.38	74.00	-26.62	peak
4	10273.328	37.64	11.37	49.01	74.00	-24.99	peak
5	10648.151	37.14	12.51	49.65	74.00	-24.35	peak
6	13856.783	34.42	16.44	50.86	74.00	-23.14	peak
7	17967.777	29.00	23.24	52.24	74.00	-21.76	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. The Band Reject filter loss factor already add into the correct factor.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4884.031	59.49	-0.12	59.37	74.00	-14.63	peak
2	4884.031	59.49	-0.12	43.66	54.00	-10.34	AVG
3	7039.167	39.20	6.79	45.99	74.00	-28.01	peak
4	8153.229	39.47	9.35	48.82	74.00	-25.18	peak
5	12289.276	36.52	14.38	50.90	74.00	-23.10	peak
6	13881.633	34.74	16.29	51.03	74.00	-22.97	peak
7	18000.000	29.12	23.27	52.39	74.00	-21.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4945.674	57.59	0.17	57.76	74.00	-16.24	peak
2	4945.674	57.59	0.17	42.05	54.00	-11.95	AVG
3	7153.599	40.25	6.88	47.13	74.00	-26.87	peak
4	7810.054	38.80	8.82	47.62	74.00	-26.38	peak
5	11357.628	36.97	13.17	50.14	74.00	-23.86	peak
6	14439.758	35.39	16.39	51.78	74.00	-22.22	peak
7	17712.063	29.58	22.36	51.94	74.00	-22.06	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. AVG Result=Peak Result + Duty Correction Factor.  
 5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.  
 6. The High Pass filter loss factor already add into the correct factor.  
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4945.674	61.62	0.17	61.79	74.00	-12.21	peak
2	4945.674	61.62	0.17	46.08	54.00	-7.92	AVG
3	7166.428	40.39	6.88	47.27	74.00	-26.73	peak
4	8226.601	38.98	9.33	48.31	74.00	-25.69	peak
5	10591.067	38.37	12.69	51.06	74.00	-22.94	peak
6	14439.758	35.54	16.39	51.93	74.00	-22.07	peak
7	17775.648	30.00	22.98	52.98	74.00	-21.02	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG Result=Peak Result + Duty Correction Factor.
  5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
  6. The High Pass filter loss factor already add into the correct factor.
  7. Proper operation of the transmitter prior to adding the filter to the measurement chain.



### 7.5. SPURIOUS EMISSIONS (18~26GHz)

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18136.000	49.76	-4.14	45.62	74.00	-28.38	peak
2	19856.000	50.47	-4.35	46.12	74.00	-27.88	peak
3	21736.000	51.32	-5.76	45.56	74.00	-28.44	peak
4	21920.000	51.20	-6.09	45.11	74.00	-28.89	peak
5	23984.000	48.92	-4.05	44.87	74.00	-29.13	peak
6	24480.000	48.52	-2.67	45.85	74.00	-28.15	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.



**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19720.000	51.00	-4.39	46.61	74.00	-27.39	peak
2	20536.000	51.84	-4.98	46.86	74.00	-27.14	peak
3	21424.000	51.24	-5.69	45.55	74.00	-28.45	peak
4	24032.000	49.58	-3.96	45.62	74.00	-28.38	peak
5	24928.000	46.97	-1.32	45.65	74.00	-28.35	peak
6	25576.000	46.79	-1.67	45.12	74.00	-28.88	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.


Note: All test mode has been tested, only the worst data record in the report.



## 7.6. SPURIOUS EMISSIONS BELOW 30M

### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)

#### 9kHz~ 150kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0097	74.93	-101.38	-26.45	47.83	-74.28	peak
2	0.0145	69.55	-101.38	-31.83	44.89	-76.72	peak
3	0.0212	67.04	-101.35	-34.31	41.16	-75.47	peak
4	0.0328	63.98	-101.40	-37.42	37.36	-74.78	peak
5	0.0641	60.46	-101.54	-41.08	31.49	-72.57	peak
6	0.1200	59.00	-101.73	-42.73	26.02	-68.75	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



**150kHz ~ 490kHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1582	72.05	-101.65	-29.60	23.62	-53.22	peak
2	0.1794	69.27	-101.68	-32.41	22.53	-54.94	peak
3	0.2285	65.90	-101.77	-35.87	20.58	-56.45	peak
4	0.2796	61.41	-101.83	-40.42	18.78	-59.20	peak
5	0.3573	60.08	-101.91	-41.83	16.63	-58.46	peak
6	0.4485	57.35	-102.01	-44.66	14.61	-59.27	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



**490kHz ~ 30MHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6965	65.55	-62.11	3.44	30.75	-27.31	peak
2	1.3263	63.48	-62.11	1.37	25.16	-23.79	peak
3	2.0834	56.50	-61.80	-5.30	29.54	-34.84	peak
4	3.4735	52.70	-61.46	-8.76	29.54	-38.30	peak
5	9.2248	50.02	-60.91	-10.89	29.54	-40.43	peak
6	25.8094	48.91	-60.37	-11.46	29.54	-41.00	peak

- Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

**9kHz~ 150kHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0091	77.84	-101.33	-23.49	48.29	-71.78	peak
2	0.0151	73.85	-101.37	-27.52	44.53	-72.05	peak
3	0.0292	68.57	-101.39	-32.82	38.34	-71.16	peak
4	0.0529	64.68	-101.49	-36.81	33.16	-69.97	peak
5	0.0801	61.35	-101.63	-40.28	29.53	-69.81	peak
6	0.1280	60.10	-101.71	-41.61	25.47	-67.08	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



**150kHz ~ 490kHz**




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	74.57	-101.65	-27.08	23.78	-50.86	peak
2	0.1789	68.55	-101.68	-33.13	22.55	-55.68	peak
3	0.2326	65.64	-101.77	-36.13	20.43	-56.56	peak
4	0.2857	62.79	-101.83	-39.04	18.56	-57.60	peak
5	0.3392	60.30	-101.90	-41.60	17.08	-58.68	peak
6	0.4200	59.66	-101.98	-42.32	15.17	-57.49	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



490kHz ~ 30MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5231	71.16	-62.07	9.09	33.27	-24.18	peak
2	0.8467	64.60	-62.18	2.42	29.06	-26.64	peak
3	1.4516	58.70	-62.06	-3.36	24.37	-27.73	peak
4	2.9464	54.28	-61.60	-7.32	29.54	-36.86	peak
5	12.5594	51.51	-60.91	-9.40	29.54	-38.94	peak
6	18.4024	50.08	-60.89	-10.81	29.54	-40.35	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
 2. All the modes had been tested, but only the worst data were recorded in the report.  
 3. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

Note: All test mode has been tested, only the worst data record in the report.



## 7.7. SPURIOUS EMISSIONS BELOW 1 GHz

### SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	161.9200	24.55	-17.68	6.87	43.50	-36.63	QP
2	250.1900	30.45	-16.12	14.33	46.00	-31.67	QP
3	350.1000	25.66	-13.16	12.50	46.00	-33.50	QP
4	449.0400	24.64	-11.42	13.22	46.00	-32.78	QP
5	680.8700	25.82	-6.94	18.88	46.00	-27.12	QP
6	943.7400	29.48	-3.52	25.96	46.00	-20.04	QP

Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



**SPURIOUS EMISSIONS (HIGH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	28.94	-20.27	8.67	40.00	-31.33	QP
2	100.8100	27.16	-21.79	5.37	43.50	-38.13	QP
3	250.1900	29.70	-16.12	13.58	46.00	-32.42	QP
4	335.5500	23.82	-13.46	10.36	46.00	-35.64	QP
5	547.0100	26.75	-9.49	17.26	46.00	-28.74	QP
6	722.5800	26.87	-6.13	20.74	46.00	-25.26	QP

- Note: 1. Result Level = Read Level + Correct Factor.  
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All test mode has been tested, only the worst data record in the report.



## 8. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

**END OF REPORT**